



Machine learning methods for rare diseases

This manuscript ([permalink](#)) was automatically generated from [jaybee84/ml-in-rd@2dfe14d](#) on August 25, 2020.

Authors

- **Jineta Banerjee**

 [0000-0002-1775-3645](#) ·  [jaybee84](#)

Sage Bionetworks · Funded by Neurofibromatosis Therapeutic Acceleration Program; Children's Tumor Foundation

- **Robert J Allaway**

 [0000-0003-3573-3565](#) ·  [allaway](#) ·  [allawayr](#)

Sage Bionetworks · Funded by Neurofibromatosis Therapeutic Acceleration Program; Children's Tumor Foundation

- **Jaclyn N Taroni**

 [0000-0003-4734-4508](#) ·  [jaclyn-taroni](#)

Childhood Cancer Data Lab, Alex's Lemonade Stand Foundation

- **Casey Greene**

 [0000-0001-8713-9213](#) ·  [cgreene](#)

Department of Systems Pharmacology and Translational Therapeutics, Perelman School of Medicine, University of Pennsylvania; Childhood Cancer Data Lab, Alex's Lemonade Stand Foundation

- **Justin Guinney**

 [0000-0003-1477-1888](#) ·  [jguinney](#)

Sage Bionetworks · Funded by Neurofibromatosis Therapeutic Acceleration Program; Children's Tumor Foundation

Synopsis

(Instructions: Describe the background, basic structure of the article, list material to be covered indicating depth of coverage, how they are logically arranged, include recent pubs in the area, 300-500 words)

Substantial technological advances have dramatically changed biomedicine by making deep characterization of patient samples routine. These technologies provide a rich portrait of genes, cellular pathways, and cell types involved in complex phenotypes. Machine learning is often a perfect fit for the types of data now being generated, and Nature Methods routinely has reports of machine learning methods that extract disease-relevant patterns from these high dimensional datasets. Often, these methods require a large number of samples to identify reproducible and biologically meaningful patterns. With rare diseases, biological specimens and consequently data, are limited due to the rarity of the condition. In this perspective, we outline the challenges and emerging solutions for using machine learning in these settings. We aim to spur the development of powerful machine learning techniques for rare diseases. We also note that precision medicine presents a similar challenge, in which a common disease is partitioned into small subsets of patients with shared etiologies and treatment strategies. Advances from rare disease research are likely to be highly informative for other applications as well.

Introduction

Machine learning (ML) is gaining momentum in biomedical data analysis as data collection becomes increasingly high-throughput and as novel computational methods for exploring those data are developed. Application of ML to any dataset requires careful execution, but the application to biomedical data and subsequent interpretation requires depth of knowledge not only in the biomedical domain but also a clear understanding of the methods and their underlying assumptions. Application of ML to any kind of data consists of the following major steps: (1) data evaluation and question formulation, (2) selection of normalization/dimension reduction to mitigate technical differences, (3) selection of appropriate algorithms which select features to answer the formulated question, (4) evaluation of the answers generated by the algorithm. Each of these steps require the practitioner to choose from a variety of methodologies to apply. The selection of the methodologies at each of these steps need to be based upon robust reasoning to ensure stability of the results.

A promising yet challenging application of machine learning is in the study of rare diseases - those with fewer than 200,000 cases in the United States [1]. Rare disease research has substantial constraints to consider when using ML methods, including lack of statistical power in dataset size, heterogeneity in available data, and sensitivity of ML methods to misinterpretation in view of small datasets. Moreover, in the context of rare disease, special considerations need to be made to safeguard against misinterpretation of results. Such considerations include incorporation of techniques that build upon prior domain-specific knowledge, methods that are resilient to challenges posed by small datasets, and methods that can mitigate technical disparities in the data. Recent advances in methodologies to accommodate rarity of samples and increased transparency in model outputs have encouraged application of ML in rare diseases. In this perspective, we discuss techniques for understanding the nature of rare disease data, methods for addressing some of the limitations of these data, and ML methods that can tolerate some of these limitations.

Managing disparities in data generation is required for robust analysis

Rare disease data often suffers from artifacts introduced by non-biological phenomena such as batch or assay platform. The consequences of these artifacts are amplified when there are few samples and heterogeneous phenotypes. Furthermore, datasets are often combined from multiple small studies where biological characteristics are confounded by technical variables. Collaboration with domain experts may result in unexpected insight into potential sources of variation. The authors experienced this when studying neurofibromatosis type 1 (NF1). The NF1 datasets were comprised of samples obtained with different surgical techniques, resulting in differences that were a consequence of sample collection method rather than differences in biology. Consequently, careful assessment of and accounting for confounding factors is critical to identifying meaningful features within a dataset.

Assessment of confounding factors and heterogeneity is perhaps most easily performed using unsupervised learning approaches. K-means clustering or hierarchical clustering can be used to characterize the structure present in genomic or imaging data. [2,3] Similarly, dimensionality reduction methods can be used to visualize heterogeneity and confounders, including multidimensional scaling, principal components analysis, t-distributed stochastic neighbor embedding (t-SNE), and uniform manifold approximation and projection (UMAP), among others. [4,5,6,7] Dimensionality reduction techniques are not restricted to 'omic' data - they can also be used in rare disease applications to characterize the structure and heterogeneity of imaging data [8], mass cytometry data [9], and others. All of these methods can be used to identify batch effects and other structure in the data, though some (like t-SNE and UMAP) require parameters that can affect the output [7,10]. Therefore, obtaining a clear interpretation from these methods requires understanding the underlying approach and parameters.

Another important consideration is discussed by Way, et. al. [11]: a single dimensionality reduction method alone may not be sufficient to reveal all of the technical or biological heterogeneity; testing multiple methods may result in a more comprehensive portrait of the data.

Once the nature of the non-biological heterogeneity has been established, different techniques can be used to correct the differences. Common approaches include reprocessing the raw data using a single analysis pipeline if the data are obtained from different sources, application of batch correction methods [12,13], and normalization of raw values[14]. It is also important to be realistic when working with rare disease data. For various reasons including ethical constraints, funding, and limited biospecimens, experimental design and the resulting data will often be less-than-ideal. In these cases, it may be prudent to take a step back, re-evaluate the data, and identify methods that can operate within the constraints of the data, rather than expecting the data to conform to your method of choice.

Techniques and procedures must be implemented to manage model complexity without sacrificing the value of machine learning

In addition to improving the input data, methodological considerations can also help address the aforementioned challenges in applying ML models to rare diseases. Below, we describe some examples, including bootstrapping sample data, regularization methods for deep learning, and hyper-ensemble techniques to minimize misinterpretation of the data.

Bootstrapping

Bootstrapping is a powerful statistical technique that can be used to estimate population values from datasets of limited sample size by resampling the data [15]. Bootstrap based techniques are used in conjunction with various learning methods to find the most informative models given a specific dataset (e.g. bootstrap aggregating or bagging used in random forests [16,17], bootstrap in neural networks [18], or regression models [19,20]). Bootstrapping can be used to enhance the information content of rare disease datasets and generate confidence intervals for the model predictions as demonstrated by Banerjee et al [21]. In this study, bootstrapping the training sample without replacement simulated generation of separate datasets that helped expose the learning models (random forests) to the incomplete nature of the data. Such bootstrapping of the training data in addition to that included in the model (bagging) helped generate a distribution (and confidence intervals) of the importance scores of the predictive features selected by the model.

Regularization

Another common strategy for handling the paucity of data in rare disease is to aggregate data from multiple studies or time points to produce a more comprehensive dataset. Given a dataset with strong preexisting study-specific technical differences between groups of samples, ML methods may model dataset-specific features instead of true biology, leading to high prediction accuracy for training data but poor performance in new test data (an “overfit” model) [22]. Minimization of overfitting can be accomplished by cross-validation (to reduce variance in predictions) and regularization (to reduce low bias in models). Regularization makes models less reliant on training data by adding a small penalty (determined by cross-validation), and can minimize overfitting while improving feature selection.

ML models can be regularized using 3 main methods, each with strengths and weaknesses. Ridge regression aims to minimize the magnitude of the features, but cannot remove unimportant features and thus may not be ideal for reducing the feature space. Another method, LASSO regression, works well for selecting few important features since it can minimize the magnitude of some features more

than the others[23]. Elastic-net regression is a combination of LASSO and ridge regression [24], and helps to select the most useful features, especially in presence of large number of correlated features.

While regression based regularization has not been used extensively in rare disease, examples in rare variant discovery and immune cell signature discovery provide insights into their possible application in rare disease. In rare variant discovery, ridge regression has been utilized to combine rare variants into a single score to increase the signal of rare variants [25], while LASSO was implemented along with group penalties to identify rare variants/low frequency predictors [26,27]. Hybrid applications of LASSO have also been tested in rare variant discovery, including boosting the signal of rare variants by capturing combinations of variants [28,29], integration with a probabilistic logistic Bayesian approach [30], combining feature selection methods with a generalized pooling strategy [31], and incorporating prior knowledge into the regularization step to select driver genes in a pathway of interest [32].

In immune cell signature discovery, elastic-net regression has been used to reduce the feature space and was found to outperform other regression approaches [24,33,34]. A variation of elastic-net, where a two-step regularized logistic regression was used to pre-select an optimal number of genes before implementing elastic-net regularization for gene selection, identified immune cell signatures in an RNA-seq dataset where the number of cells sampled were far fewer than number of genes profiled [??? 10.1186/s12859-019-2994-z].

Thus, regularization methods like LASSO or elastic-net have been methods of choice where the profiled feature space is substantially larger than the number of samples; these methods should be explored while working with rare disease datasets.

Hyperensemble

Techniques that build on prior knowledge and indirectly related data are necessary for many rare disease applications

Knowledge graphs

Rare diseases lack large, normalized datasets, limiting our ability to study key attributes of these diseases. A potentially powerful strategy for evaluating genotype-phenotype relationships or repurposing drugs when large datasets are scarce is to use knowledge graphs. Knowledge graphs integrate related-but-different data types, creating a rich data source. Examples of public biomedical knowledge graphs and frameworks that could be useful in rare disease include the Monarch Graph Database[35], hetionet[36], PheKnowLator[37], and the Global Network of Biomedical Relationships[38]. These graphs connect information like genetic, functional, chemical, clinical, and ontological data to enable the exploration of relationships of data with disease phenotypes through manual review[39] or computational methods[40,41].

In the academic rare disease space, there are a few pioneering examples of ML-based mining of knowledge graphs to repurpose drugs[40] and classify rare diseases[41]. These studies make it clear that there are challenges in using machine learning based on knowledge graphs in rare disease. For example, these projects rely on a gold standard dataset to validate the performance of the models; often, there are not robust gold standard datasets available for individual rare diseases. They also evaluate rare diseases in an unbiased manner, rather than interrogating a specific disease of interest. Consequently, it is not yet clear how effective these approaches, and knowledge graphs in general, are in studying a specific disease of interest; more work needs to be done to identify methods that can provide actionable insights for a specific rare disease application.

Beyond the aforementioned studies, there are not many examples of studies in the public domain that leverage knowledge graphs to characterize rare diseases. Private entities (e.g. healx, Boehringer Ingelheim), however, are performing an undisclosed amount of work to create proprietary rare disease knowledge graphs for ML-based drug discovery applications. The existence of private companies pursuing this idea, as well as the availability of public biomedical knowledge graphs, suggests that this is likely a fruitful untapped area of rare disease research in the public arena. More work needs to be done to assess 1) which graphs and graph features capture the salient information about rare diseases, 2) the utility of ML methods to obtain actionable insights about rare diseases and 3) which problems - like drug discovery, identification of novel rare diseases, or assessment of genotype-phenotype relationships - can be interrogated using ML of knowledge graphs.

Wisdom of the crowd: rare disease applications of ensemble methods

Implementing machine learning on data with low sample size and high label uncertainty can lead to unstable predictions. In such cases, combining various machine learning methods together (*ensemble learning*) can increase accuracy and stability of the predictions. For example, ensemble learning methods like random forests use bootstrap aggregation (or *bagging*) of independent decision trees that use similar parameters but different paths to form a consensus about the important predictive features hidden in the dataset [42]. However, successful application of consensus based ensemble learning requires “gold standard” data where the diagnosis or label of a data point in the training dataset has very little uncertainty (or “label-noise”) associated with it [46]. In rare disease the symptoms as well as any underlying biology often come with a reasonable amount label-noise leading to a *silver standard* dataset[47]. In such datasets, the limited success of the *bagging* approach has led to the use of ensemble learning or *cascade learning*, where multiple methods leveraging distinct underlying assumptions are used in tandem and augmented with algorithms like AdaBoost (*boosting*) to capture stable patterns existing in the silver standard data and reduce uncertainty [48]. A variation

of cascade learning implemented to identify rare disease patients from electronic health records from the general population utilized independent steps for feature extraction (using word2vec [51]), preliminary prediction (ensemble of decision trees with penalization for excessive tree-depth), and prediction refinement (using similarity of data points to resolve sample labels) [52]. Combining these three methods resulted in better performance than other methods when implemented on the silver standard dataset.

In datasets with multiple classes, most cascade classifiers follow a *one-classifier-at-a-time* approach where algorithms at each level predict all classes involved. But instances where the need for high prediction accuracy for one class outweighs other classes, further modification of the cascade learning efforts is required. An example of such modification was implemented for triaging psychiatric patients where the identification of one class of psychiatric patients (“severe”) far outweighed the need for optimized overall classification accuracy [53]. Due to the requirements of the problem, a *one-class-at-a-time* cascade learning approach was adopted, where at each stage a binary classifier was used to predict a specific class against all others. The final model implemented all models together each identifying one class sequentially and the union of the predictions of all the different models as the final prediction. The cascade classifiers using the one-class-at-a-time approach were found to perform better than multi-class ensemble classifiers in most cases.

Thus ensemble learning can be helpful in producing stable predictions from rare disease data, but the choice of using bagging, boosting, independent algorithmic steps, or one-class-at-a-time approach depends on the nature of the prediction question.

Representation learning

Representation learning, also called feature learning, is the process of learning features from raw data, where a feature is an individual variable. An algorithm or approach will construct features as part of training and, in a supervised application, use those features to predict labels on input data. Using an example from transcriptomics, an unsupervised method such as matrix factorization can be used to extract a low-dimensional representation of the gene-level data, learning features that are a combination of input genes’ expression levels [11, 54]. Low-dimensional representations trained on a collection of transcriptomic data can then be used as input to supervised machine learning methods [55]. Supervised neural networks used in medical imaging studies [56] (reviewed in [57]), which are trained to predict labels or classes, are also an example of representation learning. Learned features in the medical imaging domain may be a series of edges representing a blood vessel formation that discriminates between disease states. Features learned from transcriptomic data could be coordinated sets of genes involved in a biological process that are descriptive in some way [58].

In the rare disease domain, Dincer et al. leveraged publicly available acute myeloid leukemia (AML) gene expression data to improve the prediction of *in vitro* drug responses [59]. The authors trained a variational autoencoder (an unsupervised neural network that learns a series of representations from data), or VAE, on AML data that had been collected over time without the desired phenotypic information (drug response). The authors used the learned attributes to encode a low-dimensional representation of held-out AML data with phenotype labels of interest, and used this representation as input to a classifier that predicted *in vitro* drug response.

Representation learning tends to be data-intensive; many samples are required. Though there were over 6500 AML samples from many different studies used as part of the training set in Dincer et al. [59], we expect that in other rare diseases considerably fewer samples will be available or may be from different tissues in systemic diseases. The study by Dincer and colleagues highlights another challenge: samples collected as part of multiple studies may not be associated with the deep phenotypic information that would maximize their scientific value. In the next section, we will

introduce methods or approaches that may be more broadly useful in rare diseases; representation learning underlies many of them.

Transfer, multitask, and few-shot learning

To realize the potential of machine learning for biological discovery in rare diseases, we often cannot study an individual rare disease alone as samples are limited. Instead, we can build on prior knowledge and large volumes of data that do not directly assay our disease of interest, but are similar enough to be valuable for discovery. We can leverage shared features, whether they are normal developmental processes that are aberrant in disease or an imaging anomaly present in rare and common diseases, for advancing our understanding. Methods that leverage shared features include transfer learning, multitask learning, and few-shot learning approaches.

Transfer learning

Transfer learning is an approach where a model trained for one task or domain (source domain) is applied to another, typically related task or domain (target domain). Transfer learning can be supervised (one or both of the source and target domains have labels), or unsupervised (both domains are unlabeled). Though there are multiple types of transfer learning, we will focus on feature-representation-transfer [60] here. Feature-representation-transfer approaches learn representations from the source domain and apply them to a target domain [60]. This concept is embodied in Dincer et al., where features are learned from unlabeled AML data and then used to encode a low-dimensional representation of AML data with *in vitro* drug response labels [59]. The authors then used this low-dimensional representation as input to predict drug response labels—a supervised example.

In an unsupervised case, Taroni et al. trained a Pathway-Level Information Extractor (PLIER) [61] on a large generic collection of human transcriptomic data (recount2 [62]) and used the latent variables learned by the model to describe transcriptomic data from the unseen rare diseases antineutrophil cytoplasmic antibody (ANCA)-associated vasculitis (AAV) and medulloblastoma in an approach termed MultiPLIER [63]. (Here “unseen” refers to the fact that these diseases were not in the training set.) PLIER is a matrix factorization approach that takes prior knowledge in the form of gene sets or pathways and gene expression data as input; some latent variables learned by the model will align with input gene sets [61]. We demonstrated that training on larger collections of randomly selected samples produced models that captured a larger proportion of input gene sets and better distinguished closely related signals, which suggests that larger training sets produced models that are more suitable for biological discovery [63].

Though models trained on generic compendia had appealing properties, we need to also examine the relevance of learned features to the disease under study. In Taroni et al., we found that the expression of latent variables that could be matched between the MultiPLIER model and a dataset-specific model were well-correlated, particularly when latent variables were associated with input gene sets [63]. Despite the absence of AAV from the training set, MultiPLIER was able to learn a latent variable where the genes with the highest contributions encode antigens that the ANCA form against in AAV and with higher expression in more severe disease [64]. The utility of this approach stems from the fact that biological processes are often *shared* between conditions—the same ANCA antigen genes are components of neutrophilic granule development that is likely captured or assayed in the collection of transcriptomic data used for training. MultiPLIER has additional attributes that make it practical for studying rare diseases: latent variables that are not associated with input gene sets may capture technical noise separately from biological signal and we can use one model to describe multiple datasets instead of reconciling output from multiple models (see *03.heterogeneity.md*).

Taken together, DeepProfile [59] and MultiPLIER [63] suggest transfer learning can be beneficial for studying rare diseases. In the natural images field, researchers have demonstrated that the transferability of features depends on relatedness of tasks [65]. The limits of transfer learning for and the concept of relatedness in high-dimensional biomedical data assaying rare diseases are open research questions. In the authors' opinion, selecting an appropriate model for a given task and evaluations that are well-aligned with a research goal are crucial for applying these approaches in rare diseases.

Multitask and few-shot learning

Where transfer learning can be supervised or unsupervised, the related approaches multitask and few-shot learning are forms of supervised learning that generally rely on deep neural networks. Multitask learning is an approach where classifiers are learned for *related tasks* at the same time using a shared representation [66], where task refers to an individual prediction being made. Few-shot learning is the generalization of a model trained on related tasks to a new task with limited labeled data (e.g., the detection of a patient with a rare disease from a low number of examples of that rare disease).

Multitask neural networks that predict multiple tasks simultaneously are generally thought to improve performance over models that make predictions for a single task by learning a shared representation and effectively being exposed to more training data than the single task case [66,67]. Kearnes, Goldman, and Pande set out to examine the effects of dataset size and task relatedness on multitask learning performance improvements ("multitask effect") in drug discovery—an area that also suffers from insufficient data [67]. The authors found that the multitask performance gains were highly dataset-specific: smaller datasets tended to benefit most from multitask learning and the addition of more training data did not guarantee improved performance for multitask models. In predicting phenotypes from EHR data, Ding et al. demonstrated that multitask neural networks outperformed single-task networks for predicting complex rare phenotypes but not common phenotypes [68]. Liu et al. developed a method to train long short-term memory networks, a type of recurrent neural network, to predict mortality in rare diseases using EHR data as input [69]. Their method, Ada-SiT (Adaptation to Similar Tasks), was specifically designed for many tasks with insufficient data and allowed for task similarity to be measured during training.

In contrast, one-shot or few-shot learning relies on using prior knowledge to generalize to new prediction tasks where there are a low number of examples [70], where a distance metric is learned from input data and used to compare new examples for prediction [71]. Altae-Tran et al. developed a method for predicting small molecule activity that learned a meaningful distance metric over the properties of various compounds [71]. However, the authors' results suggested underperformance of one-shot learning methods relative to baseline random forest models when structural similarity could not be exploited and did not show support for generalization of models trained on very different contexts from the target task. Quellec et al. presented a few-shot learning approach for detecting rare pathologies in fundus photographs [72]. The authors trained a convolutional neural network (CNN) to predict common pathologies, which tended to cluster similar conditions in feature space. The learned feature space was then used to train a probabilistic model for each rare pathology. This approach outperformed multitask learning, which suggests few-shot learning provides an advantage in contexts where predicting common conditions simultaneously results in a loss of performance [72].

Multitask and few-shot learning are comprised of a variety of approaches and architectures that are beyond this scope of this work (see [73,74] and [70] for an overview). As with transfer learning, the utility of these approaches to rare disease research is an open question and is likely to be highly dependent on dataset availability and research goals.

Conclusions

We will conclude by discussing the potential of the above-mentioned approaches in rare diseases and other biomedical areas where data is scarce.

Outlook

References

1.
Potomac Publishing
(2018-10-08) <https://www.fda.gov/media/99546/download>
2. **Clustering cancer gene expression data: a comparative study**
Marcilio CP de Souto, Ivan G Costa, Daniel SA de Araujo, Teresa B Ludermir, Alexander Schliep
BMC Bioinformatics (2008-11-27) <https://doi.org/dqgqbn6>
DOI: [10.1186/1471-2105-9-497](https://doi.org/10.1186/1471-2105-9-497) · PMID: [19038021](https://pubmed.ncbi.nlm.nih.gov/19038021/) · PMCID: [PMC2632677](https://pubmed.ncbi.nlm.nih.gov/PMC2632677/)
3. **Removing Batch Effects From Histopathological Images for Enhanced Cancer Diagnosis**
Sonal Kothari, John H. Phan, Todd H. Stokes, Adeboye O. Osunkoya, Andrew N. Young, May D. Wang
IEEE Journal of Biomedical and Health Informatics (2014-05) <https://doi.org/gdm9jd>
DOI: [10.1109/jbhi.2013.2276766](https://doi.org/10.1109/jbhi.2013.2276766) · PMID: [24808220](https://pubmed.ncbi.nlm.nih.gov/24808220/) · PMCID: [PMC5003052](https://pubmed.ncbi.nlm.nih.gov/PMC5003052/)
4. **Multidimensional Scaling**
Michael A. A. Cox, Trevor F. Cox
Springer Berlin Heidelberg (2008) <https://doi.org/dg9m4f>
DOI: [10.1007/978-3-540-33037-0_14](https://doi.org/10.1007/978-3-540-33037-0_14)
5. **Principal component analysis: a review and recent developments**
Ian T. Jolliffe, Jorge Cadima
Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences (2016-04-13) <https://doi.org/gcsfk7>
DOI: [10.1098/rsta.2015.0202](https://doi.org/10.1098/rsta.2015.0202) · PMID: [26953178](https://pubmed.ncbi.nlm.nih.gov/26953178/) · PMCID: [PMC4792409](https://pubmed.ncbi.nlm.nih.gov/PMC4792409/)
6. (2020-06-01) https://lvdmaaten.github.io/publications/papers/JMLR_2008.pdf
7. **UMAP: Uniform Manifold Approximation and Projection for Dimension Reduction**
Leland McInnes, John Healy, James Melville
arXiv (2018-12-07) <https://arxiv.org/abs/1802.03426>
8. **Automatic detection of rare pathologies in fundus photographs using few-shot learning**
Gwenolé Quélélec, Mathieu Lamard, Pierre-Henri Conze, Pascale Massin, Béatrice Cochener
Medical Image Analysis (2020-04) <https://doi.org/ggsrc7>
DOI: [10.1016/j.media.2020.101660](https://doi.org/10.1016/j.media.2020.101660) · PMID: [32028213](https://pubmed.ncbi.nlm.nih.gov/32028213/)
9. **Sensitive detection of rare disease-associated cell subsets via representation learning**
Eirini Arvaniti, Manfred Claassen
Nature Communications (2017-04-06) <https://doi.org/gf9t7w>
DOI: [10.1038/ncomms14825](https://doi.org/10.1038/ncomms14825) · PMID: [28382969](https://pubmed.ncbi.nlm.nih.gov/28382969/) · PMCID: [PMC5384229](https://pubmed.ncbi.nlm.nih.gov/PMC5384229/)
10. **How to Use t-SNE Effectively**
Martin Wattenberg, Fernanda Viégas, Ian Johnson
Distill (2016-10-13) <https://doi.org/gffk7g>
DOI: [10.23915/distill.00002](https://doi.org/10.23915/distill.00002)
11. **Compressing gene expression data using multiple latent space dimensionalities learns complementary biological representations**

Gregory P. Way, Michael Zietz, Vincent Rubinetti, Daniel S. Himmelstein, Casey S. Greene
Genome Biology (2020-05-11) <https://doi.org/gg2mjh>
DOI: [10.1186/s13059-020-02021-3](https://doi.org/10.1186/s13059-020-02021-3) · PMID: [32393369](https://pubmed.ncbi.nlm.nih.gov/32393369/) · PMCID: [PMC7212571](https://pubmed.ncbi.nlm.nih.gov/PMC7212571/)

12. Adjusting batch effects in microarray expression data using empirical Bayes methods

W. Evan Johnson, Cheng Li, Ariel Rabinovic
Biostatistics (2007-01) <https://doi.org/dsf386>
DOI: [10.1093/biostatistics/kxj037](https://doi.org/10.1093/biostatistics/kxj037) · PMID: [16632515](https://pubmed.ncbi.nlm.nih.gov/16632515/)

13. svaseq: removing batch effects and other unwanted noise from sequencing data

Jeffrey T. Leek
Nucleic Acids Research (2014-12-01) <https://doi.org/f8k8kf>
DOI: [10.1093/nar/gku864](https://doi.org/10.1093/nar/gku864) · PMID: [25294822](https://pubmed.ncbi.nlm.nih.gov/25294822/) · PMCID: [PMC4245966](https://pubmed.ncbi.nlm.nih.gov/PMC4245966/)

14. A scaling normalization method for differential expression analysis of RNA-seq data

Mark D Robinson, Alicia Oshlack
Genome Biology (2010) <https://doi.org/cq6f8b>
DOI: [10.1186/gb-2010-11-3-r25](https://doi.org/10.1186/gb-2010-11-3-r25) · PMID: [20196867](https://pubmed.ncbi.nlm.nih.gov/20196867/) · PMCID: [PMC2864565](https://pubmed.ncbi.nlm.nih.gov/PMC2864565/)

15. Improvements on Cross-Validation: The 632+ Bootstrap Method

Bradley Efron, Robert Tibshirani
Journal of the American Statistical Association (1997-06) <https://doi.org/gfts5c>
DOI: [10.1080/01621459.1997.10474007](https://doi.org/10.1080/01621459.1997.10474007)

16. {unav}

Leo Breiman
Machine Learning (2001) <https://doi.org/d8zjwq>
DOI: [10.1023/a:1010933404324](https://doi.org/10.1023/a:1010933404324)

17. Bootstrap Methods for Developing Predictive Models

Peter C Austin, Jack V Tu
The American Statistician (2004-05) <https://doi.org/bzjjxt>
DOI: [10.1198/0003130043277](https://doi.org/10.1198/0003130043277)

18. Bootstrap for neural model selection

Riadh Kallel, Marie Cottrell, Vincent Vigneron
Neurocomputing (2002-10) <https://doi.org/c8xpqz>
DOI: [10.1016/s0925-2312\(01\)00650-6](https://doi.org/10.1016/s0925-2312(01)00650-6)

19. Fast bootstrap methodology for regression model selection

A. Lendasse, G. Simon, V. Wertz, M. Verleysen
Neurocomputing (2005-03) <https://doi.org/dx5c3p>
DOI: [10.1016/j.neucom.2004.11.017](https://doi.org/10.1016/j.neucom.2004.11.017)

20. A bootstrap resampling procedure for model building: Application to the cox regression model

Willi Sauerbrei, Martin Schumacher
Statistics in Medicine (1992) <https://doi.org/cnpg3d>
DOI: [10.1002/sim.4780111607](https://doi.org/10.1002/sim.4780111607) · PMID: [1293671](https://pubmed.ncbi.nlm.nih.gov/1293671/)

21. Integrative Analysis Identifies Candidate Tumor Microenvironment and Intracellular Signaling Pathways that Define Tumor Heterogeneity in NF1

Jineta Banerjee, Robert J Allaway, Jaclyn N Taroni, Aaron Baker, Xiaochun Zhang, Chang In Moon,

Christine A Pratilas, Jaishri O Blakeley, Justin Guinney, Angela Hirbe, ... Sara JC Gosline
Genes (2020-02-21) <https://doi.org/gg4rbj>
DOI: [10.3390/genes11020226](https://doi.org/10.3390/genes11020226) · PMID: [32098059](https://pubmed.ncbi.nlm.nih.gov/32098059/) · PMCID: [PMC7073563](https://pubmed.ncbi.nlm.nih.gov/PMC7073563/)

22. Definitions, methods, and applications in interpretable machine learning

W. James Murdoch, Chandan Singh, Karl Kumbier, Reza Abbasi-Asl, Bin Yu
Proceedings of the National Academy of Sciences (2019-10-29) <https://doi.org/ggbhmq>
DOI: [10.1073/pnas.1900654116](https://doi.org/10.1073/pnas.1900654116) · PMID: [31619572](https://pubmed.ncbi.nlm.nih.gov/31619572/) · PMCID: [PMC6825274](https://pubmed.ncbi.nlm.nih.gov/PMC6825274/)

23. Regularization

Jake Lever, Martin Krzywinski, Naomi Altman
Nature Methods (2016-09-29) <https://doi.org/gf3zrr>
DOI: [10.1038/nmeth.4014](https://doi.org/10.1038/nmeth.4014)

24. Regularization and variable selection via the elastic net

Hui Zou, Trevor Hastie
Journal of the Royal Statistical Society: Series B (Statistical Methodology) (2005-04)
<https://doi.org/b8cwwr>
DOI: [10.1111/j.1467-9868.2005.00503.x](https://doi.org/10.1111/j.1467-9868.2005.00503.x)

25. Adaptive Ridge Regression for Rare Variant Detection

Haimao Zhan, Shizhong Xu
PLoS ONE (2012-08-28) <https://doi.org/f36tm5>
DOI: [10.1371/journal.pone.0044173](https://doi.org/10.1371/journal.pone.0044173) · PMID: [22952918](https://pubmed.ncbi.nlm.nih.gov/22952918/) · PMCID: [PMC3429469](https://pubmed.ncbi.nlm.nih.gov/PMC3429469/)

26. Statistical analysis strategies for association studies involving rare variants

Vikas Bansal, Ondrej Libiger, Ali Torkamani, Nicholas J. Schork
Nature Reviews Genetics (2010-10-13) <https://doi.org/dn4jtz>
DOI: [10.1038/nrg2867](https://doi.org/10.1038/nrg2867) · PMID: [20940738](https://pubmed.ncbi.nlm.nih.gov/20940738/) · PMCID: [PMC3743540](https://pubmed.ncbi.nlm.nih.gov/PMC3743540/)

27. Association screening of common and rare genetic variants by penalized regression

H. Zhou, M. E. Sehl, J. S. Sinsheimer, K. Lange
Bioinformatics (2010-08-06) <https://doi.org/c7ndkx>
DOI: [10.1093/bioinformatics/btq448](https://doi.org/10.1093/bioinformatics/btq448) · PMID: [20693321](https://pubmed.ncbi.nlm.nih.gov/20693321/) · PMCID: [PMC3025646](https://pubmed.ncbi.nlm.nih.gov/PMC3025646/)

28. Methods for Detecting Associations with Rare Variants for Common Diseases: Application to Analysis of Sequence Data

Bingshan Li, Suzanne M. Leal
The American Journal of Human Genetics (2008-09) <https://doi.org/d4jpcb>
DOI: [10.1016/j.ajhg.2008.06.024](https://doi.org/10.1016/j.ajhg.2008.06.024) · PMID: [18691683](https://pubmed.ncbi.nlm.nih.gov/18691683/) · PMCID: [PMC2842185](https://pubmed.ncbi.nlm.nih.gov/PMC2842185/)

29. Comparison of statistical approaches to rare variant analysis for quantitative traits

Han Chen, Audrey E Hendricks, Yansong Cheng, Adrienne L Cupples, Josée Dupuis, Ching-Ti Liu
BMC Proceedings (2011-11-29) <https://doi.org/b9mf4x>
DOI: [10.1186/1753-6561-5-s9-s113](https://doi.org/10.1186/1753-6561-5-s9-s113) · PMID: [22373209](https://pubmed.ncbi.nlm.nih.gov/22373209/) · PMCID: [PMC3287837](https://pubmed.ncbi.nlm.nih.gov/PMC3287837/)

30. An Improved Version of Logistic Bayesian LASSO for Detecting Rare Haplotype-Environment Interactions with Application to Lung Cancer

Yuan Zhang, Swati Biswas
Cancer Informatics (2015-02-09) <https://doi.org/ggxxfp>
DOI: [10.4137/cin.s17290](https://doi.org/10.4137/cin.s17290) · PMID: [25733797](https://pubmed.ncbi.nlm.nih.gov/25733797/) · PMCID: [PMC4332044](https://pubmed.ncbi.nlm.nih.gov/PMC4332044/)

31. **Multiple Regression Methods Show Great Potential for Rare Variant Association Tests**
Changjiang Xu, Martin Ladouceur, Zari Dastani, J. Brent Richards, Antonio Ciampi, Celia M. T. Greenwood
PLoS ONE (2012-08-08) <https://doi.org/f35726>
DOI: [10.1371/journal.pone.0041694](https://doi.org/10.1371/journal.pone.0041694) · PMID: [22916111](https://pubmed.ncbi.nlm.nih.gov/22916111/) · PMCID: [PMC3420665](https://pubmed.ncbi.nlm.nih.gov/PMC3420665/)
32. **A Sparse-Group Lasso**
Noah Simon, Jerome Friedman, Trevor Hastie, Robert Tibshirani
Journal of Computational and Graphical Statistics (2013-04) <https://doi.org/gcvjw8>
DOI: [10.1080/10618600.2012.681250](https://doi.org/10.1080/10618600.2012.681250)
33. **Regularized logistic regression with adjusted adaptive elastic net for gene selection in high dimensional cancer classification**
Zakariya Yahya Algamal, Muhammad Hisyam Lee
Computers in Biology and Medicine (2015-12) <https://doi.org/f73xvj>
DOI: [10.1016/j.combiomed.2015.10.008](https://doi.org/10.1016/j.combiomed.2015.10.008) · PMID: [26520484](https://pubmed.ncbi.nlm.nih.gov/26520484/)
34. **Sparse logistic regression with a L1/2 penalty for gene selection in cancer classification**
Yong Liang, Cheng Liu, Xin-Ze Luan, Kwong-Sak Leung, Tak-Ming Chan, Zong-Ben Xu, Hai Zhang
BMC Bioinformatics (2013-06-19) <https://doi.org/gb8v2x>
DOI: [10.1186/1471-2105-14-198](https://doi.org/10.1186/1471-2105-14-198) · PMID: [23777239](https://pubmed.ncbi.nlm.nih.gov/23777239/) · PMCID: [PMC3718705](https://pubmed.ncbi.nlm.nih.gov/PMC3718705/)
35. **The Monarch Initiative: an integrative data and analytic platform connecting phenotypes to genotypes across species**
Christopher J. Mungall, Julie A. McMurtry, Sebastian Köhler, James P. Balhoff, Charles Borromeo, Matthew Brush, Seth Carbon, Tom Conlin, Nathan Dunn, Mark Engelstad, ... Melissa A. Haendel
Nucleic Acids Research (2017-01-04) <https://doi.org/f9v7bz>
DOI: [10.1093/nar/gkw1128](https://doi.org/10.1093/nar/gkw1128) · PMID: [27899636](https://pubmed.ncbi.nlm.nih.gov/27899636/) · PMCID: [PMC5210586](https://pubmed.ncbi.nlm.nih.gov/PMC5210586/)
36. **Systematic integration of biomedical knowledge prioritizes drugs for repurposing**
Daniel Scott Himmelstein, Antoine Lizée, Christine Hessler, Leo Brueggeman, Sabrina L Chen, Dexter Hadley, Ari Green, Pouya Khankhanian, Sergio E Baranzini
eLife (2017-09-22) <https://doi.org/cdfk>
DOI: [10.7554/elife.26726](https://doi.org/10.7554/elife.26726) · PMID: [28936969](https://pubmed.ncbi.nlm.nih.gov/28936969/) · PMCID: [PMC5640425](https://pubmed.ncbi.nlm.nih.gov/PMC5640425/)
37. **A Framework for Automated Construction of Heterogeneous Large-Scale Biomedical Knowledge Graphs**
Tiffany J. Callahan, Ignacio J. Tripodi, Lawrence E. Hunter, William A. Baumgartner
bioRxiv (2020-05-02) <https://doi.org/gg338z>
DOI: [10.1101/2020.04.30.071407](https://doi.org/10.1101/2020.04.30.071407)
38. **A global network of biomedical relationships derived from text**
Bethany Percha, Russ B Altman
Bioinformatics (2018-08-01) <https://doi.org/gc3ndk>
DOI: [10.1093/bioinformatics/bty114](https://doi.org/10.1093/bioinformatics/bty114) · PMID: [29490008](https://pubmed.ncbi.nlm.nih.gov/29490008/) · PMCID: [PMC6061699](https://pubmed.ncbi.nlm.nih.gov/PMC6061699/)
39. **Structured reviews for data and knowledge-driven research**
Núria Queralt-Rosinach, Gregory S Stupp, Tong Shu Li, Michael Mayers, Maureen E Hoatlin, Matthew Might, Benjamin M Good, Andrew I Su
Database (2020) <https://doi.org/ggsdkj>
DOI: [10.1093/database/baaa015](https://doi.org/10.1093/database/baaa015) · PMID: [32283553](https://pubmed.ncbi.nlm.nih.gov/32283553/) · PMCID: [PMC7153956](https://pubmed.ncbi.nlm.nih.gov/PMC7153956/)

40. **A Literature-Based Knowledge Graph Embedding Method for Identifying Drug Repurposing Opportunities in Rare Diseases**
Daniel N. Sosa, Alexander Derry, Margaret Guo, Eric Wei, Connor Brinton, Russ B. Altman
bioRxiv (2019-08-08) <https://doi.org/gg5j64>
DOI: [10.1101/727925](https://doi.org/10.1101/727925)
41. **Improving rare disease classification using imperfect knowledge graph**
Xuedong Li, Yue Wang, Dongwu Wang, Walter Yuan, Dezhong Peng, Qiaozhu Mei
BMC Medical Informatics and Decision Making (2019-12-05) <https://doi.org/gg5j65>
DOI: [10.1186/s12911-019-0938-1](https://doi.org/10.1186/s12911-019-0938-1) · PMID: [31801534](https://pubmed.ncbi.nlm.nih.gov/31801534/) · PMCID: [PMC6894101](https://pubmed.ncbi.nlm.nih.gov/PMC6894101/)
42. **Evaluating predictive modeling algorithms to assess patient eligibility for clinical trials from routine data**
Felix Köpcke, Dorota Lubgan, Rainer Fietkau, Axel Scholler, Carla Nau, Michael Stürzl, Roland Croner, Hans-Ulrich Prokosch, Dennis Toddenroth
BMC Medical Informatics and Decision Making (2013-12-09) <https://doi.org/f5jqvh>
DOI: [10.1186/1472-6947-13-134](https://doi.org/10.1186/1472-6947-13-134) · PMID: [24321610](https://pubmed.ncbi.nlm.nih.gov/24321610/) · PMCID: [PMC4029400](https://pubmed.ncbi.nlm.nih.gov/PMC4029400/)
43. **Analyzing bagging**
Peter Bühlmann, Bin Yu
The Annals of Statistics (2002-08) <https://doi.org/btmtjp>
DOI: [10.1214/aos/1031689014](https://doi.org/10.1214/aos/1031689014)
44. **Utilising artificial intelligence to determine patients at risk of a rare disease: idiopathic pulmonary arterial hypertension**
David G. Kiely, Orla Doyle, Edmund Drage, Harvey Jenner, Valentina Salvatelli, Flora A. Daniels, John Rigg, Claude Schmitt, Yevgeniy Samyshkin, Allan Lawrie, Rito Bergemann
Pulmonary Circulation (2019-11-20) <https://doi.org/gg4jc7>
DOI: [10.1177/2045894019890549](https://doi.org/10.1177/2045894019890549) · PMID: [31798836](https://pubmed.ncbi.nlm.nih.gov/31798836/) · PMCID: [PMC6868581](https://pubmed.ncbi.nlm.nih.gov/PMC6868581/)
45. **Double-bagging: combining classifiers by bootstrap aggregation**
Torsten Hothorn, Berthold Lausen
Pattern Recognition (2003-06) <https://doi.org/btzfh6>
DOI: [10.1016/s0031-3203\(02\)00169-3](https://doi.org/10.1016/s0031-3203(02)00169-3)
46. **Learning statistical models of phenotypes using noisy labeled training data**
Vibhu Agarwal, Tanya Podchiyska, Juan M Banda, Veena Goel, Tiffany I Leung, Evan P Minty, Timothy E Sweeney, Elsie Gyang, Nigam H Shah
Journal of the American Medical Informatics Association (2016-11) <https://doi.org/f9bxf9>
DOI: [10.1093/jamia/ocw028](https://doi.org/10.1093/jamia/ocw028) · PMID: [27174893](https://pubmed.ncbi.nlm.nih.gov/27174893/) · PMCID: [PMC5070523](https://pubmed.ncbi.nlm.nih.gov/PMC5070523/)
47. **Classification in the Presence of Label Noise: A Survey**
Benoit Frenay, Michel Verleysen
IEEE Transactions on Neural Networks and Learning Systems (2014-05) <https://doi.org/f5zdgg>
DOI: [10.1109/tnnls.2013.2292894](https://doi.org/10.1109/tnnls.2013.2292894) · PMID: [24808033](https://pubmed.ncbi.nlm.nih.gov/24808033/)
48. **Component-based face detection**
B. Heiselet, T. Serre, M. Pontil, T. Poggio
Institute of Electrical and Electronics Engineers (IEEE) (2005-08-25) <https://doi.org/c89p2b>
DOI: [10.1109/cvpr.2001.990537](https://doi.org/10.1109/cvpr.2001.990537)
49. **The Architecture of the Face and Eyes Detection System Based on Cascade Classifiers**
Andrzej Kasinski, Adam Schmidt

Advances in Soft Computing (2007) <https://doi.org/cbzq9n>
DOI: [10.1007/978-3-540-75175-5_16](https://doi.org/10.1007/978-3-540-75175-5_16)

50. Real time facial expression recognition with AdaBoost

Yubo Wang, Haizhou Ai, Bo Wu, Chang Huang

Institute of Electrical and Electronics Engineers (IEEE) (2004) <https://doi.org/crv3sq>

DOI: [10.1109/icpr.2004.1334680](https://doi.org/10.1109/icpr.2004.1334680)

51. Efficient Estimation of Word Representations in Vector Space

Tomas Mikolov, Kai Chen, Greg Corrado, Jeffrey Dean

arXiv (2013-01-16) <https://arxiv.org/abs/1301.3781v3>

52. Learning to Identify Rare Disease Patients from Electronic Health Records.

Rich Colbaugh, Kristin Glass, Christopher Rudolf, Mike Tremblay Volv Global Lausanne Switzerland

AMIA ... Annual Symposium proceedings. AMIA Symposium (2018-12-05)

<https://www.ncbi.nlm.nih.gov/pubmed/30815073>

PMID: [30815073](https://pubmed.ncbi.nlm.nih.gov/30815073/) · PMCID: [PMC6371307](https://pubmed.ncbi.nlm.nih.gov/PMC6371307/)

53. Machine learning for psychiatric patient triaging: an investigation of cascading classifiers.

Vivek Kumar Singh, Utkarsh Shrivastava, Lina Bouayad, Balaji Padmanabhan, Anna Ialynytchev, Susan K Schultz

Journal of the American Medical Informatics Association : JAMIA (2018-11-01)

<https://www.ncbi.nlm.nih.gov/pubmed/30380082>

DOI: [10.1093/jamia/ocy109](https://doi.org/10.1093/jamia/ocy109) · PMID: [30380082](https://pubmed.ncbi.nlm.nih.gov/30380082/) · PMCID: [PMC6213089](https://pubmed.ncbi.nlm.nih.gov/PMC6213089/)

54. CoGAPS: an R/C++ package to identify patterns and biological process activity in transcriptomic data

Elana J. Fertig, Jie Ding, Alexander V. Favorov, Giovanni Parmigiani, Michael F. Ochs

Bioinformatics (2010-11-01) <https://doi.org/cwqsv4>

DOI: [10.1093/bioinformatics/btq503](https://doi.org/10.1093/bioinformatics/btq503) · PMID: [20810601](https://pubmed.ncbi.nlm.nih.gov/20810601/) · PMCID: [PMC3025742](https://pubmed.ncbi.nlm.nih.gov/PMC3025742/)

55. Standard machine learning approaches outperform deep representation learning on phenotype prediction from transcriptomics data

Aaron M. Smith, Jonathan R. Walsh, John Long, Craig B. Davis, Peter Henstock, Martin R. Hodge, Mateusz Maciejewski, Xinmeng Jasmine Mu, Stephen Ra, Shanrong Zhao, ... Charles K. Fisher

BMC Bioinformatics (2020-03-20) <https://doi.org/ggpc9d>

DOI: [10.1186/s12859-020-3427-8](https://doi.org/10.1186/s12859-020-3427-8) · PMID: [32197580](https://pubmed.ncbi.nlm.nih.gov/32197580/) · PMCID: [PMC7085143](https://pubmed.ncbi.nlm.nih.gov/PMC7085143/)

56. Convolutional Neural Networks for Diabetic Retinopathy

Harry Pratt, Frans Coenen, Deborah M. Broadbent, Simon P. Harding, Yalin Zheng

Procedia Computer Science (2016) <https://doi.org/gcgk75>

DOI: [10.1016/j.procs.2016.07.014](https://doi.org/10.1016/j.procs.2016.07.014)

57. Opportunities and obstacles for deep learning in biology and medicine

Travers Ching, Daniel S. Himmelstein, Brett K. Beaulieu-Jones, Alexandr A. Kalinin, Brian T. Do, Gregory P. Way, Enrico Ferrero, Paul-Michael Agapow, Michael Zietz, Michael M. Hoffman, ... Casey S. Greene

Journal of The Royal Society Interface (2018-04-04) <https://doi.org/gddkhn>

DOI: [10.1098/rsif.2017.0387](https://doi.org/10.1098/rsif.2017.0387) · PMID: [29618526](https://pubmed.ncbi.nlm.nih.gov/29618526/) · PMCID: [PMC5938574](https://pubmed.ncbi.nlm.nih.gov/PMC5938574/)

58. Deriving disease modules from the compressed transcriptional space embedded in a deep autoencoder

Sanjiv K. Dwivedi, Andreas Tjärnberg, Jesper Tegnér, Mika Gustafsson

Nature Communications (2020-02-12) <https://doi.org/gg7krm>
DOI: [10.1038/s41467-020-14666-6](https://doi.org/10.1038/s41467-020-14666-6) · PMID: [32051402](https://pubmed.ncbi.nlm.nih.gov/32051402/) · PMCID: [PMC7016183](https://pubmed.ncbi.nlm.nih.gov/PMC7016183/)

59. DeepProfile: Deep learning of cancer molecular profiles for precision medicine

Ayşe Berceste Dincer, Safiye Celik, Naozumi Hiranuma, Su-In Lee
bioRxiv (2018-05-26) <https://doi.org/gdj2j4>
DOI: [10.1101/278739](https://doi.org/10.1101/278739)

60. A Survey on Transfer Learning

Sinno Jialin Pan, Qiang Yang
IEEE Transactions on Knowledge and Data Engineering (2010-10) <https://doi.org/bc4vws>
DOI: [10.1109/tkde.2009.191](https://doi.org/10.1109/tkde.2009.191)

61. Pathway-level information extractor (PLIER) for gene expression data

Weiguang Mao, Elena Zaslavsky, Boris M. Hartmann, Stuart C. Sealfon, Maria Chikina
Nature Methods (2019-06-27) <https://doi.org/gf75g6>
DOI: [10.1038/s41592-019-0456-1](https://doi.org/10.1038/s41592-019-0456-1) · PMID: [31249421](https://pubmed.ncbi.nlm.nih.gov/31249421/) · PMCID: [PMC7262669](https://pubmed.ncbi.nlm.nih.gov/PMC7262669/)

62. Reproducible RNA-seq analysis using recount2

Leonardo Collado-Torres, Abhinav Nellore, Kai Kammers, Shannon E Ellis, Margaret A Taub, Kasper D Hansen, Andrew E Jaffe, Ben Langmead, Jeffrey T Leek
Nature Biotechnology (2017-04-01) <https://doi.org/gf75hp>
DOI: [10.1038/nbt.3838](https://doi.org/10.1038/nbt.3838) · PMID: [28398307](https://pubmed.ncbi.nlm.nih.gov/28398307/) · PMCID: [PMC6742427](https://pubmed.ncbi.nlm.nih.gov/PMC6742427/)

63. MultiPLIER: A Transfer Learning Framework for Transcriptomics Reveals Systemic Features of Rare Disease

Jaclyn N. Taroni, Peter C. Grayson, Qiwen Hu, Sean Eddy, Matthias Kretzler, Peter A. Merkel, Casey S. Greene
Cell Systems (2019-05) <https://doi.org/gf75g5>
DOI: [10.1016/j.cels.2019.04.003](https://doi.org/10.1016/j.cels.2019.04.003) · PMID: [31121115](https://pubmed.ncbi.nlm.nih.gov/31121115/) · PMCID: [PMC6538307](https://pubmed.ncbi.nlm.nih.gov/PMC6538307/)

64. Transcription of proteinase 3 and related myelopoiesis genes in peripheral blood mononuclear cells of patients with active Wegener's granulomatosis

Chris Cheadle, Alan E. Berger, Felipe Andrade, Regina James, Kristen Johnson, Tonya Watkins, Jin Kyun Park, Yu-Chi Chen, Eva Ehrlich, Marissa Mullins, ... Stuart M. Levine
Arthritis & Rheumatism (2010-02-12) <https://doi.org/chfbtv>
DOI: [10.1002/art.27398](https://doi.org/10.1002/art.27398) · PMID: [20155833](https://pubmed.ncbi.nlm.nih.gov/20155833/) · PMCID: [PMC2887718](https://pubmed.ncbi.nlm.nih.gov/PMC2887718/)

65. How transferable are features in deep neural networks?

Jason Yosinski, Jeff Clune, Yoshua Bengio, Hod Lipson
arXiv (2014-12-09) <https://arxiv.org/abs/1411.1792>

66. {unav}

Rich Caruana
Machine Learning (1997) <https://doi.org/d3gsgj>
DOI: [10.1023/a:1007379606734](https://doi.org/10.1023/a:1007379606734)

67. Modeling Industrial ADMET Data with Multitask Networks

Steven Kearnes, Brian Goldman, Vijay Pande
arXiv (2017-01-16) <https://arxiv.org/abs/1606.08793>

68. The Effectiveness of Multitask Learning for Phenotyping with Electronic Health Records Data

Daisy Yi Ding, Chloé Simpson, Stephen Pfohl, Dave C. Kale, Kenneth Jung, Nigam H. Shah
arXiv (2019-01-08) <https://arxiv.org/abs/1808.03331>

69. Multi-task Learning via Adaptation to Similar Tasks for Mortality Prediction of Diverse Rare Diseases

Luchen Liu, Zequn Liu, Haoxian Wu, Zichang Wang, Jianhao Shen, Yiping Song, Ming Zhang
arXiv (2020-04-11) <https://arxiv.org/abs/2004.05318v2>

70. Generalizing from a Few Examples: A Survey on Few-Shot Learning

Yaqing Wang, Quanming Yao, James Kwok, Lionel M. Ni
arXiv (2019-04-10) <https://arxiv.org/abs/1904.05046v3>

71. Low Data Drug Discovery with One-Shot Learning

Han Altae-Tran, Bharath Ramsundar, Aneesh S. Pappu, Vijay Pande
ACS Central Science (2017-04-03) <https://doi.org/f95dnd>
DOI: [10.1021/acscentsci.6b00367](https://doi.org/10.1021/acscentsci.6b00367) · PMID: [28470045](https://pubmed.ncbi.nlm.nih.gov/28470045/) · PMCID: [PMC5408335](https://pubmed.ncbi.nlm.nih.gov/PMC5408335/)

72. Automatic detection of rare pathologies in fundus photographs using few-shot learning

Gwenolé Quéléec, Mathieu Lamard, Pierre-Henri Conze, Pascale Massin, Béatrice Cochener
arXiv (2019-07-22) <https://arxiv.org/abs/1907.09449v3>
DOI: [10.1016/j.media.2020.101660](https://doi.org/10.1016/j.media.2020.101660)

73. An Overview of Multi-Task Learning in Deep Neural Networks

Sebastian Ruder
arXiv (2017-06-19) <https://arxiv.org/abs/1706.05098>

74. A Survey on Multi-Task Learning

Yu Zhang, Qiang Yang
arXiv (2017-07-25) <https://arxiv.org/abs/1707.08114v2>