

# Semisimplicial Types in Internal CwFs

Joshua Chen and Nicolai Kraus

TYPES 2021

# Semisimplicial Types

A *semisimplicial type* is a semisimplicial object in “the” category of types.

Presented by:

$$A_0 : \text{Type}$$

$$A_1 : A_0 \times A_0 \rightarrow \text{Type}$$

$$A_2 : \left( \sum_{x, y, z : A_0} A_1(x, y) \times A_1(x, z) \times A_1(y, z) \right) \rightarrow \text{Type}$$

$$\vdots$$

$$A_n : \partial \Delta^n(A_0, \dots, A_{n-1}) \rightarrow \text{Type}$$

$$\vdots$$

# Semisimplicial Types

Why? [Kra18]

- Building block for homotopical/higher categorical structures. [KS17; CK17; Kra21]
- Example of higher coherence we don't know how to internalize.

This is okay:

$$\text{SST}(n) := \text{type of tuples } (A_0, \dots, A_n)$$

[Bru; Kra14]

# Semisimplicial Types

Why? [Kra18]

- Building block for homotopical/higher categorical structures. [KS17; CK17; Kra21]
- Example of higher coherence we don't know how to internalize.

This is okay:

$$\text{SST}(n) := \text{type of tuples } (A_0, \dots, A_n)$$

[Bru; Kra14]

## Open question

Define

$$\text{SST} : \mathbb{N} \rightarrow \text{Type}_1$$

in HoTT. *Can we construct semisimplicial types?* [Her15; ACK16]

# HoTT in HoTT

## Open question

Define the syntax of HoTT in HoTT together with interpretations into itself. *Can HoTT eat itself?* [Shu14; EX14; Buc17]

# HoTT in HoTT

## Open question

Define the syntax of HoTT in HoTT together with interpretations into itself. *Can HoTT eat itself?* [Shu14; EX14; Buc17]

## Theorem (expected)

If HoTT can eat itself then we can construct semisimplicial types.

# Set-Based Internal CwFs

An *internal CwF*  $\mathcal{C}$  is a category with families [Dyb95] internal to HoTT. Consists of

$$\text{Con} : \text{Type}$$
$$\text{Sub} : \text{Con} \rightarrow \text{Con} \rightarrow \text{Type}$$
$$\text{Ty} : \text{Con} \rightarrow \text{Type}$$
$$\text{Tm} : (\Gamma : \text{Con}) \rightarrow \text{Ty } \Gamma \rightarrow \text{Type}$$
$$\vdots$$

$\mathcal{C}$  is *set-based* if  $\text{Con}$ ,  $\text{Sub}$ ,  $\text{Ty}$ ,  $\text{Tm}$  are h-sets.

# SST in Internal CwFs

## Current work in progress

Construct semisimplicial types in set-based internal CwFs  $\mathcal{C}$  with  $\hat{\Pi}$ ,  $\hat{\Sigma}$  and  $U$  (and  $\mathbb{1}$ ?).  
i.e. Define

$$\text{SST}_{\mathcal{C}} : \mathbb{N} \rightarrow \text{Con}$$

where  $\text{SST}_{\mathcal{C}} n$  is the context

$$A_0 : U, A_1 : A_0 \hat{\times} A_0 \hat{\rightarrow} U, \dots, A_n : \partial\Delta^n \hat{\rightarrow} U$$



# Technicalities

Sketch of construction:

Assume set-based internal CwF  $\mathcal{C} = (\text{Con}, \text{Sub}, \text{Ty}, \text{Tm}, \hat{\Pi}, \hat{\Sigma}, U, \dots)$ . Define

$$\text{SST} : \mathbb{N} \rightarrow \text{Con} \quad \dots \quad \text{SST}_{k+2} := \text{SST}_{k+1}, \underbrace{\text{Sk}_{(k+2, \dots)} \xrightarrow{\hat{\gamma}} U}_{\text{Fillers}}$$

# Technicalities

Sketch of construction:

Assume set-based internal CwF  $\mathcal{C} = (\text{Con}, \text{Sub}, \text{Ty}, \text{Tm}, \hat{\Pi}, \hat{\Sigma}, U, \dots)$ . Define

$$\text{SST} : \mathbb{N} \rightarrow \text{Con} \quad \dots \quad \text{SST}_{k+2} := \text{SST}_{k+1}, \underbrace{\text{Sk}_{(k+2, \dots)} \xrightarrow{\hat{\cdot}} U}_{\text{Fillers}}$$

mutually with

$$\text{Sk} : (b, h, t : \mathbb{N}) \rightarrow \text{Ty}(\text{SST}_{h+1})$$

# Technicalities

Sketch of construction:

Assume set-based internal CwF  $\mathcal{C} = (\text{Con}, \text{Sub}, \text{Ty}, \text{Tm}, \hat{\Pi}, \hat{\Sigma}, U, \dots)$ . Define

$$\text{SST} : \mathbb{N} \rightarrow \text{Con} \quad \dots \quad \text{SST}_{k+2} := \text{SST}_{k+1}, \underbrace{\text{Sk}_{(k+2, \dots)} \xrightarrow{\hat{}} U}_{\text{Fillers}}$$

mutually with

$$\text{Sk} : (b, h, t : \mathbb{N}) \rightarrow \text{Ty}(\text{SST}_{h+1}) \quad \dots \quad \text{Sk}_{(b, h, t+1)} := \widehat{\sum_{x : \text{Sk}_{(b, h, t)}}} \underbrace{A_{h+1}(\text{Sk}_{\text{m}}(\dots, x))}_{\text{Fill the } (t+1)^{\text{th}} \text{ face}}$$

# Technicalities

Sketch of construction:

Assume set-based internal CwF  $\mathcal{C} = (\text{Con}, \text{Sub}, \text{Ty}, \text{Tm}, \hat{\Pi}, \hat{\Sigma}, U, \dots)$ . Define

$$\text{SST} : \mathbb{N} \rightarrow \text{Con} \quad \dots \quad \text{SST}_{k+2} := \text{SST}_{k+1}, \underbrace{\text{Sk}_{(k+2, \dots)} \xrightarrow{\hat{}} U}_{\text{Fillers}}$$

mutually with

$$\text{Sk} : (b, h, t : \mathbb{N}) \rightarrow \text{Ty}(\text{SST}_{h+1}) \quad \dots \quad \text{Sk}_{(b, h, t+1)} := \widehat{\sum_{x : \text{Sk}_{(b, h, t)}}} \underbrace{A_{h+1}(\text{Skm}(\dots, x))}_{\text{Fill the } (t+1)^{\text{th}} \text{ face}}$$

and

$$\begin{aligned} \text{Skm} : \{b, h, t, k : \mathbb{N}\} \\ &\rightarrow (f : \Delta_+(k, b)) \\ &\rightarrow \text{Tm}(\text{Sk}_{(b, h, t)}) \rightarrow \text{Tm}(\text{Sk}_{(b, h, t) \cap f}) \end{aligned}$$

# SST in Internal CwFs

## Theorem (expected)

If HoTT can eat itself then we can construct semisimplicial types.

Proof.

An interpretation of the syntax of (HoTT + a universe) as an internal set-based CwF  $\mathcal{C}$  gives

$$\text{HoTT-Con} : \text{Con} \rightarrow \text{Type}_1.$$



# SST in Internal CwFs

## Theorem (expected)

If HoTT can eat itself then we can construct semisimplicial types.

Proof.

An interpretation of the syntax of (HoTT + a universe) as an internal set-based CwF  $\mathcal{C}$  gives

$$\text{HoTT-Con} : \text{Con} \rightarrow \text{Type}_1.$$

Then we have

$$\text{SST} := \text{HoTT-Con} \circ \text{SST}_{\mathcal{C}} : \mathbb{N} \rightarrow \text{Type}_1.$$



## References I

- [ACK16] Thorsten Altenkirch, Paolo Capriotti and Nicolai Kraus. “Extending Homotopy Type Theory with Strict Equality”. In: *25th EACSL Annual Conference on Computer Science Logic (CSL 2016)*. Ed. by Jean-Marc Talbot and Laurent Regnier. Vol. 62. Leibniz International Proceedings in Informatics (LIPIcs). Dagstuhl, Germany: Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, 2016, 21:1–21:17. ISBN: 978-3-95977-022-4. DOI: 10.4230/LIPIcs.CSL.2016.21. URL: <http://drops.dagstuhl.de/opus/volltexte/2016/6561>.
- [Bru] Guillaume Brunerie. *A Python script generating Agda code for semi-simplicial types, truncated at any given level*. Accessed 23 Apr 2021. URL: <https://guillaumebrunerie.github.io/other/semisimplicial.py>.
- [Buc17] Ulrik Buchholtz. *Formalizing type theory in type theory using nominal techniques*. Invited talk at the Workshop on Homotopy Type Theory/Univalent Foundations. Accessed 9 Jun 2021. 2017. URL: <https://hott-uf.github.io/2017/slides/Buchholtz.pdf>.
- [CK17] Paolo Capriotti and Nicolai Kraus. “Univalent Higher Categories via Complete Semi-Segal Types”. In: *Proceedings of the ACM on Programming Languages* 2 (2017). Full version available at <https://arxiv.org/abs/1707.03693>, 44:1–44:29. ISSN: 2475-1421. DOI: 10.1145/3158132. URL: <http://doi.acm.org/10.1145/3158132>.
- [Dyb95] Peter Dybjer. “Internal type theory”. In: *Types for Proofs and Programs (TYPES)*. Ed. by Stefano Berardi and Mario Coppo. Vol. 1158. Lecture Notes in Computer Science. Springer-Verlag, 1995, pp. 120–134. ISBN: 978-3-540-70722-6. DOI: 10.1007/3-540-61780-9\_66.

## References II

- [EX14] Martín Hötzel Escardó and Chuangjie Xu. *Type theory eating itself?* Accessed 9 Jun 2021. 2014. URL: <https://www.cs.bham.ac.uk/~mhe/TT-perhaps-eating-itself/TT-perhaps-eating-itself.html>.
- [Her15] Hugo Herbelin. “A dependently-typed construction of semi-simplicial types”. In: *Mathematical Structures in Computer Science* 25.5 (2015), pp. 1116–1131. DOI: 10.1017/S0960129514000528.
- [Kra14] Nicolai Kraus. *A Haskell script to generate the type of  $n$ -truncated semi-simplicial types*. Available at <https://nicolaikraus.github.io/docs/generateSemiSimp.hs>. Accessed 23 Apr 2021. 2014.
- [Kra18] Nicolai Kraus. *On the Role of Semisimplicial Types*. Extended abstract presented at the 24th International Conference on Types for Proofs and Programs. Accessed 9 Jun 2021. 2018. URL: [https://nicolaikraus.github.io/docs/on\\_semisimplicial\\_types.pdf](https://nicolaikraus.github.io/docs/on_semisimplicial_types.pdf).
- [Kra21] Nicolai Kraus. *Internal  $\infty$ -Categorical Models of Dependent Type Theory: Towards 2LTT Eating HoTT*. To appear, 36th Annual Symposium on Logic in Computer Science. 2021. arXiv: 2009.01883 [cs.LO].
- [KS17] Nicolai Kraus and Christian Sattler. *Space-Valued Diagrams, Type-Theoretically (Extended Abstract)*. 2017. arXiv: 1704.04543 [math.LO]. URL: <https://arxiv.org/abs/1704.04543v1>.



## References III

- [Shu14] Michael Shulman. *Homotopy Type Theory should eat itself (but so far, it's too big to swallow)*. Blog post accessed 7 Jun 2021. 3 Mar. 2014. URL: <https://homotopytypetheory.org/2014/03/03/hott-should-eat-itself>.