
LWA Correlator

Release 1.0.0

Jack Hickish

Dec 17, 2020

CONTENTS:

1	Installation	1
1.1	Get the Source Code	1
1.2	Install Prerequisites	1
1.3	Install the Pipeline	3
2	Introduction	5
3	Hardware	7
4	Pipeline	9
5	Software	11
5.1	High-Level Parameters	11
5.2	Bifrost Block Description	11
6	Output Data Formats	41
6.1	Full Correlation Packets	41
6.2	Partial Correlation Packets	42
6.3	VLBI Beam	43
6.4	Integrated Beams	43
7	Control Interface	45
7.1	Capture Thread (blockname: capture)	45
7.2	Copy Thread (blockname: gpucopy)	46
7.3	Correlation Thread (blockname: corr)	46
7.4	Visibility Sub-Select Thread (blockname: corrsubsel)	47
7.5	Visibility Integrator (blockname: corrace)	48
7.6	Beamformer (blockname: beamform)	49
8	Indices and tables	51
	Index	53

INSTALLATION

The LWA 352 Correlator/Beamformer pipeline is available at <https://github.com/realtimeradio/caltech-bifrost-dsp>. Follow the following instructions to download and install the pipeline.

Specify the build directory by defining the `BUILDDIR` environment variable, eg:

```
export BUILDDIR=~/.src/  
mkdir -p $BUILDDIR
```

1.1 Get the Source Code

Clone the repository and its dependencies with:

```
# Clone the main repository  
cd $BUILDDIR  
git clone https://github.com/realtimeradio/caltech-bifrost-dsp  
# Clone relevant submodules  
cd caltech-bifrost-dsp  
git submodule init  
git submodule update
```

1.2 Install Prerequisites

The following libraries should be installed via the Ubuntu package manager:

```
apt install exuberant-ctags build-essential autoconf libtool exuberant-ctags libhwloc-  
↳dev python3-venv
```

The following 3rd party libraries must also be obtained and installed:

1.2.1 CUDA

CUDA can be installed as follows:

```
# Make a directory for the cuda source
mkdir -p $BUILDDIR/cuda
cd $BUILDDIR/cuda
# Download the CUDA installer
wget http://developer.download.nvidia.com/compute/cuda/11.0.2/local_installers/cuda_
↪11.0.2_450.51.05_linux.run

# blacklist nouveau drivers before installing nvidia drivers
sudo su
echo "blacklist nouveau" > /etc/modprobe.d/blacklist-nouveau.conf
echo "options nouveau modeset=0" >> /etc/modprobe.d/blacklist-nouveau.conf
update-initramfs -u
exit

# reboot the machine and nouveau drivers [hopefully] won't start
# reboot now
```

After rebooting, install the CUDA libraries

```
cd $BUILDDIR/cuda
sudo sh cuda_11.0.2_450.51.05_linux.run
# Add CUDA executables to $PATH
echo "export PATH=/usr/local/cuda/bin:${PATH}" >> ~/.bashrc
source ~/.bashrc
```

This CUDA install script will take a minute to unzip and run the installer. If it fails, log messages can be found in `/var/log/nvidia-installer.log` and `/var/log/cuda-installer.log`.

1.2.2 IB Verbs

The LWA pipeline uses Infiniband Verbs for fast UDP packet capture. The recommended version is 4.9 LTS. This can be obtained from https://www.mellanox.com/support/mlnx-ofed-matrix?mtag=linux_sw_drivers

1.2.3 xGPU

xGPU is submoduled in the main pipeline repository, to ensure version compatibility. Install with:

```
cd $BUILDDIR/caltech-bifrost-dsp
./install_xgpu
```

1.2.4 Bifrost

Bifrost is submoduled in the main pipeline repository, to ensure version compatibility.

The version provided requires Python ≥ 3.5 . It is recommended that the bifrost package is installed within a Python version environment.

To install bifrost:

```
cd $BUILDDIR/caltech-bifrost-dsp/bifrost
make
make install
```

1.3 Install the Pipeline

After installing the prerequisites above, the LWA pipeline can be installed with

```
cd $BUILDDIR/caltech-lwa-dsp/pipeline
# Be sure to run the installation in the
# appropriate python environment!
python setup.py install
```

Author Jack Hickish

INTRODUCTION

The LWA-352 X-Engine processing system performs correlation, beamforming, and triggered voltage recording for the LWA-352 array. This document outlines the hardware (Section [sec:hardware]) and software (Section [sec:software]) which makes up the X-Engine, and details the user control interface (Section [sec:api]).

HARDWARE

The LWA-352 X-engine system comprises 9 1U dual-socket Silicon Mechanics *Rackform R353.v7* servers, each hosting a pair of Nvidia GPUs and solid state memory buffers. Hardware specifications are given in Table [tab:hardware].

Hardware	Model	Notes
Server	Supermicro 1029GQ-TRT	Re-branded as Silicon Mechanics Rackform R353.v7
Motherboard	Supermicro X11 DCQ	
CPU	dual Intel Xeon Scalable Silver 4210R	2.4 GHz, 10 core, 100W TDP
RAM	768 GB PC4-23400	12 x 64 GB; 2933 MHz DDR4; ECC RDIMM
NIC	Mellanox MCX515A-GCAT	ConnectX-5 EN MCX515A-GCAT (1x QSFP28); PCIe 3.0x16
NVMe Controllers	Asus Hyper M.2 X16 Card V2	2 cards per server
NVMe Memory	8TB Samsung 970 Evo Plus	8 x 1 TB
GPU	Nvidia RTX 2080Ti	2 cards per server

PIPELINE

The pipeline is launched using the `lwa352-pipeline.py` script. This has the following options:

```
usage: lwa352-pipeline.py [-h] [-f] [-c CONFIGFILE] [-l LOGFILE] [-v]
                        [--fakesource] [--nodata] [--testdatain TESTDATAIN]
                        [--testdatacorr TESTDATACORR]
                        [--testdatacorr_acc_len TESTDATACORR_ACC_LEN]
                        [-a CORR_ACC_LEN] [--nocorr] [--nobeamform]
                        [--nogpu] [--ibverbs] [-G GPU] [-P PIPELINEID]
                        [-C CORES] [-q] [--testcorr] [--useetcd]
                        [--etcdhost ETCDHOST] [--ip IP]
                        [--bufgbytes BUFGBYTES]
                        [--target_throughput TARGET_THROUGHPUT]

LWA-SV ADP DRX Service

optional arguments:
  -h, --help                show this help message and exit
  -f, --fork                Fork and run in the background (default: False)
  -c CONFIGFILE, --configfile CONFIGFILE
                           Specify config file (default: adp_config.json)
  -l LOGFILE, --logfile LOGFILE
                           Specify log file (default: None)
  -v, --verbose            Increase verbosity (default: 0)
  --fakesource             Use a dummy source for testing (default: False)
  --nodata                 Don't generate data in the dummy source (faster)
                           (default: False)
  --testdatain TESTDATAIN
                           Path to input test data file (default: None)
  --testdatacorr TESTDATACORR
                           Path to correlator output test data file (default:
                           None)
  --testdatacorr_acc_len TESTDATACORR_ACC_LEN
                           Number of accumulations per sample in correlator test
                           data file (default: 2400)
  -a CORR_ACC_LEN, --corr_acc_len CORR_ACC_LEN
                           Number of accumulations to start accumulating in the
                           slow correlator (default: 240000)
  --nocorr                 Don't use correlation threads (default: False)
  --nobeamform            Don't use beamforming threads (default: False)
  --nogpu                 Don't use any GPU threads (default: False)
  --ibverbs               Use IB verbs for packet capture (default: False)
  -G GPU, --gpu GPU       Which GPU device to use (default: 0)
  -P PIPELINEID, --pipelineid PIPELINEID
                           Pipeline ID. Useful if you are running multiple
```

(continues on next page)

(continued from previous page)

```
pipelines on a single machine (default: 0)
-C CORES, --cores CORES      Comma-separated list of CPU cores to use (default:
                                0,1,2,3,4,5,6,7)
-q, --quiet                  Decrease verbosity (default: 0)
--testcorr                   Compare the GPU correlation with CPU. SLOW!! (default:
                                False)
--useetcd                   Use etcd control/monitoring server (default: False)
--etcdhost ETCDBHOST        Host serving etcd functionality (default: etcdhost)
--ip IP                      IP address to which to bind (default: 100.100.100.101)
--bufgbytes BUFGBYTES       Number of GBytes to buffer for transient buffering
                                (default: 4)
--target_throughput TARGET_THROUGHPUT
                                Target throughput when using --fakesource (default:
                                1000.0)
```

SOFTWARE

The LWA-352 pipeline comprises ?? independent processes, briefly described below.

1. `capture`: Receive F-engine packets and correctly arrange in buffers for downstream processing. Monitor and record missing packets and network performance statistics.
2. `copy`: Transfer blocks of data from CPU to GPU, for high-performance computation.
3. `triggered_dump`: Buffer large quantities of time-domain data for triggered dump to disk.
4. `corr`: Correlate data using the `xGPU` library.
5. `corr_output_full`: Output full, accumulated visibility matrices.
6. `corrsubsel`: Down-select a sub-set of the complete visibility matrices.
7. `corr_output_part`: Output subselected visibilities as UDP/IP streams.
8. `beamform`: Form multiple voltage beams.
9. `beamform_vlbi_output`: Package and transmit multiple voltage beams for VLBI purposes.
10. `beamform_sum_beams`: Form integrated power-spectra for multiple beams.
11. `beamform_output`: Output accumulated power beams.

5.1 High-Level Parameters

- `GSize`: “Gulp size” – the number of samples processed per batch by a processing block.

5.2 Bifrost Block Description

The bifrost pipelining framework divides streams of data into *sequences*, each of which has a header describing the stream. Different processing blocks act to perform operations on streams, and may modify sequences and their headers.

Here we summarize the bifrost blocks in the LWA-352 pipeline, and the headers they require (for input sequences) and provide (for output sequences).

5.2.1 capture

```
class lwa352_pipeline.blocks.capture_block.Capture (log,                fs_hz=196000000,
                                                chan_bw_hz=23925.78125,
                                                input_to_ant=None, nstand=352,
                                                npol=2,      system_nchan=2912,
                                                *args, **kwargs)
```

Functionality

This block receives UDP/IP data from an Ethernet network and writes it to a bifrost memory buffer.

New Sequence Condition

This block starts a new sequence each time the incoming packet stream timestamp changes in an unexpected way. For example, if a large block of timestamps are missed a new sequence will be started. Or, if the incoming timestamps decrease (which might happen if the upstream transmitters are reset) a new sequence is started.

Input Header Requirements

This block is a bifrost source, and thus has no input header requirements.

Output Headers

Output header fields are as follows:

Field	Format	Units	Description
time_tag	int		Arbitrary integer, incremented with each new sequence.
sync_time	int	UNIX seconds	Synchronization time (corresponding to spectrum sequence number 0)
seq0	int		Spectra number for the first sample in this sequence
chan0	int		Channel index of the first channel in this sequence
nchan	int		Number of channels in the sequence
system_nchan	int		The total number of channels in the system (i.e., the number of channels across all pipelines)
fs_hz	double	Hz	Sampling frequency of ADCs
sfreq	double	Hz	Center frequency of first channel in the sequence
bw_hz	int	Hz	Bandwidth of the sequence
nstand	int		Number of stands (antennas) in the sequence
npol	int		Number of polarizations per stand in the sequence
complex	bool		True if the data are complex, False otherwise
nbit	int		Number of bits per sample (or per real/imag part if the samples are complex)
input_to_ant	list[int]		List of input to stand/pol mappings with dimensions [nstand x npol, 2]. E.g. if entry N of this list has value [S, P] then the N-th correlator input is stand S, polarization P.
ant_to_input	list[ints]		List of stand/pol to correlator input number mappings with dimensions [nstand, npol]. E.g. if entry [S,P] of this list has value N then stand S, polarization P of the array is the N-th correlator input

Data Buffers

Input data buffer: None

Output data buffer: Complex 4-bit data with dimensions (slowest to fastest) Time x Freq x Stand x Polarization

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **fs_hz** (*int*) – Sampling frequency, in Hz, of the upstream ADCs
- **chan_bw_hz** (*float*) – Bandwidth of a single frequency channel in Hz.
- **nstand** (*int*) – Number of stands in the array.
- **npol** (*int*) – Number of polarizations per antenna stand.
- **input_to_ant** – An map of correlator input to station / polarization. Provided as an `[nstand x npol, 2]` array such that if `input_to_ant[i] == [S,P]` then the *i*-th correlator input is stand *S*, polarization *P*.

Keyword Arguments

Parameters

- **fmt** (*string*) – The string identifier of the packet format to be received. E.g “snap2”.
- **sock** (*bifrost.udp_socket.UDPSocket*) – Input UDP socket on which to receive.
- **ring** (*bifrost.ring.Ring*) – bifrost output data ring
- **core** (*int*) – CPU core to which this block should be bound.
- **nsrc** (*int*) – Number of packet sources. This might mean the number of boards transmitting packets, or, in the case that it takes multiple packets from each board to send a complete set of data, this could be a multiple of the number of source boards.
- **src0** (*int*) – The first source to transmit to this block.
- **system_nchan** (*int*) – The total number of channels in the complete, multi-pipeline system. This is only used to set sequence headers for downstream packet header generators which require this information.
- **max_payload_size** (*int*) – The maximum payload size, in bytes, of the UDP packets to be received.
- **buffer_ntime** (*int*) – The number of time samples to be buffered into the output data ring buffer before it is marked full.
- **utc_start** (*datetime.datetime*) – ?The time at which the block should begin receiving. Set to `datetime.datetime.now()` to start immediately.
- **ibverbs** (*Bool*) – Boolean parameter which, if true, will cause this block to use an Infiniband Verbs packet receiver. If false, or not provided, a standard UDP socket will be used.

5.2.2 copy

```
class lwa352_pipeline.blocks.copy_block.Copy(log, iring, oring, ntime_gulp=2500,
                                             buffer_multiplier=1, guarantee=True,
                                             core=-1, nbyte_per_time=129536, gpu=-1,
                                             buf_size_gbytes=None)
```

Functionality

This block copies data from one bifrost buffer to another. The buffers may be in CPU or GPU space.

New Sequence Condition

This block has no new sequence condition. It will output a new sequence only when the upstream sequence changes.

Input Header Requirements

This block has no input header requirements.

Output Headers

This block copies input headers downstream, adding none of its own.

Data Buffers

Input Data Buffer: A bifrost ring buffer of at least `nbyte_per_time` x `ntime_gulp` bytes size.

Output Data Buffer: A bifrost ring buffer whose size is set by the `buffer_multiplier` and/or `buf_size_gbytes` parameters.

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring
- **oring** (*bifrost.ring.Ring*) – bifrost output data ring
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **gpu** (*int*) – GPU device ID to which this block should copy to/from. A value of -1 indicates no binding. This parameter need not be provided if neither input nor output data rings are allocated in GPU (or GPU-pinned) memory.
- **ntime_gulp** (*int*) – Number of time samples to copy with each gulp.
- **nbyte_per_time** (*int*) – Number of bytes per time sample. The total number of bytes read with each gulp is `nbyte_per_time` x `ntime_gulp`.
- **buffer_multiplier** (*int*) – The block will set the output buffer size to be 4 x `buffer_multiplier` times the size of a single data gulp. If `buf_size_gbytes` is also provided then the output memory block size is required to be a multiple of `buffer_multiplier` x `ntime_gulp` x `nbyte_per_time` bytes.
- **buf_size_gbytes** (*int*) – If provided, attempt to set the output buffer size to `buf_size_gbytes` Gigabytes (10**9 Bytes). Round down the buffer such that the chosen size is the largest integer multiple of `buffer_multiplier` x `ntime_gulp` x `nbyte_per_time` which is less than 10**9 x `buf_size_gbytes`. Note that bifrost (seems to) round up buffer sizes to an integer power of two number of bytes, so be careful about accidentally allocating more memory than you have!

5.2.3 triggered_dump

```
class lwa352_pipeline.blocks.triggered_dump_block.TriggeredDump(log,      iring,
                                                                ntime_gulp=2500,
                                                                ntime_per_file=1000000,
                                                                guaran-
                                                                tee=True,
                                                                core=-      1,
                                                                nbyte_per_time=135168,
                                                                etcd_client=None,
                                                                dump_path='/fastdata')
```

Functionality

This block writes data from an input bifrost ring buffer to disk, when triggered.

New Sequence Condition

This block is a bifrost sink, and generates no output sequences.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq 0	int		Spectra number for the first sample in the input sequence

The field `seq` if provided by the upstream block will be overwritten.

Output Headers

This block is a bifrost sink, and generates no output headers. Headers provided by the upstream block are written to this block's data files, with the exception of the `seq` field, which is overwritten.

Data Buffers

Input Data Buffer: A bifrost ring buffer of at least `nbyte_per_time` x `ntime_gulp` bytes size.

Output Data Buffer: None

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **ntime_gulp** (*int*) – Number of time samples to copy with each gulp.
- **nbyte_per_time** (*int*) – Number of bytes per time sample. The total number of bytes read with each gulp is `nbyte_per_time` x `ntime_gulp`.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If None, do not use runtime control.
- **dump_path** – Root path to directory where dumped data should be stored. This parameter can be overridden by runtime control commands.

- `ntime_per_file(int)` – Number of time samples of data to write to each output file.
This parameter can be overridden by runtime control commands.

Runtime Control and Monitoring

This block accepts the following command fields:

Field	Format	Units	Description
command	string		Commands: Trigger: Begin capturing data ASAP Abort: Abort a capture currently in progress and delete its data Stop: Stop a capture currently in progress
ntime_per_sample	int	samples	Number of time samples to capture in each file.
nfile	int		Number of files to capture per trigger event.
dump_path	str		Root path to directory where data should be stored.

Output Data Format

When triggered, this block will output a series of `nfile` data files, each containing `ntime_per_file` time samples of data.

File names begin `lwa-dump-` and are suffixed by the trigger time as a floating-point UNIX timestamp with two decimal points of precision, a file extension “.tbf”, and a file number “.N” where N runs from 0 to `nfile` – 1. For example: `lwa-dump-1607434049.77.tbf.0`.

The files have the following structure:

- The first 4 bytes contains a little-endian 32-bit integer, `hsize`, describing the number of bytes of subsequent header data.
- The following 4 bytes contains a little-endian 32-bit integer, `hblock_size` describing the size of header block which precedes the data payload in the file.
- Bytes 8 to 8 + `hsize` contain the json-encoded header of the bifrost sequence which is contained in the payload of this file, with an additional `seq` keyword, which indicates the spectra number of the first spectra in this data file.
- Bytes `hblock_size` to EOF contain data in the shape and format of the input bifrost data buffer.

Output data files can thus be read with:

```
import struct
with open(FILENAME, "rb") as fh:
    hsize = struct.unpack('<I', fh.read(4))
    hblock_size = struct.unpack('<I', fh.read(4))
    header = json.loads(fh.read(hsize))
    fh.seek(hblock_size)
    data = fh.read() # read to EOF
```

5.2.4 corr

```
class lwa352_pipeline.blocks.corr_block.Corr(log, iring, oring, ntime_gulp=2500,
                                             guarantee=True, core=- 1, nchan=192,
                                             npol=2, nstand=352, acc_len=2400,
                                             gpu=- 1, test=False, etcd_client=None,
                                             autostartat=0, ant_to_input=None)
```

Functionality

This block reads data from a GPU-side bifrost ring buffer and feeds it to xGPU for correlation, outputting results to another GPU-side buffer.

New Sequence Condition

This block starts a new sequence each time a new integration configuration is loaded or the upstream sequence changes.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence

Output Headers

This block passes headers from the upstream block with the following modifications:

Field	Format	Units	Description
seq0	int		Spectra number for the <i>first</i> sample in the integrated output
acc_len	int		Number of spectra integrated into each output sample by this block
ant_to_input	list of ints		This header is removed from the sequence
input_to_ant	list of ints		This header is removed from the sequence

Data Buffers

Input Data Buffer: A GPU-side bifrost ring buffer of 4+4 bit complex data in order: time x channel x stand x polarization.

Each gulp of the input buffer reads `ntime_gulp` samples, which should match *both* the xGPU compile-time parameters `NTIME` and `NTIME_PIPE`.

Output Data Buffer: A GPU-side bifrost ring buffer of 32+32 bit complex integer data. This buffer is in the xGPU triangular matrix order: time x channel x complexity x baseline.

The output buffer is written in single accumulation blocks (an integration of `acc_len` input time samples).

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **oring** (*bifrost.ring.Ring*) – bifrost output data ring. This should be on the GPU.

- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **gpu** (*int*) – GPU device which this block should target. A value of -1 indicates no binding
- **ntime_gulp** (*int*) – Number of time samples to copy with each gulp.
- **nchan** (*int*) – Number of frequency channels per time sample. This should match the xGPU NFREQUENCY compile-time parameter.
- **nstand** (*int*) – Number of stands per time sample. This should match the xGPU NSTATION compile-time parameter.
- **npol** (*int*) – Number of polarizations per stand. This should match the xGPU NPOL compile-time parameter.
- **acc_len** (*int*) – Accumulation length per output buffer write. This should be an integer multiple of the input gulp size `ntime_gulp`. This parameter can be updated at runtime.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If None, do not use runtime control.
- **test** (*Bool*) – If True, run a CPU correlator in parallel with xGPU and verify the output. Beware, the (Python!) CPU correlator is *very* slow.
- **autostartat** (*int*) – The start time at which the correlator should automatically being correlating without intervention of the runtime control system. Use the value -1 to cause integration to being on the next gulp.
- **ant_to_input** (*nstand x npol list of ints*) – an [nstand, npol] list of input IDs used to map stand/polarization *S, P* to a correlator input. This allows the block to pass this information to downstream processors. *This functionality is currently unused*

Runtime Control and Monitoring

This block accepts the following command fields:

Field	Format	Units	Description
<code>acc_len</code>	<code>int</code>	<code>samples</code>	Number of samples to accumulate. This should be a multiple of <code>ntime_gulp</code>
<code>start_time</code>	<code>int</code>	<code>samples</code>	The desired first time sample in an accumulation. This should be a multiple of <code>ntime_gulp</code> , and should be related to GPS time through external knowledge of the spectra count origin (aka SNAP <i>sync time</i>). The special value -1 can be used to force an immediate start of the correlator on the next input gulp.

5.2.5 corr_acc

```
class lwa352_pipeline.blocks.corr_acc_block.CorrAcc(log, iring, oring, guarantee=True, core=-1, nchan=192,
                                                    npol=2,          nstand=352,
                                                    acc_len=24000,  gpu=-1,
                                                    etcd_client=None, autostart=0)
```

Functionality

This block reads data from a GPU-side bifrost ring buffer and accumulates it in an internal GPU buffer. The accumulated data are then copied to an output ring buffer.

New Sequence Condition

This block starts a new sequence each time a new integration configuration is loaded or the upstream sequence changes.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
acc_len	int		Number of spectra integrated into each output sample by the upstream processing

Output Headers

This block passes headers from the upstream block with the following modifications:

Field	Format	Units	Description
seq0	int		Spectra number for the <i>first</i> sample in the integrated output
acc_len	int		Total number of spectra integrated into each output sample by this block, incorporating any upstream processing
upstream_acc_len	int		Number of spectra already integrated by upstream processing

Data Buffers

Input Data Buffer: A GPU-side bifrost ring buffer of 32+32 bit complex integer data. The input buffer is read in gulps of $nchan * (nstand//2+1) * (nstand//4) * npol * npol * 4 * 2$ 32-bit words, which is the appropriate size if this block is fed by an upstream `Corr` block.

Note that if the upstream block is ``Corr``, the complexity axis of the input buffer is not the fastest changing.

Output Data Buffer: A bifrost ring buffer of 32+32 bit complex integer data of the same ordering and dimensionality as the input buffer.

The output buffer is written in single accumulation blocks (an integration of `acc_len` input vectors).

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **oring** (*bifrost.ring.Ring*) – bifrost output data ring. This should be on the GPU.

- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **gpu** (*int*) – GPU device which this block should target. A value of -1 indicates no binding
- **nchan** (*int*) – Number of frequency channels per time sample.
- **nstand** (*int*) – Number of stands per time sample.
- **npol** (*int*) – Number of polarizations per stand.
- **acc_len** (*int*) – Accumulation length per output buffer write. This should be an integer multiple of any upstream accumulation. This parameter can be updated at runtime.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If *None*, do not use runtime control.
- **autostartat** (*int*) – The start time at which the correlator should automatically begin correlating without intervention of the runtime control system. Use the value -1 to cause integration to begin on the next gulp.

Runtime Control and Monitoring

This block accepts the following command fields:

Field	Format	Units	Description
acc_len	int	samples	Number of samples to accumulate. This should be a multiple of any upstream accumulation performed by other blocks. I.e., it should be an integer multiple of a sequence's acc_len header entry.
start_time	int	samples	The desired first time sample in an accumulation. This should be compatible with the accumulation length and start time of upstream blocks. I.e. it should be offset from the input sequence header's seq0 value by an integer multiple of the input sequence header's acc_len value

5.2.6 corr_output_full

```
class lwa352_pipeline.blocks.corr_output_full_block.CorrOutputFull(log, iring,
                                                                    guaran-
                                                                    tee=True,
                                                                    core=- 1,
                                                                    nchan=192,
                                                                    npol=2,
                                                                    nstand=352,
                                                                    etcd_client=None,
                                                                    dest_port=10000,
                                                                    check-
                                                                    file=None,
                                                                    check-
                                                                    file_acc_len=1,
                                                                    antpol_to_bl=None,
                                                                    bl_is_conj=None,
                                                                    use_cor_fmt=True)
```

Functionality

Output an xGPU-spec visibility buffer as a stream of UDP packets.

New Sequence Condition

This block is a bifrost sink, and generates no downstream sequences.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
acc_len	int		Number of spectra integrated into each output sample by upstream processing
nchan	int		The number of frequency channels in the input visibility matrices
chan0	int		The index of the first frequency channel in the input visibility matrices
npol	int		The number of polarizations per stand in the input visibility matrices
bw_hz	double	Hz	Bandwidth of the input visibility matrices. Only required if <code>use_cor_fmt=False</code>
sfreq	double	Hz	Center frequency of the first channel in the input visibility matrices. Only required if <code>use_cor_fmt=False</code> .

Optional header fields, which describe the input xGPU buffer contents. If not supplied as headers, these should be provided as keyword arguments when this block is instantiated.

Field	Format	Units	Description
ant_to_bl_id	list of int		A 4D list of integers, with dimensions <code>[nstand, nstand, npol, npol]</code> which maps the correlation of <code>stand0, pol0</code> with <code>stand1, pol1</code> to visibility index <code>[stand0, stand1, pol0, pol1]</code>
bl_is_conj	list of bool		A 4D list of boolean values, with dimensions <code>[nstand, nstand, npol, npol]</code> which indicates if the correlation of <code>stand0, pol0</code> with <code>stand1, pol1</code> has the first (<code>stand0, pol0</code>) or second (<code>stand1, pol1</code>) input conjugated. If <code>bl_id_conj[stand0, stand1, pol0, pol1]</code> has the value <code>True</code> , then <code>stand0, pol0</code> is the conjugated input.

Output Headers

This is a bifrost sink block, and provides no data to an output ring.

Data Buffers

Input Data Buffer: A CPU-side bifrost ring buffer of 32+32 bit complex integer data. This input buffer is read in gulps of $nchan * (nstand//2+1) * (nstand//4) * npol * npol * 4 * 2$ 32-bit words, which is the size of an xGPU visibility matrix.

Output Data Buffer: This block has no output data buffer.

Instantiation

Parameters

- `log(logging.Logger)` – Logging object to which runtime messages should be emitted.

- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **nchan** (*int*) – Number of frequency channels per time sample.
- **nstand** (*int*) – Number of stands per time sample.
- **npol** (*int*) – Number of polarizations per stand.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If None, do not use runtime control.
- **dest_port** (*int*) – Default destination port for UDP data. Can be overridden with the runtime control interface.
- **use_cor_fmt** (*Bool*) – If True, use the LWA COR packet output format. Otherwise use a custom format. See *Output Format*, below.
- **antpol_to_bl** (*4D list of int*) – Map of antenna/polarization visibility inputs to xGPU output indices. See optional sequence header entry *ant_to_bl_id*. If not provided, this map should be available as a bifrost sequence header.
- **bl_is_conj** (*4D list of bool*) – Map of visibility index to conjugation convention. See optional sequence header entry *bl_is_conj*. If not provided, this map should be available as a bifrost sequence header.
- **checkfile** (*str*) – Path to a data file containing the expected correlator output. If provided, the data input to this block will be checked against this file. The data file should contain binary numpy.complex-format data in order *time* x *nchan* x *nstand* x *nstand* x *npol* x *npol*. Each entry in this data file should represent an expected visibility which has been integrated for *checkfile_acc_len* samples. This file can be generated with this package’s *make_golden_inputs.py* script.
- **checkfile_acc_len** (*int*) – The number of integrations which have gone into each time slice of the provided *checkfile*. For a check to be run, the accumulation length (and accumulation starts) of data input to this block should be a multiple of *checkfile_acc_len*.

Runtime Control and Monitoring

Field	Format	Units	Description
<i>dest_ip</i>	string		Destination IP for transmitted packets, in dotted-quad format. Eg. "10.0.0.1". Use "0.0.0.0" to skip sending packets
<i>dest_port</i>	int		UDP port to which packets should be transmitted.
<i>max_mbps</i>	int	Mbits/s	The maximum output data rate to allow before throttling. Set to -1 to send as fast as possible.

Output Data Format

Each packet from the correlator contains data from multiple channels for a single, dual-polarization baseline. There are two possible output formats depending on the value of *use_cor_fmt* with which this block is instantiated.

If `use_cor_fmt=True`, this block outputs packets conforming to the LWA-SV “COR” spec (though with integer rather than floating point data). This format comprises a stream of UDP packets, each with a 32 byte header defined as follows:

```
struct cor {
    uint32_t  sync_word;
    uint8_t   id;
    uint24_t  frame_number;
    uint32_t  secs_count;
    int16_t   freq_count;
    int16_t   cor_gain;
    int64_t   time_tag;
    int32_t   cor_navg;
    int16_t   stand_i;
    int16_t   stand_j;
    int32_t   data[nchans, npols, npols, 2];
};
```

Packet fields are as follows:

Field	Format	Units	Description
sync_word	uint32		Mark 5C magic number, 0xDEC0DE5C
id	uint8		Mark 5C ID, used to identify COR packet, 0x02
frame_number	uint24		Mark 5C frame number. Unused.
secs_count	uint32		Mark 5C seconds since 1970-01-01 00:00:00 UTC. Unused.
freq_count	int16		zero-indexed frequency channel ID of the first channel in the packet.
cor_gain	int16		Right bitshift used for gain compensation. Unused.
time_tag	int64	ADC sample period	Central sampling time since 1970-01-01 00:00:00 UTC.
cor_navg	int32	TODO: sub-slots doesn't work	Integration time.
stand_i	int16		1-indexed stand number of the unconjugated stand.
stand_j	int16		1-indexed stand number of the conjugated stand.
data	int32*		The data payload. Data for the visibility of antennas at stand_i and stand_j, with stand_j conjugated. Data are a multidimensional array of 32-bit integers, with dimensions [nchans, npols, npols, nchans, 2]. The first axis is frequency channel. The second axis is the polatizaioon of the antenna at stand_i. The second axis is the polarization of the antenna at stand_j. The fourth axis is complexity, with index 0 the real part of the visibility, and index 1 the imaginary part.

If `use_cor_fmt=False`, this block outputs a stream of UDP packets, with each comprising a 56 byte header followed by a payload of signed 32-bit integers. The packet definition is as follows:

```
struct corr_output_full_packet {
    uint64_t  sync_time;
```

(continues on next page)

(continued from previous page)

```

uint64_t spectra_id;
double    bw_hz;
double    sfreq_hz;
uint32_t  acc_len;
uint32_t  nchans;
uint32_t  chan0;
uint32_t  npols;
uint32_t  stand0;
uint32_t  stand1;
int32_t   data[npols, npols, nchans, 2];
};

```

Packet fields are as follows:

Field	Format	Units	Description
sync_time	uint64	UNIX seconds	The sync time to which spectra IDs are referenced.
spectra_id	int		The spectrum number for the first spectra which contributed to this packet's integration.
bw_hz	double (bi- nary64)	Hz	The total bandwidth of data in this packet
sfreq_hz	double (bi- nary64)	Hz	The center frequency of the first channel of data in this packet
acc_len	uint32		The number of spectra integrated in this packet
nchans	uint32		The number of frequency channels in this packet. For LWA-352 this is 184
chan0	uint32		The index of the first frequency channel in this packet
npols	uint32		The number of polarizations of data in this packet. For LWA-352, this is 2.
stand0	uint32		The index of the first antenna stand in this packet's visibility.
stand1	uint32		The index of the second antenna stand in this packet's visibility.
data	int32*		The data payload. Data for the visibility of antennas at stand0 and stand1, with stand1 conjugated. Data are a multidimensional array of 32-bit integers, with dimensions [npols, npols, nchans, 2]. The first axis is the polarization of the antenna at stand0. The second axis is the polarization of the antenna at stand1. The third axis is frequency channel. The fourth axis is complexity, with index 0 the real part of the visibility, and index 1 the imaginary part.

5.2.7 corrsubsel

```
class lwa352_pipeline.blocks.corr_subsel_block.CorrSubsel (log, iring, oring, guarantee=True, core=-1, etcd_client=None, nchan=192, npol=2, nstand=352, nchan_sum=4, gpu=-1, antpol_to_bl=None, bl_is_conj=None)
```

Functionality

This block selects individual visibilities from an xGPU buffer, averages them in frequency, and rearranges them into a sane format.

New Sequence Condition

This block starts a new sequence each time a new baseline selection is loaded or if the upstream sequence changes.

Input Header Requirements

This block requires the following headers from upstream:

Field	Format	Units	Description
seq0	int	.	Spectra number for the first sample in the input sequence
acc_len	int	.	Number of spectra accumulated per input data sample
nchan	int	.	Number of channels in the input sequence
bw_hz	double	Hz	Bandwidth of the input sequence
sfreq	double	Hz	Center frequency of first channel in the input sequence

Output Headers

This block copies headers from upstream with the following modifications:

Field	Format	Units	Description
seq0	int	•	Spectra number for the first sample in the output sequence. This may diverge from the input sequence seq0.
nchan	int	•	Number of frequency channels in the output data stream, after any integration performed by this block
nvis	int	•	Number of visibilities in the output data stream
baselines	list of ints	•	A list of output stand/pols, with dimensions [nvis, 2, 2]. E.g. if entry [V] of this list has value [[N_0, P_0], [N_1, P_1]] then the V-th entry in the output data array is the correlation of stand N_0, polarization P_0 with stand N_1, polarization P_1
bw_hz	double	Hz	Bandwidth of the output sequence, after averaging
sfreq	double	Hz	Center frequency of first channel in the output sequence, after averaging

Data Buffers

Input Data Buffer: A GPU-side bifrost ring buffer of 32+32 bit complex integer data. The input buffer is read in gulps of $nchan * (nstand//2+1) * (nstand//4) * npol * npol * 4 * 2$ 32-bit words, which is the appropriate size if this block is fed by an upstream Corr block.

Note that if the upstream block is ``Corr``, the complexity axis of the input buffer is not the fastest changing.

Output Data Buffer: A bifrost ring buffer of 32+32 bit complex integer data. The output buffer may be in GPU or CPU memory, and has dimensions time x frequency channel x visibility x complexity. The output buffer is written in blocks of $nchan // nchan_sum * nvis_out [=4656]$ 64-bit words.

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **oring** (*bifrost.ring.Ring*) – bifrost output data ring. This may be on the CPU or GPU.
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **nchan** (*int*) – Number of frequency channels per time sample.
- **nstand** (*int*) – Number of stands per time sample.
- **npol** (*int*) – Number of polarizations per stand.
- **nchan_sum** (*int*) – Number of frequency channels to sum together when generating output.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If None, do not use runtime control.

- **antpol_to_bl** (*4D list of int*) – Map of antenna/polarization visibility inputs to xGPU output indices. See optional sequence header entry `ant_to_bl_id`.
- **bl_is_conj** (*4D list of bool*) – Map of visibility index to conjugation convention. See optional sequence header entry `bl_is_conj`.

Runtime Control and Monitoring

Field	Format	Units	Description
<code>subsel</code>	3D list of int		A list of baselines for subselection. This field should be provided as a multidimensional list with dimensions <code>[nvis, 2, 2]</code> . The first axis runs over the 4656 baselines which may be selected. The second index is 0 for the first (unconjugated) input selected and 1 for the second (conjugated) input selected. The third axis is 0 for stand number, and 1 for polarization number.

Example

To set the baseline subsection to choose:

- visibility 0: the autocorrelation of antenna 0, polarization 0
- visibility 1: the cross correlation of antenna 5, polarization 1 with antenna 6, polarization 0

use:

```
subsel = [ [[0,0], [0,0]], [[5,1], [6,0]], ... ]
```

Note that the uploaded selection list must always have 4656 entries.

5.2.8 corr_output_part

```
class lwa352_pipeline.blocks.corr_output_part_block.CorrOutputPart (log, iring,
                                                                    use_cor_fmt=False,
                                                                    guaran-
                                                                    tee=True,
                                                                    core=- 1,
                                                                    etcd_client=None,
                                                                    dest_port=10001,
                                                                    nvis_per_packet=16)
```

Functionality

Output a block of visibilities as a UDP data stream

New Sequence Condition

This block is a bifrost sink, and generates no downstream sequences.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
acc_len	int		Number of spectra integrated into each output sample by upstream processing
nchan	int		The number of frequency channels in the input visibility matrices
chan0	int		The index of the first frequency channel in the input visibility matrices
npol	int		The number of polarizations per stand in the input visibility matrices
bw_hz	double	Hz	Bandwidth of the input visibility matrices. Only required if <code>use_cor_fmt=False</code>
sfreq	double	Hz	Center frequency of the first channel in the input visibility matrices. Only required if <code>use_cor_fmt=False</code> .
nvis	int	•	Number of visibilities in the output data stream
baselines	list of ints	•	A list of output stand/pols, with dimensions <code>[nvis, 2, 2]</code> . E.g. if entry <code>[V]</code> of this list has value <code>[[N_0, P_0], [N_1, P_1]]</code> then the <code>V</code> -th entry in the output data array is the correlation of stand <code>N_0</code> , polarization <code>P_0</code> with stand <code>N_1</code> , polarization <code>P_1</code>

Output Headers

This is a bifrost sink block, and provides no data to an output ring.

Data Buffers

Input Data Buffer: A CPU-side bifrost ring buffer with `32+32` bit complex integer data in order `time × channel × visibility × complexity`. This input buffer is read in gulps of `nchan × nvis` words, each 8 bytes in size.

Output Data Buffer: This block has no output data buffer.

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If None, do not use runtime control.
- **dest_port** (*int*) – Default destination port for UDP data. Can be overridden with the runtime control interface.
- **use_cor_fmt** (*Bool*) – If True, use the LWA COR packet output format. Otherwise use a custom format. See *Output Format*, below. Currently, only `use_cor_fmt=False` is supported.

- **nvis_per_packet** (*int*) – Number of visibilities to pack into a single UDP packet, if using the custom format (i.e., if `use_core_fmt=False`).

Runtime Control and Monitoring

Field	Format	Units	Description
dest_ip	string		Destination IP for transmitted packets, in dotted-quad format. Eg. "10.0.0.1". Use "0.0.0.0" to skip sending packets
dest_port	int		UDP port to which packets should be transmitted.

Output Data Format

The COR packet format is not yet supported. The below description details the packet format when `use_cor_fmt=False`.

Each packet from the correlator contains data from multiple channels for multiple single-polarization baselines. There are two possible output formats depending on the value of `use_cor_fmt` with which this block is instantiated.

If `use_cor_fmt=False`, this block outputs a stream of UDP packets, with each comprising a 56 byte header followed by a payload of signed 32-bit integers. The packet definition is as follows:

```
struct corr_output_partial_packet {
    uint64_t    sync_time;
    uint64_t    spectra_id;
    double      bw_hz;
    double      sfreq_hz;
    uint32_t    acc_len;
    uint32_t    nvis;
    uint32_t    nchans;
    uint32_t    chan0;
    uint32_t    baselines[nvis, 2, 2];
    int32_t     data[npols, npols, nchans, 2];
};
```

Packet fields are as follows:

Field	Format	Units	Description
sync_time	uint64	UNIX seconds	The sync time to which spectra IDs are referenced.
spectra_id	int	•	The spectrum number for the first spectra which contributed to this packet's integration.
bw_hz	double (binary64)	Hz	The total bandwidth of data in this packet
sfreq_hz	double (binary64)	Hz	The center frequency of the first channel of data in this packet
acc_len	uint32	•	The number of spectra integrated in this packet
nvis	uint32	•	The number of single polarization visibilities present in this packet.
nchans	uint32	•	The number of frequency channels in this packet. For LWA-352 this is 184
chan0	uint32	•	The index of the first frequency channel in this packet
baselines	uint32*	•	An array containing the stand and polarization indices of the multiple visibilities present in this packet. This entry has dimensions [nvis, 2, 2]. The first index runs over the number of visibilities within this packet. The second index is 0 for the first (unconjugated) visibility input and 1 for the second (conjugated) antenna input. The third index is zero for stand number, and 1 for polarization number.
data	int32*	•	The data payload. Data for the visibility of antennas at stand0 and stand1, with stand1 conjugated. Data are a multidimensional array of 32-bit integers, with dimensions [nvis, nchans, 2]. The first axis runs over the multiple visibilities in this packet. Each index can be associated with a physical antenna using the <code>baselines</code> field. The second axis is frequency channel. The third axis is complexity, with index 0 the real part of the visibility, and index 1 the imaginary part.

5.2.9 beamform

```
class lwa352_pipeline.blocks.beamform_block.Beamform(log, iring, oring, nchan=256,
                                                    nbeam=1,      ninput=704,
                                                    ntime_gulp=2500,
                                                    ntime_sum=None,   guarantee=
                                                    tee=True, core=- 1, gpu=- 1,
                                                    etcd_client=None)
```

Functionality

This block reads data from a GPU-side bifrost ring buffer and feeds it to a beamformer, generating either voltage or (integrated) power beams.

New Sequence Condition

This block starts a new sequence each time the upstream sequence changes.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
nchan	int		Number of channels in the sequence
sfreq	double	Hz	Center frequency of first channel in the sequence
bw_hz	int	Hz	Bandwidth of the sequence
nstand	int		Number of stands (antennas) in the sequence
npol	int		Number of polarizations per stand in the sequence

Output Headers

This block passes headers from the upstream block with the following modifications:

Field	Format	Units	Description
nstand	int		Number of beams in the sequence
nbeam	int		Number of beams in the sequence
nbit	int		Number of bits per output sample. This block sets this value to 32
npol	int		Number of polarizations per beam. This block sets this value to 1.
complex	Bool		This block sets this entry to <code>True</code> , indicating that the data out of this block are complex, with real and imaginary parts each of width <code>nbit</code>

Data Buffers

Input Data Buffer: A GPU-side bifrost ring buffer of 4+4 bit complex data in order: `time x channel x input`.

Typically, the `input` axis is composed of `stand x polarization`, but this block does not assume this is the case.

Each gulp of the input buffer reads `ntime_gulp` samples, i.e. `ntime_gulp x nchan x ninput` bytes.

Output Data Buffer: A GPU-side bifrost ring buffer of 32+32 bit complex floating-point data containing beamformed data. With `ntime_sum=None`, this is complex beamformer data with dimensionality `time x channel x beams x complexity`. This output buffer is written in blocks of `ntime_gulp` samples, i.e. `ntime_gulp x nchan x nbeam x 8` bytes.

With `ntime_sum != None`, this block will generate dynamic power spectra rather than voltages. This mode is experimental. See `bifrost/beamform.h` for details.

Instantiation

Parameters

- **log** (`logging.Logger`) – Logging object to which runtime messages should be emitted.
- **iring** (`bifrost.ring.Ring`) – bifrost input data ring. This should be on the GPU.
- **oring** (`bifrost.ring.Ring`) – bifrost output data ring. This should be on the GPU.

- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **gpu** (*int*) – GPU device which this block should target. A value of -1 indicates no binding
- **ntime_gulp** (*int*) – Number of time samples to copy with each gulp.
- **nchan** (*int*) – Number of frequency channels per time sample. This should match the sequence header `nchan` value, else an `AssertionError` is raised.
- **ninput** – Number of inputs per time sample. This should match the sequence headers `nstand` x `npol`, else an `AssertionError` is raised.
- **ntime_sum** (*int*) – Set to `None` to generate voltage beams. Set to an integer value ≥ 0 to generate accumulated dynamic spectra. Values other than `None` are *experimental*.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If `None`, do not use runtime control.

Runtime Control and Monitoring

This block accepts the following command fields:

Field	Format	Units	Description
delays	2D list of float	ns	An <code>nbeam</code> x <code>ninput</code> element list of geometric delays, in nanoseconds.
gains	2D list of complex32)		A two dimensional list of calibration gains with shape <code>nchan</code> x <code>ninput</code>
load_sample	int	sample	NOT YET IMPLEMENTED Sample number on which the supplied delays should be loaded. If this field is absent, new delays will be loaded as soon as possible.

5.2.10 beamform_sum_beams

```
class lwa352_pipeline.blocks.beamform_sum_beams_block.BeamformSumBeams (log,
                                                                    ir-
                                                                    ing,
                                                                    or-
                                                                    ing,
                                                                    nchan=256,
                                                                    ntime_gulp=2500,
                                                                    ntime_sum=24,
                                                                    guar-
                                                                    an-
                                                                    tee=True,
                                                                    core=-
                                                                    1,
                                                                    gpu=-
                                                                    1,
                                                                    etcd_client=None)
```

Functionality

This block reads beamformed voltage data from a GPU-side ring buffer and generates integrated power spectra.

New Sequence Condition

This block starts a new sequence each time the upstream sequence changes.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
nchan	int		Number of channels in the sequence
nstand	int		Number of stands (antennas) in the sequence
nbeam	int		Number of single polarization beams in the sequence

Output Headers

This block passes headers from the upstream block with the following modifications:

Field	Format	Units	Description
nbeam	int		Number of dual polatization beams in the sequence. Equal to half the input header <code>nbeam</code>
nbit	int		Number of bits per output sample. This block sets this value to 32
npol	int		Number of polarizations per beam. This block sets this value to 2.
complex	Bool		This block sets this entry to <code>True</code> , indicating that the data out of this block are complex, with real and imaginary parts each of width <code>nbit</code>
acc_len	int		Number of spectra integrated into each output sample by this block

Data Buffers

Input Data Buffer: A GPU-side bifrost ring buffer of 32+32 bit complex floating-point data containing beam-formed voltages. The input buffer has dimensionality (slowest varying to fastest varying) `time` \times `channel` \times `beams` \times `complexity`. The number of beams should be even.

Each gulp of the input buffer reads `ntime_gulp` samples, I.e `ntime_gulp` \times `nchan` \times `nbeam` \times 8 bytes.

This block considers beam indices 0, 2, 4, ..., `nbeam`-2 to be X polarized, and beam indices 1, 3, 5, ..., `nbeam`-1 to be Y polarized. As such, `nbeam`/2 output beams are generated by this block, with 4 polarization products each.

Output Data Buffer: A CPU- or GPU-side bifrost ring buffer of 32 bit, floating-point, integrated, beam powers. Data has dimensionality `time` \times `channel` \times `beams` \times `beam-element`.

`channel` runs from 0 to `nchan`.

`beam` runs from 0 to the output `nbeam`-1 (equivalent to the input `nbeam`/2 - 1).

`beam-element` runs from 0 to 3 with the following mapping:

- index 0: The accumulated power of a beam's X polarization
- index 1: The accumulated power of a beam's Y polarization
- index 2: The accumulated real part of a beam's $X \times \text{conj}(Y)$ cross-power
- index 3: The accumulated imaginary part of a beam's $X \times \text{conj}(Y)$ cross-power

This block sums over `ntime_sum` input time samples, thus writing `ntime_gulp / ntime_sum` output samples for every `ntime_gulp` samples read.

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **oring** (*bifrost.ring.Ring*) – bifrost output data ring. This should be on the GPU.
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **gpu** (*int*) – GPU device which this block should target. A value of -1 indicates no binding
- **ntime_gulp** (*int*) – Number of time samples to copy with each gulp.
- **nchan** (*int*) – Number of frequency channels per time sample. This should match the sequence header `nchan` value, else an `AssertionError` is raised.
- **ntime_sum** (*int*) – The number of time sample which this block should integrate. `ntime_gulp` should be an integer multiple of `ntime_sum`, else an `AssertionError` is raised.

Runtime Control and Monitoring

This block has no runtime control keys. It is completely configured at instantiation time.

5.2.11 beamform_output

```
class lwa352_pipeline.blocks.beamform_output_block.BeamformOutput(log, iring,
                                                                    guaran-
                                                                    tee=True,
                                                                    core=- 1,
                                                                    etcd_client=None,
                                                                    dest_port=10000,
                                                                    ntime_gulp=480)
```

Functionality

This block reads beamformed power data from a CPU-side buffer and transmits as a stream of UDP packets.

New Sequence Condition

This block is a bifrost sink, and generates no downstream sequences.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
nchan	int		The number of frequency channels in the input data buffer
chan0	int		The index of the first frequency channel in the input data buffer
nbeam	int		The number of beams in the input data buffer
nbit	int		The number of bits (per real/imag part) of the input data samples. Must be 32
complex	Bool		True indicates that the input samples are complex, with real and imaginary parts both having <code>nbit</code> bits. Must be True.
system_nchan	int		The total number of frequency channels in the multi-pipeline system. Must be a multiple of <code>nchan</code> .
npol	int		The number of polarizations in the input data buffer. Must be 1

Output Headers

This is a bifrost sink block, and provides no data to an output ring.

Data Buffers

Input Data Buffer: A CPU-side bifrost ring buffer of 32 bit, floating-point, integrated, beam powers. Data has dimensionality `time x channel x beams x beam-element`.

`channel` runs from 0 to `nchan`.

`beam` runs from 0 to the output `nbeam-1` (equivalent to the input `nbeam/2 - 1`).

`beam-element` runs from 0 to 3 with the following mapping:

- index 0: The accumulated power of a beam's X polarization
- index 1: The accumulated power of a beam's Y polarization
- index 2: The accumulated real part of a beam's $X \times \text{conj}(Y)$ cross-power
- index 3: The accumulated imaginary part of a beam's $X * \text{conj}(Y)$ cross-power

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **ntime_gulp** (*int*) – Number of time samples to copy with each gulp.
- **dest_port** (*int*) – Default destination port for UDP data. Can be overridden with the runtime control interface.

Runtime Control and Monitoring

This block reads the following control keys

Field	Format	Units	Description
dest_ip	[list of] string		Destination IP addresses for transmitted packets, in dotted-quad format. Eg. "10.0.0.1". Use "0.0.0.0" to skip sending packets. If a single string is provided, all packets will be sent to this address. If a list of strings is provided, beam <i>i</i> is sent to <code>dest_ip[i % len(dest_ip)]</code> .
dest_port	int		UDP port to which packets should be transmitted.

Output Data Format

TODO: This should be updated to a TBC “pbeam” format

Each packet output contains a single time sample of data from multiple channels and a single power beam. The output data format complies with the LWA-SV “IBEAM” spec, with slight meta-data overloading.

This format comprises a stream of UDP packets, each with a 32 byte header defined as follows:

```

struct ibeam {
    uint8_t    server;
    uint8_t    gbe;
    uint8_t    nchan;
    uint8_t    nbeam;
    uint8_t    nserver;
    uint16_t   chan0;
    uint64_t   seq;
    float      data[nchan, nbeam, 4]; // Channel x Beam x Beam Element x 32-bit_
    ↪ float
};

```

Packet fields are as follows:

Field	Format	Units	Description
server	uint8		One-based “pipeline number”. Pipeline 1 processes the first <code>nchan</code> channels, pipeline <i>p</i> processes the <i>p</i> -th <code>nchan</code> channels. Pipeline ID counts through each channel block, and then multiple beams in the system. Eg, if the system has 512 channels, 256 channels per packet, and 3 beams, <code>server</code> runs from 1 to 6.
gbe	uint8		AKA “tuning”. Set to 0.
nchan	uint8		Number of frequency channels in this packet
nbeam	uint8		Number of beams in this packet. Currently always 1.
nserver	uint8		The total number of pipelines in the system times the number of beams per pipeline
chan0	uint32		Zero-indexed ID of the first frequency channel in this packet.
seq	uint64		Zero-indexed spectra number for the spectra in this packet. Specified relative to the system synchronization time.
data	float		Data payload. Beam powers, in order (slowest to fastest) Channel x Beam x Beam Element. Beam elements are <code>[XX, YY, real(XY), imag(XY)]</code> .

5.2.12 beamform_vlbi_output

```
class lwa352_pipeline.blocks.beamform_vlbi_output_block.BeamformVlbiOutput (log,
                                                                    ir-
                                                                    ing,
                                                                    guar-
                                                                    an-
                                                                    tee=True,
                                                                    core=-
                                                                    1,
                                                                    etcd_client=None,
                                                                    dest_port=10000,
                                                                    ntime_gulp=480)
```

Functionality

Output a stream of UDP packets containing multiple beam voltages

New Sequence Condition

This block is a bifrost sink, and generates no downstream sequences.

Input Header Requirements

This block requires that the following header fields be provided by the upstream data source:

Field	Format	Units	Description
seq0	int		Spectra number for the first sample in the input sequence
nchan	int		The number of frequency channels in the input data buffer
chan0	int		The index of the first frequency channel in the input data buffer
nbeam	int		The number of beams in the input data buffer
nbit	int		The number of bits (per real/imag part) of the input data samples. Must be 32
complex	Bool		True indicates that the input samples are complex, with real and imaginary parts both having nbit bits. Must be True.
system_nchan	int		The total number of frequency channels in the multi-pipeline system. Must be a multiple of nchan.
npol	int		The number of polarizations in the input data buffer. Must be 1

Output Headers

This is a bifrost sink block, and provides no data to an output ring.

Data Buffers

Input Data Buffer: A CPU- or GPU-side bifrost ring buffer of 32+32 bit complex floating-point data containing beamformed voltages. Data have dimensions (slowest to fastest): time x channel x beams x complexity. This buffer is read in blocks of ntime_gulp samples.

Output Data Buffer: This block has no output data buffer.

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.

- **iring** (*bifrost.ring.Ring*) – bifrost input data ring. This should be on the GPU.
- **guarantee** (*Bool*) – If True, read data from the input ring in blocking “guaranteed” mode, applying backpressure if necessary to ensure no data are missed by this block.
- **core** (*int*) – CPU core to which this block should be bound. A value of -1 indicates no binding.
- **etcd_client** (*etcd3.client.Etcd3Client*) – Etcd client object used to facilitate control of this block. If None, do not use runtime control.
- **dest_port** (*int*) – Default destination port for UDP data. Can be overridden with the runtime control interface.
- **ntime_gulp** (*int*) – Number of time samples to read on each loop iteration.

Runtime Control and Monitoring

Field	Format	Units	Description
dest_ip	string		Destination IP for transmitted packets, in dotted-quad format. Eg. "10.0.0.1". Use "0.0.0.0" to skip sending packets
dest_port	int		UDP port to which packets should be transmitted.

Output Data Format

Each packet output contains a single time sample of data from multiple channels and multiple voltage beams. The output data format complies with the LWA-SV “IBEAM” spec This format comprises a stream of UDP packets, each with a 32 byte header defined as follows:

```
struct ibeam {
    uint8_t  server;
    uint8_t  gbe;
    uint8_t  nchan;
    uint8_t  nbeam;
    uint8_t  nserver;
    uint16_t chan0;
    uint64_t seq;
    float    data[nchan, nbeam, 2]; // Channel x Beam x Complexity x 32-bit float
};
```

Packet fields are as follows:

Field	Format	Units	Description
server	uint8		One-based “pipeline number”. Pipeline 1 processes the first nchan channels, pipeline p processes the p-th nchan channels.
gbe	uint8		AKA “tuning”. Set to 0.
nchan	uint8		Number of frequency channels in this packet
nbeam	uint8		Number of beams in this packet
nservice	uint8		The total number of pipelines in the system.
chan0	uint32		Zero-indexed ID of the first frequency channel in this packet.
seq	uint64		Zero-indexed spectra number for the spectra in this packet. Specified relative to the system synchronization time.
data	float		Data payload. Beam voltages, in order (slowest to fastest) Channel x Beam x Complexity

5.2.13 dummy_source

The Dummy Source block is not used in the default LWA pipeline, but can replace the `Capture` block for testing purposes.

```
class lwa352_pipeline.blocks.dummy_source_block.DummySource (log,          oring,
                                                             ntime_gulp=2500,
                                                             core=-1,
                                                             nchan=192,
                                                             nstand=352,
                                                             npol=2,
                                                             skip_write=False,
                                                             tar-
                                                             get_throughput=22.0,
                                                             testfile=None)
```

Functionality

A dummy source block for throughput testing. Optionally writes test data to an output buffer.

New Sequence Condition

This block starts a single new sequence when `main()` is called.

Input Header Requirements

This block is a bifrost source, and thus has no input header requirements.

Output Headers

Field	Format	Units	Value	Description
<code>sync_time</code>	int	UNIX seconds	<code>int (time.time())</code>	Synchronization time (corresponding to spectrum sequence number 0).
<code>seq0</code>	int		0	Spectra number for the first sample in this sequence
<code>chan0</code>	int		0	Channel index of the first channel in this sequence
<code>nchan</code>	int		<code>nchan</code>	Number of channels in the sequence
<code>system_nchan</code>	int		<code>nchan</code>	The total number of channels in the system (i.e., the number of channels across all pipelines)
<code>sfreq</code>	double	Hz	0.0	Center frequency of first channel in the sequence
<code>bw_hz</code>	int	Hz	<code>24000 * nchan</code>	Bandwidth of the sequence
<code>nstand</code>	int		<code>nstand</code>	Number of stands (antennas) in the sequence
<code>npol</code>	int		<code>npol</code>	Number of polarizations per stand in the sequence
<code>input_to_ant</code>	list[int]		entry <code>i</code> is <code>[i // npol, i % npol]</code>	List of input to stand/pol mappings with dimensions <code>[nstand x npol, 2]</code> . E.g. if entry <code>N</code> of this list has value <code>[S, P]</code> then the <code>N</code> -th correlator input is stand <code>S</code> , polarization <code>P</code> .
<code>ant_to_input</code>	list[ints]		entry <code>[s,p]</code> is <code>npol*s + p</code>	List of stand/pol to correlator input number mappings with dimensions <code>[nstand, npol]</code> . E.g. if entry <code>[S, P]</code> of this list has value <code>N</code> then stand <code>S</code> , polarization <code>P</code> of the array is the <code>N</code> -th correlator input

Data Buffers

Input data buffer: None

Output data buffer: Complex 4-bit data with dimensions (slowest to fastest) Time x Freq x Stand x Polarization x Complexity

Instantiation

Parameters

- **log** (*logging.Logger*) – Logging object to which runtime messages should be emitted.
- **oring** (*bifrost.ring.Ring*) – bifrost output data ring
- **nstand** (*int*) – Number of stands in the array.
- **npol** (*int*) – Number of polarizations per antenna stand.
- **nchan** (*int*) – Number of frequency channels this block will output
- **core** (*int*) – CPU core to which this block should be bound. If -1, no binding is used.
- **ntime_gulp** (*int*) – The number of time samples to output on each processing loop iteration.
- **test_file** (*str*) – Path to a file containing test data, as a raw binary file containing 4+4 bit complex data in time x channel x stand x polarization order, with polarization changing fastest. This file should contain a multiple of ntime_gulp samples. When the end of the file is reached, it is repeated.
- **target_throughput** (*float*) – The target Gbits/s at which this block should output data. Throttling will be used to target this rate if necessary.
- **skip_write** (*Bool*) – If set to `True`, no data will be copied to the output buffer, blocks of memory will just be marked full as fast as possible. This can be useful to test the maximum throughput of the downstream pipeline blocks. If set to `False` and no testfile is provided, the output data is a ramp, with each 4+4-bit data sample taking the value `stand % 8`

OUTPUT DATA FORMATS

This section defines the output packet formats for each of the pipeline output data products. Unless otherwise specified, all data products are transmitted in network- (i.e. big-) endian format.

Packet sizing is partially determined by the pipeline configuration. Specifically:

- NCHAN – The number of channels processed per pipeline.
- NSTAND – The number of antenna stands in the array.
- NPOL – The number of polarizations per antenna stand.

For the LWA-352 system:

- NCHAN = 184
- NSTAND = 352
- NPOL = 2

6.1 Full Correlation Packets

Data from the full, slow correlator are transmitted as a series of UDP packets, with each packet carrying data for one dual-polarization baseline, for multiple channels. Each packet has a 56 byte header followed by a payload of signed 32-bit integers.

```
struct corr_output_full_packet {  
    uint64_t    sync_time;  
    uint64_t    spectra_id;  
    double      bw_hz;  
    double      sfreq_hz;  
    uint32_t    acc_len;  
    uint32_t    nchans;  
    uint32_t    chan0;  
    uint32_t    npols;  
    uint32_t    stand0;  
    uint32_t    stand1;  
    int32_t     data[npols, npols, nchans, 2];  
};
```

Packet fields are as follows:

Field	Format	Units	Description
sync_time	uint64	UNIX sec- onds	The sync time to which spectra IDs are referenced.
spectra_id	int		The spectrum number for the first spectra which contributed to this packet's integration.
bw_hz	double (bi- nary64)	Hz	The total bandwidth of data in this packet
sfreq_hz	double (bi- nary64)	Hz	The center frequency of the first channel of data in this packet
acc_len	uint32		The number of spectra integrated in this packet
nchans	uint32		The number of frequency channels in this packet. For LWA-352 this is 184
chan0	uint32		The index of the first frequency channel in this packet
npols	uint32		The number of polarizations of data in this packet. For LWA-352, this is 2.
stand0	uint32		The index of the first antenna stand in this packet's visibility.
stand1	uint32		The index of the second antenna stand in this packet's visibility.
data	int32*		The data payload. Data for the visibility of antennas at stand0 and stand1, with stand1 conjugated. Data are a multidimensional array of 32-bit integers, with dimensions [NPOLS, NPOLS, NCHANS, 2]. The first axis is the polarization of the antenna at stand0. The second axis is the polarization of the antenna at stand1. The third axis is frequency channel. The fourth axis is complexity, with index 0 the real part of the visibility, and index 1 the imaginary part.

6.2 Partial Correlation Packets

Data from the fast dump correlator are transmitted as a series of UDP packets, with each packet carrying data for multiple frequency channels of multiple, single-polarization visibilities.

Each packet has a variable length header followed by a payload of signed 32-bit integers.

```

struct corr_output_partial_packet {
    uint64_t   sync_time;
    uint64_t   spectra_id;
    double     bw_hz;
    double     sfreq_hz;
    uint32_t   acc_len;
    uint32_t   nvis;
    uint32_t   nchans;
    uint32_t   chan0;
    uint32_t   baselines[nvis, 2, 2];
    int32_t    data[nvis, nchans, 2];

```

Packet fields are as follows:

Field	Format	Units	Description
sync_time	uint64	UNIX sec-onds	The sync time to which spectra IDs are referenced.
spectra_id	int		The spectrum number for the first spectra which contributed to this packet's integration.
bw_hz	double (binary64)	Hz	The total bandwidth of data in this packet
sfreq_hz	double (binary64)	Hz	The center frequency of the first channel of data in this packet
acc_len	uint32		The number of spectra integrated in this packet
nvis	uint32		The number of single polarization visibilities present in this packet.
nchans	uint32		The number of frequency channels in this packet. For LWA-352 this is 184
chan0	uint32		The index of the first frequency channel in this packet
baselines	uint32*		An array containing the stand and polarization indices of the multiple visibilities present in this packet. This entry has dimensions [nvis, 2, 2]. The first index runs over the number of visibilities within this packet. The second index is 0 for the first (unconjugated) visibility input and 1 for the second (conjugated) antenna input. The third index is zero for stand number, and 1 for polarization number.
data	int32*		The data payload. Data for the visibility of antennas at stand0 and stand1, with stand1 conjugated. Data are a multidimensional array of 32-bit integers, with dimensions [NVIS, NCHANS, 2]. The first axis runs over the multiple visibilities in this packet. Each index can be associated with a physical antenna using the <code>baselines</code> field. The second axis is frequency channel. The third axis is complexity, with index 0 the real part of the visibility, and index 1 the imaginary part.

6.3 VLBI Beam

6.4 Integrated Beams

CONTROL INTERFACE

Control and monitoring of the X-Engine pipeline is carried out through the passing of JSON-encoded messages through an `etcd`¹ key-value store. Each processing block in the LWA system has a unique identifier which defines a key to which runtime status is published and a key which should be monitored for command messages.

The unique key of a processing block is derived from the `blockname` of the module within the pipeline, the `hostname` of the server on which a pipeline is running, and the pipeline id - `pid` - of this pipeline.

In general, keys to which status information is published have the prefix:

```
/mon/corr/xeng/<hostname>/pipeline/<pid>/<blockname>.
```

Keys to which users should write commands have the prefix

```
/cmd/corr/xeng/<hostname>/pipeline/<pid>/<blockname>.
```

The format of these status and command messages, and their allowed values are given in the remainder of this section on a per-block basis.

7.1 Capture Thread (blockname: `capture`)

7.1.1 Commands

The `capture` block accepts no runtime commands. When a pipeline is executed, the capture module will automatically begin filling processing buffers. Buffer boundaries occur every `G_SIZE` samples.

7.1.2 Monitoring

The `capture` block writes monitoring data to the key `/mon/corr/xeng/<hostname>/pipeline/<pid>/capture`. Data are written as a JSON-encoded dictionary with the following entries:

Field	Format	Units	Description
<code>throughput</code>	float	Gbits/s	Block throughput
<code>n_dropped</code>	int	packets	Number of packets dropped since pipeline start
<code>n_received</code>	int	packets	Number of packets received since pipeline start
<code>frac_dropped</code>	float		Fraction of packets dropped since pipeline start
<code>n_late</code>	int	packets	Number of late packets since pipeline start
<code>n_f_missing</code>	int	boards	TODO
<code>n_part_dropped</code>	int	packets	TODO
<code>time</code>	float	UNIX time	The time this key was updated.

¹ See `etcd.io`

7.2 Copy Thread (blockname: `gpubcopy`)

The `gpubcopy` block accepts no runtime commands and outputs no run-time statistics.

7.3 Correlation Thread (blockname: `corr`)

The `corr` block takes blocks of `G_SIZE` 4-bit time samples from the `gpubcopy` thread and generates visibility matrices using an xGPU computation kernel. Integration takes place over the `G_SIZE` input samples.

7.3.1 Commands

The `corr` block has a run-time configurable accumulation length and start time. These can be set by writing a JSON-encoded dictionary to the key `/cmd/corr/xeng/<hostname>/pipeline/<pid>/corr`, which should have the following fields:

`c c c X` Field & Format & Units & Description

`acc_len` & int & samples & Number of samples to integrate. Must be a multiple of `G_SIZE`. `acc_len = 0` can be used to force the `corr` module to stop processing.

`start_time` & int & samples & Sample index on which to begin integrating. Must be a multiple of `G_SIZE`.

Sample indices are relative to the F-Engine sync time – i.e., sample index 0 is the first sample after an F-Engine sync event. Sample indices can only be converted to real time with the knowledge of the F-Engine sync time and F-Engine ADC clock rate.

It should be noted that modifying the run-time configuration of the `corr` module will impact both the fast- and slow-visibility processing streams. Both streams will re-synchronize onto new correlator integration boundaries.

7.3.2 Monitoring

The `corr` block writes status data as a JSON-encoded dictionary to the key:

`/mon/corr/xeng/<hostname>/pipeline/<pid>/corr`

The status dictionary has the following fields:

`c c c X` Field & Format & Units & Description

`throughput` & float & Gbits/s & Block throughput

`acc_len` & int & samples & Number of samples currently set to integrate

`start_sample` & int & samples & Current start time.

`curr_sample` & int & samples & The last sample to be processed.

`update_pending` & bool & - & True if new integration parameters are waiting to be loaded.

`last_update_time` & float & seconds & The time since UNIX epoch that the integration parameters were last updated.

`new_acc_len` & int & samples & The commanded integration length

`new_start_sample` & int & samples & The commanded start sample

`last_cmd_time` & float & seconds & The time since UNIX epoch that the last command was received

7.4 Visibility Sub-Select Thread (blockname: `corrsubsel`)

7.4.1 Commands

The `corrsubsel` block outputs a run-time configurable set of baselines. These can be set by writing a JSON-encoded dictionary to the key `/cmd/corr/xeng/<hostname>/pipeline/<pid>/corrsubsel`, which should have the following fields:

`c c c X` Field & Format & Units & Description

`subsel` & `list(int)` & - & A list of baselines for subselection. This field should be provided as a multidimensional list with dimensions `[N_VIS, 2, 2]`. The first axis runs over the 4656 baselines which may be selected. The second index is 0 for the first (unconjugated) input selected and 1 for the second (conjugated) input selected. The third axis is 0 for stand number, and 1 for polarization number.

Example

To set the baseline subsection to choose:

- visibility 0: the autocorrelation of antenna 0, polarization 0
- visibility 1: the cross correlation of antenna 5, polarization 1 with antenna 6, polarization 0

use:

```
subsel = [ [[0,0], [0,0]], [[5,1], [6,0]], ... ]
```

Note that the uploaded selection list must always have 4656 entries.

7.4.2 Monitoring

The `corr` block writes status data as a JSON-encoded dictionary to the key: `/mon/corr/xeng/<hostname>/pipeline/<pid>/corrsubsel`.

The status dictionary has the following fields:

Field	Format	Units	Description
<code>throughput</code>	float	Gbits/s	Block throughput
<code>subsel</code>	<code>list(int)</code>	samples	Current set of visibility indices being selected
<code>update_pending</code>	bool		True if new selection parameters are waiting to be loaded.
<code>last_update_time</code>	float	seconds	The time since UNIX epoch that the selection parameters were last updated.
<code>new_subsel</code>	<code>list(int)</code>	samples	The commanded visibility selection indices.
<code>last_cmd_time</code>	float	seconds	The time since UNIX epoch that the last command was received

7.5 Visibility Integrator (blockname: `corracc`)

7.5.1 Commands

The `corracc` block further integrates the output of the `corr` block. Integration parameters can be set by writing a JSON-encoded dictionary to the key:

```
/cmd/corr/xeng/<hostname>/pipeline/<pid>/corracc
```

This should have the following fields:

Field	Format	Units	Description
<code>acc_len</code>	int		Number of samples to integrate. <code>acc_len = 0</code> can be used to force the <code>corracc</code> module to stop processing.
<code>start_time</code>	int	samples	Sample index on which to begin integrating.

Note that the `acc_len` configuration must be compatible with – i.e., must be a multiple of – the accumulation length set in the `corr` block. Furtherm the `start_time` must be compatible with the integration boundaries associated with the `corr` block’s integration settings.

Run-time checks will flag bad configurations as errors, but no check is made on issuing a command to ensure it is valid. After booting the pipeline, a safe order of configuration is:

1. Boot pipeline.
2. Configure `corracc` block
3. Configure `corr` block

For changes of configuration, the safe order of updates is:

7.5.2 Monitoring

The `corracc` block writes status data as a JSON-encoded dictionary to the key:

```
/mon/corr/xeng/<hostname>/pipeline/<pid>/corracc.
```

The status dictionary has the following fields:

Field	Format	Units	Description
acc_len	int	samples	Number of samples currently set to integrate
start_sample	int	samples	Current start time.
curr_sample	int	samples	The last sample to be processed.
update_pending	bool		True if new integration parameters are waiting to be loaded.
last_update_time	float	seconds	The time since UNIX epoch that the integration parameters were last updated.
new_acc_len	int	samples	The commanded integration length
new_start_sample	int	samples	The commanded start sample
last_cmd_time	float	seconds	The time since UNIX epoch that the last command was received

7.6 Beamformer (blockname: beamform)

The `beamform` block forms $2 \times \text{NBEAM}$ independent, single polarization voltage beams. Beam pointings are specified by relative antenna delays and a set of universal, frequency-dependent calibration coefficients, which are shared among all beams. Note that this interface precludes direction-dependent calibrations.

7.6.1 Commands

Commands are sent to the `beamform` module by writing a JSON-encoded command to the key:

```
/cmd/corr/xeng/<hostname>/pipeline/<pid>/beamform
```

This command should have the following fields

Field	Format	Units	Description
delays[x]	list(float)	ns	An <code>NINPUT</code> element list of geometric delays, in nanoseconds. [x] is a beam index, and should be between 0 and <code>NBEAM - 1</code>
gains	list(complex32)		A two dimensional list of calibration gains with shape <code>[NCHAN, NINPUT]</code>
load_sample	int	sample	Sample number on which the supplied delays should be loaded. If this field is absent, new delays will be loaded as soon as possible

The `beamform` block calculates voltage beams only and has no concept of polarization. Instead, the `beamform` block generates $2 \times \text{NBEAM}$ beams and computes the auto- and cross-power spectra between beams in order to generate auto- and cross-pol products. Beams are paired such that the cross-power of beams $2n$ and $2n+1$ are computed – it is the user’s responsibility to ensure that these beams have the same pointing and are formed from complementary antenna polarizations.

7.6.2 Monitoring

The `beamform` block writes status data as a JSON-encoded dictionary to the key:

```
/mon/corr/xeng/<hostname>/pipeline/<pid>/beamform.
```

The status dictionary has the following fields:

Field	Format	Units	Description
throughput	float	Gbits/s	Block throughput
delays[x]	list(float)	ns	An <code>NINPUT</code> element list containing the delays currently loaded for beam <code>x</code>
gains	list(complex32)		A two dimensional list of currently loaded calibration gains. The dimensions of this list should be <code>NCHAN × NINPUT</code>
new_delays[x]	list(float)	ns	An <code>NINPUT</code> element list containing the next set of delays to be loaded for beam <code>x</code>
new_gains	list(complex32)		A two-dimensional list of calibration gains with shape <code>[NCHAN, NINPUT]</code>
curr_sample	int	samples	The last sample to be processed.
update_pending	bool	•	True if new integration parameters are waiting to be loaded.
last_update_time	float	seconds	The time since UNIX epoch that the integration parameters were last updated.
new_acc_len	int	samples	The commanded integration length
new_start_sample	int	samples	The commanded start sample
last_cmd_time	float	seconds	The time since UNIX epoch that the last command was received

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

B

Beamform (class in *lwa352_pipeline.blocks.beamform_block*),
30

BeamformOutput (class in
lwa352_pipeline.blocks.beamform_output_block),
34

BeamformSumBeams (class in
lwa352_pipeline.blocks.beamform_sum_beams_block),
32

BeamformVlbiOutput (class in
lwa352_pipeline.blocks.beamform_vlbi_output_block),
37

C

Capture (class in *lwa352_pipeline.blocks.capture_block*),
12

Copy (class in *lwa352_pipeline.blocks.copy_block*), 13

Corr (class in *lwa352_pipeline.blocks.corr_block*), 17

CorrAcc (class in *lwa352_pipeline.blocks.corr_acc_block*),
19

CorrOutputFull (class in
lwa352_pipeline.blocks.corr_output_full_block),
20

CorrOutputPart (class in
lwa352_pipeline.blocks.corr_output_part_block),
27

CorrSubsel (class in
lwa352_pipeline.blocks.corr_subsel_block), 25

D

DummySource (class in
lwa352_pipeline.blocks.dummy_source_block),
39

T

TriggeredDump (class in
lwa352_pipeline.blocks.triggered_dump_block),
15