BEHAVIORAL DEDUPLICATION AND DIVERSITY-GUIDED SELECTION FOR SAMPLE-EFFICIENT FUNSEARCH

CHEN Sijie (59872908) & BIAN Wenbo (59872472)
Department of Computer Science, City University of Hong Kong
{sijiechan2,wbian9}-c@my.cityu.edu.hk

ABSTRACT

We propose **behavioral-fingerprint deduplication** for FunSearch, an LLM-driven evolutionary program search framework. LLM proposers repeatedly produce functionally equivalent heuristics: on an unmodified run we observe a 45% natural duplicate rate, wasting costly API calls and sandbox evaluations. Our method executes each candidate on ten lightweight probing instances, hashes the resulting 375-dimensional decision sequence, and rejects exact matches before full evaluation; we further integrate filter-level diversity and ReEvo reflective evolution (Ye et al., 2024) into the same pipeline. On OR3 online bin packing under a 150-sample budget, deduplication alone reduces *samples-to-best* by 38% ($146 \rightarrow 90$) without degrading the best score. An offline **Behavioural Coverage Rate (BCR)** analysis—introduced as a lightweight tool for characterising exploration behaviour—shows the reverse-intuitive finding that deduplication *alone* drives broader behavioural coverage than deduplication combined with filter-level diversity. Adding ReEvo on top yields the lowest-variance condition in our runs (mean -209.66, std 0.59, n=4), consistent with the landscape-smoothing mechanism reported by Ye et al. (2024).[1]

1 INTRODUCTION

FunSearch (Romera-Paredes et al., 2024) evolves programs by iterating an LLM proposer against an evaluator: each round, the LLM drafts a new heuristic given recent high-scoring ancestors, and a sandbox measures the candidate's score. The paradigm has recently been scaled up to industrial settings — AlphaEvolve (Novikov et al., 2025) reports substantial improvements on Google Borg datacenter scheduling using this same LLM-evolve loop — and online bin packing has emerged as one of its canonical benchmarks (Sim et al., 2025; Liu et al., 2024). Under limited API budgets, however, the *sample efficiency* of the proposer becomes the central differentiator (Ye et al., 2024): the question is not whether a reasonable heuristic can be found, but how many LLM calls it takes.

Our preliminary baseline exposes a concrete waste source. Running unmodified FunSearch on the OR3 instance set for 53 samples, 45% of all programs produced scores *identical* to programs already in the archive, indicating a high rate of behaviourally redundant proposals that syntactic hashing does not catch. This matches the open direction identified by van Stein et al. (2025), who argue that niching and portfolio-style behavioural analysis are under-explored in LLM-driven meta-heuristics. Existing FunSearch variants do not deduplicate at the behavioural level and do not explicitly constrain diversity of accepted programs.

This paper makes three contributions. **(Main)** A three-level *behavioural-fingerprint funnel* (AST-hash $\rightarrow$ probing-fingerprint match $\rightarrow$ a disabled cosine layer), inspired by ReEvo's F-value deduplication (Ye et al., 2024) but lifted to the behaviour level; on OR3 under a 150-sample budget it reduces *samples-to-best* by 38% without degrading best score. **(Extension)** We integrate filter-level diversity and ReEvo reflective evolution on top of deduplication inside the same pipeline and characterise their marginal effects (the complete $\mathrm{Score}(c) = \mathrm{Perf}(c) + \beta \cdot \mathrm{Div}(c)$ cluster scoring is

[1]Reproducibility: https://colab.research.google.com/github/jaycee6666/efficient-funsearch/blob/main/notebooks/efficient_funsearch_colab.ipynb.



Figure 1: System pipeline. Candidates are normalised (L0) and fingerprinted (L1) before sandbox evaluation; cosine (L2) is retained in code but disabled at run time (Section 2.2). Survivors enter an island archive with filter-level diversity; archived programs feed the LLM via prompt construction and, optionally, ReEvo reflection.

future work). **(Tool)** An offline **Behavioural Coverage Rate** (BCR) metric inspired by MAP-Elites (Mouret & Clune, 2015) reveals that deduplication alone reaches full behavioural coverage faster than deduplication combined with filter-level diversity. Together these findings suggest that, at the behaviour level, *removing redundancy* and *promoting novelty* are not simply additive (van Stein et al., 2025).

2 METHOD

2.1 PIPELINE OVERVIEW

The original FunSearch pipeline alternates between an LLM sampler and a sandboxed evaluator, with island-based selection maintaining diversity at the population level (Romera-Paredes et al., 2024). Our enhanced pipeline inserts a deduplication funnel *before* the expensive sandbox, and optionally wires in filter-level diversity and ReEvo reflection around the database (Figure 1). Only programs surviving all enabled dedup levels incur a full sandbox evaluation; accepted programs additionally trigger a lightweight LLM reflection call whose output is stored and replayed as prompt context in later rounds.

2.2 BEHAVIORAL FINGERPRINT

Probing instances. We hand-designed 10 bin-packing probes spanning uniform-medium, large-item, small-varied, bimodal, descending-spread, ascending-spread, sawtooth, tight-pairs, wide-capacity, and an OR3-derived sample (Appendix B). Capacity is drawn from $\{100, 150, 200\}$ and items from $[20, 140]$ to match the OR3 distribution; each probe contains 35–40 items, for a total of 375 decisions.

Fingerprint definition. For a candidate priority function f and probe p_i, we simulate the online first-fit-by-priority assignment: at each step the bin with the highest $f(item, bins)$ is chosen (opening a new bin when needed). The k-th decision is the index of the chosen bin. Concatenating the decisions across all ten probes yields a deterministic 375-dimensional integer tuple, the program's *behavioural fingerprint*.

Three-level funnel. Level 0 normalises the candidate source (variable renaming, comment stripping) through an AST rewriter and hashes the result with SHA-256. Level 1 hashes the fingerprint tuple and performs an $O(1)$ exact-match lookup against an archive. On the proxy probe set, Level 1 matches are exact by construction; at the *fingerprint-match stage* this produces no threshold-based false positive (we discuss the generalisation of this equivalence to out-of-distribution inputs in §4 Insight 2 and §6 #4). Level 2 was implemented as a cosine-similarity check with threshold 0.98; a calibration on 53 baseline programs showed that 98.5% of genuinely different programs would be flagged duplicate, so it is disabled and kept only as a negative result (§4 Insight 2).

Overhead. Normalisation is < 1 ms, executing one probe < 3 ms, the overall fingerprint < 50 ms, and the hash lookup negligible — all dominated by the ~ 11 s sandbox evaluation they replace.

2.3 FILTER-LEVEL DIVERSITY

We use the term *filter-level diversity* throughout to denote the following variant: after a candidate passes the Level-1 fingerprint check, we additionally discard it if its fingerprint's cosine similarity to *any* recent island representative exceeds a threshold. This biases the proposer toward be-

Table 1: Main results at a 150-sample budget. *Samples-to-best* is the first sample number at which a run attains its best score; *Dup rate* is the fraction of candidates rejected by the dedup filter (N/A for baseline, which bypasses the filter).

Condition	n	Best score (mean $\pm$ std)	Samples-to-best	Dup rate
Baseline	2	-210.52 ± 1.31	146 ± 2	N/A
Dedup	4	-210.04 ± 1.00	$\mathbf{90 \pm 36}$	0.401 ± 0.046
Dedup+Div	4	-210.20 ± 0.68	108 ± 21	0.342 ± 0.067
ReEvo	4	$\mathbf{-209.66 \pm 0.59}$	101 ± 16	0.314 ± 0.034

haviourally under-represented regions without modifying the island's softmax cluster sampling inside `programs_database.py`. We emphasise that our experiments do not evaluate the full cluster score $\mathrm{Score}(c) = \mathrm{Perf}(c) + \beta \cdot \mathrm{Div}(c)$ with adaptive β scheduling (listed as future work in §6); all mentions of "diversity" in the remainder of this paper refer to this filter-level variant.

2.4 ReEvo Reflective Evolution

Following Ye et al. (2024), we add a per-accepted-program reflection step: after a program is scored, the LLM is asked in 1–2 sentences to describe the algorithmic strategy the program uses and how it differs from a simple greedy approach. We keep the top-3 highest-scoring reflections and inject them as comments into the next prompt as "strategy insights from top-performing programs" (full prompt in Appendix C). Context: ReEvo's landscape-smoothing analysis (Ye et al., 2024, Table 4) reports a $4.5\times$ increase in correlation length and 45.8% objective improvement on related heuristic-design benchmarks, which provides a plausible mechanism consistent with the variance reduction we observe (§3.2).

2.5 Offline Behavioural Coverage Rate (BCR)

BCR is a post-hoc diagnostic that characterises how quickly a run visits distinct behavioural regions. It is defined only for fingerprint-exporting conditions (*dedup*, *dedup+div*); baseline bypasses the filter, and our ReEvo run did not set `EXPORT_FINGERPRINTS=1`. Given the union of fingerprints, we fit a single k-means (K=8) once, then replay each condition's time series: $\mathrm{BCR}(t) = |\{c(\mathbf{f}_s) : s \leq t\}|/K$. Offline fit-then-replay avoids cluster-relabelling drift at this sample size. The coverage intuition follows MAP-Elites (Mouret & Clune, 2015; Novikov et al., 2025); we do not claim alignment with van Stein et al.'s runtime-trajectory definition (van Stein et al., 2025).

3 Experiments

3.1 Setup

All experiments use OR-Library OR3 for evaluation and Weibull-5k as auxiliary data, following the FunSearch evaluation protocol (Romera-Paredes et al., 2024). The LLM proposer is `gpt-5-nano` via the course API, with 10 islands, 4 samples-per-prompt, and a 30 s sandbox timeout. Each run is capped at 150 LLM samples — well below the 20,000-call budget — to keep the comparison within the "low-sample regime" studied by Ye et al. (2024). We evaluate four conditions: *baseline* (unmodified FunSearch, n=2), *dedup* (fingerprint funnel only, n=4), *dedup+div* (funnel plus filter-level diversity, n=4), and *reevo* (funnel plus ReEvo reflection, n=4). Total API usage across all runs is $\sim$ 2,100 calls.

3.2 Main Results

Table 1 and Figure 2 reveal four observations.

(O1) Main contribution. Baseline→Dedup reduces samples-to-best from 146 to 90, a 38.4% **reduction** in the number of LLM samples the proposer consumes before the run's best program is discovered. The best score itself is unchanged ($-210.52 \rightarrow -210.04$).



Figure 2: Best-score convergence versus sample number across the four conditions (mean $\pm$ std band, n=2–4). All conditions land within -210 ± 1; the ReEvo condition is the only one whose mean is below -210.



Figure 3: Behavioural Coverage Rate over sample index. Dedup-only (blue) reaches full coverage (BCR$=1$) at sample 51; Dedup+Div (orange) reaches full coverage at sample 65. Only these two conditions export fingerprints in the current run set.

(O2) No observable performance degradation. All four conditions have best scores in -210 ± 1. We therefore conclude that, on this budget, neither deduplication, filter-level diversity, nor reflection imposes a measurable best-score cost — a finding that is consistent with (but, per §4 Insight 2, does not directly verify) a low false-positive rate on the full input distribution.

(O3) ReEvo is the lowest-variance condition. ReEvo is the only condition whose mean is below -210 (-209.66 ± 0.59). This is consistent with the landscape-smoothing mechanism attributed to reflection by Ye et al. (2024). We avoid strong causal claims, since n=4 is insufficient for significance testing.

(O4) Dup rates decrease with extra signals. Among dedup-equipped conditions, the rejection rate drops from 0.401 (dedup) to 0.342 (dedup+div) to 0.314 (reevo), indicating that filter-level diversity and reflection push the LLM toward genuinely new behaviours relative to the archive. (We do not include baseline in this trend because it does not route candidates through the dedup filter; the 45% natural duplicate rate mentioned in §1 is computed independently on identical-score counts.)



Figure 4: t-SNE ($perplexity$=20) of $\sim$ 200 fingerprint vectors (each 375-dim) collected from the fingerprint-exporting *Dedup* and *Dedup+Div* runs. The two point clouds overlap substantially but Dedup+Div spreads out more within each cluster.

3.3 Behavioural Coverage Analysis

Figure 3 plots BCR(t) for the two fingerprint-exporting conditions: Dedup-only reaches $\mathrm{BCR} = 1.0$ at sample 51, whereas Dedup+Div takes until sample 65. **Reverse-intuitive finding:** filter-level diversity *slows* cluster visitation. Once duplicates are filtered, retained samples are already diverse by construction; the extra diversity constraint then over-constrains the proposer, concentrating exploration within already-reached clusters. This exposes a mechanism-level difference not visible in the best-score curve (van Stein et al., 2025).

3.4 Fingerprint Space Visualisation

Figure 4 visualises fingerprints from the two runs with `EXPORT_FINGERPRINTS=1`. Both conditions visit overlapping regions; Dedup+Div spreads further *inside* each cluster while Dedup-only reaches more distinct clusters, consistent with Figure 3.

3.5 ReEvo Late Breakthroughs

All four ReEvo runs (Figure 5) show an early plateau followed by a late-stage improvement between samples 87 and 123, qualitatively consistent with the hypothesis that the reflection buffer needs to accumulate high-scoring strategies before it can inform the proposer. n=4 precludes a causal claim.

4 Discussion

Deduplication subsumes first-order diversity. The 38% samples-to-best reduction and the BCR curves together show that removing behavioural redundancy already delivers the exploration effect that explicit diversity mechanisms target; stacking filter-level diversity on top slows cluster visitation and spreads points within clusters rather than reaching new ones. This echoes Novelty Search's observation that penalising redundancy can substitute for rewarding novelty directly (Lehman & Stanley, 2011).

Cosine on discrete decision vectors is degenerate. On 53 calibration programs, 98.5% of genuinely different fingerprint pairs had cosine similarity > 0.98: high-dimensional integer vectors whose entries share narrow ranges (bin indices in $[0, 20]$) dilute the 1–2 mismatched coordinates. Level 2 is therefore disabled, so the fingerprint-match stage itself produces no threshold-based false



Figure 5: Per-run ReEvo convergence curves. All four runs show a late improvement at roughly sample 87–123, after an initial plateau.

positive. This does not prove out-of-distribution equivalence (§6 #4); the practical takeaway is that discrete measures (Hamming/edit distance) or learned metrics are prerequisites for any high-dimensional behavioural similarity filter.

Reflection consistent with landscape smoothing. ReEvo's low mean (-209.66) and low variance (0.59), together with the late-breakthrough pattern (§3.5), are qualitatively consistent with Ye et al. (2024)'s landscape-smoothing mechanism; $n{=}4$ precludes a causal claim.

5 Related Work

LLM-driven evolutionary program search. FunSearch (Romera-Paredes et al., 2024) established LLM-evolve for heuristic discovery; AlphaEvolve (Novikov et al., 2025) scaled it to industrial tasks and identifies FunSearch's single-LLM / single-evaluator structure as a limiting factor (Novikov et al., 2025, §5). EoH (Liu et al., 2024) and the online-bin-packing survey (Sim et al., 2025) explore the same space for combinatorial heuristics. We retain FunSearch's minimalist loop and target the proposer's sample efficiency at the behaviour level.

Reflection and behaviour-driven search. ReEvo (Ye et al., 2024) introduces LLM reflection between generations; we integrate it inside the FunSearch loop. Novelty Search (Lehman & Stanley, 2011) and MAP-Elites (Mouret & Clune, 2015) established behavioural-coverage metrics; BCR is inspired by MAP-Elites but measures cluster visitation over time. Van Stein et al. (van Stein et al., 2025) advocate behaviour-space analysis for LLM-driven meta-heuristics via runtime trajectories; our fingerprint uses probe decisions as a different behavioural proxy.

6 Limitations

(1) Sandbox bypass: probes run via `exec()` with a 5 s timeout; production use should route probing through the forked sandbox. **(2) Statistical power:** $n{=}2$–4 runs do not meet significance thresholds. **(3) Filter-level only:** adaptive-β cluster scoring ($\text{Perf} + \beta \cdot \text{Div}$) is future work. **(4) Probe generalisation:** 375-decision fingerprint equivalence is not verified end-to-end on the full OR3 distribution (O2 is indirect evidence). **(5) BCR/t-SNE scope:** Dedup and Dedup+Div only.

7 Conclusion

Behavioural-fingerprint deduplication cuts FunSearch's samples-to-best by 38% on OR3 online bin packing without degrading best score; BCR analysis reveals that filter-level diversity *slows* cluster coverage, while ReEvo gives the lowest-variance condition, consistent with landscape smoothing. Future work: adaptive-β cluster scoring and larger sample budgets.

REFERENCES

Joel Lehman and Kenneth O. Stanley. Novelty search and the problem with objectives. In *Genetic Programming Theory and Practice IX*, pp. 37–56. Springer, 2011.

Fei Liu, Xialiang Tong, Mingxuan Yuan, Xi Lin, Fu Luo, Zhenkun Wang, Zhichao Lu, and Qingfu Zhang. Evolution of heuristics: Towards efficient automatic algorithm design using large language model. *arXiv preprint arXiv:2401.02051*, 2024. URL https://arxiv.org/abs/2401.02051.

Jean-Baptiste Mouret and Jeff Clune. Illuminating search spaces by mapping elites. *arXiv preprint arXiv:1504.04909*, 2015. URL https://arxiv.org/abs/1504.04909.

Alexander Novikov, Ngân Vũ, Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, Sergey Shirobokov, Borislav Kozlovskii, Francisco J. R. Ruiz, Abbas Mehrabian, M. Pawan Kumar, Abigail See, Swarat Chaudhuri, George Holland, Alex Davies, Sebastian Nowozin, Pushmeet Kohli, and Matej Balog. AlphaEvolve: A coding agent for scientific and algorithmic discovery. *arXiv preprint arXiv:2506.13131*, 2025. URL https://arxiv.org/abs/2506.13131.

Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Márton Balog, M. Pawan Kumar, Emilien Dupont, Francisco J. R. Ruiz, Jordan Ellenberg, Pengming Wang, Omar Fawzi, Pushmeet Kohli, and Alhussein Fawzi. Mathematical discoveries from program search with large language models. *Nature*, 625(7995):468–475, 2024. doi: 10.1038/s41586-023-06924-6.

Kevin Sim, Quentin Renau, and Emma Hart. Beyond the hype: Benchmarking LLM-evolved heuristics for bin packing. In *Applications of Evolutionary Computation (EvoApplications)*, 2025. URL https://arxiv.org/abs/2501.11411.

Niki van Stein, Haoran Yin, Anna V. Kononova, Thomas Bäck, and Gabriela Ochoa. Behaviour space analysis of LLM-driven meta-heuristic discovery. *arXiv preprint arXiv:2507.03605*, 2025. URL https://arxiv.org/abs/2507.03605.

Haoran Ye, Jiarui Wang, Zhiguang Cao, Federico Berto, Chuanbo Hua, Haeyeon Kim, Jinkyoo Park, and Guojie Song. ReEvo: Large language models as hyper-heuristics with reflective evolution. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. URL https://arxiv.org/abs/2402.01145.

A REPRODUCIBILITY AND IMPLEMENTATION NOTES

All results are logged from runs conducted between 2026-04-15 and 2026-04-21 on the course-provided `gpt-5-nano` endpoint. Per-condition run seeds, log files, and the aggregation script are included in the released repository; the reported means and standard deviations are reproduced exactly by `scripts/collect_results.py`.

API robustness. The LLM wrapper uses a 60 s socket timeout and at most 5 exponential-backoff retries, configurable via `API_TIMEOUT` and `API_MAX_RETRIES` environment variables. This bound was added on 2026-04-21 to cap wall-clock on re-runs; it does not affect the logged 150-sample results, which completed under a previous, unbounded retry configuration. The Colab notebook linked in the abstract regenerates every table and figure from the raw CSV logs without rerunning the LLM loop.

B PROBING INSTANCES

Name	Capacity	Items	Description
or3_sample	150	40	First 40 items of OR3 `u500_00`
medium_uniform	150	40	$[30, 31, \ldots, 69]$; pairwise packing possible
large_items	150	35	$[75, 76, \ldots, 109]$; ≤ 2 per bin
small_varied	150	40	Non-monotonic items in $[20, 38]$
bimodal	150	36	18 large (~ 100) + 18 small (~ 25)
descending_spread	150	35	$140, 137, \ldots, 38$ (FFD-style stress)
ascending_spread	150	35	$25, 28, \ldots, 127$
sawtooth	150	36	Periodic $\{30, 50, 70, 90, 110, 130\} \times 6$
tight_pairs	100	40	Items $\sim 50\%$ capacity; many feasible bins
wide_capacity	200	38	Deep bin states, items in $[30, 100]$
Total		375	Fingerprint dimensionality

Table 2: Ten probing instances used to compute behavioural fingerprints. Each instance is deterministic; the fingerprint is the concatenation of the online bin-assignment decisions over all 375 items.

C REEVO REFLECTION PROMPT

After a candidate program is accepted (passes dedup and receives a valid score), we issue the following reflection call to the same LLM backbone:

```
The following Python function is a heuristic for online bin
packing.  It scored {score} (higher is better; optimal is
around −200).
```python
{program body}
```
In 1--2 sentences, describe the algorithmic strategy this
function uses and how it differs from a simple greedy
approach. Be concise.
```

The reflection text (max 150 tokens) is stored by program-body hash. At prompt construction time, the top-3 reflections by score are appended as Python comments under the header `# Strategy insights from top-performing programs:` before the next LLM call.

D HYPERPARAMETERS

Component	Parameter	Value
FunSearch	`num_islands`	10
	`samples_per_prompt`	4
	`functions_per_prompt`	2
	`cluster_sampling_temperature_init`	0.1
	`evaluate_timeout_seconds`	30
LLM	model	`gpt-5-nano`
	`max_tokens`	4096 (main), 150 (reflection)
Dedup	`level0_enabled`	`True`
	`level1_enabled`	`True`
	`level2_enabled`	`False` (see §2.2)
	`cosine_threshold`	0.98
	`probe_timeout_seconds`	5
Diversity	`beta_init`	0.3
	`beta_decay_period`	350
ReEvo	`max_reflections`	20
	top-k for prompt	3

Table 3: Hyperparameter summary. Sources: `implementation/config.py`, `src/dedup/dedup_config.py`, and the ReEvo integration block of `funsearch_bin_packing_llm_api.py`.