

Test execution automation

- Write test cases
 - ☐ Document intended behavior
 - ☐ Execute the program
 - ☐ Check observed behavior against intended behavior.
- Frameworks:
 - ☐ Unit testing: Junit,
 - ☐ GUI testing: Selenium, Robotium, Monkey
 - ☐ BDT: Cucumber

Advantages

- Script once, execute multiple times (per day)
- Document oracles
- Measurable in terms of adequacy and effectiveness

Testing with JUnit

- Junit is a **unit test environment** for Java programs developed by *Erich Gamma* and *Kent Beck*.
 - Writing test cases
 - Executing test cases
 - Pass/fail? (expected result = obtained result?)
- Consists in a **framework** providing all the tools for testing.
 - framework: set of classes and conventions to use them.
- It is **integrated into Eclipse** through a graphical plug-in.


Junit (3.x and 4.x)

■ Test framework

- test cases are Java code
- test case = “sequence of operations + inputs + expected values”

■ Production code

```
public int min(...){  
    //return the minimum  
}
```



■ Test code

```
void testMin(...) {  
    int result= obj.mean(2, 7);  
    assertEquals(2, result);  
}
```

JUnit 3.x for testing programs

- JUnit tests
 - “substitute the use of **main()** to check the program behaviour”
- All we need to do is:
 - write a sub-class of **TestCase** ← **junit.framework.***
 - add to it one or more **test methods**
 - Method names starting with “test”: **testMean()**
 - run the test using JUnit

Framework elements

- **TestCase**


- Base class for classes that contain tests

- **assert*()**

- Method family to ***check conditions***

- **TestSuite**

- Enables grouping several test cases



An example

```
class Stack {  
    public boolean isEmpty(){ ... }  
    public void push(int i){ ... }  
    public int pop(){ ... }  
    ...  
}
```

```
import junit.framework.TestCase;
```

```
public class StackTester extends TestCase {
```

```
    public void testIsEmpty() {  
        Stack aStack = new Stack();  
        System.out.println("Is stack empty: " + aStack.isEmpty());  
        // it should be empty.  
    }
```

```
}
```

Must begin with
"test"

Assert*()

- Public methods defined in the base class `TestCase`
- Their names begin with “assert” and *are used in test methods*
 - es. `assertTrue(“stack should be empty”, aStack.empty());`
- If the condition is false:
 - test fails
 - execution skips the rest of the test method
 - the message (if any) is printed
- If the condition is true:
 - execution continues normally

An example


```
import junit.framework.TestCase;

public class StackTester extends TestCase {

    public void testIsEmpty() {
        Stack aStack = new Stack();
        assertTrue("stack should be empty", aStack.empty());
    }

}
```

Assert*()

- for a boolean condition
 - **assertTrue("message for fail", condition);**
 - **assertFalse("message", condition);**
- for object, int, long, and byte values
 - **assertEquals(expected_value,  expression);**
- for float and double values
 - **assertEquals(expected, expression, error);**
- for objects references
 - **assertNull(reference)**
 - **assertNotNull(reference)**
- ...

Assert: example

```
public void testStack() {  
    Stack aStack = new Stack();  
    assertTrue("Stack should be empty!", aStack.isEmpty());  
    aStack.push(10);  
    assertFalse("Stack should not be empty!", aStack.isEmpty());  
    aStack.push(4);  
    assertEquals(4, aStack.pop());  
    assertEquals(10, aStack.pop());  
}
```

```
class Stack {  
    public boolean isEmpty(){ ... }  
    public void push(int i){ ... }  
    public int pop(){ ... }  
    ...  
}
```

One concept at a time ...

```
public class StackTester extends TestCase {  
    public void testStackEmpty() {  
        Stack aStack = new Stack();  
        assertTrue("Stack should be empty!", aStack.isEmpty());  
        aStack.push(10);  
        assertFalse("Stack should not be empty!", aStack.isEmpty());  
    }  
    public void testPushPop() {  
        Stack aStack = new Stack();  
        aStack.push(10);  
        aStack.push(-4);  
        assertEquals(-4, aStack.pop());  
        assertEquals(10, aStack.pop());  
    }  
}
```

Working rule

- For each test case class, JUnit
 - execute all of its test methods
 - i.e. those whose name starts with “test” or annotated with @Test
 - ignores everything else ...

TestSuite

- Groups several test cases:

junit.framework.*




```
public class AllTests extends TestSuite {  
    public static TestSuite suite() {  
        TestSuite suite = new TestSuite();  
        suite.addTestSuite(StackTester.class);  
        suite.addTestSuite(AnotherTester.class);  
        return suite;  
    }  
}
```

Test of “Exceptions”

- There are two cases:
 1. We expect a **normal behavior** and then no exceptions.
 2. We expect **an anomalous behavior** and then an exception.

We expect a normal behavior ...


```
try {  
    // We call the method with correct parameters  
    object.method("Parameter");  
    assertTrue(true); // OK  
} catch(PossibleException e){  
    fail("method should not fail !!!");  
}
```



```
class TheClass {  
    public void method(String p)  
        throws PossibleException  
    { /*... */ }  
}
```

We expect an exception ...

```
try {  
    // we call the method with wrong parameters  
    object.method(null);  
    fail("method should fail!!");  
} catch(PossibleException e){  
    assertTrue(true); // OK  
}
```



```
class TheClass {  
    public void method(String p)  
        throws PossibleException  
    { /*... */ }  
}
```

SetUp() and tearDown()

- **setUp()** method initialize object(s) under test.
 - called before every test method
- **tearDown()** method release object(s) under test
 - called after every test case method.


```
ShoppingCart cart;  
Book book;  
  
protected void setUp() {  
    cart = new ShoppingCart();  
    book = new Book("JUnit", 29.95);  
    cart.addItem(book);  
}  
...
```

Create a new JUnit test case

Eclipse Menu

File Edit Source Refactor Navigate Search Project Run Window Help

- File
 - New
 - Junit Test Case
 - Set the parameters:
 - Junit 3.x or 4.x
 - name of the class
 - etc.
 - Finish




Run as JUnit Test

Eclipse Menu

File Edit Source Refactor Navigate Search Project **Run** Window Help

- Run
 - Run As
 - Junit Test





Maven and Unit testing


- All test code should go under:
 - `src/test/java`
- All test resources should go under:
 - `src/test/resources`
- Tests can be run (command line):
 - `mvn test`

Red / Green Bar

Fail



Pass



expected <-3> but was <-4>

JUnit 3.x and JUnit 4.x

- Most things are about equally easy
 - JUnit 4 can still run JUnit 3 tests
- All the old **assertXXX** methods are the same
- JUnit 4 has some additional features
- JUnit 4 provides protection against infinite loops
- JUnit 4 uses annotations (@)

From JUnit 3.x to 4.x

- JUnit 4 requires Java 5 or newer
- Don't extend **junit.framework.TestCase**; just use an ordinary class
- Import **org.junit.*** and **org.junit.Assert.***
 - Use a *static* import for **org.junit.Assert.***
 - Static imports replace inheritance from **junit.framework.TestCase**
- Use annotations instead of special method names:
 - Instead of a **setUp** method, put **@Before** before some method
 - Instead of a **tearDown** method, put **@After** before some method
 - Instead of beginning test method names with '**test**', put **@Test** before each test method

Annotations in J2SE

- J2SE 5 introduces the **Metadata** feature (data about data)
- Annotations allow you to add **decorations** to your code (remember javadoc tags: *@author*)
- Annotations are used for code documentation, compiler processing (*@Deprecated*), code generation, runtime processing
- New annotations can be created by developers

<http://java.sun.com/docs/books/tutorial/java/javaOO/annotations.html>

JUnit 4.x for testing programs

Import the JUnit 4 classes you need

```
import org.junit.*;  
import static org.junit.Assert.*;
```

Declare your (conventional) Java class

```
public class MyProgramTest {
```

Declare any variables you are going to use, e.g., an instance of the class being tested

```
MyProgram program;  
int [ ] array;  
int solution;
```

JUnit 4.x for testing programs (2)

If needed, define *one* method to be executed *just once*, when the class is first loaded. For instance, when we need to connecting to a database

@BeforeClass

```
public static void setUpClass() throws Exception {  
    // one-time initialization code  
}
```

If needed, define *one* method to be executed *just once*, to do cleanup after all the tests have been completed

@AfterClass

```
public static void tearDownClass() throws Exception {  
    // one-time cleanup code  
}
```

JUnit 4.x for testing programs (3)

If needed, define *one or more* methods to be executed before each test, e.g., typically for initializing values

@Before

```
public void setUp() {  
    program = new MyProgram();  
    array = new int[] { 1, 2, 3, 4, 5 };  
}
```

If needed, define *one or more* methods to be executed after each test, e.g., typically for releasing resources (files, etc.)

@After

```
public void tearDown() {  
}
```

JUnit 4.x for testing programs (4)

- A test method is annotated with **@Test**
- It takes no parameters, and returns no result.
- All the usual **assertXXX** methods can be used

@Test

```
public void sum() {  
    assertEquals(15, program.sum(array));  
    assertTrue(program.min(array) > 0);  
}
```

Additional Features of @Test

To avoid infinite loops, an execution time limit can be used. The time limit is specified in milliseconds. The test fails if the method takes too long.

```
@Test (timeout=10)  
    public void greatBig() {  
        assertTrue(program.ackerman(5, 5) > 10e12);  
    }
```

Some method calls should throw an exception. We can specify that an exception is expected. The test will pass if the expected exception is thrown, and fail otherwise

```
@Test (expected=IllegalArgumentException.class)  
    public void factorial() {  
        program.factorial(-5);  
    }
```


Parameterized tests

Using **@RunWith(value=Parameterized.class)** and a method **@Parameters**, a test class is executed with several inputs

```
@RunWith(value=Parameterized.class)
```

```
public class FactorialTest {  
    private long expected;  
    private int value;
```

Parameters used to exercise
different instances of the class



```
@Parameters
```

```
public static Collection data() {  
    return Arrays.asList( new Object[ ][ ] { { 1, 0 }, { 1, 1 }, { 2, 2 }, { 120, 5 } } );  
}
```

```
public FactorialTest(long expected, int value) { // constructor  
    this.expected = expected;  
    this.value = value;  
}
```

```
@Test
```

```
public void factorial() {  
    assertEquals(expected, new Calculator().factorial(value));  
}  
}
```

Ignoring tests

The `@Ignore` annotation says to not run a test

```
@Ignore("I don't want Dave to know this doesn't work")
@Test
public void add() {
    assertEquals(4, sum(2, 2));
}
```

You shouldn't use `@Ignore` without a very good reason!


```
import org.junit.runners.Suite;  
import org.junit.runners.Suite.SuiteClasses;
```

Test suites

As before, you can define a suite of tests

```
@RunWith(value=Suite.class)  
@SuiteClasses(value={  
    value=test1.class,  
    value=test2.class  
})  
public class AllTests { ... }
```

It could be empty



Hamcrest (cool assertions)

- Enhances readability of test code
- Example:
 - `assertEquals(theBook, myBook)`
 - **`assertThat(theBook, is(equalTo(myBook)))`**

See <http://code.google.com/p/hamcrest/wiki/Tutorial>

Exercise: Test the calculator (JUnit 4)

```
public class Calculator {  
    public int add(int a, int b)  
    public int divide(int a, int b)  
    ...  
}
```

```
@Test
public void addition() {
    Calculator calculator = new Calculator ();
    int result = calculator.add(2, 3);
    assertEquals(5, result);

    result = calculator.add(-2, -3);
    assertEquals(-5, result);
}
```

```
@Test
public void divisionNormal() {
    Calculator calculator = new Calculator ();
    int result = calculator.divide(4, 2);
    assertEquals(2, result);
}
```

```
@Test
public void divisionByZero() {
    Calculator calculator = new Calculator ();
    try {
        int result = calculator.divide(2, 0);
        fail("Division by zero exception was expected!");
    } catch (ArithmeticException success) {
        assertNotNull(success.getMessage()); /* Pass! 😊 */
    }
}
```

```
public class FizzBuzz {  
  
    private static final int THREE = 3;  
    private static final int FIVE = 5;  
  
    public String calculate(int number) {  
        if (isDivisibleBy(number, THREE) && isDivisibleBy(number, FIVE)) {  
            return "FizzBuzz";  
        }  
  
        if (isDivisibleBy(number, THREE)) {  
            return "Fizz";  
        }  
  
        if (isDivisibleBy(number, FIVE)) {  
            return "Buzz";  
        }  
  
        return String.valueOf(number);  
    }  
  
    private boolean isDivisibleBy(int dividend, int divisor) {  
        return dividend % divisor == 0;  
    }  
}
```

```
@Test
@Parameters({"1", "2", "4", "7", "11", "13", "14"})
public void returnsNumberForNumberNotDivisibleByThreeAndFive(int number) {
    assertThat(fizzBuzz.calculate(number)).isEqualTo("" + number);
}
```

```
@Test
@Parameters({"3", "6", "9", "12", "18", "21", "24"})
public void returnFizzForNumberDivisibleByThree(int number) {
    assertThat(fizzBuzz.calculate(number)).isEqualTo("Fizz");
}
```

```
@Test
@Parameters({"5", "10", "20", "25", "35", "40", "50"})
public void returnBuzzForNumberDivisibleByFive(int number) {
    assertThat(fizzBuzz.calculate(number)).isEqualTo("Buzz");
}
```

```
@Test
@Parameters({"15", "30", "45", "60"})
public void returnsFizzBuzzForNumberDivisibleByThreeAndFive(int number) {
    assertThat(fizzBuzz.calculate(number)).isEqualTo("FizzBuzz");
}
```

Test the calculator (JUnit 4)

```
public class Calculator {  
    public int add(int a, int b)  
    public int divide(int a, int b)  
    ...  
}
```

```
@Test  
public void addition() {  
    Calculator calculator = new Calculator ();  
    int result = calculator.add(2, 3);  
    assertEquals(5, result);  
  
    result = calculator.add(-2, -3);  
    assertEquals(-5, result);  
}
```

Test the average method

```
public class Calculator {  
    private double average(double[] m)  
    {  
        double sum = 0;  
        for (int i = 0; i < m.length; i++) {  
            sum += m[i];  
        }  
        return sum / m.length;  
    }  
}
```

```
@Test  
public void average() {  
  
}
```

Testability is important

```
public class Calculator {  
    private double average(double[] m)  
    {  
        double sum = 0;  
        for (int i = 0; i < m.length; i++) {  
            sum += m[i];  
        }  
        return sum / m.length;  
    }  
}
```


```
@Test  
public void average() {  
  
    // NOT TESTABLE because average is private!  
  
}
```

When testing programs?

- Test last
 - The conventional way for testing in which testing follows the implementation
- Test first
 - The agile view in which testing is used as a development tool

Test last

New functionality



Understand

Implement functionality

Write tests

Run all tests

Rework

Result?

fail


pass

Next functionality

“Extreme programming” (XP) champions the use of tests as a development tool ...

Test first

New functionality




Best Unit Testing Practices

- **During Development:** When you need to add new functionality to the system, write the **tests first**. Then, you will be done developing when the test runs.
- **During Debugging:** When someone discovers a bug in your code, first write a test case that fails (finds the failure). Then debug and repair the code until the test succeeds.

TDD (test first) Advantages

- Each method has an associated testcase
 - the **confidence** of our code increases ...
- It simplifies:
 - **refactoring**/restructuring
 - maintenance
 - the introduction of new functionalities
- Test first helps to build the **documentation**
 - testcases are good “use samples”
- Programming is more fun ...

Test-first with Junit



When do we have enough testing?

“Each software system should be thoroughly tested”.

- What does thorough mean?
- How can we measure *test adequacy*?
- When can we stop testing?