


# UI Component and React

Dr Harshad Prajapati  
30 Nov 2023

1

## Function: Let's Understand What a Function Does



Output will change as input changes

**Example:**


```
sortedStudentList = sort(studentList)
```

2


# Object




Real world object  
(Student)




# Component in General



# What is a React Component



# What is a React Component



# Instantiate Object versus Component

If there is a class named **Student**, we instantiate it using the following:

```
student = new Student("Tom", 21, 6);
```

When we want to display student object, we use its `toString()` method.

If there is a component named **Student**, we instantiate it using the following:

```
<Student name="Tom" age=21 sem=6 />
```

When we want to display student component, we use `render()` method of class component or return value of functional component.

7

## View of **Object** versus UI **Component** for Outside World

Return value of method (`toString()`):

```
"Information about" + "Tom" + "\n" +  
"\tAge:" + 20 + "\tSem:" + 6
```

This is what  
method  
returns

```
Information about Tom  
Age: 20  
Sem: 6
```


This is what  
is printed

Return value of component:

```
<div ...>  
    
  <div ...>Tom</div>  
  <div ...>Age: 21</div>  
  <div ...>Semester: 6</div>  
</div>
```

This is what  
component  
returns

This is what  
component  
looks like



8

# What else a React Component can do?

- ✓ A component is a self contained **reusable** UI part.



Component can allow a user to **interact with itself**


For example, change profile picture by interacting with it using keyboard /touch/mouse

We define a Student component once and then can create multiple instances of the component for different students.

9


## React Component

- A React component is composed of:
  - A template (HTML)
  - Interactivity (JavaScript)
  - Styles (CSS)



10

# Separation of Data and View



11

## Data Related to Component

- A React component can have **dynamic information** in **two forms**:

- ✓ **props** (Properties): Initialization values.

- **state**: State is within the component.

- ✓ **Props**:

- **Props** are **arguments** passed into **React component**, similar to arguments passed to a function.
- Props are **immutable**.

- ✓ **State**:

- State is **mutable**.
- The **state object** can contain **multiple properties**.

12

# Props (Initialization values)

- ✓ Information that is passed from one component to another is called as props in React.
- A component's props is an object and it holds initialization information about the component.
- These props are transferred to the component through the constructor of the class component and through function arguments in functional component.
- We can access props object inside a component using `this.props.<propName>` in class component or `props.<propName>` in a functional component.

13

## What is a React Component with Props

- ✓ We can pass data as props to the component.
- Suppose, the student component is defined (class or function) and is named as **Student**.
- And Student component is used in **StudentList** component.

The parent component (StudentList) can pass values to three props (name, age, and sem)

```
<div ... >  
  <Student name="Keanu" age=21 sem=6 />  
  <Student name="Tom" age=21 sem=6 />  
</div>
```

Student component




Each component instance will have its own props.

14

# What is a React Component with **State**

- The state is **not passed from the outside**. A component decides **its own state**.
- To create state, we need to assign an object (called **state object**) to **this.state** property in **class component** OR using hook (**useState**) in a **functional component**.
- For example,
  - When we **click + or - button**, the **counter** gets **incremented or decremented**.
  - This **count value** is the **state** of the component.




15

# React Component with **Composition**

- We can **compose existing components** to create a **new component**.
- For example, We can implement Counter using **existing component Button and Count**.

```
<div ...>
  <Button ... />
  <Count .../>
  <Button ... />
</div>
```


Code fragment of  
Counter component



16




# What Should Happen if Props Change



17

# What Should Happen if State Change



18

# What React is Responsible for

- React is responsible for:
  - ✓ **Rendering** and **re-rendering** component (creating **virtual DOM**).
  - ✓ **Updating** virtual DOM into **actual browser DOM** efficiently.