AOS
DAIE

~~Resource~~ - ~~Avail~~

PAGE No. DATE 01/2/24

Eg:

	Allocation A	B	C	Max			Available			Need		
							~~7 5 5~~					
P_0	0	1	0	7	5	3	~~3 3 2~~			7	4	3
P_1	2	0	0	3	2	2	~~5 3 2~~			1	2	2
P_2	3	0	2	9	0	2	10 5 7			6	0	0
P_3	2	1	1	2	2	2	~~7 4 3~~			0	1	1
P_4	0	0	2	4	3	3	~~7 4 5~~			4	3	1

work = 3 3 2, finish = [T T T T T] (P_0 P_1 P_2 P_3 P_4)
(available).

⇒ 7 4 3 ≤ 3 3 2 ✗ → so P_0 have to wait.

1 2 2 ≤ 3 3 2 ✓ → P_1 will be allocated resource and finished.

∴ work = work + allocation
= 3 3 2 + 2 0 0
= [5 3 2]

~~{7 4 3 ≤ 5 3 2 ✗ wait}~~ ✗

6 0 0 ≤ 5 3 2 ✗ wait

0 1 1 ≤ 5 3 2 ✓ → P_3 will be allocated resource finished

∴ work = work + allocation
= 5 3 2 + 2 1 1
work = [7 4 3]

4 3 1 ≤ 7 4 3 ✓ → P_4 will be allocated.

∴ work = work + allocation
= 7 4 3 + 0 0 2
= [7 4 5]

⇒ 7 4 3 ≤ 7 4 5 ✓ → P_0 executes.

∴ work = work + allocation
= 7 4 5 + 0 1 0
= [7 5 5]

→ 6 0 0 ≤ 7 5 5 ✓ → P_2 resource will be allocated.

∴ work = 7 5 5 + 3 0 2
= [10 5 7]

⇒ Resource-Request Algo^r.

→ When a request is made by P_i, following actions are taken

① if (request ≤ need), go to step ②
otherwise raise the error
(Exceeded max^m limit);

② if (request ≤ available), go to step ③
otherwise P_i must wait.

③ Allocate resources to P_i. (pretend).

④ (Available = Available − request,)
then (allocation$^{[i]}$ = allocation$^{[i]}$ + request[i])

& {need[i] = need[i] − request[i]}

→ Check the resulting resource allocation is safe or not.
If yes allocate resource and if no then old state is restored.

Q. Suppose in the prev. ques. P_1 request 1 additional instance of A and 2 instances of C,

P_1 = [1 0 2]
req^s(P_1)

→ here, 1 0 2 ≤ need(P_1)
1 0 2 ≤ 1 2 2 ✓

then check, req(Pi) < available req(Pi)

1 0 2 < 3 3 2 ✓

means; allocate resources (pretend).

⇒ available (Pi) = avail^b − req^s
= 3 3 2 − 1 0 2
= [2 3 0] → work.

allocation (Pi) = alloc + req^s
= 2 0 0 + 1 0 2
= [3 0 2]

need (Pi) = need − req^s
= 1 2 2 − 1 0 2
= [0 2 0]

⇒ now check for safe state,

need ≤ available.

0 2 0

7 4 3 ≤ 2 3 0 X → P0 wait

0 2 0 ≤ 2 3 0 ✓ → P1 exec.

work = work + allocation
= 2 3 0 + 3 0 2
= 5 3 2

6 0 0 ≤ 5 3 2 X → P2 exec wait

~~work = work + alloc~~
~~= 6 3 4 + 3 0 2~~
~~= 9 3 6~~

0 1 1 ≤ 5 3 2 ✓ → P3 exec

work = 5 3 2 + 2 1 1
= 7 4 3

Disk scheduling X

4 3 1 ≤ 7 4 3 → P_4 exec

work = 7 4 3 + 0 0 2

= 7 4 5

⇒ 7 4 3 ≤ 7 4 5 → P_0 exec

work = 7 4 5 + 0 1 0

= 7 5 5

6 0 0 ≤ 7 5 5 → P_2 exec

work = 7 5 5 + 3 0 2

= [10 5 7]

Ans.

Safe seq^n found so it is in safe state.

$[P_1 \rightarrow P_3 \rightarrow P_4 \rightarrow P_0 \rightarrow P_2]$

Eg

	Allocation A B C	Max	Available	Need
P_0	1 0 1	4 3 1	3 3 0	3 3 0
P_1	1 1 2	2 1 4	~~4 3 1~~	1 0 2
P_2	1 0 3	1 3 3	~~5 4 3~~	0 3 0
P_3	2 0 0	5 4 1	~~8 4 6~~	3 4 1

Finish = [✓ ✓ ✓ ✓]

⇒ Total resources : 8 4 6

∴ Available = 8 4 6 − (Total allocation)

= 8 4 6 − 5 1 6

= 3 3 0.

⇒ 3 3 0 ≤ 3 3 0 → P_0 executed.

work = work + allocation

= 3 3 0 + 1 0 1

= 4 3 1

1 0 ② ≤ 4 3 1 ✗ P_1 exec wait

work = 4 3 1 + 1 1 2

= 5 4 3

0 3 0 ≤ 4 3 1 → P_2 exec

Work = 4 3 1 + 1 0 3

= 6 4 5 3 4

6 2 0 0 ≤ 5 3 4 → P_3 exec

Work = 5 3 4 + 2 0 0

= [7 3 4] Ans.

⇒ Safe seqn : $[P_0 \rightarrow P_1 \rightarrow P_2 \rightarrow P_3]$ ✓.

1 0 2 ≤ 7 3 4 → P_1 exec

Work = 1 0 2 + 7 3 4

= [8 4 6] Ans