

Ola reliability

Ola is a hackathon project by Jayden Bruck.

132 tests ran to a test outcome. 130 passed, 0 failed, 0 errors, 2 blocked and 1 skipped. 133 evidence rows in total.

Tested commit 4fcc52ff398e28555143a75ec8b9aafd0690ebb9. Window 2026-09-13T20:26:30+02:00 to 2026-09-13T20:31:18+02:00. Python 3.13.1 on Windows; real-model setting x-ai/grok-4.5.

Method

The runner executes the entire server unit directory, then e2e, then live, using the same Python environment. Python rows come from pytest JUnit output, with parameter cases counted separately. Swift rows come from completed XCTest case lines checked against the suite total, preserving skips. WhatsApp checks exercise the browser wrapper against local pages. E2e checks use the real model when configured. Live checks require their account credentials. Blocked means an attempted journey did not establish its requested outcome; it is not a pass. A skip proves nothing about a live service. Portable Swift tests then run in an isolated build directory; the real route journey supplies their SSE fixture. Only the scoped live journeys and supplemental browser checks are included. This does not compile or test iOS rendering. Sanitized XML, command logs and the run manifest are stored under build/reliability. No count is a success-rate forecast.

Real-site outcomes

Site	Observed outcome	Evidence
kleinanzeigen	PASSED: listing 'Wir kaufen Ihr altes Fahrrad ,bar cash,sofort, K e i n e E-Bikes!' opened at https://www.kleinanzeigen.de/s-anzeige/wir-kaufen-ihr-altes-fahrrad-bar-cash-sofort-k-e-i-n-e-e-bikes-/499677045-217-1052, price 150 €.	server/tests/live/logs/kleinanzeigen-20260913-203046.md
lieferando	BLOCKED: A dialog remained open on the restaurant list; the cart was not reached. See the live log.	server/tests/live/logs/lieferando-20260913-203038.md
uber	BLOCKED: No fare was displayed after both route fields were set; the ride options required sign-in. See the live log.	server/tests/live/logs/uber-20260913-202944.md

Conversation and concurrent jobs

What it proves	How it was run	Result
Turn event order	unit: test_agent	PASSED
Two jobs run in parallel	unit: test_agent	PASSED
Needs you then resume	unit: test_agent	PASSED
Resume from chat tool	unit: test_agent	PASSED
Cancel job	unit: test_agent	PASSED
Cut arguments are answered	unit: test_agent	PASSED
Unknown tool gets the real list	unit: test_agent	PASSED
Language and facts in prompt	unit: test_agent	PASSED
Job sees only job tools and gets the member language	unit: test_agent	PASSED
Failed job is spoken honestly	unit: test_agent	PASSED
Job without job tools fails honestly	unit: test_agent	PASSED
Cancel while waiting clears needs you	unit: test_agent	PASSED
Streams text and accumulates tool call fragments	unit: test_model	PASSED
Cut arguments are marked	unit: test_model	PASSED
Retries on 429 and 5xx then succeeds	unit: test_model	PASSED
Gives up after retries and reports 4xx plainly	unit: test_model	PASSED
Image parts and tool messages	unit: test_model	PASSED
Env defaults	unit: test_model	PASSED

Conversation and concurrent jobs (continued)

What it proves	How it was run	Result
The real model starts two jobs and speaks their controlled lookup results in German	e2e: test_turn_real_model	PASSED
The real model answers an English request using stored test memory	e2e: test_turn_real_model	PASSED

Reminders

What it proves	How it was run	Result
Remember and remind	unit: test_agent	PASSED
The real model schedules a reminder that appears later in the conversation	e2e: test_turn_real_model	PASSED

Browser and takeover

What it proves	How it was run	Result
Goto returns the page and a step sentence	unit: test_browser_actions	PASSED
Goto failure says why and does not raise	unit: test_browser_actions	PASSED
Dismiss dialog prefers reject	unit: test_browser_actions	PASSED
Dismiss dialog closes a modal without a reject control	unit: test_browser_actions	PASSED
Click the header anmelden not the footer partner link	unit: test_browser_actions	PASSED
Click a stale ref fails with fresh refs	unit: test_browser_actions	PASSED
Fill many fields at once	unit: test_browser_actions	PASSED
Pick completes a suggestion picker first time	unit: test_browser_actions	PASSED
Pick never takes the location or map rows	unit: test_browser_actions	PASSED
Pick on a plain field says so	unit: test_browser_actions	PASSED
Pick with no matching row lists what it offers	unit: test_browser_actions	PASSED
Press and scroll and read	unit: test_browser_actions	PASSED
Wait for waits for readiness not a fixed time	unit: test_browser_actions	PASSED
Wait for url	unit: test_browser_actions	PASSED
Upload puts the attachment into the file input	unit: test_browser_actions	PASSED
Needs you returns the reason and url	unit: test_browser_actions	PASSED
Unknown action is reported not raised	unit: test_browser_actions	PASSED
Close job closes the page	unit: test_browser_actions	PASSED

Browser and takeover (continued)

What it proves	How it was run	Result
Extension export shape is normalized to playwright shape	unit: test_browser_cookies	PASSED
Same site none forces secure and placeholder cookies are dropped	unit: test_browser_cookies	PASSED
Seed accepts an extension export and the cookie lands	unit: test_browser_cookies	PASSED
One bad cookie does not sink a good one	unit: test_browser_cookies	PASSED
Seed log carries only counts and path never a value	unit: test_browser_cookies	PASSED
Absent seed file is a no op	unit: test_browser_cookies	PASSED
Bad seed file is skipped without raising	unit: test_browser_cookies	PASSED
No seed env is a no op	unit: test_browser_cookies	PASSED
Refs are stable across rereads	unit: test_browser_snapshot	PASSED
Refs never repeat within a job across pages	unit: test_browser_snapshot	PASSED
Regions put header before footer and dialog first	unit: test_browser_snapshot	PASSED
Footer is capped with a count	unit: test_browser_snapshot	PASSED
Picker fields are flagged and plain fields are not	unit: test_browser_snapshot	PASSED
Password page says use needs you and never shows a value	unit: test_browser_snapshot	PASSED
Sign up page carries the warning	unit: test_browser_snapshot	PASSED
Snapshot is short and read is long	unit: test_browser_snapshot	PASSED
Element cap holds on a busy page	unit: test_browser_snapshot	PASSED
Site facts reach the page head for known sites only	unit: test_browser_snapshot	PASSED

Browser and takeover (continued)

What it proves	How it was run	Result
Tool schema names every action	unit: test_browser_snapshot	PASSED
Frame route serves the latest jpeg and checks the bearer	unit: test_browser_takeover	PASSED
Member signs in through input then after resume shows the page	unit: test_browser_takeover	PASSED
Sign in survives a browser restart on the same profile	unit: test_browser_takeover	PASSED
Frames are sharp and the model image small	unit: test_browser_takeover	PASSED
A desktop page keeps the frame shape and maps taps	unit: test_browser_takeover	PASSED
Expected site failure is blocked	unit: test_reliability	PASSED
Signin wall needs you takeover resume through the wire	e2e: test_agent_browser	PASSED
The real model hands over a local sign-in form and reads the balance after the test member resumes	e2e: test_browser_takeover	PASSED
Real HTTP and SSE carry two overlapping browser jobs, chat during takeover, sign-in input, resume and page results	live: test_agent_routes	PASSED
Attempts the requested Uber route; only a displayed fare passes	live: test_browser_sites	BLOCKED: No fare was displayed after both route fields were set; the ride options required sign-in. See the live log.
Lieferando margherita to the cart	live: test_browser_sites	BLOCKED: A dialog remained open on the restaurant list; the cart was not reached. See the live log.
Supplemental browser check: opens a Kleinanzeigen listing and reads its price	live: test_browser_sites	PASSED

Server, memory and tool contracts

What it proves	How it was run	Result
Seq per thread and history	unit: test_events	PASSED
Close all ends every stream	unit: test_events	PASSED
Sse framing	unit: test_events	PASSED
Stream replays then goes live with keepalive	unit: test_events	PASSED
Bearer on every route	unit: test_main	PASSED
Chat events jobs resume	unit: test_main	PASSED
Server stops without waiting on streams	unit: test_main	PASSED
Cancel and attachments	unit: test_main	PASSED
Keeps passes, failures, skips and setup errors distinct	unit: test_reliability	PASSED
Swift skip cannot count as pass	unit: test_reliability	PASSED
Incomplete swift results are error	unit: test_reliability	PASSED
Removes configured secrets and access tokens from saved evidence	unit: test_reliability	PASSED
Preserves explicit environment settings when loading a file	unit: test_reliability	PASSED
A failed or empty test collection is an error. Case: 2	unit: test_reliability	PASSED
A failed or empty test collection is an error. Case: 3	unit: test_reliability	PASSED
A failed or empty test collection is an error. Case: 4	unit: test_reliability	PASSED
A failed or empty test collection is an error. Case: 5	unit: test_reliability	PASSED
An unfinished suite is an error	unit: test_reliability	PASSED

Server, memory and tool contracts (continued)

What it proves	How it was run	Result
Nonzero exit cannot be hidden by passing xml	unit: test_reliability	PASSED
Register module openai and bare shapes	unit: test_tools_memory_prompt	PASSED
Load optional skips missing modules	unit: test_tools_memory_prompt	PASSED
Memory roundtrip	unit: test_tools_memory_prompt	PASSED
Example facts file is valid	unit: test_tools_memory_prompt	PASSED
Prompts carry voice rules and facts	unit: test_tools_memory_prompt	PASSED
Language detection	unit: test_tools_memory_prompt	PASSED
Parse when	unit: test_tools_memory_prompt	PASSED

WhatsApp

What it proves	How it was run	Result
Sends the exact text once and confirms a new message ID with a send receipt	unit: test_whatsapp	PASSED
Reads loaded chat messages without sending anything	unit: test_whatsapp	PASSED
Reads the visible chat list without sending anything	unit: test_whatsapp	PASSED
Requests QR takeover before trying to open or send a chat	unit: test_whatsapp	PASSED
Whatsapp hidden chat list does not mask qr	unit: test_whatsapp	PASSED
Continues on the same page after linking	unit: test_whatsapp	PASSED
Does not send when two contacts have the same name	unit: test_whatsapp	PASSED
Does not send to a missing contact	unit: test_whatsapp	PASSED
Does not retry a send without a new receipt. Case: queued	unit: test_whatsapp	PASSED
Does not retry a send without a new receipt. Case: no-new-message	unit: test_whatsapp	PASSED
Stops if the selected recipient changes before sending	unit: test_whatsapp	PASSED
Does not guess when the send button is missing	unit: test_whatsapp	PASSED
An unfinished page load is not mistaken for a linked account	unit: test_whatsapp	PASSED
Rejects an empty contact or message before opening the browser. Case: -Hello	unit: test_whatsapp	PASSED
Rejects an empty contact or message before opening the browser. Case: None-Hello	unit: test_whatsapp	PASSED
Rejects an empty contact or message before opening the browser. Case: Alex-	unit: test_whatsapp	PASSED
Rejects an empty contact or message before opening the browser. Case: Alex-None	unit: test_whatsapp	PASSED
Rejects an empty contact or message before opening the browser. Case: Alex-12	unit: test_whatsapp	PASSED

WhatsApp (continued)

What it proves	How it was run	Result
Each reported action has a page image captured after it	unit: test_whatsapp	PASSED
Whatsapp registry handler emits frames	unit: test_whatsapp	PASSED
Whatsapp concurrent sends keep their recipient	unit: test_whatsapp	PASSED
The real WhatsApp QR page provides a takeover request and image	live: test_whatsapp_live	PASSED
A real send receipt and matching message ID confirm the chat round trip	live: test_whatsapp_live	SKIPPED: Missing OLA_WHATSAPP_TEST_CONTACT, an authorized test recipient

iPhone event parsing and state

What it proves	How it was run	Result
Blank Events Comments And Incomplete Disconnect	swift: CoreTests	PASSED
Byte Boundaries And Multiline	swift: CoreTests	PASSED
CRAnd Persistent IDAnd Empty Data	swift: CoreTests	PASSED
Captured Real Server Events	swift: CoreTests	PASSED
Completion Repairs Missing Deltas	swift: CoreTests	PASSED
Concurrent Replies Complete Once	swift: CoreTests	PASSED
Every Card Transition And No Duplicate	swift: CoreTests	PASSED
Failure And Reordered Card	swift: CoreTests	PASSED
Fitted Frame Rejects Letterbox	swift: CoreTests	PASSED
Public Door Prefix On Every Route	swift: CoreTests	PASSED
Rejected Input Cannot Count As An Accepted Action	swift: CoreTests	PASSED
Shutdown Comment Requests Reconnect Without Changing Cursor	swift: CoreTests	PASSED
Snapshot And Persistence	swift: CoreTests	PASSED

What failed and what we changed

The first real WhatsApp visit showed a browser compatibility screen with Playwright's default headless identity. Using a desktop Chrome identity reached the real QR linking page. The browser lane was given that finding so linking and takeover use the same persistent session. No message was sent in that probe. The first local WhatsApp run had 17 passes and one fixture failure: resetting a page redeclared its JavaScript variables. We scoped the fixture script to each page load, then all 18 WhatsApp checks passed. A later run hit two browser setup errors, including a Playwright driver allocation failure on this shared PC. The test fixture now reuses one Chromium process with a fresh context for each test. An encoding error in a German assertion was corrected; all 20 WhatsApp checks then passed. Swift's parallel xUnit output counted a skipped fixture test as a pass, so the runner now reads serial XCTest outcomes and checks their count against the suite summary. The first combined run on ed14410 recorded 117 passes and two failures. A due reminder spoke before its slow acknowledgement; the core now waits for that acknowledgement before delivering the reminder. WhatsApp showed an IndexedDB error under the deeply nested Windows pytest profile path. The same QR check passed with a short isolated workspace profile, which the live test now uses. The founder removed email and Calendar from scope; their tests are excluded from this report.

Known limits

WhatsApp needs one QR linking step and an explicitly configured test contact for a live send; a QR screen is not a sent message.

WhatsApp, Lieferando and Uber are the scoped apps. Sign-in walls and blocked pages do not prove completed errands.

This is one run of Ola, a hackathon project by Jayden Bruck. It does not prove phone acceptance or production reliability.