

Loops

CSE160: Computer Science A: Honors

Paul Fodor

Stony Brook University

<http://www.cs.stonybrook.edu/~cse160>

Contents

- Motivation for loops
- What is Iteration?
- Java and iteration
 - while loops
 - do ... while loops
 - for loops
- Caution: don't use equality for reals
- Common algorithms with loops
- Nested Loops
- Local Variables and Blocks
- Keywords break and continue

Motivation

- Suppose that you need to print a string (e.g., **"Welcome to Java!"**) a user-entered times N:

```
Scanner input = new Scanner(System.in);  
System.out.print("Enter N: ");  
int N = input.nextInt();
```

N? {
 System.out.println("Welcome to Java!");
 ...
 System.out.println("Welcome to Java!");

Motivation

- Without iteration (or recursion) this would be impractical
 - We do not know N , when we are about to write the program
 - So, we need a cascade of if statements to check all cases for the value of N .

Without iteration or recursion

```
Scanner input = new Scanner(System.in);
System.out.print("Enter N: ");
int N = input.nextInt();
if(N == 1)
    System.out.println("Welcome to Java!");
else if(N == 2){
    System.out.println("Welcome to Java!");
    System.out.println("Welcome to Java!");
}else if(N == 3){
    System.out.println("Welcome to Java!");
    System.out.println("Welcome to Java!");
    System.out.println("Welcome to Java!");
}...
```

Inefficient coding (repetition)!

Loops Solution

- While loop:

```
Scanner input = new Scanner(System.in);  
System.out.print("Enter N: ");  
int N = input.nextInt();  
int count = 0;  
while (count < N) {  
    System.out.println("Welcome to Java");  
    count++;  
}
```

Motivation Example 2

- How would we write code to print $N!$ (factorial), where N is a number entered by the user?

Without iteration or recursion

```
Scanner input = new Scanner(System.in);  
System.out.print("Enter N: ");  
int N = input.nextInt();  
int factorial = 1;  
if ((N == 1) || (N == 0)) factorial = 1;  
else if (N == 2) factorial = 2 * 1;  
else if (N == 3) factorial = 3 * 2 * 1;  
else if (N == 4) factorial = 4 * 3 * 2 * 1;  
else if (N == 5) factorial = 5 * 4 * 3 * 2 * 1;  
...  
System.out.println(factorial);
```

Inefficient coding (repetition)!

With iteration/loops

```
Scanner input = new Scanner(System.in);  
System.out.print("Enter N: ");  
int N = input.nextInt();  
int factorial = 1;  
int i = 1;  
while(i <= N)  
    factorial *= i++;  
System.out.println(factorial);
```

What is Iteration?

- Repeating a set of instructions a **specified number of times** or **until a specific result is achieved**
- How do we repeat steps?
 - Imagine 3 instructions A, B, & C:
Instruction A
Instruction B
Instruction C can be conditional jump to A (meaning **go back to A**)
 - Iteration might result in:
Execute A
Execute B
Execute C
Execute A
Execute B


...

Java and iteration

- We have 3 types of iterative statements
 - **a while loop**
 - **a do ... while loop**
 - **a for loop**
- All 3 can be used to do similar things
- Which one should you use?
 - a matter of individual preference / convenience
- Note: When we will learn arrays, we will see a 4th kind of loop: for-each loop


while Loop Flow Chart

```
while (loop-continuation-condition) {  
    // loop-body;  
    Statement(s);  
}
```



(A)

```
int count = 0;  
while (count < 100) {  
    System.out.println("Welcome to Java!");  
    count++;  
}
```



(B)

Trace while Loop

```
int count = 0;
```

Initialize count

```
while (count < 2) {
```

```
    System.out.println("Welcome to Java!");
```


```
    count++;
```

```
}
```

Trace while Loop

```
int count = 0;
```

(count < 2) is true



```
while (count < 2) {
```

```
    System.out.println("Welcome to Java!");
```


```
    count++;
```

```
}
```

Trace while Loop

```
int count = 0;  
while (count < 2) {  
    System.out.println("Welcome to Java!");  
    count++;  
}
```

Print Welcome to Java




System.out.println("Welcome to Java!");

Welcome to Java!

Trace while Loop

```
int count = 0;  
while (count < 2) {  
    System.out.println("Welcome to Java!");  
    count++;  
}
```



Increase count by 1
count is 1 now

Welcome to Java!

Trace while Loop

```
int count = 0;
```

```
while (count < 2) {
```

(count < 2) is still true since count
is 1

```
    System.out.println("Welcome to Java!");
```

```
    count++;
```


```
}
```

Welcome to Java!

Trace while Loop

```
int count = 0;  
while (count < 2) {  
    System.out.println("Welcome to Java!");  
    count++;  
}
```

Print Welcome to Java




System.out.println("Welcome to Java!");

Welcome to Java!

Welcome to Java!

Trace while Loop

```
int count = 0;  
while (count < 2) {  
    System.out.println("Welcome to Java!");  
    count++;  
}
```



Increase count by 1
count is 2 now

Welcome to Java!
Welcome to Java!

Trace while Loop

```
int count = 0;
```

```
while (count < 2) {
```

```
    System.out.println("Welcome to Java!");
```

```
    count++;
```

```
}
```

(count < 2) is false since count is 2
now

Welcome to Java!

Welcome to Java!

Trace while Loop

```
int count = 0;  
while (count < 2) {  
    System.out.println("Welcome to Java!");  
    count++;  
}
```

The loop exits. Execute the next statement after the loop.



Welcome to Java!
Welcome to Java!

Caution: don't use equality for reals

- **Don't use floating-point values for equality checking** in a loop control - because floating-point values are **approximations** for some values

```
System.out.print(1 - 0.1 - 0.1 - 0.1);  
prints 0.700000000000000001
```

- Loop example: the following code for computing $1 + 0.9 + 0.8 + \dots + 0.1$:


```
double item = 1, sum = 0;  
while (item != 0) { // No guarantee item will be 0 or 0.0  
    sum += item;      // change the condition: item > 0  
    item -= 0.1;  
}  
System.out.printf("%.1f", sum);
```

- **It is actually an infinite loop!**

- Variable item starts with 1 and is reduced by 0.1 every time the loop body is executed
- The loop should terminate when item becomes 0
 - However, there is no guarantee that item will be exactly 0, because the floating-point arithmetic is approximated
 - **So, it continues running forever**

do-while Loop

```
do {  
    // Loop body;  
    Statement(s) ;  
} while (loop-continuation-condition) ;
```



Why use do ... while?

- For when you have a loop body that must execute at least once.
- Example: a program menu

```
Scanner in = new Scanner(System.in);  
String selection;  
int counter = 0;  
do{  
    System.out.println("Choose a Menu Option:");  
    System.out.println("P) Print Counter");  
    System.out.println("Q) Quit");  
    System.out.print("ENTER: ");  
    selection = in.nextLine();  
    if (selection.toUpperCase().equals("P"))  
        System.out.println("Counter: " + counter++);  
}while(!selection.toUpperCase().equals("Q"));  
System.out.println("Goodbye!");
```


• An Example Session

Choose a Menu Option:

P) Print Counter

Q) Quit

ENTER: P

Counter: 0

Choose a Menu Option:

P) Print Counter

Q) Quit

ENTER: A

Choose a Menu Option:

P) Print Counter

Q) Quit

ENTER: P

Counter: 1

Choose a Menu Option:

P) Print Counter

Q) Quit


ENTER: Q

Goodbye!

for Loops

```
for (initial-action;  
    loop-continuation-condition;  
    action-after-each-iteration) {  
    // loop body;  
    Statement(s);  
}
```

```
int i;  
for (i = 0; i < N; i++)  
    System.out.println(  
        "Welcome to Java!");
```



for loops and counting

- for loops are popular for counting loops
 - through the indices of a string
 - through the indices of an array (later)
 - through iterations of an algorithm
- Good for algorithms that require a known number of iterations
 - *counter-controlled loops*

Trace for Loop

```
int i;
```

Declare i

```
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

Execute initializer
i is now 0

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

(i < 2) is true
since i is 0

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

Print Welcome to Java



Welcome to Java!

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

Execute adjustment statement
i now is 1

Welcome to Java!

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

(i < 2) is still true
since i is 1

Welcome to Java!

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

Print Welcome to Java



Welcome to Java!
Welcome to Java!

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

Execute adjustment statement
i now is 2

Welcome to Java!
Welcome to Java!

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++) {  
    System.out.println(  
        "Welcome to Java!");  
}
```

(i < 2) is false
since i is 2

Welcome to Java!
Welcome to Java!

Trace for Loop

```
int i;  
for (i = 0; i < 2; i++)  
    System.out.println(  
        "Welcome to Java.");  
}
```

Exit the loop. Execute the next
statement after the loop

Welcome to Java!
Welcome to Java!

for loops

The initial-action in a for loop can be a list of zero or more comma-separated expressions.

The action-after-each-iteration in a for loop can be a list of zero or more comma-separated statements.

```
for (int i = 0, j = 0; (i + j < 10); i++, j++) {  
    // Do something  
}
```

The loop body can be the no-op statement:

```
for (int i = 0; i < 100; System.out.println(i++)) ;
```

Caution ;

Adding a semicolon at the end of the for clause before the loop body is a common mistake:


```
for (int i=0; i<10; i++) ;  
{  
    System.out.println("i is " + i);  
}    // i does not exist anymore  
    // it is a syntax error
```



Same Caution ; for while

Adding a semicolon at the end of the while clause before the loop body is a common mistake:

```
int i=0;
while (i < 10) ;  
{  
    System.out.println("i is " + i);  
    i++;  
}
```



Logic Error

this will cause an infinite loop

Infinite loops

If the loop-continuation-condition in a for loop is omitted, it is implicitly true.

```
for ( ; ; ) {  
    // Do something  
}
```

(a)

Equivalent

```
while (true) {  
    // Do something  
}
```

(b)

Which Loop to Use?

while, do-while, and for loops are expressively equivalent

```
while (loop-continuation-condition) {  
    // Loop body  
}
```

(a)

Equivalent

```
for ( ; loop-continuation-condition; )  
    // Loop body  
}
```

(b)

```
for (initial-action;  
     loop-continuation-condition;  
     action-after-each-iteration) {  
    // Loop body;  
}
```

(a)

Equivalent

```
initial-action;  
while (loop-continuation-condition) {  
    // Loop body;  
    action-after-each-iteration;  
}
```

(b)

Caution: Loop variables

```
int sum = 0;  
for (int j=1; j<=4; j++) {  
    sum = sum + j;  
    j++;  
}
```

**Be careful not to
double the update of
your counting
variable**

Sums

```
int sum = 0;  
for (int i=1; i<=4; i++)  
    sum = sum + i;
```

sum	i
0	1
1	2
3	3
6	4
10	5

Nested Loops

```
for (int i = 1; i <= 10; i++) {  
    for (int j = 1; j <= 10; j++) {  
        int product = i*j;  
        System.out.print(product + " ");  
    }  
    System.out.println();  
}
```

1	2	3	4	5	6	7	8	9	10
2	4	6	8	10	12	14	16	18	20
3	6	9	12	15	18	21	24	27	30
...									
10	20	30	40	50	60	70	80	90	100

Local Variables and Blocks

- A variable declared inside a block is known only inside that block
 - it is *local* to the block, therefore it is called a *local variable*
 - when the block finishes executing, local variables disappear
 - references to it outside the block cause a compiler error
- That includes *Init field* for loops:

```
for (int i=0; i < 10; i++) {
```

```
    ...
```

```
}
```

```
System.out.print(i);
```

```
// Compile Error: no variable i (anymore)
```

Keywords break and continue

- You can also use **break** in a loop to immediately terminate the loop:

```
public static void main(String[] args) {  
    int sum = 0;  
    int number = 0;  
    while (number < 20) {  
        number++;  
        sum += number;  
        if (sum >= 100) // increments until the sum is  
                        break; // greater than 100  
    }  
    System.out.println("The number is " + number);  
    System.out.println("The sum is " + sum);  
}
```

The number is 14

The sum is 105

Keywords break and continue

- You can also use **continue** in a loop to end the current iteration and program control goes to the end of the loop body (and continues the loop):

```
public static void main(String[] args) {  
    int sum = 0;  
    int number = 0;  
    while (number < 20) { // adds integers from 1 to 20  
        number++;        // except 10 and 11 to sum  
        if (number == 10 || number == 11)  
            continue;  
        sum += number;  
    }  
    System.out.println("The number is " + number);  
    System.out.println("The sum is " + sum);  
}
```

The number is 20
The sum is 189