

# Airpay Payment Services POSPay Documentation

**VERSION 1.5** 

**AIRPAY** 



#### **Statement of Confidentiality**

The information contained in or supplied with this document is submitted solely for the purpose of evaluating the products and services of Airpay Payment Services Pvt. Ltd., and/or its affiliates and subsidiaries ("airpay"). The information contained in or supplied with this document, in its entirety, is the confidential and proprietary information of airpay, and it may not be copied by or disclosed to any person or entity (other than to the intended recipient), without the prior written consent of airpay. With or without airpay' prior written consent, airpay accepts no liability whatsoever for any consequences arising from the reproduction of the information contained in or supplied with this document, or from its disclosure to any person or entity, including to the intended recipient. airpay additionally accepts no liability for the use of the information contained in, or supplied with this document, by the intended recipient, or by any other person or entity, with or without airpay' express prior consent. The intended recipient shall not use any part of the information contained in, or supplied with this document, in any way to the competitive disadvantage of airpay, and will take all steps designed to assure its compliance with this provision.

This proposal is neither an offer nor intended by airpay, upon acceptance by the intended recipient, or otherwise, to create a binding agreement with airpay. Such an agreement shall be reflected only by a definitive contract, executed by both parties.

#### **Trademarks**

All other trademarks are the property of their owners.

Company, product, and service names used by Airpay Payment Services Pvt. Ltd. within, or supplied with this document may be trademarks or service marks of other persons or entities.

#### Copyright

Copyright<sup>©</sup> 2018 Airpay Payment Services Pvt. Ltd.

All Rights Reserved.

# **API Specification Doc**

# (airpay payment via pos terminal)

Versio n	Date	Author	Description
1.0	14-Jul-2016	Mathew	Initial Draft
1.1	10-Apr-201 7	Mathew	Additional pos transaction type variable added.
1.2	01-Feb-201 8	Mathew	Added api to handle cancel request for un-initiated pos transaction
1.3	22-Feb-201 8	Mathew	Added variable to handle save card transaction type
1.4	24-May-201 8	Mathew	Adding Card Type and surcharge
1.5	27-June-20 16	Kinnari	Adding transaction status

# Index

1. Initiate Payment

Request

Response

2. Transaction Response

Request

Response

3. Sale/Void Cancel

Request

Response

Status Codes
Currency ISO Codes
Transaction Type Codes
Card Type Codes
Transaction Status Codes

# Methods

# 1. Initiate Payment

Initiate Payment Request

# Request

Metho d	URL
POST	http://opi.airpay.co.in/web/api/pos/create

Params	Values	Length	Requir ed	Comments
mercid	string	1-12	Υ	
orderid	string	4-12	Υ	
amount	number	12,2	Υ	Not required in the case of save card
currency	number	3	N	356
isocurrency	string	3	N	INR
customvar	string	250	N	
uniqueid	string	4-10	Υ	
mobile	number	10-15	N	
postxntype	Number	2	N	By default the pos txn type is 1(sale). For void txn type is 8.For preauth the txn type is 7. For sale completion txn type is 10.For Authrelease txn type is 11. For save card txn type is 12

originalrrn	string	20	N	In case of Void, sale completion, auth release the original successful transaction RRN should be passed
authcode	string	6	N	In case of sale completion it is required
invoiceno	string	2-6	N	In case of void it is required
cardtype	string	5	N	

# Response

```
{"status": <STATUS CODE>, "message": []}
```

# 2. Transaction Response

**Get Transaction Payment Status** 

#### Request

Metho d	URL
POST	http://opi.airpay.co.in/web/api/pos/transaction-response

Params	Values	Length	Requir ed	Comments
mercid	string	1-12	Υ	
orderid	string	1-20	Υ	
uniqueid	String	50	Υ	

#### Response

```
{"status": <STATUS CODE>, "message": []}
```

#### **Sample Success Response**

```
"status": 200,
"message": {
"TRANSACTIONID":
"151452903",
"APTRANSACTIONID": "4117941",
"INVOICE_NO": "000068",
"MERCHANTID": "24213",
"TERMINALID": "32702664",
"CARDISSUER": "mastercard",
"CHMOD": "pos",
"AMOUNT": "100.00",
"SURCHARGE": "1.00",
"CURRENCYCODE": "356",
"TRANSACTIONSTATUS": "200",
"MESSAGE": "Successful",
"RRN": "000881088250",
"AUTHCODE": "555687",
```

```
"CUSTOMER": "Mathew thomas",
"CUSTOMERPHONE": "9768852964",
"CARD_NUMBER":"524254xxxxxx384"
"CARDUNIQUECODE": ""
"CUSTOMEREMAIL": "",
"TOKEN": "",
"TRANSACTIONTYPE": "420",
"ISRISK": "N",
"IPNID": "995122",
"ap_SecureHash": "2798130167"
}
```

Note: TRANSACTIONSTATUS are mentioned in the Transaction Status Codes and TRANSACTIONTYPE are mentioned in the Transaction Type codes

#### Sample Error Response

```
{
"status": 502,
"message": {"ORDER_ID": ["Order does not exist."] }
}
```

# 3. Sale/Void cancel

### Request

Metho d	URL
POST	http://opi.airpay.co.in/web/api/pos/cancel-txn

Params	Values	Length	Requir ed	Comments
mercid	string	1-12	Y	
orderid	string	4-12	Y	
amount	number	12,2	Υ	
uniqueid	string	4-10	Υ	
postxntype	Number	1	Y	By default the postxn type is 1(sale).  For void cancel txn type is 8.
originalrrn	string	20	N	In case of void it is required.  In case of sale it is not required

# Response

```
{"status": <STATUS CODE>, "message": []}
```

# Status Codes (<STATUS CODE>)

Status Code	Description
200	Success
502	Failed

# Currency ISO Code (<currecy iso code>)

Status Code	Description
356	Indian Rupee

# Transaction Type Codes (<TRANSACTION TYPE CODE>)

Status Code	Description
310	Authorization
320	Sale
330	Capture
340	Refund
350	Chargeback
420	Void

# POS TRANSACTION TYPE (<postxntype>)

Code	Description
01	Sale/Purchase
08	Void
07	Pre auth
10	Sale completion
11	Auth Release
12	Save card

# Transaction Status Codes (<TRANSACTIONSTATUS>)

Status Code	Description
200	Success
400	Failed
510	Account not valid
112	Invalid Order id
113	Amount not valid

# Card Type Codes (<cardtype>)

Code	Description
СС	Credit Card
dc	Debit Card
amex	Amex
icc	Intenational Credit