

# 1. Description

## 1.1. Project

Project Name	ottobock
Board Name	NUCLEO-F429ZI
Generated with:	STM32CubeMX 6.6.1
Date	10/24/2022


## 1.2. MCU

MCU Series	STM32F4
MCU Line	STM32F429/439
MCU name	STM32F429ZITx
MCU Package	LQFP144
MCU Pin number	144

## 1.3. Core(s) information

Core(s)	Arm Cortex-M4

## 2. Pinout Configuration



# 3. Pins Configuration


Pin Number	Pin Name	Pin Type	Alternate	Label
LQFP144	(function after		Function(s)	
	reset)			
6	VBAT	Power		
7	PC13	I/O	GPIO_EXTI13	USER_Btn [B1]
8	PC14/OSC32_IN	I/O	RCC_OSC32_IN	
9	PC15/OSC32_OUT	I/O	RCC_OSC32_OUT	
16	VSS	Power		
17	VDD	Power		
23	PH0/OSC_IN	I/O	RCC_OSC_IN	MCO [STM32F103CBT6_PA8]
24	PH1/OSC_OUT	I/O	RCC_OSC_OUT	
25	NRST	Reset		
27	PC1	I/O	ETH_MDC	RMII_MDC [LAN8742A-CZ- TR_MDC]
30	VDD	Power		
31	VSSA	Power		
32	VREF+	Power		
33	VDDA	Power		
35	PA1	I/O	ETH_REF_CLK	RMII_REF_CLK [LAN8742A-CZ- TR_REFCLK0]
36	PA2	I/O	ETH_MDIO	RMII_MDIO [LAN8742A-CZ- TR_MDIO]
38	VSS	Power		
39	VDD	Power		
40	PA4	I/O	ADC1_IN4	
41	PA5	I/O	ADC1_IN5	
43	PA7	I/O	ETH_CRS_DV	RMII_CRS_DV [LAN8742A- CZ-TR_CRS_DV]
44	PC4	I/O	ETH_RXD0	RMII_RXD0 [LAN8742A-CZ- TR_RXD0]
45	PC5	I/O	ETH_RXD1	RMII_RXD1 [LAN8742A-CZ- TR_RXD1]
46	PB0 *	I/O	GPIO_Output	LD1 [Green]
51	VSS	Power		
52	VDD	Power		
61	VSS	Power		
62	VDD	Power		
71	VCAP_1	Power		
			<u> </u>	

Pin Number	Pin Name	Pin Type	Alternate	Label
LQFP144	(function after		Function(s)	
2011111	reset)		r unouon(o)	
72	VDD	Power		
74	PB13	I/O	ETH_TXD1	RMII_TXD1 [LAN8742A-CZ-
/	1013	1/0	LIII_IXDI	TR_TXD1]
75	PB14 *	I/O	GPIO_Output	LD3 [Red]
77	PD8	I/O	USART3_TX	STLK_RX
				[STM32F103CBT6_PA3]
78	PD9	I/O	USART3_RX	STLK_TX [STM32F103CBT6_PA2]
83	VSS	Power		[STWISZETUSCBT0_FA2]
84	VDD	Power		
91	PG6 *	I/O	GPIO_Output	USB_PowerSwitchOn
	. 50	., 0		[STMPS2151STR_EN]
92	PG7 *	I/O	GPIO_Input	USB_OverCurrent
				[STMPS2151STR_FAULT]
94	VSS	Power		
95	VDD	Power		
96	PC6	I/O	USART6_TX	
97	PC7	I/O	USART6_RX	
100	PA8	I/O	USB_OTG_FS_SOF	USB_SOF [TP1]
101	PA9	I/O	USB_OTG_FS_VBUS	USB_VBUS
102	PA10 **	I/O	USB_OTG_FS_ID	USB_ID
103	PA11	I/O	USB_OTG_FS_DM	USB_DM
104	PA12	I/O	USB_OTG_FS_DP	USB_DP
105	PA13	I/O	SYS_JTMS-SWDIO	TMS
106	VCAP_2	Power		
107	VSS	Power		
108	VDD	Power		
109	PA14	I/O	SYS_JTCK-SWCLK	TCK
113	PC12	I/O	GPIO_EXTI12	e_stop
120	VSS	Power		
121	VDD	Power	FT:	DAM TV
126	PG11	I/O	ETH_TX_EN	RMII_TX_EN [LAN8742A- CZ-TR_TXEN]
128	PG13	I/O	ETH_TXD0	RMII_TXD0 [LAN8742A-CZ- TR_TXD0]
130	VSS	Power		
131	VDD	Power		
137	PB7 *	I/O	GPIO_Output	LD2 [Blue]
138	BOOT0	Boot		
143	PDR_ON	Reset		
144	VDD	Power		

*	The	pin	is	affected	with	an	I/O	function
---	-----	-----	----	----------	------	----	-----	----------

<sup>\*\*</sup> The pin is affected with a peripheral function but no peripheral mode is activated

## 4. Clock Tree Configuration



# 5. Software Project

## 5.1. Project Settings

Name	Value
Project Name	ottobock
Project Folder	C:\Users\user\Documents\STM32CubeIDE\workspace_1.7.0\ottobock
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_F4 V1.27.1
Application Structure	Advanced
Generate Under Root	Yes
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

## 5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

## 5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name	
1	SystemClock_Config	RCC	
2	MX_GPIO_Init	GPIO	
3	MX_DMA_Init	DMA	
4	MX_ETH_Init	ETH	
5	MX_USART3_UART_Init	USART3	
6	MX_USB_OTG_FS_PCD_Init	USB_OTG_FS	
7	MX_USART6_UART_Init	USART6	
8	MX_ADC1_Init	ADC1	

## 6. Power Consumption Calculator report

### 6.1. Microcontroller Selection

Series	STM32F4
Line	STM32F429/439
MCU	STM32F429ZITx
Datasheet	DS9405_Rev9

### 6.2. Parameter Selection

Temperature	25
Vdd	3.3

## 6.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


## 6.4. Sequence

Step	Stop1	Step2
Step	Step1	Step2
Mode	RUN	STOP UDM (Under Drive)
Vdd	3.3	3.3
Voltage Source	Battery	Battery
Range	Scale1-High	No Scale
Fetch Type	FLASH	n/a
CPU Frequency	180 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator LP Flash-PwrDwn
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	57 mA	100 μΑ
Duration	0.1 ms	0.9 ms
DMIPS	225.0	0.0
Ta Max	97.48	104.99
Category	In DS Table	In DS Table

### 6.5. Results

Sequence Time	1 ms	Average Current	5.79 mA
Battery Life	24 days, 10 hours	Average DMIPS	225.0 DMIPS

## 6.6. Chart



## 7. Peripherals and Middlewares Configuration

7.1. ADC1 mode: IN4 mode: IN5

7.1.1. Parameter Settings:

ADCs\_Common\_Settings:

Mode Independent mode

ADC\_Settings:

Clock Prescaler PCLK2 divided by 4

Resolution 12 bits (15 ADC Clock cycles)

Data Alignment

Scan Conversion Mode

Continuous Conversion Mode

Disabled

Discontinuous Conversion Mode

Disabled

DMA Continuous Requests

Disabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC\_Regular\_ConversionMode:

Number Of Conversion 1

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None
Rank 1

Channel 4
Sampling Time 3 Cycles

ADC\_Injected\_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.2. ETH

Mode: RMII

7.2.1. Parameter Settings:

**General: Ethernet Configuration:** 

Ethernet MAC Address 00:80:E1:00:00:00

Rx Buffers Length 1524

**Ethernet Basic Configuration:** 

Rx Mode Polling Mode

#### 7.2.2. Advanced Parameters:

#### **External PHY Configuration:**

PHY LAN8742A\_PHY\_ADDRESS

PHY Reset delay these values are based on a 1 ms

Systick interrupt

0x000000FF \*

PHY Configuration delay

PHY Read TimeOut

Ox0000FFF \*

PHY Write TimeOut

Ox0000FFF \*

#### **Common: External PHY Configuration:**

Transceiver Basic Control Register 0x00 \* Transceiver Basic Status Register 0x01 \* **PHY Reset** 0x8000 \* Select loop-back mode 0x4000 \* Set the full-duplex mode at 100 Mb/s 0x2100 \* Set the half-duplex mode at 100 Mb/s 0x2000 \* Set the full-duplex mode at 10 Mb/s 0x0100 \* Set the half-duplex mode at 10 Mb/s 0x0000 \* Enable auto-negotiation function 0x1000 \* Restart auto-negotiation function 0x0200 \* Select the power down mode 0x0800 \* Isolate PHY from MII 0x0400 \* Auto-Negotiation process completed 0x0020 \* Valid link established 0x0004 \* Jabber condition detected 0x0002 \*

#### **Extended: External PHY Configuration:**

PHY special control/status register Offset

Ox10 \*

PHY Speed mask

Ox0002 \*

PHY Duplex mask

Ox0004 \*

PHY Interrupt Source Flag register Offset

Ox001D \*

PHY Link down inturrupt

Ox000B \*

#### 7.3. RCC

High Speed Clock (HSE): BYPASS Clock Source Low Speed Clock (LSE): Crystal/Ceramic Resonator

7.3.1. Parameter Settings:

**System Parameters:** 

VDD voltage (V) 3.3
Instruction Cache Enabled
Prefetch Buffer Enabled
Data Cache Enabled

Flash Latency(WS) 5 WS (6 CPU cycle)

**RCC Parameters:** 

HSI Calibration Value 16
TIM Prescaler Selection Disabled
HSE Startup Timout Value (ms) 100
LSE Startup Timout Value (ms) 5000

**Power Parameters:** 

Power Regulator Voltage Scale Power Regulator Voltage Scale 1

Power Over Drive Disabled

7.4. SYS

**Debug: Serial Wire** 

Timebase Source: SysTick

**7.5. USART3** 

**Mode: Asynchronous** 

7.5.1. Parameter Settings:

**Basic Parameters:** 

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

**Advanced Parameters:** 

Data Direction Receive and Transmit

Over Sampling 16 Samples

#### 7.6. **USART6**

**Mode: Asynchronous** 

### 7.6.1. Parameter Settings:

#### **Basic Parameters:**

Baud Rate 57600 \*

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

**Advanced Parameters:** 

Data Direction Receive and Transmit

Over Sampling 16 Samples

### 7.7. USB\_OTG\_FS

Mode: Device\_Only mode: Activate\_SOF mode: Activate\_VBUS

## 7.7.1. Parameter Settings:

Speed Device Full Speed 12MBit/s

Low powerDisabledLink Power ManagementDisabledVBUS sensingEnabledSignal start of frameEnabled

<sup>\*</sup> User modified value

# 8. System Configuration

## 8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PA4	ADC1_IN4	Analog mode	No pull-up and no pull-down	n/a	
ADCI	PA5	ADC1_IN4	Analog mode	No pull-up and no pull-down	n/a	
ETH	PC1	ETH_MDC	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_MDC [LAN8742A- CZ-TR_MDC]
	PA1	ETH_REF_CLK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_REF_CLK [LAN8742A-CZ- TR_REFCLK0]
	PA2	ETH_MDIO	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_MDIO [LAN8742A- CZ-TR_MDIO]
	PA7	ETH_CRS_DV	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_CRS_DV [LAN8742A-CZ- TR_CRS_DV]
	PC4	ETH_RXD0	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_RXD0 [LAN8742A- CZ-TR_RXD0]
	PC5	ETH_RXD1	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_RXD1 [LAN8742A- CZ-TR_RXD1]
	PB13	ETH_TXD1	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_TXD1 [LAN8742A- CZ-TR_TXD1]
	PG11	ETH_TX_EN	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_TX_EN [LAN8742A- CZ-TR_TXEN]
	PG13	ETH_TXD0	Alternate Function Push Pull	No pull-up and no pull-down	Very High	RMII_TXD0 [LAN8742A- CZ-TR_TXD0]
RCC	PC14/OSC3 2_IN	RCC_OSC32_IN	n/a	n/a	n/a	
	PC15/OSC3 2_OUT	RCC_OSC32_O UT	n/a	n/a	n/a	
	PH0/OSC_I	RCC_OSC_IN	n/a	n/a	n/a	MCO [STM32F103CBT6_PA8]
	PH1/OSC_O UT	RCC_OSC_OUT	n/a	n/a	n/a	
SYS	PA13	SYS_JTMS- SWDIO	n/a	n/a	n/a	TMS
	PA14	SYS_JTCK- SWCLK	n/a	n/a	n/a	тск
USART3	PD8	USART3_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	STLK_RX [STM32F103CBT6_PA3]
	PD9	USART3_RX	Alternate Function Push Pull	No pull-up and no pull-down		STLK_TX

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
					Very High	[STM32F103CBT6_PA2]
USART6	PC6	USART6_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
	PC7	USART6_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
USB_OTG_ FS	PA8	USB_OTG_FS_ SOF	Alternate Function Push Pull	No pull-up and no pull-down	Very High	USB_SOF [TP1]
	PA9	USB_OTG_FS_ VBUS	Input mode	No pull-up and no pull-down	n/a	USB_VBUS
	PA11	USB_OTG_FS_ DM	Alternate Function Push Pull	No pull-up and no pull-down	Very High	USB_DM
	PA12	USB_OTG_FS_ DP	Alternate Function Push Pull	No pull-up and no pull-down	Very High	USB_DP
Single Mapped Signals	PA10	USB_OTG_FS_I D	Alternate Function Push Pull	No pull-up and no pull-down	Very High	USB_ID
GPIO	PC13	GPIO_EXTI13	External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	n/a	USER_Btn [B1]
	PB0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD1 [Green]
	PB14	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD3 [Red]
	PG6	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	USB_PowerSwitchOn [STMPS2151STR_EN]
	PG7	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	USB_OverCurrent [STMPS2151STR_FAULT]
	PC12	GPIO_EXTI12	External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	n/a	e_stop
	PB7	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD2 [Blue]

### 8.2. DMA configuration

DMA request	Stream	Direction	Priority
USART6_RX	DMA2_Stream1	Peripheral To Memory	Low
USART6_TX	DMA2_Stream6	Memory To Peripheral	Low

### USART6\_RX: DMA2\_Stream1 DMA request Settings:

Mode: Circular \*
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Byte
Memory Data Width: Byte

### USART6\_TX: DMA2\_Stream6 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Byte

Peripheral Data Width: Byte
Memory Data Width: Byte

## 8.3. NVIC configuration

## 8.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority	
·			-	
Non maskable interrupt	true	0	0	
Hard fault interrupt	true	0	0	
Memory management fault	true	0	0	
Pre-fetch fault, memory access fault	true	0	0	
Undefined instruction or illegal state	true	0	0	
System service call via SWI instruction	true	0	0	
Debug monitor	true	0	0	
Pendable request for system service	true	0	0	
System tick timer	true	0	0	
DMA2 stream1 global interrupt	true	0	0	
DMA2 stream6 global interrupt	true	0	0	
USART6 global interrupt	true	0	0	
PVD interrupt through EXTI line 16		unused		
Flash global interrupt		unused		
RCC global interrupt		unused		
ADC1, ADC2 and ADC3 global interrupts		unused		
USART3 global interrupt		unused		
EXTI line[15:10] interrupts	unused			
Ethernet global interrupt	unused			
Ethernet wake-up interrupt through EXTI line 19	unused			
USB On The Go FS global interrupt	unused			
FPU global interrupt		unused		

## 8.3.2. NVIC Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true
DMA2 stream1 global interrupt	false	true	true
DMA2 stream6 global interrupt	false	true	true

Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
USART6 global interrupt	false	true	true

<sup>\*</sup> User modified value

# 9. System Views

9.1. Category view

9.1.1. Current



## 10. Docs & Resources

Type Link

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_embedded\_software\_solutions.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_eval-

tools\_portfolio.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_stm8\_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_software\_development\_tools.pdf

Training Material https://www.st.com/resource/en/sales\_guide/sg\_sc2154.pdf

Flyers https://www.st.com/resource/en/flyer/flnucleolrwan.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32gui.pdf

Product https://www.st.com/resource/en/certification\_document/stm32\_authenticat

Certifications ion\_can.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2639-soldering-

recommendations-and-package-information-for-leadfree-ecopack-mcus-

and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2834-how-to-get-the-

best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2867-oscillator-

design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application\_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3997-audio-playback-and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3998-pdm-audio-software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4031-using-the-stm32f2-stm32f4-and-stm32f7-series-dma-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4073-how-to-improve-adc-accuracy-when-using-stm32f2xx-and-stm32f4xx-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4229-how-to-

- implement-a-vocoder-solution-using-stm32-microcontrollersstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4230-stm32-microcontroller-random-number-generation-validation-using-the-nist-statistical-test-suite-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4488-getting-started-with-stm32f4xxxx-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4547-migrating-from-stm32f407xx417xx-to-stm32f427xx429xx437xx439xx-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4640-peripherals-interconnections-on-stm32f4057xx-stm32f4157xx-stm32f42xxx-stm32f43xxx-stm32f446xx-and-stm32f469479xx-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4658-migration-of-applications-from-stm32f429439-lines-to-stm32f446-line-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4660-migration-of-microcontroller-applications-from-stm32f42xxxf43xxx-devices-to-stm32f7-series-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4675-migration-of-microcontroller-applications-from-stm32f42xxxstm32f43xxx-to-stm32f469xxstm32f479xx-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4739-stm32cube-firmware-examples-for-stm32f4-series-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application\_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4838-managing-memory-protection-unit-in-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4850-stm32-mcusspreadspectrum-clock-generation-principles-properties-andimplementation-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4861-lcdtft-display-controller-ltdc-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4879-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activitystmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5020-digital-camera-interface-dcmi-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5073-receiving-spdif-

audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5543-enhanced-methods-to-handle-spi-communication-on-stm32-devices-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4899-stm32-microcontroller-gpio-hardware-settings-and-lowpower-consumption-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1202\_freertos\_guide-

for related Tools freertos-guide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an1602\_semihosting\_in for related Tools \_\_truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an1801\_stm32cubeprog for related Tools rammer\_in\_truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/atollic\_editing\_keyboard for related Tools \_shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/iar\_to\_atollic\_truestudio for related Tools \_migration\_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/stm32cubemx\_installatio

for related Tools n\_in\_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2656-stm32f10xxx-

& Software

Application Notes https://www.st.com/resource/en/application\_note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3078-stm32-for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3174-implementing-for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3241-qvga-tftlcd-for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3307-guidelines-for-for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3364-migration-and-

for related Tools compatibility-guidelines-for-stm32-microcontroller-applications-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3965-

for related Tools stm32f40xstm32f41x-inapplication-programming-using-the-usart-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3969-eeprom-

for related Tools emulation-in-stm32f40xstm32f41x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3990-upgrading-

for related Tools stm32f4discovery-board-firmware-using-a-usb-key-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3997-audio-playback-for related Tools and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3998-pdm-audio-for related Tools software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4044-floating-point-for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4187-using-the-crcfor related Tools peripheral-in-the-stm32-family-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4323-getting-started-for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4365-using-stm32f4-for related Tools mcu-power-modes-with-best-dynamic-efficiency-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32- & Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4457-implementing-for related Tools an-emulated-uart-on-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4499-stm32-for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4502-stm32-for related Tools smbuspmbus-embedded-software-expansion-for-stm32cube-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4657-stm32-for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4666-parallel-for related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4678-full-duplex-spifor related Tools emulation-for-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4701-proprietary-

for related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4739-stm32cube-

for related Tools firmware-examples-for-stm32f4-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4758-proprietary-for related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5426-migrating-for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5464-position-control-

for related Tools of-a-threephase-permanent-magnet-motor-using-xcubemcsdk-or-

& Software xcubemcsdkful-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Errata Sheets https://www.st.com/resource/en/errata\_sheet/es0206-stm32f427437-and-

stm32f429439-line-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00071990.pdf

Programming https://www.st.com/resource/en/programming\_manual/pm0214-stm32-Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference\_manual/rm0090-

Manuals stm32f405415-stm32f407417-stm32f427437-and-stm32f429439-

advanced-armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn0516-overview-of-the-& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

**Technical Notes** https://www.st.com/resource/en/technical\_note/tn1205-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packagesstmicroelectronics.pdf https://www.st.com/resource/en/technical\_note/tn1206-tape-and-reel-**Technical Notes** & Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packagesstmicroelectronics.pdf **Technical Notes** https://www.st.com/resource/en/technical\_note/tn1207-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packagesstmicroelectronics.pdf **Technical Notes** https://www.st.com/resource/en/technical\_note/tn1208-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssoppackages-stmicroelectronics.pdf