

QuizMaster API Endpoints

Created by: Jayharron

Creation Date: 10/17/2023

Last update by: _____

Last update date: _____

Overview: This api endpoint will serve as the digital location where the API will receive requests and send out responses.

ACCOUNT API - Microservice						
Note: When creating a partial user, a user must be partially created and stored in the database, when logging in with username and password, the Auth API should return an ID that will be used in the front-end to retrieve the account by ID, from there, it will be determined if a user is partial or full in details. The front-end will prompt an account update to a partially created user to be a fully created user.						
METHOD	URL	DESCRIPTION	REQUIRE ADMIN	AUTHENTICATED	RESPONSE CODE/S	RESPONSE BODY
POST	api/account/create	Create a new account, all fields required, take parameter AccountCreateDto	NO	NO	201, 400, 500	Returns a message
POST	api/account/create_partial	Create new account with only username and email, take parameter AccountCreatePartialDto	NO	NO	201, 400, 500	Returns a message
GET	api/account	Retrieve all accounts.	YES	YES	200, 500	List of AccountDto in json, password is not included in the body
GET	api/account/{id}	Retrieve account by ID, used to retrieve account first before updating	NO	YES	200, 500	Single Account Data, password is included
PATCH	api/account/update/{id}	Update the account info based on the attributes requested in the body	NO	YES	200, 400, 500	Returns a message

DEL	api/account/delete/{id}	Soft delete an account based on the ID	NO	YES	200, 400, 500	Returns a message
-----	-------------------------	--	----	-----	---------------	-------------------

AUTH API - Microservice

Note: When logging in, it will return a cookie which stores the JWT, inside the JWT token, the user role status is also included. If the cookie contains a user with a role of an admin, then the '**REQUIRE ADMIN**' column in the table below is satisfied.

METHOD	URL	DESCRIPTION	REQUIRE ADMIN	AUTHENTICATED	RESPONSE CODE/S	RESPONSE BODY
POST	api/auth/login	Login to account, based on username and password included in the request body	NO	NO	200, 400, 500	- Returns a message - Returns a cookie with JWT included - Returns an ID of the user, the frontend must check if a user is a partial or in full details by fetching the api/account/{id}
POST	api/auth/logout	When fetched, clears the cookie and logs out the user	NO	YES	200, 400, 500	Returns a message
POST	api/auth/set_admin/{id:u_name}	This endpoint will give a user an admin role, the requestor must have a cookie with a user that has an admin role to give admin access. Included in the request body is a flag setting the user with an id of {n} to be an admin : true or false	YES	YES	200, 400, 500	Returns a message
GET	api/auth/info	Retrieve logged-in user info based on the cookie provided in the request	NO	YES	200,400,500	UserAccount

QUIZ API - Microservice						
Note: Question Type and Difficulty are preloaded PostManJson: https://drive.google.com/file/d/1itsP7TQjctg8WfVdtWcVHpNa5EXQZWxA/view?usp=sharing						
METHOD	URL	DESCRIPTION	REQUIRE ADMIN	AUTHENTICATED	RESPONSE CODE/S	RESPONSE BODY
Question						
POST	api/question	Creates a new question. Accepts parameter QuestionCreateDto from request body.	YES	YES	201, 400, 500	Returns 201 Create for success. Returns 401 (Bad Request). Returns 404 (Not found). Returns 500 (Server Error) for failing create new question.
PATCH	api/question	Update the question. Only Category, Difficulty, and QuestionStament can be updated.	YES	YES	200, 400, 500	Returns a message
GET	api/question	Get all the questions. Accepts a nullable type of QuestionResourceParameter from query.	NO	NO	200, 400, 500	Returns a List of QuestionDto .
GET	api/question/{id}	Get a specific question by ID.	YES	YES	200, 400, 500	Returns 200 Ok with a QuestionDto for succes. Returns 404 (Not Found).
DEL	api/question/{id}	Soft delete a specific questionnaire. Only the owner will be able to call this api endpoint, otherwise, they are forbidden.	YES	YES	200, 400, 500	Returns 200 Ok for success. Returns 404 (Not Found).

QuestionDetails						
POST	api/question/{questionId}/question-detail	Creates a question detail for the question. Accepts parameter QuestionDetailCreatDto from request body.	YES	YES	201, 400, 500	Returns 201 Created for success. Returns 401 (Bad Request). Returns 404 (Not found). Returns 500 (Server Error) for failing to create a new questionDetail.
PATCH	api/question/{questionId}/question-detail/{id}	Update the questionDetail. Only qDetailDesc, and detailTypes can be updated.	YES	YES	200, 400, 500	Returns 200 Ok for success. Returns 401 (Bad Request), Returns 404 (Not Found). Returns (Server Error) for failing to update questionDetail.
GET	api/question/{questionId}/question-detail	Get all the questionDetails associated with the given questionId.	NO	NO	200, 400, 500	Returns a List of QuestionDetailDto .
GET	api/question/{questionId}/question-detail/{id}	Get a specific questionDetail associated with the given questionId.	YES	YES	200, 400, 500	Returns 200 (Ok) with the questionDetailDto for success. Returns 404 (Not Found)
DEL	api/question/{questionId}/question-detail/{id}	Soft delete a specific questionDetail.	YES	YES	200, 400, 500	Returns 200 Ok for success. Returns 404 (Not Found).
Category						
POST	api/question/category	Create a new category that will be used in creating questionnaires. Takes a parameter of type CategoryCreateDto .	YES	YES	201, 400, 500	Returns either of the following: ResponseDto CategoryDto

GET	api/question/category	Retrieves a list of categories created and will be used for creating questionnaires	YES	YES	200, 400, 500	Returns either of the following: ResponseDto List of CategoryDto
PATCH	api/question/category	Updates a question category.	YES	YES	200, 400, 500	Returns either of the following: ResponseDto CategoryDto
DEL	api/question/category/{id}	Soft delete a question category	YES	YES	200, 400, 500	Returns either of the following: ResponseDto
Difficulty						
POST	api/question/difficulty	Creates a question difficulty that will be used in creating questionnaires. Takes a parameter of type DifficultyCreateDto .	YES	YES	201, 400, 500	Returns either of the following: ResponseDto DifficultyDto
GET	api/question/difficulty	Retrieves a list of question difficulty that will be used in creating questionnaires	YES	YES	200, 400, 500	Returns either of the following: ResponseDto List of DifficultyDto
PATCH	api/question/difficulty	Updates a question difficulty based on the attributes sent together in the request body	YES	YES	200, 400, 500	Returns either of the following: ResponseDto DifficultyDto
DEL	api/question/difficulty/{id}	Soft delete a question difficulty	YES	YES	200, 400, 500	Returns either of the following: ResponseDto
Type						
POST	api/question/type	Create a new question type that will be used in creating questionnaires. Takes a parameter of type TypeCreateDto .	YES	YES	201, 400, 500	Returns either of the following: ResponseDto TypeDto

GET	api/question/type	Gets all the types of questions created by admins, shown in the frontend and will be used to create a questionnaire	YES	YES	200, 400, 500	Returns either of the following: ResponseDto List of TypeDto
PATCH	api/question/type	Updates a question type based on the attributes included in the request body	YES	YES	200, 400, 500	Returns either of the following: ResponseDto TypeDto
DEL	api/question/type/{id}	Soft delete a question type	YES	YES	200, 400, 500	Returns either of the following: ResponseDto

METHOD	URL	DESCRIPTION	REQUIRE ADMIN	AUTHENTICATED	RESPONSE CODE/S	RESPONSE BODY
POST	api/session/create	Creates a quiz room including the quiz details, Accepts CreateSessionDTO	YES	YES	201, 400, 500	Returns a room ID
PATCH	api/session/update/{id}	Updates the quiz session	YES	YES	200, 400, 500	Returns a message
DELETE	api/session/delete/{id}	Remove the session, users must not be able to find the room since it's already deleted	YES	YES	200, 400, 500	Returns a message
POST	api/session/start/{id}	Start the quiz session, ensure that clients are already connected in the websocket connection.	YES	YES	200, 400, 500	Returns a message
GET	api/session/{id}	Gets the quiz room data, such as RoomId, participants list, list of question set, room options	YES	YES	200, 400, 500	Returns a message
GET	api/session	Retrieve all sessions in a list	YES	YES	200, 400, 500	Returns a message
POST	api/room/join/{ws-clientId}	Join a room, require RoomID and username, checks if username already exists in the JWT Token	NO	YES	200,400,500	Returns a message
POST	api/room/{id}/submit	Submit participant's answer, room Id, time, question id. Only accept the request if the session is open for answer submission.	NO	YES	200,400,500	Returns a message
POST	api/room/{id}/chat	Post a chat, this is not saved in the database, it will only be displayed on the frontend but once the session is ended, all chat info will not be saved	NO	YES	200,400,500	Returns a message
WS	ws/quizmaster_ws	– Websocket endpoint –	NO	YES	-	– Websocket Connection –
WS	: notif	Realtime notification (player join/left, remaining time before start/end)	ENTRYPOINT DEPENDENT	ENTRYPOINT DEPENDENT	-	– WS method to invoke in frontend –

WS	: chat	Receive real time chat messages	ENTRYPOINT DEPENDENT	ENTRYPOINT DEPENDENT	-	– WS method to invoke in frontend –
WS	: game_update	Game info, if quiz started or ended, current question to be displayed (answer is not included in the response)	ENTRYPOINT DEPENDENT	ENTRYPOINT DEPENDENT	-	– WS method to invoke in frontend –
WS	: leaderboard	Shows the leaderboards or scores	ENTRYPOINT DEPENDENT	ENTRYPOINT DEPENDENT	-	– WS method to invoke in frontend –
WS	: round_set	Show the current set of the quiz	ENTRYPOINT DEPENDENT	ENTRYPOINT DEPENDENT	-	– WS method to invoke in frontend –
WS	: participants	Realtime information of participants joined in room/lobby	ENTRYPOINT DEPENDENT	ENTRYPOINT DEPENDENT	-	– WS method to invoke in frontend –

MEDIA API - Microservice

This api handles uploading of files such as images, audios or videos

METHOD	URL	DESCRIPTION	REQUIRE ADMIN	AUTHENTICATED	RESPONSE CODE/S	RESPONSE BODY
POST	api/media	Uploads a file	YES	YES	201, 400, 500	Returns an ID
GET	api/media	Get's all the files stored in the database	YES	YES	200, 400, 500	List of File info
GET	api/media/{id}	Retrieves the file details including the file link. File info includes the type of file and the size.	YES	YES	200, 400, 500	File info
GET	api/media/download/{id}	Downloads the file based on the file link	YES	YES	200, 400, 500	FILE
DEL	api/media/{id}	Deletes the file, erase in the memory	YES	YES	200, 400, 500	Returns a message

MONITORING API - Microservice

This api handles

METHOD	URL	DESCRIPTION	REQUIRE ADMIN	AUTHENTICATED	RESPONSE CODE/S	RESPONSE BODY
GET	api/logs	Get system logs	YES	YES	200, 400, 500	
GET	api/status/{api_id}	Get health status of each api microservices by ID	YES	YES	200, 400, 500	
POST	api/logs	Save a log, note that this should only be accessed by other services via gRPC	NO	NO	200, 400, 500	

Classes for request/response:

ResponseDto “Returns a Message”	
Message	String
Type	String “Error” “Warn” “Info”

AccountCreateDto	
LastName	string(50)
FirstName	string(50)
Email	string(50), Required
UserName	string(20), Required
Password	string, Required

AccountCreatePartialDto	
Email	string
UserName	string(20), Required

AccountDto	
Id	int
LastName	string

FirstName	string
Email	string
UserName	string
ActiveData	bool
DateCreated	DateTime
DateUpdated	DateTime?
UpdatedByUserId	int

FileInfo	
Id	guid
FileType	string
FileSize	double
FileName	string
DateCreated	datetime

QuestionCreateDto	
qStatement	string(Max)
qAudio	string?(Max)

qImage	string?(Max)
qVideo	string?(Max)
qCategoryId	int
qDifficultyId	int
qDifficultyId	int
qDetails	QuestionDetailCreateDto []

QuestionDetailCreateDto	
qDetailDesc	string
detailTypes	string[]

*content of detail types can only be of the ff: 'answer', 'option', 'minimum', 'maximum', 'interval', 'textToAudio', 'language'

QuestionDetailDto	
Id	int
qDetailDesc	string
detailTypes	string[]

*content of detail types can only be of the ff: 'answer', 'option', 'minimum', 'maximum', 'interval', 'textToAudio', 'language'

QuestionResourceParameter	
IsOnlyActiveData	bool
IncludeDetails	bool
SearchQuery	string?
PageNumber	int
PageSize	int

QuestionDto	
Id	int
qStatement	string(Max)
qAnswer	string(Max)
qCategory	CategoryDto
qDifficulty	DifficultyDto
qType	TypeDto
qDetails	string

CategoryCreateDto	
qCategoryDesc	string(50)

CategoryDto	
Id	int
qCategoryDesc	string(50)

DifficultyCreateDto	
qDifficultyDesc	string(10)

DifficultyDto	
Id	int
qDifficultyDesc	string(50)

TypeCreateDto	
qTypeDesc	string(50)
qDetailRequired	bool

TypeDto

Id	int
qTypeDesc	string(50)
qDetailRequired	bool

PCreateSessionDTO	
Sets	Int[] // question set Id's
Options	string[]

Options:

```
[
    "Mode:elimination|normal", default normal | on elimination round, top 50% will proceed to next round
    "Show_leaderboard_each_round:true|false", default true
    "Display_top_10_only:true|false", default true, on false, everyone is shown based on ranking
    "Allow_reconnect:true|false", default true
    "Allow_join_on_game_started:true|false", default false
]
```

RoomDTO	
Id	int
Sets	Int[] // question set Id's
Options	string[]