Quantum Error Correction and Entanglement Purification

Tanay Bhat Jay Mehta Rajwardhan Toraskar

Department of Electrical Engineering Indian Institute of Technology, Bombay

October 10, 2025

Outline

- Introduction
- Quantum Errors
- 3 3-Qubit Bit-Flip Code
- 4 9-Qubit Shor Code
- 5 Entanglement Purification (BBPSSW)
- 6 Implementation & Results
- 7 Conclusion

Motivation

- Quantum states are quite sensitive and prone to errors arising due to decoherence, imperfect application of gates and measurments.
- To combat these errors, two main strategies are employed:
 - Entanglement purification Use multiple noisy entangled pairs to generate a few high-fidelity pairs.
 - Quantum error correction (QEC) encode logical qubits into many physical qubits to detect and correct errors.
- In this PPT, we shall analyse the 3-bit and 9-bit Shor codes for QEC and also look at the BBPSSW protocol for entanglement purification.

Types of Quantum Errors

Common categories:

- **Coherent errors**: Systematic over/under rotations (unitary). Generally arise due to incorrect operation of gates.
- Environmental decoherence: Coupling to the environment leads to loss of coherence.
- Loss / leakage / measurement / initialization errors.

Coherent errors

Small rotation $U = e^{i\epsilon\sigma_x}$ applied to a qubit N times:

$$|\psi\rangle = \left(e^{i\epsilon\sigma_x}\right)^{\otimes N}|0\rangle = \cos(N\epsilon)|0\rangle + i\sin(N\epsilon)|1\rangle.$$

Measurement probabilities:

$$P(|0\rangle) = \cos^2(N\epsilon) \approx 1 - (N\epsilon)^2, \qquad P(|1\rangle) \approx (N\epsilon)^2.$$

With QEC we can suppress such errors to higher orders ($O(\epsilon^2) o O(\epsilon^6)$).

Decoherence due to environment

Example: system entangles with environment $|e_0\rangle$, $|e_1\rangle$. The state of the environment flips if the qubit is $|1\rangle$. Hence on application of the operation *HIH* to the state $|0\rangle|e_0\rangle$, we get:

$$\ket{\psi} = extit{HIH} \ket{0}\ket{e_0} = rac{1}{2}(\ket{0}+\ket{1})\ket{e_0} + rac{1}{2}(\ket{0}-\ket{1})\ket{e_1}.$$

We can then consider the density matrix of the combined system and trace out the environment to get the reduced density matrix of the system:

$$ho = \operatorname{tr}_{E}(\ket{\psi}ra{\psi}) = \frac{1}{2}(\ket{0}ra{0} + \ket{1}ra{1})$$

Hence the qubit is in a completely mixed state, i.e. it has decohered.

3-Qubit Bit-Flip Code — Encoding

Logical codewords:

$$|0\rangle_L = |000\rangle \,, \qquad |1\rangle_L = |111\rangle \,.$$

Encode an arbitrary qubit $|\psi\rangle=\alpha\,|0\rangle+\beta\,|1\rangle$ as

$$|\psi\rangle_L = \alpha |000\rangle + \beta |111\rangle.$$

This code is able to correct for any single bit-flip error.

Syndrome extraction & correction

Use two ancillas (parity checks). Syndrome table:

Syndrome	Correction
00	No error
01	<i>X</i> ₃
10	X_2
11	X_1

Circuit: encode with two CNOTs, measure ancillas, apply conditional X.

Error suppression (coherent small rotations)

For $U = e^{i\epsilon\sigma_x}$ on each physical qubit:

$$E = U^{\otimes 3} = c_0 \, \sigma_I \sigma_I \sigma_I + c_1 \, (\sigma_x \sigma_I \sigma_I + \dots) + c_2 (\dots) + c_3 \, \sigma_x \sigma_x \sigma_x,$$

where

$$c_0 = \cos^3 \epsilon, \quad c_1 = i \cos^2 \epsilon \sin \epsilon, \quad c_2 = -\cos \epsilon \sin^2 \epsilon, \quad c_3 = -i \sin^3 \epsilon.$$

Unencoded fidelity: $F_{\text{unencoded}} = \cos^2 \epsilon \approx 1 - \epsilon^2$.

After post-selecting the no-error syndrome, encoded fidelity:

$$F_{\rm encoded} \approx 1 - \epsilon^6$$
.

(Error reduced from $O(\epsilon^2)$ to $O(\epsilon^6)$.)

Shor 9-Qubit Code — Logical states

Combine phase-flip and bit-flip repetition codes.

$$|0\rangle_{L} = \frac{1}{2\sqrt{2}}(|000\rangle + |111\rangle)^{\otimes 3}, \quad |1\rangle_{L} = \frac{1}{2\sqrt{2}}(|000\rangle - |111\rangle)^{\otimes 3}.$$

Each block of 3 corrects an X error; inter-block checks correct Z errors.

How it protects against arbitrary single-qubit errors

An arbitrary single-qubit error can be expanded in Pauli basis. The combined bit-flip and phase-flip checks detect and correct single-qubit X, Z (and hence Y) errors. Coherent rotation generalization:

$$E = \bigotimes_{i=1}^{9} (\cos \epsilon \, \sigma_{I} + i \sin \epsilon \, \sigma_{x}),$$

followed by appropriate syndrome circuits increases logical fidelity compared to unencoded qubit.

Werner states and depolarization

Any two-qubit state can be depolarized to a Werner form without changing fidelity with $|\phi_{00}\rangle$:

$$\rho_W(x) = x |\phi_{00}\rangle \langle \phi_{00}| + \frac{1-x}{4}I_4.$$

Fidelity relative to $|\phi_{00}\rangle$: $F = \langle \phi_{00} | \rho_W | \phi_{00} \rangle = \frac{3x+1}{4}$.

BBPSSW protocol (recurrence)

Starting with pairs of fidelity F > 1/2:

- **1** Depolarize to Werner form $\rho_W(F)$.
- $exttt{2}$ Take two copies; apply bilateral CNOT (A1oA2 and B1oB2).
- Measure target qubits (A2,B2) in Z- and X-bases; keep control pair if measurement results match.

Fidelity update and success probability

After one successful purification step the surviving pair (still Werner) has fidelity

$$F' = \frac{F^2 + \left(\frac{1-F}{3}\right)^2}{F^2 + 2F\left(\frac{1-F}{3}\right) + 5\left(\frac{1-F}{3}\right)^2},$$

and the success probability is

$$p_{\text{succ}} = F^2 + 2F\left(\frac{1-F}{3}\right) + 5\left(\frac{1-F}{3}\right)^2.$$

Iterating increases fidelity but reduces yield (consume 2 pairs to keep 1).

Qiskit simulations

- 3-qubit bit-flip and phase-error simulations: encoding, injecting error, syndrome extraction, correction, decode. Observed fidelity improvement consistent with theory (e.g. $1 \epsilon^2 \rightarrow 1 \epsilon^6$).
- 9-qubit Shor code simulation: injected single Z error, used 6 ancillas for syndrome extraction; decoded and observed restored logical state.

Code repository (included in report):

https://github.com/jaymehta132/QuantumErrorCorrection-EE7001

Example figures (placeholders)

Conclusions & Outlook

- QEC and entanglement purification are foundational for fault-tolerant quantum computing and long-distance quantum communication.
- Simple codes (3- and 9-qubit) illustrate suppression of coherent errors and correction of arbitrary single-qubit errors.
- Real devices: gate errors, measurement noise, and leakage limit achievable fidelities; fault-tolerance requires concatenation or more advanced topological/subsystem codes and careful experimental engineering.

References I



S. J. Devitt, W. J. Munro, K. Nemoto, "Quantum error correction for beginners," Reports on Progress in Physics, 2013.



W. Dür and H.-J. Briegel, "Entanglement purification and quantum error correction," Reports on Progress in Physics, 2007.



Project report (uploaded): "Quantum Error Correction (EE7001)" by Tanay Bhat et al. :contentReference[oaicite:2]index=2