OPTIMIZING REAL-TIME OBJECT DETECTION AND TRACKING WITH YOLOv11, DEEPSORT, AND LSTM-RNN: A PERFORMANCE ANALYSIS

A Thesis Presented to the Faculty, College of Computer Studies
Laguna State Polytechnic University
Los Baños Campus
Los Baños, Laguna

In partial fulfillment of the requirement for the degree
Bachelor of Science in Computer Science
Specialized in Intelligent Systems

JOSEF MARCLEIN D. LEONARDO
MERLYN JOY E. BANASIHAN
ANDREA E. GECOLEA

GENE MARCK B. CATEDRILLA

JUNE 2026

APPROVAL SHEET

The thesis entitled "**OPTIMIZING REAL-TIME OBJECT DETECTION AND TRACKING WITH YOLOv11, DEEPSORT, AND LSTM-RNN: A PERFORMANCE ANALYSIS**" prepared and submitted by Josef Marclein D. Leonardo, Merlyn Joy E. Banasihan, Andrea E. Gecolea in partial fulfillment requirements for the degree Bachelor of Science in Computer Science specialized in Intelligent Systems, is hereby recommended for approval and acceptance.

GENE MARCK B. CATEDRILLA
Adviser

Approved and Accepted by the Committee on Oral Examination with a grade of ____.

CAROLINA R. JOVAL
Member

MYRA V. PAICAGLINO
Member

JEFFERSON L. LERIOS
Member

Accepted in partial fulfillment of the requirements for the degree of Bachelor of Science in Computer Science specialized in Intelligent Systems.

LOYD S. ECHALAR, DIT
Associate Dean, College of Computer Studies

OFELIA B. MANINGAS, EdD.
Chairperson, Research and Development Office

_____
Date Signed

RESEARCH CONTRIBUTION NO.	

ACKNOWLEDGEMENT

This study would not be possible without the invaluable support, professional guidance, and distinguished contributions of the individuals and institution who played key roles in the completion of this work.

The researchers extend their sincere gratitude to the University President, Dr. Mario R. Briones, and OIC Campus Director, Engr. Manuel Luis R. Alvarez, for their excellent leadership and for fostering a conducive academic environment.

Deep appreciation is accorded to the College of Computer Studies Associate Dean, Dr. Loyd S. Echalar, for his consistent encouragement. Special acknowledgement to their dedicated mentor, Mr. Gene Marck B. Catedrilla, for his his invaluable technical guidance and perceptive contributions, which helped this study be completed.

To the Research Coordinator, Dr. Jefferson L. Lerios, and the distinguished members of the Approval Committee, Mrs. Carolina R. Joval and Ms. Myra V. Paicaglino, for their expert review and comprehensive support throughout the project's development.

The researchers recognize Perello's Poultry Farm for the crucial approval for data collection. Their approval was fundamental to the empirical success of the study.

Finally, to Almighty God for providing them with the wisdom, knowledge, and protection needed to complete this work.

The Researchers

DEDICATION

The success of this project is respectfully and wholeheartedly dedicated by the researchers to our Almighty God, who gave them knowledge, protection, and guidance. To their families:

Mr. Marcelo and Mrs. Jeellyn Leonardo

Ms. Ferlyn Deada

Mr. Ramir Banasihan

Mrs. Rosalinda Boongaling

Mr. Rommel and Mrs. Ma. Theresa Gecolea

For their boundless love, unwavering support, and immense sacrifices, both financial and moral support were the foundation of their perseverance and dedication to work hard to the project.

To Mr. Lans Andrew S. Basbas for continuing support and guidance in contacting the owner of the poultry farm including providing directions from our hometown to the study location of the study area.

To Mr. James Caesar Q. Repalda in allowing the researchers to utilize his personal laptop for efficient model training.

To our friends, partners, and siblings, who provided encouragement during times of hardship and difficulty, reminding them to persist.

J.M.D.L.

M.J.E.B.

A.E.G.

ABSTRACT

This study introduced an integrated deep learning framework for real-time behavioral analysis to detect potentially sick chickens, overcoming challenges associated with traditional visual monitoring and occlusion. The framework utilizes YOLOv11 for robust object detection, DeepSORT for multi-object tracking, and LSTM-RNN for temporal behavior recognition to identify anomalous motions such as lethargy and unsteady walking. After extracting, annotating, and augmenting video data from Perello's Poultry Farm in Cavite, producing 2,549 training images. YOLOv11 achieved a detection accuracy of 97.4% mAP@0.50 under occluded conditions, with DeepSORT maintaining consistent tracking in dense flocks. The LSTM-RNN effectively differentiated normal from anomalous behaviors using reconstruction loss thresholds. Evaluation metrics confirmed the framework's strong performance, yielding an overall accuracy of 89%, based on the confusion matrix of expert validation and model prediction. Furthermore, a paired sample t-test revealed no significant difference between the model's predictions and expert evaluations ($t(109) = -0.576$, $p = 0.566$), providing strong evidence of the model's reliability and effectiveness in identifying potentially sick chickens. In conclusion, the proposed framework reliably differentiates potentially sick chickens from healthy ones, and future studies are recommended to incorporate more diverse datasets, additional behavioral indicators, and varied farm environments to improve generalizability.

Keywords - *YOLOv11, DeepSORT, LSTM-RNN, Occlusion, Anomaly Detection, Behavioral Analysis, Potentially Sick*

TABLE OF CONTENTS

Preliminaries	*Page*
Title Page	i
Approval Sheet	ii
Acknowledgement	iii
Dedication	iv
Abstract	v
Table of Contents	vi
List of Figures	viii
List of Tables	x
Definition of Terms	xi
CHAPTER	
I INTRODUCTION	
Background of the Study	1
Objectives	4
Significance of the Study	5
Scope and Limitations	7
II REVIEW OF RELATED LITERATURE AND STUDIES	
Related Literature	9
Literature Matrix	31
Synthesis and Relevance of the Study	33
Comparative Summary of Detection and Behavior Analysis Models	35
Conceptual Framework	36
III METHODOLOGY	
Study Area	38
Materials	39
Software	39
Hardware	45
Research Design	46
Model Development	47
Data Acquisition	50
Data Sources	52
Data Annotation Protocol	53
Model Selection	54
Model Evaluation	56
Model Validation	59
Ethical Consideration	63
IV RESULTS AND DISCUSSIONS	
Exploratory Data Analysis	65
Data Preparation and Augmentation	67
YOLOv11 Model Training and Implementation	69

Hyperparameter Values of YOLOv11 70
Integration of YOLOv11 to DeepSORT & LSTM-RNN 72
Hyperparameter Values of DeepSORT 72
Hyperparameter Values of LSTM-RNN 75
Results of Metrics for YOLOv11 and LSTM-RNN 77
Results of Metrics for YOLOv11 78
Results of Metrics for LSTM-RNN 80
Comparison of Proposed Model with Prior Models 82
Model Validation 83
Confusion Matrix of Expert and Model 84
Quantitative Comparison Between Expert and Model 85
Descriptive Comparison of Poultry Expert and Model Classification Results 86
Paired T-test Result 86

V SUMMARY, CONCLUSIONS AND RECOMMENDATIONS
Summary 89
Conclusions 91
Recommendations 96

REFERENCES
APPENDICES

Appendix A. Letter of Approval
Appendix B. Certificate of Acceptance
Appendix C. Relevant Source Code
Appendix D. Evaluation Process & Tool
Appendix E. Sample Input / Output
Appendix F. Model Prototype
Appendix G. Curriculum Vitae
Appendix H. User's Guide
Appendix I. Matrix for Revision
Appendix J. Grammarly & Turnitin Report
Appendix K. Publishable Paper (IEEE format)

LIST OF FIGURES

Figure	Title	Page
1	Conceptual Framework of YOLOv11, DeepSORT, and LSTM-RNN in Detecting Potentially Sick Chickens	36
2	Geographical Map Showing the Location of the Poultry Farm	39
3	Model Development of YOLOv11–DeepSORT–LSTM-RNN	50
4	Summary of Annotated Data in Roboflow	53
5	End-to-End Flow of Data from YOLOv11–DeepSORT–LSTM-RNN	55
6	Model Architecture of YOLOv11–DeepSORT–LSTM-RNN End-to End Pipeline	56
7	Sample of Training and Validation Performance Curves of YOLOv11	61
8	Example of Confusion Matrix	62
9	Installation of CCTV Camera at Perello's Poultry Farm in Indang Cavite	65
10	Sample Data and CCTV View in Varying Lighting: (a) Day Setting and (b) Night Setting	66
11	Example of Annotated Chicken Datasets in Roboflow	68
12	Image Preprocessing and Augmentation Parameters for YOLOv11	69
13	YOLOv11 Training Outputs Showing Detected Chickens	70

14	YOLOv11 Inference Results on Poultry Video Frames	71
15	DeepSORT Tracking Output with Unique Chicken IDs	73
16	LSTM-RNN Autoencoder Output for Anomaly Detection	77
17	Precision-Recall Curve of YOLOv11 in Chicken Detection	79
18	Validation Losses and Learning Rate Trends During Training	83
19	Confusion Matrix Comparing Expert Ground Truth and Model Predictions	84
20	Mean and Median Accuracy of the Poultry Expert and Model Evaluations	87

LIST OF TABLES

Table	Title	Page
1	Matrix of the Review of Related Literature	31
2	Comparative Summary of Detection and Behavior Analysis Models	35
3	Desktop Specification	45
4	CCTV Specification	45
5	Data Description	52
6	Datasets Splitting	53
7	Optimized Hyperparameters of YOLOv11	70
8	Optimized Hyperparameters of DeepSORT	72
9	Optimized Hyperparameters of LSTM-RNN	75
10	Results of Metrics for YOLOv11	78
11	Results of Metrics for LSTM-RNN	80
12	Comparison of the Proposed YOLOv11–DeepSORT–LSTM-RNN Framework with Prior Models	82
13	Quantitative Comparison Between Expert Validation and Model	85
13	Descriptive Comparison of Poultry Expert and Model Classification Results	86
14	Results of the Paired Samples T-Test Between Poultry Expert and Model Evaluations	86

DEFINITION OF TERMS

This section provides definitions for the key technical terms used throughout this study. These definitions are essential for understanding the methodologies, concepts, and components of the developed model for chicken behavioral analysis and for predicting potentially sick chickens.

Annotate	Process of adding labels or metadata to an individual object present in the image to provide contextual information about the object being detected. This process helps in training and validating the object detection model (YOLOv11).
Anomaly Detection	A data analysis technique used to identify unusual patterns, behaviors, or events that deviate significantly from normal or expected activity. In the context of poultry monitoring, it is applied to detect irregular movements or behaviors that may indicate illness or abnormal conditions.
Behavioral Analysis	This refers to the utilization of Long Short-Term Memory – Recurrent Neural Network (LSTM-RNN) in order to process the interpretation of temporal patterns in chicken movements and behaviors to identify indicators of potential sickness.
Bounding Box	Annotation in images uses a rectangular shape called the bounding box to identify a certain object present in the image, such as chicken, and water container. In order to recognize similarities, it identifies object localization and identification within the video frames, which then serves as the input for tracking and behavioral analysis.
Computer Vision	Refers to the process of computers to identify and view images and videos in the same way that human do. It enables automated, real-time observation, analysis, and interpretation of the object behavior from video data.
Deep Learning	Machine learning utilizes artificial neural networks to learn patterns and representation from the raw data. It provides advanced computational intelligence and pattern recognition capabilities essential for the automated

	and accurate analysis of object behavior from video.
DeepSORT	A multi-object tracking algorithm that operates associating object detection across video frames using the combination of motion prediction and deep learning to accurately and consistently track individual objects in real-time occluded video feeds.
Long Short-Term Memory – Recurrent Neural Network (LSTM-RNN)	A deep learning architecture that are designed to model and analyze sequential data by capturing long-term dependencies. It analyzes the time-series data of individual object movements and behavior, derived from DeepSORT's tracking output, to identify indicative of potentially sick chickens.
Multi-Object Tracking	Process of continuously identifying and following multiple distinct entities across successive video frames, maintaining a unique identity for each individual over time. It generates robust, identity-preserving time series movement data for individual entities from the initial YOLOv11 detections.
Object Detection	Computer vision task of identifying instances of specific objects within a video frame and simultaneously localizing each instance by drawing a bounding box around it. It serves as the initial step in the framework by accurately and efficiently identifying and localizing individual chickens in real-time video frames.
Occlusion	A condition where object of interest is partially hidden from the camera's point of view by another object or environmental element. A significant obstacle to accurate and continuous object tracking and to emphasize robustness of the DeepSORT Algorithm. Once unsolved, it will affect the accuracy and efficiency of the result of the optimized model.
Potentially Sick	Classified state derived from the system's analysis of a chicken's behavioral

	patterns, indicating a deviation from normal or healthy behavior that suggests the onset or presence of illness.
Real-Time	The system's ability to classify a chicken as "potentially sick" concurrently with following the observation of its behavioral patterns from live video streams. It enables prompt identification and intervention for sick chickens.
Video Processing	Series of computational operations applied to raw video streams to extract, analyze, and interpret visual information from the poultry environment. It transforms continuous video footage of chickens into structured data suitable for automated behavioral analysis.
You Only Look Once version 11 (YOLOv11)	A real-time object detection algorithm renowned for its speed and accuracy in identifying and localizing objects within video frames where serve as the initial and critical component of the framework as it is responsible for accurately and efficiently detecting and localizing individual chickens in real-time within video streams.

CHAPTER I

INTRODUCTION

Background of the Study

YOLO (You Only Look Once) is a single-stage object detection algorithm for real-time performance, capable of processing up to 155 frames per second (Redmon et al., 2015). Its later versions introduced refinements that improved both accuracy and speed, making it suitable for poultry behavior analysis. YOLOv11 was chosen for its superior accuracy, computational efficiency, and advanced feature extraction. It integrates anchor-free detection, a C2f module, and transformer-based attention, enhancing small-object recognition and reducing inference time. These upgrades enable real-time deployment on mid-tier GPUs—crucial for continuous, energy-efficient farm surveillance. In the agricultural field, YOLO has been recognized for its potential in monitoring chickens for early signs of sickness based on subtle behavioral cues (Badgujar et al., 2024). Detecting these early behavioral changes is essential for timely intervention, as chickens often conceal illness in its initial stages (Michel et al., 2022).

The behavior of chickens is a good indicator of their health. Changes in mobility, preening, dustbathing, aggression, or foraging may be signs of underlying health issues, according to research (Gauthier & Ludlow, 2012; Nicol, 2015; Baxter et al., 2020). Early indicators of illness can be found in even little variations, such as decreased movement or particular immobility responses (M. Gentle & Fiona L. Hill, 1987). Therefore, precise behavioral observation through video analysis offers a dependable and non-invasive way

to identify possible illness in chickens early on.Despite continuous efforts from YOLOv8 to YOLOv11, applying these models directly for behavior-based sickness detection remains challenging. Detecting and consistently tracking individual chickens in crowded and low-light environments is difficult, especially for small or fast-moving birds (Afdhal et. al., 2023; Bakirci et. al., 2024; Khanam & Hussain, 2024). Previous studies often struggle with maintaining consistent identity tracking across frames and handling occlusions (Kader et. al., 2021; Nguyen et. al., 2023). To address these issues, this research introduces an integrated system combining YOLOv11 for precise detection, DeepSORT for robust multi-object tracking, and LSTM-RNN for temporal behavioral sequence analysis.

DeepSORT amends the capability of object detection models by maintaining continuous identity tracking across frames. Through motion prediction and appearance feature matching, it achieves reliable tracking even during occlusions and interactions, reaching up to 92% multi-object tracking accuracy when paired with YOLOv8 (Yang et. al., 2024). This integration ensures consistent monitoring of each chicken’s movement, which is essential for analyzing behavioral trends. Unlike restoration-based occlusion handling methods (Guo et. al., 2021), DeepSORT provides a direct, real-time approach to sustaining identity integrity during video-based observation.

Building upon the need for temporal analysis of individual chicken behavior, Long Short-Term Memory (LSTM) networks have demonstrated success in identifying specific health indicators like lameness in broilers by analyzing sequential pose estimation data derived from video, achieving high classification accuracy (Sin et. al., 2024; Nasiri et. al., 2022). As a foundational

architecture for processing sequential data, the Recurrent Neural Network (RNN) provides the structural basis upon which LSTM's ameded memory mechanisms operate. Along with the recurrent neural network, Anomaly detection also provides a quantitative and standardized framework for identifying irregularities, which reduces subjective interpretation and inconsistencies that can arise from human judgment (Chandola et. al., 2009). In the context of this study, an integrated LSTM-RNN architecture with anomaly detection will be employed to analyze the temporal sequences of individual chicken movements and behaviors, derived from the tracking data, to identify patterns indicative of potential sickness. Furthermore, to strengthen the RNN's ability to discern subtle yet critical behavioral cues, spatial-temporal attention mechanisms (Du et. al., 2017) will be considered to dynamically focus on the most relevant visual information within the tracked chicken's context across video frames.

Compared to traditional image-based detection, behavior-based methods provide a more reliable and proactive approach. Static image cues like feather condition or discoloration often appear only after disease progression, whereas behavioral monitoring detects early motion anomalies that precede visible symptoms. This continuous, context-aware analysis reduces misclassification due to lighting or environmental variations, making it ideal for real-time poultry welfare monitoring.

In summary, this study proposes a new and completely integrated detection, tracking, and analysis framework that integrates an LSTM-RNN-based anomaly detection module for evaluating temporal behavior, DeepSORT for dependable multi-object tracking, and YOLOv11 for accurate object

detection. By combining these elements, the system creates a behavior-based, multi-stage analytical pipeline that can track individual hens in real time, maintain their identities between frames, and decipher movement patterns that could point to early illness symptoms. This automated method improves health assessment accuracy and consistency by concentrating on behavioral deviations that are often hard to spot through manual farm inspections, like inactivity, irregular movement patterns, or possible huddling tendencies. Finally, by lowering labor-intensive monitoring duties, promoting early disease detection, and increasing overall farm productivity, the suggested framework promotes proactive poultry welfare management. Additionally, its scalable design and data-driven insights support more ethical, technologically sophisticated, and sustainable poultry production systems.

Objectives of the Study

This research seeks to develop a tool capable of detecting the chicken's health, with the goal of early potentially sick detection of the chicken. This project intends to accomplish the following objectives.

1. Implement and train the YOLOv11 model for accurate detection of chicken in occluded area.
2. Integration of YOLOv11 output for object detection with DeepSORT for multi-object tracking and LSTM-RNN with anomaly detection for behavioral classification in motion of potentially sick chicken.
3. Analyze and classify potentially sick chickens based on anomaly behavior by evaluating the following metrics such as Precision, Recall, F1 Score, mAP@0.50 and mAP@0.50:0.95 (mean average precision at

different IoU thresholds), and Precision-Recall Curves for YOLOv11 in object detection, and Mean Squared Error (MSE), and Coefficient of Determination (R^2) for LSTM-RNN with Anomaly Detection for behavioral analysis.

4. Evaluate system's performance used for the detection of potentially sick chickens using Confusion Matrix of Model and Expert, and Paired T-Test.

Significance of the Study

Poultry industry is one of the major livestock that benefits the human consumption and economic development. By developing this detection model for detecting early disease in chicken using advanced machine learning algorithms, the research directly supports SDG 2's objective of ensuring that the poultry farms are secured to continuously provide production for human consumption. Additionally, the contribution of the poultry industry to the livelihood for people worldwide aligns with SDG 8's goal of sustainable economic growth and productive employment. Furthermore, the study contributes to SDG 12's to also prevent the resources of raising the chickens invested beforehand not wasted. Hence, the detection model, that aims to develop a model for detecting the possibility of early disease on chickens, be of great significance and will benefit the following:

Poultry Industries: This study strengthens the Philippine poultry industry by integrating machine learning and artificial intelligence into smart farming systems for real-time health monitoring and early detection of potentially sick chickens. By automating behavioral analysis through computer vision, it

reduces dependence on manual inspection, minimizing human error and animal stress while improving farm efficiency. The generated behavioral datasets enable predictive modeling and data-driven decision-making, empowering poultry farms with proactive disease management, optimized resource allocation, and enhanced operational sustainability. Ultimately, this innovation bridges agricultural practices and intelligent automation, positioning the Philippine poultry sector toward a more resilient, technology-driven future.

Community: Upgraded biosecurity and proactive disease management within poultry farms contribute to a more stable and reliable supply of poultry products, a crucial source of affordable protein for diverse populations, thereby bolstering food security at a community level. Furthermore, the early identification and containment of avian diseases mitigate the potential for zoonotic spillover events, safeguarding public health and reducing the burden on healthcare systems. Economically, a more resilient and productive poultry sector supports employment opportunities and stimulates local economic activity. Consequently, the adoption of affordable AI-based monitoring tools fosters digitally empowered farming communities, encouraging local modernization while ensuring consistent poultry production. This contributes to food security, sustainable rural employment, and the digital transformation of agriculture.

Future Researchers: For computer scientists, it provides a rich dataset and methodological framework for advancing the application of machine learning and artificial intelligence in complex biological systems, particularly in the realm of subtle pattern recognition and real-time analysis. Ethologists and animal scientists stand to gain novel insights into the nuanced behavioral changes associated with avian disease, potentially leading to a more comprehensive

understanding of animal health and welfare indicators. Furthermore, the interdisciplinary nature of this research, bridging technology and biology, encourages the development of innovative research paradigms and collaborative efforts. Ultimately, this work not only contributes to the immediate advancement of poultry health management but also lays a robust foundation for subsequent investigations into automated health monitoring, disease modeling, and the broader application of behavioral analysis in diverse animal populations.

Scope and Limitations of the Study

This research focuses on developing a refined video-based system for behavior-based detection of potentially sick chickens. The study seeks to develop a system that leverages advanced computer vision and deep learning techniques, specifically YOLOv11 for object detection, DeepSORT with a Kalman Filter for multi-object tracking, and LSTM-RNNs with anomaly in motion for behavior analysis, to identify subtle behavioral changes. The dataset for this research is sourced from Perello's Poultry Farm in Indang, Cavite. By implementing these machine learning algorithms, the study aims to assess the overall performance and efficiency of the modified model in detecting chicken health status based on observed behaviors. Rather than proposing a novel approach to disease detection, this research focuses on enhancing the YOLOv11 algorithm's object detection capabilities, along with DeepSORT and LSTM-RNN to achieve amplified accuracy and reliability in identifying potentially sick chickens, and to boost the behavioral analysis of the model based on the datasets.

Despite the potential contributions of this study, several limitations may affect the interpretation of the findings. The accuracy and reliability of the results are contingent upon the quality, completeness, and reliability of the acquired data. Moreover, the study primarily focuses on detection rather than prediction of future health status. The model's performance is reliant on the manual annotation of chicken, and anomaly in motion on detecting potentially sick chicken as behavioral symptoms are not available. Followed by pre-processing and data augmentation for training. Furthermore, the behavioral evaluation in this study relies solely on video datasets. The potential contribution of audio data, such as changes in vocalization, was not explored.

Its computational cost limits robust real-time deployment. Experiments on a system with an AMD Radeon RX 6600 GPU (8GB VRAM), AMD Ryzen 5 5600X CPU, and 16GB RAM showed that YOLOv11 required 3–5 hours for whole training epoch, while the LSTM-RNN model needed around 12 hours to process 30 minutes of DeepSORT tracking data. Real-time inference achieved 2–5 FPS depending on flock size and movement complexity.

Nevertheless, the dataset may introduce bias due to limited environmental diversity, camera angles, and lighting conditions. This constraint could affect the generalization of the model when applied to other farm settings or breeds. Future work should include a larger and more varied dataset and explore model compression techniques to minimize computational overhead. Nonetheless, this research establishes a robust foundation for behavior-based detection of potentially sick chickens using advanced deep learning approaches.

CHAPTER II

THEORETICAL FRAMEWORK OF THE STUDY

Review of Related Literature and Studies

This chapter presents a comprehensive review of existing literature and research relevant to this study. It examines key concepts, methodologies, and findings, establishing the theoretical and empirical foundation for our investigation. Synthesizing insights from diverse fields, this review highlights significant trends, gaps, and advancements in the area of automated chicken disease detection. By considering both local and international perspectives, we contextualize our research within the broader academic discourse, providing a well-rounded understanding of the subject. This synthesis not only supports our research objectives but also identifies opportunities for future exploration, contributing to a more robust and informed approach to the research problem.

Behaviors of Chicken

Detecting anomalies in a poultry house is crucial for maintaining optimal chicken health conditions, minimizing economic losses, and bolstering profitability (Ehsan & Mohtavipour, 2024). The early detection and warning of poultry infectious diseases play a critical role in the poultry breeding and production systems, improving animal welfare and reducing losses (He et. al, 2022). As a prey species, chickens often mask early illness symptoms, making manual detection difficult until diseases reach advanced stages (Sander, 2021; Tizard, 2008). The health of the chicken is reflected in their behaviors. Health issues of a chicken result in the development of behavioral changes, which will

further result to impaired body conditions and further health issues (Michel et. al., 2022).

The behavior of a healthy chicken shows when they care about their feathers; Preening, this is when the chicken uses her beak to take dabs of oil from the preen gland and strokes her feathers to rub the oil in (Gauthier & Ludlow, 2012). Dustbathing is also one of the behaviors of a chicken regarding their feathers, it is where the chicken flops around in the dirt for 20 minutes or more (Gauthier & Ludlow, 2012). The purpose of dustbathing is to remove stale liquids and ectoparasites from the chickens (van Liere, 1992; Martin and Mullens, 2012; Nicol, 2015). Another behavior is Foraging, this is when the chicken pecks the ground with speed and the rapid scratching movements of their feet (Nicol, 2015) and this also means that they are working for their food even when food is readily available (McCrea & Baker, 2022). Perching is where chickens perch during the day and sleep at night; they do this to monitor their environment and be protected from predators (Nicol, 2015). Locomotion activities of a chicken is where they play, walk, standing up and lying down, stretching the limbs.

Sparring is also included in the Locomotion Activities of a chicken, this is where they show adult aggression such as jumping, kicking and pecking, but it doesn't result in injuries (Baxter et. al., 2020). Aggression also shows a sign of healthy behavior to chicken, this is where the chicken intends to injure another chicken (University of Maryland Extension, 2021; Baxter et. al., 2020). This could also be asserted as a dominant behavior of a chicken where they fight with their flock to establish the social hierarchy (Jacob, 2021). Chickens will also demonstrate nesting and egg laying, and maternal habits. Hens will

seek out nesting sites and make nests prior to laying eggs, then sit on or incubate them until they hatch (Chaiseha and El Halawani, 2015).

When chickens are ill, their behaviors match. Any chicken that is excluded with the group or quiet in a corner, shows that there is something wrong (McNamara, 2023).

There is a certain pattern of behavior when an animal is said sick, the inactivity, loss of appetite and sleepiness are a programmed way of having the animal stop looking for food, or moving about and saving vital body resources for fighting the infection (Hart and Hart, 2019). When faced with heat stress, chickens tend to display restless walking behavior, but they also spread out their wings, laid down with their face down, and panting (Li et. al., 2015). When chickens, pants or they breathe faster than average it means anything but healthy (Jacob & Pescatore. 2013). On other occasions, chickens could be seen huddling to each other. But when they pile on top of each, this may lead to illness and fatalities (Ehsan & Mohtavipour, 2024). Chickens that express withdrawal, aggression, or changes in social hierarchy as indicators of health problems (Weary et. al., 2014). Chickens that are not fully healthy may show in their body. They may keep their eyes half-closed, droop their heads, or pull their heads into their shoulders, showing signs of fatigue and illness. As described in the MSD Veterinary Manual, these droopy eyes and lowered postures are common indicators of respiratory distress or general weakness among poultry.

Sick chickens could be seen as less active, less interested in their surroundings, and may isolate themselves from the flock (Matthijs et. al., 2017). They also display sedentary behavior and limited movement within the area

(Ehsan & Mohtavipour, 2024). The way chicken moves is how most identify the health of chicken, it was shown on a study the lethargy and decreased in activity, reduced movement and response to their environment, is also an indicator to the health of a chicken (Sander, 2021). Another study focuses on the abnormal walking behavior of a chicken, this is seen as unsteady gait of the chicken, this shows lameness distress in chickens. Caplen et. al. (2012) stated that specific lame broilers showed shorter strides or instability that is visible to the chicken's gait pattern. Chickens that express withdrawal, aggression, or changes in social hierarchy as indicators of health problems (Weary et. al., 2014).

Time-Based Behavioral Monitoring as an Early Indicator of Illness

Monitoring the behavior of chickens within a specific time frame plays a vital role in identifying early signs of illness, as behavioral deviations often manifest before visible symptoms appear. Rizwan et. al. (2024) explained that sudden drops in activity levels, clustering behaviors, or irregular movements among broilers can be detected in relatively short intervals through continuous computer vision monitoring. Their study demonstrated how short-term behavioral changes are sufficient to trigger early detection mechanisms, emphasizing that frequent and consistent observation is more valuable than occasional checks. Neethirajan et. al. (2022) reinforced this idea through their "ChickTrack" system, which quantifies movement patterns and identifies irregularities over predetermined monitoring periods. Their findings revealed that a 30- to 60-minute observation window is often enough to distinguish normal resting behavior from abnormal inactivity that may signal disease onset.

By focusing on a structured time frame, their approach minimized false alarms and improved the accuracy of behavioral anomaly detection.

Xing et. al. (2021) provided further support by demonstrating that relying on accumulated movement data over time, rather than single observations, leads to more reliable detection of sick or dead chickens. Their system used continuous monitoring to capture gradual changes in activity patterns, showing that abnormal behaviors are best identified when analyzed over longer intervals. Kim et. al. (2023) offered a particularly compelling contribution by proving that chickens exhibiting non-movement for more than 30 minutes were highly likely to develop sickness or die later on. These finding highlights that extended inactivity, when monitored consistently, can act as a strong predictive indicator of disease progression. Colles et. al. (2016) expanded on this time-based perspective by analyzing flock-level movement and found that changes in optical flow patterns could signal Campylobacter infection several days before it became clinically detectable. This demonstrates that behavioral monitoring over set intervals not only applies to individual chickens but can also be scaled to flock-level disease detection.

Moreover, Guo et. al. (2022) emphasized the importance of establishing baseline behavioral patterns for chickens at different ages to detect deviations effectively. By classifying various activities such as standing, walking, and feeding using deep learning models, their study provided reference points that can be monitored over defined periods to identify abnormal changes. Similarly, a review by Applied Sciences (2022) concluded that consistent behavioral observation over structured time intervals is one of the most practical and reliable early warning methods for disease detection in poultry farms. These

studies collectively build a strong case for using a monitoring window of 30 minutes to one hour as a standard practice in detecting early signs of illness. This time frame balances responsiveness and reliability, allowing researchers and farm operators to capture meaningful behavioral patterns without being misled by temporary, non-critical inactivity.

Challenges in Traditional Chicken Disease Detection

Traditional methods of detecting chicken diseases are time-consuming and labor-intensive, often relying on subjective visual observation of symptoms like lethargy, ruffled feathers, or changes in droppings. This makes accurate and timely diagnosis challenging, as diseases and viruses can spread rapidly within a flock confined to a single cage or land area (Triyanto et. al., 2023). The Philippine chicken industry is diverse, encompassing both commercial and backyard operations (Chang, 2007). This diversity presents unique challenges for disease management. Bejar et. al. (2012) highlighted several problems faced by native chicken raisers in the province of Samar, including increased disease incidence due to unpredictable climatic conditions, pilferage, limited feed supply, predation, and poor transportation infrastructure. These challenges, particularly the susceptibility to disease outbreaks, underscore the need for more efficient and objective disease detection methods.

These challenges are particularly pronounced in the Philippines, where poultry farms face significant challenges due to the late detection of diseases and disorders in chickens. This late detection is often exacerbated by a combination of physical and environmental factors, including overcrowding, poor biosecurity practices, and heat stress. Overcrowding, a major contributing

factor, creates chronic stress in chickens due to limited space and social disruption, where chickens exposed to long-term stress experience reduced welfare and immunosuppression, making them more susceptible to disease (Gomes et. al., 2013). Heat stress, another significant stressor, further compromises chicken health by negatively impacting productivity and immune response. This can lead to reduced growth rates, decreased egg production, and diminished poultry and egg quality and safety (Lara & Rostagno, 2013). Despite these challenges, flocks are often only classified as 'healthy' if they perform according to their genetic potential and are considered free from clinical disease (Liebhart et. al., 2023). This definition of health can be dangerously misleading, as it overlooks the prevalence of subclinical infections and early-stage diseases. These hidden threats can spread rapidly within a flock, causing significant damage before outward symptoms become apparent, hindering effective intervention and potentially leading to widespread losses.

To address these challenges and ensure the continued growth of the Philippine chicken meat industry, innovative technologies for disease detection are crucial. Chicken meat has been a major product in the market of the Philippines, where a 7.67% increase or 506 277.33 metric tons are produced in the 1st quarter of 2024 compared to the same period in 2023 (Serd, 2024). The rise in production led to lower farmgate and retail prices of chicken meat. While this increased production is positive for the market, it also presents heightened challenges for disease management. Higher densities of chickens in farms, driven by the demand for increased production, can create environments where diseases spread more easily and rapidly. Therefore, to minimize losses due to disease and mortality, the use of technologies for symptom detection can

monitor the health status of chickens in a continuous, noninvasive, and automated way, and potentially assist in the early warning decision-making process (He et. al., 2022).

Deep Learning-Based Object Detection and Tracking in the Poultry Industry

Researchers can now identify and track individual chickens in real-time better than before. This improvement comes from using deep learning algorithms in poultry monitoring systems. Early studies looked into using computer vision to count and identify chickens in different conditions. Khairunissa et al. (2020) achieved a precision of 60.4% using the Multi-Object Tracking and Single Shot Multi-Box Detector (SSD) algorithm at a frame rate of 15 frames per second. The way that intersecting objects move, which allows targets to exchange identities, was not considered in their study. This led to less consistent tracking. Similarly, Geffen et. al. (2020) designed detection and tracking algorithms for hens in cages using Faster R-CNN with multi-angular view-shifted images. After initial detection, hens' relative positions along the feeder were tracked and updated using a sequential tracking algorithm. Their model demonstrated the feasibility of deep learning for accurate flock-size estimation in commercial settings, receiving an accuracy of 89.6% at the cage level with a mean absolute error of 2.5 hens per cage when validated against human-counted "gold-standard" observations.

The accuracy of detection and identity preservation was further enhanced by developments in tracking the behavior of poultry. Fang et. al. (2020) used a deep-regression network to track individual birds dynamically

and carried out a comparative analysis of poultry target-tracking algorithms. Their model highlighted the shift from static object detection to spatial-temporal tracking frameworks that can analyze movement trajectories, emphasizing temporal continuity of motion. Recently, Cruz et. al. (2025) presented the Automated Counting and Monitoring System for Poultry Tracking (ACMSPT), which implemented an edge computing solution based on YOLOv10 in real broiler sheds. The system took a big step toward practical AI solutions for poultry management. It achieved 93.1% precision and 93.0% recall, with inference latency under 200 milliseconds. This performance was based on over 1,300 high-resolution images collected during growth phases.

Fang et al. (2020) evaluated multiple poultry methods for tracking using a deep regression network. The goal was to improve the tracking of individual birds in huge flocks. There is enormous space for improvement in the system's ability to retain identities and handle occlusions. However, the study's mixed-tracking performance evaluation (MTPE) score of 0.730, or 73%, indicates a modest success rate for monitoring birds over time. Regression-based tracking proved well in poultry situations. Nonetheless, the authors raised important concerns, such as the challenges of monitoring in dynamic, real-world business contexts. These issues include dense groups of birds, frequent identification swaps as birds' cross routes, and constraints caused by static backdrops.

A machine vision system detected and counted laying hens in battery cages using a CNN detection algorithm called Faster R-CNN, along with a tracking component. This method aimed at counting the flock as a whole, rather than focusing on individual movements (Geffen et al., 2020). With an approximate validation dataset, the system achieved a mean absolute error

(MAE) of 2.5 hens per cage and 89.6% accuracy at the cage level from 2,000 images. Even with these strong results, the study found some issues. Counts were overestimated in cages with 18 to 24 hens and underestimated in cages with 25 to 30 hens. The system used a multi-angular view shift and a moving camera arm, which may not work well with static camera setups or tracking the behavior of individual birds over time.

Despite these advances, earlier systems still have limitations. Occlusion, mutual obstruction among birds, and difficulty maintaining stable identities during long-term tracking remain challenges. To solve these issues, we need to combine strong detection, tracking, and time analysis models. These should work well in dense and changing flock environments.

Building on this gap, the current study introduces an enhanced deep learning framework that integrates YOLOv11, DeepSORT, and LSTM-RNN to improve real-time object detection, multi-object tracking, and behavior-based health assessment in poultry monitoring. YOLOv11 provides high-precision detection through anchor-free mechanisms and transformer-based attention, enabling reliable identification of chickens even in crowded and visually complex farm environments. DeepSORT strengthens system stability by using Kalman Filter motion prediction and appearance-based feature matching to maintain consistent identities across frames, ensuring accurate tracking under high-density conditions. The LSTM-RNN module then analyzes temporal movement sequences derived from DeepSORT to detect subtle behavioral anomalies—such as prolonged inactivity or irregular motion patterns—that may indicate early signs of illness. By combining these components into a unified pipeline, the framework achieves stable, identity-preserving detection and

effective behavior classification, ultimately enhancing automated health monitoring and supporting early intervention in poultry production settings.

You Only Look Once (YOLO) Generations Application

YOLO (You Only Look Once) is a revolutionary object detection algorithm that has gained widespread adoption across various domains. Originally introduced by Redmon et. al. (2015), YOLO frames object detection as a regression problem, enabling real-time processing at up to 155 frames per second. Its unified architecture allows end-to-end optimization and learns general object representations. YOLO has found extensive applications in medical imaging (Ragab et. al., 2024) and agriculture (Badgujar et. al., 2024), outperforming existing methods in tasks such as lesion detection, retinal abnormality identification, and agricultural object recognition.

Despite its advantages, YOLO faces challenges including the need for well-balanced datasets and high computational demands (Ragab et. al., 2024). Ongoing research has led to improved versions like YOLOv3, which addresses some limitations of the original algorithm (Sharma et. al., 2020). From YOLOv1 to YOLOv8, these models have demonstrated advancements in accuracy and speed (Ruta Mulajkar & Sanjay Yede, 2024). Subsequent versions incorporated enhancements such as skip connections, feature pyramid networks, and anchor boxes to boost performance (Aabidah Nazir & M. Wani, 2023). From the stable YOLOv5, it introduces innovations like the CSPDarknet backbone and Mosaic Augmentation, balancing speed and accuracy (Hussain, 2024). ChickTrack, a deep learning model based on YOLOv5, demonstrated enhanced tracking precision for detecting and counting chickens in complex

environments (Neethirajan, 2021). While highly performant, YOLOv5's accuracy could be slightly lower than some subsequent models on certain benchmarks. YOLOv6 focused on industrial applications, emphasizing a strong balance between speed and accuracy with an efficient reparameterization backbone. More recent iterations like YOLOv6 (Li et. al., 2022), YOLOv7 (Wang et. al., 2022), YOLOv8 (Ultralytics, 2023), YOLOv9 (Wang et. al., 2023), YOLOv10 (Li et. al., 2024), and YOLO11 (Ultralytics, 2024) have introduced further enhancements, including anchor-free detection, improved feature fusion techniques, and optimized network designs, pushing the boundaries of real-time object detection accuracy and efficiency while addressing limitations in handling small objects, occlusions, and computational costs (arXiv, 2024; Ultralytics Blog, 2025). YOLO's impact on object detection continues to grow, shaping the future of various technological applications.

YOLO in the Chicken Industry

Through the investigation of subtle behavioral indicators, this study investigates the use of the You Only Look Once (YOLO) object detection algorithm as a basis for automated chicken disease detection. As a cutting-edge detection model, YOLO provides a robust speed-accuracy balance (Terven et al., 2023), which makes it ideal for real-time health monitoring tasks where quick decisions are crucial. The growing demand for scalable digital monitoring solutions in poultry farms, especially those with limited labor resources, is in line with its capacity to process video frames efficiently. According to recent studies, YOLO has the potential to speed up disease detection workflows and provide a more proactive approach to managing the health of poultry (Yang et al., 2024). This is especially crucial because chicken

diseases result in large financial losses, which are exacerbated in backyard and free-range farming systems where it is more difficult to maintain controlled monitoring. High infectious disease mortality rates threaten food security and the livelihoods of smallholder farmers, particularly in low- and middle-income countries, in addition to decreasing farm productivity (Muñoz-Gomez et al., 2023). By leveraging YOLO's superior capabilities, this project seeks to contribute to more efficient, accessible, and data-driven methods for early health issue detection in chicken production.

However, significant challenges remain, particularly in free-range poultry farming. Accurate chicken detection is often hampered by the birds' small size due to distance from the camera and frequent mutual occlusion (chickens clustering together), which complicates YOLO's detection capabilities (Tong et. al., 2023). Beyond these detection challenges, the poultry industry faces substantial hurdles in maintaining flock health and welfare, especially in large-scale operations. Early detection of sick or deceased birds is crucial for effective management and disease control (Syafaah et. al., 2023; Elmessery et. al., 2023). Changes in chicken behavior can provide valuable insights into potential health issues, making behavioral analysis a key area of focus.

While YOLO has shown remarkable performance in real-time object detection, it may become less accurate when detecting small objects, which is a common problem in poultry environments where partially occluded chickens or chicks appear in a range of sizes. Recent research has investigated combining an autoencoder with YOLO to overcome this restriction. This will allow for the classification and detection of lesions and disease-related abnormalities in a variety of chicken breeds, facilitating the early detection of

potentially infected chickens in confined populations (Nguyen et al., 2023). Furthermore, it has been demonstrated that using Soft Non-Maximum Suppression (Soft-NMS) lessens the suppression of overlapping bounding boxes, enabling the model to maintain more reliable detections even in crowded scenes or blurry frames (Wati & Roestam, 2023). This allows the algorithm to retain more potential detections, increasing the chances of correctly identifying individual chickens in crowded scenes, even with partial occlusion, and ultimately improving the accuracy of behavioral analysis. The ongoing development of YOLO has led to even more advanced versions, continuously refining the balance between speed and accuracy to better suit diverse application needs.

YOLOv4 with Kalman Filter and YOLOv11 with DeepSORT in Object Detection

The YOLO (You Only Look Once) series has gained prominence in this field, with YOLOv4 becoming a widely adopted model due to its balance of speed and usability. With YOLOv4, Systems have demonstrated high accuracy in detecting and tracking broiler behaviors, including feeding and aggression (Wahjuni et. al., 2024; Triyanto et. al., 2023).

Integration of the Kalman Filter into this version improved the monitoring and management system inside the farm. The Kalman filter, developed by R.E. Kalman in 1960, is a recursive state estimator for linear dynamic systems that provides optimal estimates from noisy measurements (Andrade-Cetto, 2002; Snyder, 2014). YOLOv4 with DeepSORT and Kalman filters for improved multi-object tracking, demonstrating potential applications in various fields

including animal management (Kumar et. al., 2021). A novel real-time framework uses YOLOv4 for chicken detection and a fast tracker with a Kalman Filter to analyze individual behaviors like inactivity and huddling in cage-free poultry houses for timely anomaly detection and improved productivity (Ehsan & Mohtavipour, 2024).

Despite their advancement, YOLOv4 with an integrated Kalman Filter limits their criteria in terms of the non-linear nature of animal motion. YOLOv4 is a popular object detection algorithm, but it faces challenges in accurately detecting small objects and adapting to complex environments. Also, limitations persist in real-world scenarios with uncertain environments and limited a priori information.

For instance, ongoing research aims to further strengthen detection capabilities. YOLOv11, the latest advancement, incorporates architectural refinements, such as optimized network structures and anchor-free detection, to improve both accuracy and efficiency. Different YOLOv11 variants (n, s, m, i, x) offer trade-offs between speed and accuracy, with smaller models achieving faster inference times and larger models excelling in detection accuracy (Kishor, 2024). Studies indicate that YOLOv11 demonstrates superior accuracy while maintaining competitive speed, suggesting its potential to propel the precision and reliability of automated systems in poultry farming (Topview.ai, n.d.).

Integrating YOLO with DeepSORT improves multi-object tracking, achieving up to 94% tracking accuracy in poultry environments by maintaining identity consistency across frames (Yang et. al., 2024). For multi-object tracking

of chicks, a modified tracktor approach using DeepSORT and a multi-scale re-identification model has been proposed to address challenges such as animal similarity and sudden shape changes (Ali et. al., 2022). With the integration of DeepSORT to YOLOv11, advancement in multi-object detection with balance accuracy and performance will be obtained to provide a reliable yet significant result as the algorithm provides unique IDs per object to learn their behavioral patterns.

Long Short-Term Memory Recurrent Neural Networks (LSTM-RNNs) in Chicken Behavior Analysis

Long Short-Term Memory Recurrent Neural Networks (LSTM-RNNs) have emerged as a powerful tool for analyzing sequential data across various domains, and their utility is increasingly being recognized in the field of poultry farming, particularly for understanding and predicting chicken behavior. LSTM-RNNs excel at capturing long-term dependencies in temporal sequences (Staudemeyer & Morris, 2019). One of the primary applications of LSTM-RNNs in this domain is the automated classification of various chicken behaviors. By analyzing sequential data obtained from video recordings or sensor data, LSTM models can be trained to recognize and categorize distinct behavioral patterns. Xie, B. & Chung, L. Chang (2022) demonstrated the high accuracy of LSTM-RNNs in recognizing broiler chicken behaviors by analyzing skeletal data extracted from object detection in video. LSTM-based models have been developed to quantify and predict behavior patterns in laying hens, utilizing time series data (Jiang Wuhao et. al., 2020). These studies demonstrate the increasing contribution of LSTM-RNNs to automated behavioral analysis,

providing insightful information that facilitates data-driven poultry management and more accurate health monitoring.

DeepSORT

The use of multi-object tracking (MOT) algorithms in poultry farming has increased in recent years as researchers and farm operators seek automated solutions for monitoring chicken behavior and movement. One of the most widely used tracking frameworks is DeepSORT, an improved version of Simple Online and Realtime Tracker (SORT) that incorporates deep learning-based feature embeddings to improve object re-identification (Wojke et. al., 2017). Unlike traditional trackers that rely only on motion prediction, DeepSORT integrates appearance features to ensure that objects remain correctly identified across multiple frames. This is particularly beneficial in commercial poultry farms, where chickens overlap, move in groups, and share similar appearances, making it difficult to track them using motion-based tracking alone (Bochinski et. al., 2017). Studies have shown that using appearance-based embeddings significantly reduces tracking errors, ensuring that chickens retain a consistent identity even when moving in crowded environments (Luo et. al., 2019).

A key feature of DeepSORT is the Kalman filter, which predicts an object's movement based on previous trajectory data. This predictive capability helps maintain tracking accuracy even when objects temporarily disappear due to occlusion or motion blur (Kalman, 1960). Research has demonstrated that combining Kalman filtering with deep learning-based embeddings significantly strengthens tracking performance, especially in high-density poultry

environments where chickens frequently overlap or become momentarily hidden behind obstacles (Djuric et. al., 2003; Luo et. al., 2019). However, despite these improvements, DeepSORT still faces computational challenges when tracking fast-moving poultry, as rapid changes in movement can result in identity switching or tracking failures (Zhang et. al., 2021). To mitigate this, researchers have suggested adjusting the update frequency of DeepSORT or using higher frame-rate cameras to improve tracking precision (Chu et. al., 2017).

One of the biggest challenges in poultry tracking is occlusion, which occurs when chickens move behind feeders, water dispensers, or other obstacles on the farm. When occlusion happens, the tracking system may lose track of an individual chicken, leading to identity confusion or incorrect re-assignment (Neethirajan, 2021). Additionally, chickens have similar feather colors and patterns, making it difficult for tracking algorithms to distinguish between individuals in group settings (Sun et. al., 2020). This issue is further compounded when farm conditions include poor lighting or background clutter, which can lower detection accuracy (He et. al., 2022). Several studies have proposed integrating multi-sensor data, such as depth cameras and infrared imaging, to reduce these tracking errors (Liu et. al., 2023; Zhang et. al., 2021).

DeepSORT has been applied in various real-world scenarios, such as pedestrian tracking, vehicle tracking, and surveillance systems. However, its application in poultry tracking is still being optimized, with researchers focusing on improving efficiency in high-density environments (Aharon et. al., 2022). Some studies have suggested combining DeepSORT with Re-Identification (ReID) networks, which have been shown to improve long-term object tracking

in crowded settings (Chu et. al., 2017; Liu et. al., 2023). Additionally, new tracking frameworks like Observation-Centric SORT have been developed to optmize object association methods, reducing identity switching errors and improving tracking stability (Cao et. al., 2023). These improvements ensure that automated poultry tracking systems provide accurate and reliable monitoring of individual chickens, allowing for detailed movement analysis, feeding behavior tracking, and early detection of health issues in large-scale poultry operations.

YOLO and DeepSORT

The integration of YOLO (You Only Look Once) with DeepSORT has further improved poultry tracking by combining fast object detection with robust tracking capabilities. YOLO is a high-speed object detection model that processes images in a single pass, making it ideal for real-time tracking applications (Redmon et. al., 2016). The latest versions, such as YOLOv8, incorporate Feature Pyramid Networks (FPN) and Path Aggregation Networks (PAN) to improve detection across various object sizes and scales (Solawetz & Francesco, 2023). This is particularly useful in poultry farming, where chickens may appear at different distances or angles depending on camera placement (Zhang et. al., 2021). Studies have demonstrated that combining YOLO with Kalman Filter allows for more accurate and stable tracking, as YOLO provides precise object detections, while Kalman Filter ensures that each object retains its identity across frames (Neethirajan, 2021).

One of the biggest advantages of using YOLO with Kalman Filter is that it enables both individual and flock-level tracking, allowing farm operators to monitor chicken movement, detect unusual behavior, and analyze social

interactions (Neethirajan, 2021). In the ChickTrack system, YOLOv5 was used to detect chickens in complex farm environments, while Kalman Filter maintained their identities across frames, even when chickens temporarily disappeared due to occlusion. This tracking model successfully measured walking speed, feeding intervals, and movement patterns, providing valuable insights into chicken health and welfare (Sun et. al., 2020; Neethirajan, 2021). However, real-world implementation still faces challenges in low-light environments and in settings with frequent occlusion. Some researchers suggest integrating LiDAR, thermal imaging, or 3D depth cameras to further boost detection accuracy in challenging conditions (Zhang et. al., 2021; He et. al., 2022).

The balance between computational speed and accuracy is an important factor in selecting a tracking algorithm. YOLO is known for its fast-processing speed, with some versions achieving real-time detection at 155 frames per second (fps), making it one of the fastest object detection models available (Redmon et. al., 2016). In contrast, Mask R-CNN, another popular object detection model, is more accurate but significantly slower, often running at 5–10 fps, making it impractical for real-time poultry tracking (He et. al., 2017). Studies have shown that Mask R-CNN performs better in complex environments with occlusions, but YOLO remains the preferred choice for speed-dependent applications such as livestock monitoring (Solawetz & Francesco, 2023; Yadav et. al., 2023).

Tracking accuracy in large-scale poultry farms remains a challenge due to high-density tracking requirements. Research indicates that replacing traditional tracking models with optimized DeepSORT-based methods can

increase tracking accuracy by up to 18.9%, reducing identity switches and misclassification errors (Yadav et. al., 2023). Other studies have highlighted that multi-camera tracking frameworks could further improve accuracy, ensuring that chickens remain identified even when they move between different farm areas (Liu et. al., 2023). These advancements will enable automated poultry farm management, reduce manual labor costs while improve overall efficiency (Cao et. al., 2023).

The future of AI-driven livestock monitoring will depend on further improving tracking efficiency and computational scalability. As technology advances, lightweight AI models, cloud-based processing, and hardware acceleration (e.g., edge computing with GPUs) may enable real-time, large-scale poultry tracking solutions at lower computational costs (He et. al., 2022). By integrating fast object detection models like YOLO with deep tracking frameworks like DeepSORT, poultry farms can adopt fully automated monitoring systems, ensuring better productivity, improved welfare, and early disease detection in poultry management (Neethirajan, 2021; Yadav et. al., 2023).

Anomaly Detection

The integration of anomaly detection in automated poultry monitoring systems is strongly justified by both operational needs and technological advantages. In large-scale poultry farms, continuously monitoring hundreds or even thousands of chickens through manual observation are not only labor-intensive but also prone to error due to human fatigue and the limitations of visual inspection (Wang et. al., 2022). Subtle behavioral changes that may

indicate early stages of illness—such as reduced movement, irregular clustering, or delayed reactions—often occur gradually and can easily go unnoticed during routine farm inspections. Automated anomaly detection systems address these challenges by continuously processing streams of video or sensor data, enabling the identification of unusual behavioral patterns in real time (Park et. al., 2020). These systems are designed to learn a model of “normal” activity patterns using techniques such as LSTM-based predictive models, autoencoders, or memory-augmented networks. Once this baseline is established, any significant deviation from expected behavior can be flagged as an anomaly, allowing for earlier detection of health or environmental issues compared to manual observation (Gong et. al., 2019; Medel et. al., 2016).

Anomaly detection also provides a quantitative and standardized framework for identifying irregularities, which reduces subjective interpretation and inconsistencies that can arise from human judgment (Chandola et. al., 2009). For instance, by statistically modeling prediction errors or reconstruction errors from neural networks, thresholds can be determined based on either sigma rules or percentile-based methods, ensuring that alerts are triggered based on objective metrics rather than personal assessment. This standardization is particularly valuable in commercial settings where consistent and reliable monitoring is crucial for managing disease outbreaks. Poultry diseases can spread rapidly in densely populated environments, and even a short delay in detection can lead to widespread infection and economic losses. By detecting anomalies early—often before visible symptoms appear—farm managers can isolate affected animals or adjust environmental conditions to

prevent further spread, improving both animal welfare and operational efficiency (Wang et. al., 2022).

Furthermore, integrating anomaly detection with object detection and tracking models, such as YOLO and Deep SORT, enhances the system's ability to not only detect individual chickens but also track their behavior over time, producing richer data for analysis. This hybrid approach allows for high-precision detection of deviations in movement patterns, ultimately leading to a smarter, data-driven decision-making process in farm management. In this context, anomaly detection is not merely a complementary tool but a critical component in building intelligent, automated systems that can operate at the scale and speed required in modern poultry farming.

Literature Matrix

Table 1. Matrix of Review of Related Literature

AUTHOR(S)	YEAR	TITLE	ALGORITHM / MODEL	FINDINGS
Ehsan, T. Z., & Mohtavipour, S. M.	2024	Broiler-Net: A Deep Convolutional Framework for Broiler Behavior Analysis in Poultry Houses	YOLOv4 and Kalman Filter	The Broiler-Net framework achieved **0.90 mAP**, demonstrating high accuracy in detecting huddling (P = 0.93, R = 0.88, F1 = 0.85) and inactive chickens (P = 0.92, R = 0.90, F1 = 0.91), indicating strong potential for early sickness detection in poultry.
Khanam, R., & Hussain, M.	2024	What is YOLOv5: A deep look into the internal features of the popular object detector	YOLOv5	YOLOv5 advances object detection with its CSP backbone and PA-Net neck, delivering efficient, accurate performance across models optimized for diverse hardware, all streamlined through its PyTorch implementation.

Yang, X., Bist, R., Paneru, B., & Chai, L.	2024	Monitoring activity index and behaviors of cage-free hens with advanced deep learning technologies	Object Detection (YOLO, Enhanced R-CNN, DETR), Object Tracking (DeepSORT, ByteTrack), and Behavior Recognition (2D and 3D CNN-Based Approaches, RNN and Transform Networks)	The YOLOv8 and DeepSORT combination achieved a 94% MOTA, effectively detecting abnormal behaviors like smothering and piling, and quantifying flock activity into low, medium, and high levels to assess footpad health.
Mishra, A., Mane, N., Pagare, R., Mishra, A., Dixit, A., Mishra, S., & Agrawal, A.	2022	An improved object tracking and estimating using Yolov5 model based on adaptive Kalman filter and efficient inference performance on surveillance	Enhanced YOLOv5	An improved object tracking and classification method using YOLOv5 and an adaptive Kalman filter is proposed, achieving 97.6% accuracy on a surveillance database by optimizing processor selection and parallel distribution of features.
Xie, B. X., & Chang, C. L.	2022	Behavior Recognition of a Broiler Chicken using Long Short-Term Memory with Convolution Neural Networks.	Long Short-Term Memory (LSTM), Convolution Neural Networks (CNN)	The chicken behavior recognition scheme has been validated in an outdoor environment. The average precision, average recall and F1-score obtained by the proposed scheme were 82%, 81% and 81%, respectively.
Neethirajan, S.	2021	ChickTrack - A Quantitative Tracking Tool for Measuring Chicken Activity. TechRxiv.	Object Detection, Object Tracking Algorithm	The YOLOv5 model achieved precise real-time tracking of multiple chickens using a Kalman filter, accurately detecting and counting them across video frames despite background interference, demonstrating strong performance for on-farm applications.
Jiang, W., Wang, K., Lv, Y., Guo, J., Ni, Z., & Ni, Y.	2019	Time series based behavior pattern quantification analysis and prediction — A study on animal behavior.	Long Short-Term Memory (LSTM),	The proposed LSTM-based behavior recognition scheme achieved strong performance with an average precision of 82%, average recall of 81%, and an F1-score of 81%, outperforming an MLP-based approach using the YoLov4 model in the study.

Bochinski, E., Eiselein, V., & Sikora, T.	2017	High-Speed Tracking-by-Detection without Using Image Information. In 2017 14th IEEE International Conference on Advanced Video and Signal Based Surveillance	Kalman Filter specifically a Constant Velocity Kalman Filter	The proposed IOU tracker outperforms state-of-the-art methods on the DETRAC dataset in terms of accuracy, precision, and tracking consistency, while achieving over 100,000 frames per second with R-CNN detections, though its performance heavily depends on the quality of the object detections.
Wojke, N., Bewley, A., & Paulus, D.	2017	DeepSORT: Simple Online and Realtime Tracking with a Deep Association Metric. arXiv preprint	DeepSORT and incorporating Deep Learning-based Re-ID network	The proposed method reduced identity switches by approximately 45% compared to the original SORT algorithm, with a slight increase in track fragmentation, but a significant increase in mostly tracked objects and a decrease in mostly lost objects. The integration of appearance information enabled the method to successfully maintain object identities during longer periods of occlusion.

Synthesis and Relevance of the Study

A growing body of work validates the two-stage strategy adopted in this study: fast detection followed by identity-preserving tracking and temporal modeling, laying a strong foundation for behavior-based disease detection. Foundational object tracking work by Bochinski et. al. (2017) introduced the IOU Tracker using a Constant Velocity Kalman Filter, achieving high-speed performance on DETRAC data. However, its dependency on detection quality highlights the need for robust object detectors, which directly motivates the use of YOLOv11 in this research to ensure consistent and accurate detections that robust tracking reliability.

YOLO-based models remain central to poultry behavior analysis. Khanam and Hussain (2024) and Mishra et. al. (2022) emphasized YOLOv5's architectural efficiency and its adaptability across platforms, findings that

informed the adoption of YOLOv11 for its fortified feature extraction and transformer-based backbone. Mishra et. al. further demonstrated 94.6% accuracy through an adaptive Kalman filter, guiding this study's parameter tuning for motion prediction and covariance adjustment. Likewise, Neethirajan (2021) reinforced YOLOv5's reliability in real farm settings, supporting the use of data augmentation and soft-NMS to modify detection under varied lighting and background conditions.

Recent efforts have integrated behavior recognition into these pipelines. Jiang et. al. (2019) and Xie and Chang (2022) validated the use of LSTM networks for time-series-based animal behavior prediction, achieving F1-scores around 81%, which guided the selection of sequence length and hidden layer size to effectively capture short-term behavioral dynamics. Yang et. al. (2024) extended this by incorporating YOLO, DeepSORT, and CNN/RNN hybrids to evaluate cage-free hen behavior, attaining 94% tracking accuracy and detecting critical abnormal behaviors like smothering. Their results directly informed our decision to pair DeepSORT with YOLOv11, and to optimize DeepSORT's cosine distance threshold to balance identity retention and real-time computation.

Zarrat and Mohtavipour (2024) introduced Broiler-Net, using YOLOv4 and Kalman Filters to detect sickness-related behaviors such as inactivity and huddling with F1-scores exceeding 0.85. Similarly, DeepSORT, as proposed by Wojke et. al. (2017), improved long-term identity tracking by integrating a deep appearance descriptor, reducing ID switches by 45%. This approach directly shaped our tracker configuration, where appearance embeddings are periodically updated to maintain stable IDs during occlusions.

In light of these studies, our research builds upon YOLOv11's advancements in detection by integrating LSTM for behavior analysis and DeepSORT for robust tracking, aiming to maximize the real-time identification of potential sickness in chickens through subtle behavior cues captured in video sequences. By aligning model architecture and hyperparameters with proven strategies from recent literature, this study establishes a behavior-based detection framework that is both theoretically grounded and empirically validated. The selection of key hyperparameters—such as confidence, IoU, and sequence length—was directly informed by prior works, ensuring that the proposed model is not only empirically grounded but also optimized for real-time poultry monitoring.

Table 2. Comparative Summary of Detection and Behavior Analysis Models

Model / Study	Application / Dataset	Accuracy / mAP (%)	Strengths	Limitations
Mishra et. al. (2022) – YOLOv5 + Kalman Filter	Poultry surveillance	94.6	Adaptive tracking and real-time response	Limited temporal context; no behavior classification
Yang et. al. (2024) – YOLO + DeepSORT + RNN	Cage-free hen behavior monitoring	94.0	Integrated detection and tracking with behavior recognition	Difficulty detecting small-scale motion anomalies
Zarrat & Mohtavipour (2024) – Broiler-Net (YOLOv4 + Kalman Filter)	Sickness behavior detection	90.0	Effective in detecting inactivity and huddling	Limited generalization to large flocks
LSTM-RNN (Proposed)	Behavior classification for sickness detection	89.09 (Accuracy)	Effective temporal analysis; reliable anomaly reconstruction	Requires large datasets for optimal generalization

CONCEPTUAL FRAMEWORK




Figure 1. Conceptual Framework of the YOLOv11-DeepSORT-LSTM-RNN Framework

The conceptual framework of this study outlines a comprehensive pipeline for detecting potentially sick chicken based on behavioral analysis using computer vision and deep learning techniques. The process is structured into four distinct stages: data collection and preprocessing, tracking and feature extraction, behavior analysis, and detecting potentially sick chickens.

The framework begins with the Image Input phase; video data of broiler chickens are gathered from poultry environments and prepared for model training. The raw footage is then meticulously preprocessed by annotating each chicken with bounding boxes to label individual chickens, standardizing the data, and applying augmentation techniques such as flipping, cropping, and brightness adjustment to enhance the robustness and generalization of the detection model. These prepared images are then used to train the YOLOv11 model, a cutting-edge object detection algorithm selected for its speed and

accuracy in identifying and localizing each chicken within the video frames. The output of this model is a set of bounding boxes that precisely locate each chicken in an image.

The framework progresses to the tracking and feature extraction phase, which begins with the application of the DeepSORT tracking algorithm. DeepSORT is employed to assign unique IDs to each detected chicken, enabling consistent tracking across frames. This tracking facilitates the extraction of behavioral features, including posture, movement, and speed, for each chicken over time. These extracted features serve as the input for the LSTM (Long Short-Term Memory) neural network, a specialized form of Recurrent Neural Network (RNN) designed for temporal data. The LSTM analyzes sequences of movements to identify behavioral patterns and detect anomalies. This analysis constitutes the Behavior Analysis Layer, which is critical for understanding long-term behavior and recognizing signs of distress or illness.

The final component of the framework is potentially sick detection. The behavioral patterns identified by the LSTM are further analyzed through a classification module to determine the health condition of each chicken. Based on their behavior, chickens are categorized as either “Normal” or “Potentially Sick”. This classification provides serves as the final output, providing early, proactive detection of potentially sick chicken based on their anomalous behavior. Ultimately, the success of the proposed pipeline is to facilitate rapid intervention and significantly streamline flock health management by identifying at-risk individuals before a disease can have a significant impact on the entire poultry environment.

CHAPTER III

METHODOLOGY

Study Area

The study was conducted at Perello's Poultry Farm located along Lumampong Balagbag Road, Barangay Indang, 4122 Cavite, Philippines. This poultry farm operates on a commercial scale and maintains approximately 6,000 broiler chickens per production cycle. It was selected as the primary site for data collection due to its consistent poultry management practices and the availability of a large sample population, which is ideal for behavioral observation and analysis.

Data used in this study were collected through images captured using an installed CCTV camera in the poultry farm. These images serve as the primary dataset for training the model aimed at detecting potentially diseased chickens based on inactivity and irregular behavior patterns. The study does not focus on diagnosing specific diseases, but rather on identifying chickens that may exhibit signs of illness by analyzing behavioral cues, through the use of image-based datasets and artificial intelligence techniques.

Perello's Poultry Farm provides a practical environment for applying object detection and tracking algorithms. Given the naturally occurring challenges in such settings, including frequent occlusions due to the high density of chickens, the study also incorporates a tracking system designed to address occlusion issues. This elevates the reliability of behavioral assessments even in complex visual scenarios.

The selected study area not only supports the development and testing of the model but also represents typical conditions found in commercial poultry operations. Insights and outcomes derived from this location may contribute to the implementation of technology-based health monitoring systems in similar settings, promoting early identification of potentially diseased chickens and supporting better farm management decisions.




Figure 2. Geographical Map Showing the Location of the Poultry Farm

MATERIALS

The researchers used the following sets of materials and sources to conduct the development and evaluation of the chicken disease detection system based on behavioral analysis.

Software

This study utilized a variety of software tools for data processing, annotation, model training, tracking, and behavioral analysis. These include

integrated development environments, cloud-based platforms, and specialized libraries for machine learning and computer vision.

Google Colaboratory (Colab)

Colaboratory, or Colab, is a cloud-based platform provided by Google that enables users to execute Python code in an interactive Jupyter Notebook environment with access to GPU acceleration. In this study, Colab served as the main environment for training the object detection model. It was used to implement and train the YOLOv11s model, manage datasets from Roboflow, and perform model evaluation. Colab's cloud-based resources simplified model experimentation, especially for training with GPU-intensive tasks such as object detection.

EZGif

A free, web-based tool used for converting video files into image sequences in JPG format. The tool provides a straightforward and efficient way to transform videos into frame-by-frame images without requiring advanced software installation, making it suitable for preprocessing visual data in research workflows.

Online Converter – Video to JPEG

This online converter was utilized to extract still image frames from video files. It supports multiple media formats and enables the conversion of video sequences into individual JPEG images. The tool ensured efficient frame extraction while maintaining image quality and consistency, which are essential for reliable computer vision analysis.

Roboflow

Roboflow is an online platform used for image dataset management. It was used in this research for annotating the images, applying data augmentation, and exporting the dataset into YOLOv11-compatible format. Roboflow's preprocessing tools, such as image resizing, noise reduction, and brightness adjustments, helped prepare a robust dataset for training.

Visual Studio Code

Visual Studio Code (VS Code) was used as the local development environment for scripting, model integration, and visualization testing. VS Code enabled smooth code integration, tracking, and post-processing of model outputs. It was also used to run custom tracking logic using DeepSORT and future modules for behavioral classification.

Ultralytics YOLOv11s

YOLOv11s is a lightweight object detection model developed by Ultralytics. It was used for real-time chicken detection in video frames. The model uses a CNN-based architecture with custom modules including C3k2, SPPF, and C2PSA blocks. The backbone of YOLOv11s consists of convolutional layers designed for efficient feature extraction, allowing it to detect chickens quickly and accurately even on lower-resource environments.

DeepSORT

DeepSORT is a tracking algorithm that uses Kalman filtering and deep appearance descriptors to assign consistent IDs to detected objects across frames. In this study, DeepSORT was integrated with YOLOv11s to track

individual chickens over time. It uses a CNN-based Re-identification (ReID) network to extract features from each chicken's appearance, enabling accurate and consistent multi-object tracking.

Long Short-Term Memory – Recurrent Neural Network (LSTM-RNN)

A type of deep learning architecture designed to analyze and learn from sequential or time-dependent data. This model is capable of capturing both short-term and long-term dependencies within a sequence, making it well-suited for applications that require understanding temporal patterns or contextual relationships over time. It offers a robust solution for handling complex temporal data by effectively learning patterns that unfold over time.

Python Libraries

A variety of Python libraries were employed in the development of the chicken detection and tracking system, each serving a distinct role in the process. These libraries facilitated everything from numerical operations to computer vision tasks and web integration.

NumPy

NumPy is a fundamental library for numerical computing in Python. It provides support for large, multi-dimensional arrays and matrices, along with a wide range of mathematical functions to operate on these arrays efficiently. In this study, NumPy was used for handling array operations required during the preprocessing of video frames and detection results. It also supported mathematical computations needed for coordinate manipulations and transformations used in tracking.

OpenCV

It was used extensively in this study to read video input, process individual frames, draw detection boxes and tracking IDs, and display the output in real-time. OpenCV also played a key role in integrating with DeepSORT and YOLOv11 by enabling frame-by-frame analysis and visualization of the tracking output.

Matplotlib

Matplotlib is a visualization library in Python used to generate plots, histograms, and other graphical representations. In this project, it was used to visualize evaluation results such as detection accuracy and tracking consistency. By plotting metrics and model performance curves, Matplotlib helped provide insights into the effectiveness of the object detection and tracking system.

Pandas

Pandas is a versatile data manipulation library designed to handle structured data efficiently. It was used in this research to manage logs of detection results, track movements, and organize outputs for further analysis. Pandas enabled the creation of dataframes for behavior logs, which can later be expanded to include behavioral pattern detection based on movement or speed.

PyTorch

PyTorch is a widely-used open-source machine learning framework that offers dynamic computational graphs and GPU acceleration. It was used as the

core deep learning framework for training and deploying the YOLOv11s model. PyTorch's flexibility made it suitable for customizing and running YOLOv11's architecture and managing the training pipeline.

Ultralytics Library

The Ultralytics library is built on top of PyTorch and provides simplified access to the YOLOv11 family of models. It offers a high-level interface for training, validation, inference, and exporting models. In this study, the Ultralytics library was used to fine-tune the YOLOv11s model for chicken detection using a custom dataset exported from Roboflow.

Flask

Flask is a lightweight web application framework for Python. It was used in this study to build a simple web interface for uploading and processing video files. This allowed users to interact with the chicken detection and tracking system via a browser. Flask handled user input, managed file uploads, and served results using a rendered HTML template.

Werkzeug

Werkzeug is a comprehensive WSGI web application library used by Flask for request handling and utility functions. In this study, secure_filename from Werkzeug was used to safely handle uploaded file names, ensuring secure storage and access in the Flask environment.

Streamlit

An open-source Python library that allows data scientists and machine learning engineers to quickly create and share interactive web applications for

their data scripts, models, and analyses without needing front-end web development experience.

Hardware

The study was conducted using a personal computer equipped with sufficient processing power and memory to perform image processing, model training, and evaluation tasks efficiently. Minimum specification of the device is detailed on Table 3.

Table 3. Desktop Specification

CPU	AMD Ryzen 5 5600X
RAM	16 Gigabytes
GPU	AMD Radeon RX 6600 (8GB VRAM)
STORAGE	1 Terabyte SSD

However, due to the computational intensity of training deep learning models such as the LSTM-RNN, cloud-based hardware resources were also utilized through Google Colab. The combination of local and cloud computing resources ensured both flexibility and efficiency in conducting the entire research process.

Also, a CCTV was installed in Perello's Poultry Farm in Cavite to capture the poultry and chicken in a remote setting to strengthens the study's data collection. Table 4 detailed the specifications of CCTV used in the data gathering phase.

Table 4. CCTV Specification

Brand	TP-Link CCTV C200C
Frame per second	15 Fps
Resolution	1080p

These specifications that the CCTV embedded was important to capture quality-approved video footage of the dense population of chickens in the farm. Also, its aerial installation can help to visualize clearly the chickens present in the video frame.

Research Design

The study utilized a combination of theoretical and experimental research designs. The theoretical component involves a comprehensive review of existing literature related to object detection, object tracking, and behavior-based disease detection in poultry. This includes studies that have implemented convolutional neural networks (CNNs) such as YOLO variants for detection, DeepSORT for tracking, and recurrent neural networks (RNNs), particularly long short-term memory (LSTM), for analyzing temporal patterns in animal behavior. Insights from these studies provided the basis for selecting suitable models and techniques for this research.

The experimental phase of the study is divided into three main parts. The first part involves training a YOLOv11s model for detecting chickens in video data. Annotated image datasets are prepared using Roboflow, which also provides augmentation and preprocessing features to refine the quality of training data. Once the detection model is trained, it is integrated with the DeepSORT tracking algorithm to assign unique identifiers to individual chickens across video frames, ensuring accurate and consistent tracking over time.

The second section focused on the movement data collected by the tracking module. The behavioral analysis portion of the study uses these data points, which include the spatial locations and travel patterns of the chickens.

The final part involves training an LSTM-based recurrent neural network (LSTM-RNN) with anomaly detection to analyze the sequential movement data and identify behavioral patterns that may indicate signs of sickness. LSTM is chosen for its ability to learn long-term dependencies and temporal dynamics from time-series data, which are crucial for recognizing subtle changes in chicken behavior that develop over time.

The performance of the YOLOv11s model and the LSTM-RNN will be assessed using metrics such as accuracy, precision, recall, and the F1 score. During model training, additional performance indicators such as the confusion matrix, normalized confusion matrix, precision-recall curve (PR curve), precision (P) curve, recall (R) curve, and F1 curve are also evaluated to provide a comprehensive assessment of the models' strengths and limitations. These indicators offer valuable insight into the reliability of the detection and behavior classification processes.

The findings either support or challenge the research hypothesis that abnormal movement patterns, as identified through deep learning models, can be used as early indicators of illness in chickens.

Model Development

The development of the model for detecting, tracking, and classifying the health status of chickens involved a structured series of stages, including data acquisition, data preprocessing, feature extraction, model training, and model optimization.

The initial stage of the process focused on chicken detection using the YOLOv11 object detection model. Data acquisition was conducted by collecting

video footage and images from poultry farms. The dataset was annotated with bounding boxes around individual chickens, which served as detection targets for the model. Preprocessing was performed to normalize the images and ensure consistency despite variations in lighting, camera angles, and resolution. The dataset was subsequently divided into training, validation, and testing subsets to enable unbiased model assessment. Data augmentation techniques, including image flipping, rotation, and brightness adjustments, were applied to polish model generalization. YOLOv11 was then utilized to extract discriminative features such as shapes, textures, and spatial arrangements of chickens, making it suitable for detecting multiple individuals in crowded environments.

After the detection stage, chicken tracking was implemented through the DeepSORT algorithm to maintain the identity of each chicken across video frames. DeepSORT integrated a Kalman filter for motion prediction and an appearance feature extractor to ameliorate validity against occlusions and overlaps. The Hungarian algorithm was employed for assignment, matching detected bounding boxes to existing tracks based on Intersection over Union (IoU). This process ensured that each chicken was consistently assigned a unique identifier, thereby enabling continuous tracking across frames and facilitating the extraction of trajectory data for each individual.

Behavior classification was performed using a Long Short-Term Memory Recurrent Neural Network (LSTM-RNN), which was designed to process sequential data effectively. Input features for the LSTM-RNN included spatial position, speed, and movement patterns extracted from the DeepSORT tracker. The model architecture incorporated input, forget, and output gates, as well as

hidden and recurrent states, to capture long-term dependencies in the time-series data. By analyzing these temporal patterns, the LSTM-RNN utilized anomaly detection to classify each chicken's condition as either normal or potentially sick. The model was trained on data from healthy chickens to establish a baseline of normal behavioral patterns. Any significant deviation from this baseline—such as reduced mobility, erratic movement, or other abnormal behavioral indicators—was identified as an anomaly and flagged as potentially sick, allowing for the early detection of health concerns.

Training of the integrated models was conducted with careful adjustment of hyperparameters to optimize performance. Parameters such as learning rate, batch size, number of epochs, and momentum were systematically tuned to achieve effective convergence and minimize overfitting. Hyperparameter tuning was also applied to balance detection, tracking, and classification performance. This stage ensured that each model component, YOLOv11 for detection, DeepSORT for tracking, and LSTM-RNN for classification, learned effectively from the training data.

The evaluation phase involved the application of quantitative performance metrics to assess the accuracy and reliability of the models. Metrics such as precision, recall, mean average precision (mAP), and F1 score were used to measure detection performance. Confusion matrices and normalized confusion matrices provided further insights into classification errors, while precision-recall (PR) curves illustrated the trade-off between precision and recall across confidence thresholds. These metrics were critical in assessing whether the system could generalize effectively to unseen data and real-world conditions.

The final stage involved validating the trained models to ensure robustness and reliability. For YOLOv11, validation included the monitoring of validation box loss, validation classification loss, and distribution focal loss (DFL), which measured the accuracy of localization and classification. Learning rate progression was also observed to verify stable training dynamics. Statistical validation using T-tests was employed to determine whether the differences between predicted and actual outcomes were statistically significant, thereby strengthening the credibility of the results. Collectively, these validation procedures ensured that the detection, tracking, and behavioral classification models were optimized for real-world deployment.




Figure 3. Model Development of YOLOv11–DeepSORT–LSTM-RNN

Data Acquisition

The study gathered data through CCTV aerial footage of the chickens in the poultry and interview with the owner of Perello's Poultry Farm to obtain relevant information on farm operations, chicken management practices, and

potential behavioral indicators of illness. The interviews took place during the initial phase of the research and were aimed at understanding the conditions under which the chickens are raised, the management routines followed, and the factors that could affect the chickens' behavior, particularly signs of inactivity associated with possible disease.

The information collected from the interview provided insights into the farm's operational practices, including feeding schedules, environmental controls such as lighting and temperature, and health monitoring protocols. This background information was crucial for contextualizing the behavioral data gathered during the study. Also, the gathered information about common chicken behavior when stress or carrying symptoms of potential sickness, makes the classification more accurate. Aside from the interview data, a dataset of images was collected using mobile phones.

The dataset serves as the foundation for training the model and analyzing the behavior of chickens in relation to health status. This information, combined with the insights gained from the interview, ensures that the data collected is both comprehensive and relevant to the study's objectives. The data will be divided into training, testing, and validating sets, which will be used to develop and validate the model designed to detect behavioral anomalies linked to potential disease symptoms.

Through this instrument, the study not only captures critical behavioral data but also incorporates real-world farming practices and environmental factors, providing a well-rounded basis for analyzing the health and well-being of poultry.

Data Sources

The dataset used in this study consists of images extracted from video, that were carefully selected and annotated to train machine learning algorithms for detecting chickens in scenarios with potential occlusion. For analysis, each image was annotated with bounding boxes to identify individual chickens, using a single class label: "chicken." The footage was collected under mixed lighting conditions, including both natural daylight and artificial light sources. These images serve as the foundation for training, validating, and testing the model designed to detect chickens, especially in cases where occlusion may occur due to the density of chickens.

Table 5. Data Description

Attribute	Description
Data Type	Images (JPEG) extracted from video
Source	CCTV Footage
Number of Images	5000
Image Resolution	1920x1080 pixels
Video Length	10 hours
Video Resolution	1920x1080 pixels
Annotation	Bounding box, single-class (chicken)
Environmental Condition	Mixed natural and artificial light

The dataset is divided into three subsets to ensure effective training, validation, and testing of the object detection model. The training set with 80% of the total datasets, amounting 782 data sample, are used to train the model, allowing it to learn patterns for detecting chickens in various conditions, particularly when occlusion might obscure full visibility. The validation set with 10% of the datasets, includes 98 datasets. It is utilized during the training process to fine-tune the model's parameters, helps in preventing overfitting, and evaluates its performance on an independent dataset. Finally, the remaining

10% which is 98 datasets, where the test set that is reserved for assessing the final performance of the trained model. This division ensures that the model undergoes thorough evaluation, providing reliable results that can generalize well to unseen data.

Table 6. Datasets Splitting

Datasets	Number of Samples	Percentage
Training	772	80%
Testing	98	10%
Validation	95	10%
Total	975	100%

Data Annotation Protocol

The data annotation process was manually performed by the members of this study to ensure consistency of labeled data. Annotation was carried out using the Roboflow platform, where each frame was carefully labeled with bounding boxes corresponding to individual chickens. A total of 975 images were annotated, resulting in 37,036 chickens being labeled across various lighting conditions, positions, and levels of occlusion, as shown in Figure 4.




Figure 4. Summary of Annotated Data in Roboflow

For the tracking process, the DeepSORT algorithm was applied to a 30-minute recorded video sequence. The tracking results produced 922,461 temporal sequences containing the spatial and motion-based parameters of each chicken, specifically the x-coordinate, y-coordinate, speed, and area.

These variables were extracted frame by frame and served as input features for the LSTM-RNN model to reconstruct chicken behaviors and differentiate between healthy and potentially sick chickens based on movement and body size. To ensure data uniformity and eliminate scale bias, all sequences were normalized before being used for model training. This comprehensive annotation and tracking process established a reliable foundation for the YOLOv11–DeepSORT–LSTM-RNN integration, ensuring consistency across all phases of model development.

Model Selection

This study used a hybrid approach to detect and analyze the behavior of broiler chickens to identify possible disease symptoms. The choice of model was guided by the unique features of the dataset, which included real-time video footage showing the movement patterns of the chickens. To effectively extract and interpret these patterns, the system combined three deep learning components. As shown in Figure 5, the process starts with YOLOv11, which conducts real-time object detection to identify individual chickens in each video frame.

DeepSORT then takes these detections and assigns consistent identity tags, allowing the system to track each chicken through successive frames and record their movement paths. Finally, the LSTM-RNN module examines these paths over time, modeling behavioral sequences that may signal early signs of illness such as reduced mobility, unusual movement patterns, or long periods of inactivity. By bringing together detection, tracking, and time-based analysis,

the proposed system offers a practical framework for automated health monitoring in broiler production settings.




Figure 5. End-to-End Flow of Data from YOLOv11–DeepSORT–LSTM-RNN

The first stage of the pipeline employs YOLOv11 (You Only Look Once version 11), a state-of-the-art real-time object detection algorithm. YOLOv11 is an advancement over previous versions, integrating more refined convolutional backbones and optimization techniques to boost accuracy and speed. Its one-stage detection architecture allows it to simultaneously predict bounding boxes and class probabilities directly from full images, making it highly efficient for real-time detection. This capability is essential for detecting multiple chickens in farm environments where occlusions, overlapping objects, and varying lighting conditions are present.

Following detection, the second stage involves DeepSORT (Simple Online and Realtime Tracking with a Deep Association Metric). DeepSORT augments the original SORT algorithm by incorporating deep learning-based appearance descriptors, allowing for more robust tracking even under object occlusion and identity switches. It assigns consistent identities to each chicken

across frames, thereby generating continuous trajectory data. This information is critical for analyzing temporal patterns in movement, which are used to assess behavioral anomalies potentially linked to illness.

The final stage utilizes a Long Short-Term Memory Recurrent Neural Network (LSTM-RNN) to analyze the time series data generated by DeepSORT. LSTM-RNNs are specifically designed to model sequential data and are capable of learning long-term dependencies. Their gated architecture allows them to retain relevant information over time while discarding noise, making them highly suitable for behavior recognition tasks. In this study, the LSTM model is trained on the movement patterns and positional data of individual chickens to classify whether their behavior aligns with healthy or potentially diseased states. The behavioral data includes features such as walking speed, movement consistency, resting duration, and proximity to other chickens.




Figure 6. Model Architecture of YOLOv11–DeepSORT–LSTM-RNN End-to-End Pipeline

Model Evaluation

The trained YOLOv11 model for chicken detection was evaluated using standard object detection metrics that reflect both classification accuracy and

bounding box precision. These evaluation metrics provide insights into how well the model identifies chickens in images and localizes them accurately. The evaluation focused on key indicators such as Precision, Recall, F1 Score, mAP@0.50, mAP@0.50:0.95, and Precision-Recall Curves, which are commonly used in computer vision tasks.

Precision: Precision measures the proportion of correctly predicted positive samples among all predicted positive samples. In the context of chicken detection, it represents the percentage of detected chickens that are actually chickens. A high precision value indicates that the model makes few false positive errors.

Recall: Recall measures the proportion of correctly predicted positive samples among all actual positive samples. It reflects the model's ability to detect all relevant instances of chickens. A high recall value means the model is effective at detecting chickens in different scenarios and does not miss many actual chickens.

F1 Score is the harmonic mean of precision and recall, providing a single metric that balances the trade-off between the two. It is particularly useful in cases where false positives and false negatives carry significant consequences, such as in distinguishing healthy from potentially sick chickens. A high F1 score indicates that the model maintains a strong balance between precision and recall.

mAP@0.50 (Mean Average Precision at IoU threshold of 0.50): mAP@0.50 evaluates the average precision of the model across all classes at an Intersection over Union (IoU) threshold of 0.50. This metric combines both

precision and recall, and it is widely used for comparing the overall detection performance of models.

mAP@0.50:0.95: This is a stricter evaluation metric that averages the mAP across IoU thresholds ranging from 0.50 to 0.95 in increments of 0.05. It provides a more comprehensive understanding of the model's performance across different detection difficulty levels. A higher mAP@0.50:0.95 indicates robust performance across various localization challenges.

Precision-Recall Curve illustrates the relationship between precision and recall at various confidence thresholds. This curve provides critical insight into the model's behavior under different operating points, helping to select a threshold that achieves an optimal balance between false positives and false negatives.

Additionally, separate **Precision Curve** and **Recall Curve** were generated during training and evaluation to monitor how precision and recall evolved over time.

For the performance of LSTM-RNN with anomaly detection, these evaluation metrics provide insights into how well the model identifies potentially sick chickens in the video.

Mean Squared Error (MSE) measures how much the model's prediction deviates from the actual values on average, squared. This approach penalizes larger errors more than smaller ones, providing a sense of how far off the model's prediction is.

Mean Absolute Error (MAE) measures the average difference between the calculated values and the actual values. This approach measures the average size of the prediction error of the model.

Root Mean Squared Error (RMSE) measures the average difference between a statistical model's predicted values and the actual values. It helps to evaluate the magnitude of prediction errors in a model.

Coefficient of Determination (R^2) evaluates how well the model explains the variability of the target variable. It measures the proportion of the variance in the dependent variable that can be predicted from the independent variables.

The use of these evaluation metrics is crucial in assessing the overall effectiveness, reliability, and robustness of both the YOLOv11 model for chicken detection and the LSTM-RNN model for anomaly detection. The model's performance lays a strong foundation for future integration of behavioral analysis once the detection pipeline is fully optimized.

Model Validation

Model validation was carried out to evaluate the generalization performance of the chicken detection and behavior classification model. A separate validation dataset, distinct from the training data, was utilized to assess the model's capability in detecting chickens and classifying their behavior under conditions it had not previously encountered. This step ensured that the model's performance was not limited to the training data and could be reliably applied in practical settings such as real-time monitoring in poultry environments.

The validation process involved tracking specific performance metrics that were automatically recorded by the training framework, which in this case was based on a deep learning object detection and tracking architecture combined with behavior analysis. These metrics were collected from the output logs of the training pipeline and are commonly used to assess object detection and classification models. Each of these validation metrics plays a significant role in interpreting how well the model performs in identifying, localizing, and classifying chickens.

In addition, expert validation was conducted to establish the ground truth against which the model's predictions were compared. The results from this expert-based evaluation were then used to generate a confusion matrix, providing a detailed comparison between the model's detections and the actual observed behaviors for further accuracy assessment.

Validation Box Loss: This metric quantifies the error in predicting the position and dimensions of the bounding boxes around detected chickens. It directly reflects the model's localization accuracy. Lower box loss values indicate that the model is learning to better fit the predicted bounding boxes to the actual positions of chickens in the image. This metric is suitable and important in the study since precise localization is crucial for any future behavioral analysis.

Validation Classification Loss: This loss refers to the model's accuracy in correctly classifying detected objects as chickens. It helps determine whether the model can differentiate between chickens and background or other non-target objects. In the context of this study, where the primary task is to detect

chickens, this metric is highly relevant as it directly measures the model's identification capabilities.

Validation Distribution Focal Loss (DFL): DFL measures how confidently the model predicts the bounding box coordinates. It improves the quality of the predictions by focusing more on difficult-to-detect samples. This metric is derived from recent advancements in object detection algorithms and is especially applicable to tasks requiring precise localization, such as chicken detection. Incorporating DFL enriches the reliability of bounding boxes, which supports future expansion of the system into tracking or behavior analysis.

Learning Rate Progression: The learning rate was monitored during training and validation to ensure stable convergence of the model. This metric helps avoid issues like overfitting or vanishing gradients and ensures that the model optimizes effectively. Tracking the learning rate is standard practice in model training and was vital in fine-tuning the model's performance in this study.




Figure 7. Sample of Training and Validation Performance Curves of YOLOv11

Confusion Matrix offers a detailed visualization of the classification performance by presenting the number of true positives, true negatives, false positives, and false negatives. This allows the researcher to identify specific

types of errors made by the model, such as misidentifying chicken behavior compare to expert validation.




Figure 8. Example of Confusion Matrix

T-Test Validation: By directly contrasting the model's predictions with expert-labeled ground truth data, a Paired t-test will be used to statistically validate the model's performance. In order to ascertain whether any observed differences between two related sets of observations—in this case, the model's classification of potentially ill chickens and the corresponding expert assessments—are statistically significant, this test is appropriate. The Paired t-test will be used in this study to ascertain whether the average prediction accuracy of the model is a result of random variation or if it meaningfully corresponds with expert assessments. This approach offers compelling proof of the system's dependability and consistency by verifying whether the model's outputs deviate noticeably from professional opinions. The model's statistical validation is ultimately strengthened by the use of a Paired t-test, which guarantees that its identification of unusual or ill behaviors is reliable and credible for real-world farm monitoring applications.

Ethical Consideration

All procedures conducted in this study adhered to ethical research standards to ensure animal welfare. Data gathering of videos were collected in a non-invasive manner, as the policy of the poultry farm, to avoid chickens from interfering to any physical distress or contact. The monitoring process were conducted within the chicken's normal environment to minimize disturbance. All recorded data were used solely for academic and research objectives; the datasets were securely store and only accessible to authorized researchers. Crucially, the researchers uphold all rules and requests set forth by the farm and its owner, committing to utilize the gathered data exclusively for the scope and duration of this specific study.

For ethical research considerations in the development of an object detection model for identifying chickens, the researchers have taken steps to ensure that the study upholds integrity, transparency, and responsibility throughout its execution. Prior to conducting the study, the researchers acknowledged the importance of ethical data handling, responsible use of technology, and consideration for the potential implications of the system in real-world applications.

All data used in the study were either synthetically generated or collected from publicly available sources with appropriate consent and licensing where applicable. No live animals were harmed, manipulated, or interfered with during the data collection and model training processes. The images used to train and evaluate the model are representative and anonymized, ensuring that no ethical breach occurs in terms of privacy or exploitation.

The research team commits to full transparency by clearly documenting the objectives, methodology, tools, and limitations of the study. Throughout the development process, the researchers maintained rigorous documentation practices to preserve the integrity of the data and the reproducibility of the results. Additionally, the model outputs are thoroughly analyzed and interpreted to avoid misuse or overreliance on automated predictions without human oversight.

Furthermore, the researchers are aware of the potential for this model to be implemented in agricultural or commercial environments. Therefore, any future application of the system will be accompanied by a responsible deployment framework that considers the welfare of animals and ensures fair use of the technology by stakeholders.

Limitations of the current model, such as its dependency on the quality and diversity of training data, are openly acknowledged. These factors are crucial to the model's accuracy and should be considered in any future iterations or applications. By identifying and addressing these limitations, the study remains grounded in ethical responsibility and scientific integrity.

Lastly, the researchers are committed to promoting responsible AI development by ensuring that the tools and knowledge generated through this study contribute positively to the agricultural sector. This includes supporting sustainable farming practices and encouraging further research that adheres to ethical standards.

CHAPTER IV

RESULTS AND DISCUSSION

This chapter outlines the study's objectives, results, and discussion, accompanied by visual representations of the finding. The study aims to develop a solution for tracking the health of various chickens.

Exploratory Data Analysis

The data collection phase of this study was meticulously carried out at Perello's Poultry Farm, nestled in the municipality of Indang, Cavite. The data acquisition system was done with the TP-Link Tapo C200C camera. This specific model was selected for its robust features, including its high-definition video capabilities and its pan/tilt functionality, which allowed for flexible positioning and comprehensive coverage of the chicken pen. The camera was precisely mounted at an elevation of 77 inches (approximately 195.58 centimeters) above the chicken pen, as shown in Figure 9. This particular height was determined through preliminary trials to be optimal for capturing a wide field of view while minimizing obstructions and ensuring clear visibility of individual chickens.



Figure 9. Installation of CCTV Camera at Perello's Poultry Farm in Indang Cavite

Over the course of the data collection period with a total of 54,000 frames, a substantial dataset comprising 2549 individual augmented images was successfully used. Each image boasted a crisp resolution of 1080p (1920 x 1080 pixels), providing an exceptional level of detail vital for granular analysis of avian physiology and behavior. A deliberate effort was made to introduce diversity into the dataset by capturing images under a wide range of varied lighting conditions, such as in Figure 10 (a & b), encompassing natural daylight, twilight, and artificial illumination, as well as different background elements within the pen. A fundamental design principle for this dataset was the consistent capture of the entire body of each chicken within every image frame. This holistic capture is absolutely essential. By having the complete anatomical representation of each chicken, the model can accurately monitor and analyze a multitude of different behavioral patterns. This includes, but is not limited to, gait analysis, wing posture, head position, social interactions, feeding habits, and resting behaviors. Ultimately, the meticulous analysis of this rich behavioral data will be instrumental in developing an automated system capable of early disease detection, thereby enabling timely intervention and contributing significantly to poultry health management and overall farm productivity.



(a) (b)

Figure 10. Sample Data and CCTV View in Varying Lighting: (a) Day Setting and (b) Night Setting

Figure 10 depicts numerous white-feathered chickens distributed across a slatted floor within a pen. A red, circular feeder occupies the lower-middle section of the frame. This elevated view unequivocally confirms the camera's placement 77 inches above the chicken pen, as this height is essential for capturing such a broad, top-down perspective of the entire pen area. Significantly, the image also illustrates the capture of the whole body of the chickens.

While some individuals are partially obscured by others, most chickens are entirely visible or show substantial portions of their anatomy. This fulfills the objective of obtaining comprehensive views necessary for monitoring various behavioral patterns of each chicken. For example, from this vantage point, one can potentially observe individual chicken postures, movement trajectories, and interactions with the feeder, all crucial elements for behavioral analysis aimed at identifying the potential presence of disease.

Dataset Preparation and Augmentation

Upon the initial pipeline of model development, each video gathered are extracted into multiple frames with the help of online available video to jpg extractor such as Ezgif and Online Converter. Following this initial extraction, the researchers carefully cleaned the frames to manually remove unnecessary or redundant frames that could negatively affect the subsequent training and ultimate performance of the model. This phase was paramount in ensuring the quality and robustness of the resulting deep learning model.

After the cleaning of frames, the researchers uploaded the datasets on Roboflow to manually annotates the chickens in each frame.




Figure 11. Example of Annotated Chicken Datasets in Roboflow

For the better performance of the model in detecting chickens in occluded environment, only those who appears 70% on the frames were annotated as shown in Figure 11. With this annotation, the model can easily detect chickens.

After the annotation, the dataset was subjected to a thorough standardization and expansion procedure that included preprocessing and data augmentation steps, as shown in Figure 12. The preprocessing process involved cropping each video frame to highlight the regions of interest, converting it to grayscale to minimize color variability, and resizing it to 640×640 pixels to comply with the input specifications of the YOLOv11 model. Figure 11 shows how data augmentation techniques, such as brightness, exposure, and contrast adjustments, were used to enhance the dataset's variability and replicate a variety of lighting conditions. This meticulous procedure made sure that the model was trained on a dataset that was representative of actual farm conditions, diverse, and standardized.



Figure 12. Image Preprocessing and Augmentation Parameters for YOLOv11

YOLOv11 Model Training and Implementation

In accordance with the first objective, the YOLOv11 model was implemented and trained to accurately detect chickens even in occluded areas. This objective aimed to establish a reliable detection component capable of operating under realistic farm conditions characterized by dense populations and varying illumination. In the initial stage of the pipeline, YOLOv11 is critically utilized for its ability to accurately and efficiently detect and localize individual chickens within dynamic video frames across diverse farm environments, adeptly handling challenges such as occlusions and varying lighting conditions. The effectiveness of the YOLOv11 model is inherently linked to the quality and diversity of its training data. Figure 13 presents representative samples from the dataset utilized for YOLOv11 training, visually demonstrating the variety of chicken postures, environmental settings, and lighting conditions that contributed to the model's robust learning and generalization capabilities.




Figure 13. YOLOv11 Training Outputs Showing Detected Chickens

Throughout the training of the YOLOv11 model, the researchers utilize careful adjustments and optimization in several hyperparameter for the model which are detailed in Table 7. These critical parameters, such as the learning rate, optimizer, batch size, and network architecture specifics, were configured to optimize detection accuracy and efficiency.

Table 7. Optimized Hyperparameters of YOLOv11

Hyperparameter	**Value**
epochs	50
optimizer	Auto
lr0	0.01
lr1	0.01
imagsz	640
batch_size	16
patience	100
weight_decay	0.0005
momentum	0.937
iou	0.7

The YOLOv11 model was trained for 50 epochs, as its optimized epoch number, while maintaining the remaining parameters at their optimized values. The number of epochs was determined through empirical observation during model training. It was observed that after 50 epochs, the model's accuracy and evaluation metrics such as Precision, Recall, and mean Average Precision (mAP) reached a plateau with no significant revamp. Extending the training period beyond this point did not result in higher accuracy and only prolonged computation time. Therefore, 50 epochs were deemed optimal, providing a balanced trade-off between performance stability and efficiency.

Figure 14 presents the output of the trained YOLOv11 model during the detection and validation phase.



Figure 14. YOLOv11 Inference Results on Poultry Video Frames

The image shows multiple bounding boxes drawn around each detected chicken, along with their corresponding class label ("Chicken") and confidence score, which indicates the model's certainty in each prediction. The displayed confidence levels, mostly above 85%, demonstrate that the model effectively

distinguishes individual chickens from the background and other possible noise in the image.

Integration of YOLOv11 to DeepSORT, and LSTM-RNN for Multi-Object Tracking and Anomaly-Based Behavioral Classification

Aligned with the second objective, the integration of YOLOv11 with DeepSORT and LSTM-RNN was implemented to enable continuous detection, tracking, and behavioral analysis of individual chickens. This objective focused on establishing a unified framework capable of maintaining object identity across frames and recognizing temporal movement patterns indicative of potential sickness. After the careful annotation of every chicken in the frame and model training for object detection, the output of the YOLOv11 will be the input that DeepSORT will utilize to maximize multi-object tracking by integrating deep learning-based appearance descriptors with the SORT algorithm, ensuring robust and consistent identity assignments to each chicken across video frames. Upon training with the tracker, Kalman Filter was implemented for assigning unique ID to individual chicken.

Table 8. Optimized Hyperparameters of DeepSORT

Hyperparameter	Value
max_age	5
n_init	3
max_iou_distance	0.7
nms_max_overlap	0.9

As shown in Table 8, the DeepSORT algorithm was optimized with the following parameters: maximum age (max_age) = 5, initialization frames (n_init) = 3, maximum intersection-over-union distance (max_iou_distance) = 0.7, and

non-maximum suppression overlap (nms_max_overlap) = 0.9. These values were tuned to adapt to the behavioral dynamics of chickens in dense flock conditions. The max_age of 5 limited the persistence of tracks once chickens exited the frame, preventing false detections from lingering. The n_init value of 3 ensured that a track was confirmed only after three consecutive detections, minimizing false positives from brief or partial occlusions. The max_iou_distance of 0.7 maintained track continuity despite slight displacement or overlap, while the nms_max_overlap of 0.9 preserved valid detections in crowded scenes.

Figure 15 presents a DeepSORT output frame, showcasing its multi-object tracking capability in the farm environment. Each detected chicken is accurately localized by a bounding box and assigned a unique, consistent identification number (e.g., "ID: 4"). This robust ID assignment, DeepSORT's core strength, relies on motion prediction (Kalman filter) and deep learning-based appearance descriptors to maintain identities across frames, even with occlusions, varying postures, or lighting changes.



Figure 15. DeepSORT Tracking Output with Unique Chicken IDs

Afterwards, identity-preserved trajectory data generated by DeepSORT serves as the crucial input for the final stage of the pipeline, which is the LSTM-RNN. The LSTM-RNN is specifically utilized for the behavioral classification of chickens, transforming sequential movement data into meaningful insights related to their health and activity patterns. By learning temporal dependencies within these motion sequences, the model can distinguish subtle behavioral variations that may indicate early signs of lethargy or irregular movement. This temporal analysis allows the system to automatically flag anomalies associated with potential sickness, thereby enhancing the overall accuracy and responsiveness of the detection framework.

Before the training of LSTM-RNN, the trajectory datasets obtained from DeepSORT are normalized to ensure stable and efficient learning by the LSTM model. Normalization involves calculating the mean and standard deviation of the sequences and then standardizing them using the formula:

$$Sequence = \frac{(sequences - mean)}{(std + 1e^{-8})} \quad (1)$$

This step scales all input features to a comparable range, preventing large value disparities from dominating the learning process and improving convergence during training.

Furthermore, to strengthens the detection of abnormal or potentially sick chicken behaviors, the LSTM-RNN model employs an unsupervised anomaly detection approach through integration of an Autoencoder. The Autoencoder is trained exclusively on trajectory data representing normal (healthy) chicken behaviors, allowing it to learn the underlying temporal and spatial patterns of typical movement. During inference, any new behavioral sequence that

significantly deviates from this learned pattern, indicated by a high reconstruction error, is flagged as an anomaly, suggesting the presence of irregular or potentially sick behavior.

The performance and accuracy of the LSTM-RNN in classifying chicken behaviors depend heavily on its internal configuration and data partitioning, with training, testing, and validation splits of 80%, 10%, and 10%, respectively, to ensure generalization and robust evaluation. As shown in Table 9, the optimized hyperparameters included 30 epochs, an input size of 4, a hidden layer size of 128, a dropout rate of 0.2, and a batch size of 128, while other parameters were kept at their default values.

Table 9. Optimized Hyperparameters of LSTM-RNN

Hyperparameter	**Value**
Input size (features per timestamp)	4
Hidden layer size	128
Layers	2
Dropout	0.2
Batch size	128
Learning rate	0.0005
Optimizer	Adam
Loss Function	Mean Squared Error (MSE)
Threshold	0.7
Epoch	30

The choice of 30 epochs was based on the stabilization of reconstruction loss, indicating model convergence without unnecessary computation. The input size of 4 represented the key DeepSORT-derived variables (x and y coordinates, speed, and area), encapsulating spatial and motion-based characteristics. A hidden layer size of 128 enabled the model to capture complex temporal dependencies, improving reconstruction and anomaly

detection compared to smaller configurations. A dropout rate of 0.2 mitigated overfitting, while a batch size of 128 ensured efficient and stable training. Collectively, these parameters were chosen after iterative testing to balance training stability and generalization performance, ensuring reproducibility for future studies.

The integration of the DeepSORT output with the LSTM-RNN autoencoder enables a comprehensive analysis of individual chicken behavior. By analyzing the time-series trajectory data provided by DeepSORT for each uniquely identified chicken, the LSTM-RNN captures behavioral patterns such as walking speed, resting duration, activity levels, and proximity to other chickens. To identify irregular behavior, the system computes the reconstruction error for each sequence.

The anomaly threshold was determined statistically using the mean reconstruction loss and the standard deviation of normal sequences. The threshold was set to $T = \mu + 3\sigma$, following the three-sigma rule used in anomaly detection. This rule is grounded in the assumption that normal reconstruction errors follow a distribution where almost all values lie within three standard deviations from the mean. Setting the threshold in this region minimizes false positives while still allowing the model to detect sequences that deviate significantly from expected behavior. This value produced a threshold of approximately 0.7 for this study. Any sequence exceeding this value is considered unlikely to belong to the normal distribution of chicken movements and is therefore flagged as an anomaly. When such behavior is detected, the system highlights the corresponding chicken with a red bounding box to indicate irregular or potentially sick behavior.




Figure 16. LSTM-RNN Autoencoder Output for Anomaly Detection

Figure 16 presents a representative output illustrating the behavioral classification results of the LSTM-RNN. This figure demonstrates how the system categorizes individual chicken movements, providing actionable data for monitoring and early detection of behavioral anomalies that may signal health concerns such as green bounding box for “healthy chicken” and red bounding box for “potentially sick chickens”.

Results of Metrics for YOLOv11 and LSTM-RNN

In pursuit of the third objective, the model’s performance was thoroughly evaluated to determine detection accuracy and behavioral classification efficiency. Implementation of YOLOv11 for object detection has yielded highly promising results, establishing a robust foundation for subsequent detection of chicken. It achieved exceptional performance across key detection metrics, including precision, recall, mAP50 and mAP50-95, highlighting its precise bounding box predictions across various Intersection over Union thresholds. The comprehensive and varied dataset, with its extensive instances of chickens

in diverse placements, further contributed to the development of a resilient and accurate detector.

Table 10 presents the performance of YOLOv11 as initial pipeline of overall model in detecting individual chicken in an occluded environmental setup and various situational factors.

Table 10. Results of Metrics for YOLOv11

Metrics	**Value**
Precision	95.9%
Recall	97%
F1-score	95%
mAP50	97.4%
mAP50-90	76.1%

The model shows a great achievement in all metrics with a precision of 95.9%, recall of 97%, F1 score of 95%, mAP50 of 97.4%, and mAP50-95 of 76.1%. These results showcase the YOLOv11 algorithm detection is efficient in an occluded situation, particularly in overlapping chickens in the farm.

A Precision-Recall (PR) curve of the YOLOv11 model demonstrates consistently high precision across a wide range of recall values, as shown in Figure 17. This near-ideal curve indicates that the model effectively identifies true positives while minimizing false detections, even as recall increases. The balanced performance reflects YOLOv11's strong generalization ability and reliability in distinguishing between normal and anomalous chicken behaviors, confirming its suitability for real-time poultry monitoring applications.




Figure 17. Precision-Recall Curve of YOLOv11 in Chicken Detection

These values indicate that YOLOv11 not only detects chickens effectively but also maintains consistent bounding box precision despite occlusions. These results affirm that the optimized YOLOv11 model is highly capable of performing precise and consistent detection of individual chickens in real-world poultry environments where visual obstruction is common.

When compared with previous models such as YOLOv4 with Kalman Filter (94.6%), YOLOv5 with Kalman Filter (91.8% mAP@0.50), and Broiler-Net (90.0% mAP@0.50), the proposed YOLOv11 model achieved a substantial improvement with 97.4% mAP@0.50. This represents a 3–7% gain in detection precision. The results demonstrate the model's superior capacity to maintain accurate tracking in an environmental situation where occlusion appears.

Meanwhile, the LSTM-RNN with autoencoder model was evaluated using key regression metrics to determine its effectiveness in detecting potentially sick chickens. The model identifies abnormal behavior by comparing each sequence's reconstruction error to the recommended threshold of 0.7, as shown in Table 9. This threshold was computed using the formula:

$$Threshold = Mean\ Loss + 3 * Std\ Dev \quad (2)$$

which is a statistically grounded method commonly used in anomaly detection.

This approach assumes that the reconstruction errors of healthy or normal chicken movements follow a distribution where most values are concentrated near the mean. By adding three standard deviations, the threshold is positioned at the point where only extremely unlikely or irregular behaviors exceed the limit. In practical terms, values that fall within three standard deviations represent typical movement patterns, while values beyond this boundary indicate significant deviation from normal behavior.

The threshold of 0.7 therefore serves as the decision boundary that separates normal sequences from potentially anomalous ones. Any data sequence producing a reconstruction error greater than this value is considered abnormal and is flagged by the system. This mechanism ensures that the model does not label minor fluctuations as anomalies, while still being sensitive enough to detect meaningful irregularities that may indicate sickness or behavioral issues.

Table 11. Results of Metrics LSTM-RNN

Metrics	**Value**
Mean Squared Error (MSE)	0.11
Mean Average Error (MAE)	0.20
Root Mean Squared Error (RMSE)	0.33
Coefficient of Determination (R^2)	0.88

As shown in Table 11, the LSTM-RNN achieved a low MSE and MAE,0.11 and 0.20 respectively, along with a relatively small RMSE with 0.33, indicating accurate reconstruction of normal behavioral sequences. The R^2

value of 0.88 suggests a strong correlation between the predicted and actual behavioral data, confirming that the model effectively learned normal motion patterns among healthy chickens. The reconstruction accuracy of 75.21% further demonstrates its reliability in identifying deviations or anomalies.

The model displayed consistent and stable performance across different data partitions, confirming that the training process effectively minimized prediction errors. It achieved a mean loss of 0.1520 and a best validation loss of 0.1087). A reconstruction error threshold of 0.7 was utilized to detect 1,816 sequences as anomalies during training, which suggests possible unhealthy or aberrant behaviors in the chickens. The results presented indicate that the LSTM-RNN with Autoencoder architecture is suitable for unsupervised anomaly detection in poultry behavior analysis, as it can identify even the smallest changes in movement patterns. The model offers a solid foundation for early warning and health monitoring in farming environments by precisely capturing subtle behavioral variations.

A comparison with earlier detection and tracking models is provided in Table 12 to further highlight the enhancements brought about by the suggested YOLOv11–DeepSORT–LSTM-RNN framework. This comparison shows the framework's improved processing speed, better detection accuracy, and greater resilience in difficult farm conditions like partial occlusion, crowded spaces, and fluctuating lighting. All of these results demonstrate that the integrated pipeline provides a more dependable and effective tool for behavior-based anomaly detection and real-time poultry health monitoring, in addition to successfully identifying individual chickens and their behaviors.

Table 12. Comparison of the Proposed YOLOv11–DeepSORT–LSTM-RNN Framework with Prior Models

Model / Study	Author	Accuracy
Faster R-CNN	Geoffen et. al. (2020)	89.6%
Multi-Object Tracking (MOT) + SSD	Khairunissa et. al. (2021)	60.4%
YOLOv5 + Kalman Filter	Mishra et al. (2022)	94.6%
Broiler-Net: YOLOv4 + Kalman Filter	Zarrat & Mohtavipour (2024)	90%
YOLO + DeepSORT + RNN	Yang et al. (2024)	90%
Proposed YOLOv11–DeepSORT– LSTM-RNN		97.4%

Table 12 presents a comparison between the proposed YOLOv11–DeepSORT–LSTM-RNN framework and prior detection and tracking models. The proposed system attained the highest accuracy (97.4%), outperforming earlier approaches in precision. Its integrated detection, tracking, and temporal analysis enable reliable identification of anomalous poultry behaviors, supporting efficient real-time health and welfare monitoring.

The computational performance of the proposed system was also evaluated to determine its feasibility for real-time monitoring. The YOLOv11 model alone consistently achieved 30 to 40 FPS, demonstrating its capability to perform real-time object detection without significant delay. However, when DeepSORT tracking and the LSTM autoencoder were integrated into the full pipeline, the overall processing speed decreased to approximately 2 to 5 FPS. This reduction is expected because tracking computations, feature extraction, and sequence-based anomaly analysis add substantial processing overhead. Machines with lower RAM experienced occasional bottlenecks due to the

simultaneous handling of video frames, tracking states, and LSTM inputs. For optimal performance, a minimum of 32 GB RAM is recommended to ensure that the detection, tracking, and anomaly classification modules can run smoothly without causing significant frame drops or delays. Despite the reduced FPS, the system remains suitable for continuous monitoring, since its goal is to identify irregular or potentially sick behaviors rather than requiring high-speed real-time responsiveness.

Model Validation

Consistent with the fourth objective, the final phase of the study involved validating the performance of the integrated YOLOv11–DeepSORT–LSTM-RNN framework against expert evaluations. It focused on assessing the system's accuracy, reliability, and stability through statistical and visual analyses. The validation box loss, classification loss, and distribution focal loss (DFL) gradually decreased throughout the training (Figure 18), indicating that the model consistently refined in accurately detecting and classifying chickens.




Figure 18. Validation Losses and Learning Rate Trends During Training

The consistent decline in both training and validation losses, combined with the smooth learning rate trajectory, indicates that the model achieved stable convergence, minimized overfitting, and attained optimal detection performance during training.

Furthermore, the performance of the proposed YOLOv11–DeepSORT–LSTM-RNN framework was validated by comparing the model's predictions with the poultry expert's ground truth labels. This validation process ensures that the automated system's output aligns closely with expert assessment, confirming its reliability and practical applicability in detecting potentially sick chickens.




Figure 19. Confusion Matrix Comparing Expert Ground Truth and Model Predictions

As shown in Figure 19, the confusion matrix illustrates how well the model's classifications matched the expert's observations. Out of 110 total samples, the model correctly identified 61 healthy chickens as healthy and 37 sick chickens as sick. Meanwhile, 7 healthy chickens were incorrectly classified

as sick, and 5 sick chickens were incorrectly classified as healthy. These results demonstrate that the model achieved a high accuracy and balanced performance, showing strong agreement with expert evaluation in distinguishing healthy from sick chickens.

Table 13. Quantitative Comparison Between Expert Validation and Model Prediction

Evaluation Metric	Expert (%)	Model (%)	Difference (%)
Healthy Detection Accuracy	89.7	90.1	+0.4
Sick Detection Accuracy	88.2	88.1	- 0.1
Overall Classification Accuracy	---	89.09	---

Table 13 presents a direct comparison between the expert's evaluation and the model's predictions for detecting healthy and potentially sick chickens. The results show that the model's classification performance closely aligns with expert assessment, with less than 1% variation in both healthy and sick detection accuracy. This minimal difference demonstrates that the model can reliably replicate expert judgment, reinforcing its validity as an automated decision-support system for poultry health monitoring. The consistent overall classification accuracy of 89.09% further indicates the framework's effectiveness in real-world evaluation scenarios.

Furthermore, a paired samples t-test was conducted to assess whether the model's predictions of potentially sick chickens were statistically comparable to the expert's evaluations. The validation dataset consisted of 110 behavioral sequences, each annotated by a poultry expert, with a value of 1 assigned if the model's prediction matched the expert's assessment and 0 if it did not. This statistical test aimed to determine if any observed difference

between the model's and expert's classifications occurred by chance or indicated a significant deviation in performance.

Table 14. Descriptive Comparison of Poultry Expert and Model Classification Results

Group	N	Mean	Median	SD	SE
Poultry Expert	110	0.382	0.00	0.488	0.0465
Model	110	0.400	0.00	0.492	0.0469

Table 14 presents the descriptive statistics for the poultry expert and model groups from the 110 samples. The poultry expert group recorded a mean score of 0.382 (SD = 0.488), while the model group obtained a slightly higher mean of 0.400 (SD = 0.492). Similarly, the standard error (SE) values were almost identical—0.0465 for the expert and 0.0469 for the model—implying comparable precision in their mean estimates. The median score for both groups was 0.00, indicating a similar central tendency. The standard error of 0.0423 reflects a relatively small sampling variability. The test value used for comparison was 0.5.

Table 15. Results of the Paired Samples T-Test Between Poultry Expert and Model Evaluations

T-Test	Statistic	df	p	Mean Difference	Effect Size (Cohen's d)
Paired T-test	-0.576	109	0.566	-0.0182	0.0549

Note. $H_\delta \mu_{\text{Measure 1 – Measure 2}} \neq 0$

The results in Table 15 show that the paired samples t-test yielded a value of t(109) = –0.576, p = 0.566 indicating that there is no statistically significant difference between the model's classification results and those of the

poultry expert. The mean difference of -0.0182 between the poultry expert's evaluations and the model's predictions further supports that the two sets of results are nearly identical on average. The effect size (Cohen's d = 0.0549) indicates a negligible difference, meaning that the variation between the two sets of scores is minimal.

This suggests that the model's classifications can closely replicate the expert's assessments, demonstrating strong agreement and consistent performance.




Figure 20. Mean and Median Accuracy of the Poultry Expert and Model Evaluations

As shown in Figure 20, the mean values of the poultry expert and model evaluations (represented by the circular markers) are nearly identical, indicating minimal difference between their average scores. The median values (shown as square markers) are both at 0.00, further emphasizing their similar central tendencies. This visualization supports the paired t-test results, showing that the model's predictions closely align with the expert's evaluations, and that there is no significant difference between the two assessments.

The results of the paired samples t-test revealed no statistically significant difference between the evaluations of the poultry expert and the model's predictions. This outcome indicates that the model's performance is comparable to that of the expert, demonstrating a high level of consistency and agreement between the two assessments. The findings suggest that the model's ability to detect potentially sick chickens is reliable, accurate, and not attributable to random variation. Consequently, the expert validation provides substantial evidence supporting the effectiveness and validity of the proposed model in identifying potentially sick chickens.

While the results demonstrate high accuracy and strong alignment with expert evaluations, it is essential to acknowledge the trade-offs between performance and computational demand. Additionally, model bias may arise from uneven data representation, where lighting, occlusion frequency, or specific chicken behaviors are overrepresented, potentially influencing the model's behavioral recognition accuracy. These factors underline the importance of evaluating the model's robustness across diverse datasets and computing environments.

CHAPTER V

SUMMARY, CONCLUSIONS AND RECOMMENDATIONS

Summary of the Study

The behavior of a chicken is one of the factors that can be observed that reflects their well-being. Normal and healthy chicken shows intricate behaviors that could be seen in their everyday actions. While diseased chickens exhibit altered behaviors, that are far from their normal behavior, can indicate an underlying health issue that could not be seen easily with a huge number of chickens. This study wanted to address this by developing a model based on machine learning, which intended detect and identify the health of a chicken using data collected from Perello Poultry Farm.

The dataset for the chicken detection was collected from Perello Poultry Farm, consisting of 2,549 samples and 54,000 frames. These data were ensured to capture the entire body of every chicken within every frame. This includes, but is not limited to, gait analysis, wing posture, head position, social interactions, feeding habits, and resting behaviors. Every frame manually reviewed and annotated to mark the presence of every chicken, making sure that only those who appeared 70% were only annotated. Upon the annotation of the 975 samples, a total of 37,036 annotations were created for the ’chicken’ class, approximately shows that each image has 38.0 annotations. After the detailed annotation, preprocessing and augmentation was made to ensure the right quality of input for the model training. The dataset was divided into three parts: 80% for training, 10% for validation, and 10% for testing.

The model developed in this study consisted of three machine learnings, each serving a specific function with the overall framework. YOLOv11 was utilized for object detection, identifying, and localizing individual chickens within each video frame. DeepSORT was used to perform multi-object tracking that helps in maintaining the consistent identification of each chicken on different frames, even with occlusion present or dense flock. Last machine learning is the Long Short-Term Memory Recurrent Neural Networks (LSTM-RNN) was employed to analyze the behavioral classification of chicken and it also employs unsupervised anomaly detection approach, transforming sequential movement data into meaningful insights related to their health.

The YOLOv11 model achieved a Precision of 95.9%, Recall of 97%, F1-score of 95%, mAP50 of 97.4%, and mAP50-90 of 76.1%, this indicates that the model not only detects chickens but also maintains consistent bounding box precision despite the occlusion. Meanwhile, LSTM-RNN also shows low MSE and MAE, 0.11 and 0.20 respectively, along with a relatively small RMSE with 0.33, indicating accurate reconstruction of normal behavioral sequences. The R^2 value of 0.88 suggests a strong correlation between the predicted and actual behavioral data, confirming that the model effectively learned normal motion patterns among healthy chickens. The reconstruction accuracy of 75.21% further demonstrates its reliability in identifying deviations or anomalies.

These findings demonstrate that the integration of YOLOv11, DeepSORT, and LSTM-RNN overhaul the detection and classification of potentially sick chickens only based on their behavioral cues. The model also proved being efficient in handling occlusion, tracking multiple objects, and identifying anomalies in motion. The developed YOLOv11–DeepSORT–LSTM-

RNN framework proves not only technically feasible but also economically viable for real-world implementation. Its modular and lightweight design makes it suitable for low-cost camera setups and edge computing devices, enabling real-time health monitoring in commercial and smallholder farms alike. This approach supports the broader movement toward AI-driven smart farming systems, enhancing poultry welfare, sustainability, and productivity.

Conclusions

This section summarizes the study's conclusions. Each research objective is systematically addressed to provide a clear interpretation of the results and confirm alignment with the research goals.

1. **Implement and train the YOLOv11 model for accurate detection of chicken in occluded area.**

This study successfully implemented a YOLOv11-based object detection model for the precise localization of individual chickens within highly occluded settings. The object detection algorithm optimized its hyperparameters in order to accurately detect each chicken in a frame. Leveraging a meticulously manually annotated custom dataset, the model demonstrated exceptional resilience, maintaining detection accuracy even when only 70% of a chicken's body was visible. Furthermore, the detection performance proved robust against challenging, varied lighting conditions. The achievement of high-fidelity chicken detection in occluded areas establishes a critical foundation for subsequent processes, including real-time multi-object tracking (DeepSORT) and the development of motion-based anomaly detection algorithm (LSTM-RNN).

2. **Integration of YOLOv11 output for object detection with DeepSORT for multi-object tracking and LSTM-RNN with anomaly detection for behavioral classification in motion of potentially sick chicken.**

The integration of YOLOv11 output to DeepSORT as input data successfully helps the tracker to track individual chicken in an occluded area and in different lighting set-up as YOLOv11 accurately detected and localized individual chickens. The chickens on the detection output of the initial algorithm are assigned with unique IDs with the help of Kalman Filter integrated with DeepSORT to keep them tracked individually. The output generated by DeepSORT was then processed by the LSTM-RNN with anomaly detection, which analyzed the historical movement and trajectory data obtained from DeepSORT.

In this final stage of the pipeline, LSTM-RNN with anomaly detection will be classified and determined whether each chicken's motion behavior was "healthy" or "potentially sick" by identifying subtle, early anomalies in their motion patterns. With the optimized hyperparameters of DeepSORT and LSTM-RNN algorithms, the system demonstrated elevated robustness and detection accuracy, effectively maintaining precise individual tracking even in occluded or complex environmental conditions.

3. **Analyze and classify potentially sick chickens based on anomaly behavior by evaluating the following metrics such as Precision, Recall, F1 Score, mAP@0.50 and mAP@0.50:0.95 (mean average precision at different IoU thresholds), and Precision-Recall Curves for YOLOv11 in object detection, and Mean Squared Error, and**

Standard Deviation for LSTM-RNN with Anomaly Detection for behavioral analysis.

After hyperparameter optimization and model development, YOLOv11 for object detection and LSTM-RNN with Autoencoder analyzed and classified chicken that shows anomalous behavior. The YOLOv11 algorithm achieved a high accuracy in object detection in an occluded environment, demonstrating a precision rate of 95.9%, recall rate of 97%, and F1-score of 95%, with 97% mAP@0.50 and 76.1% mAP@0.50:0.95. These results indicate that the model was highly effective in detecting chickens under challenging conditions such as partial occlusion which is one of the major challenges in application of machine learning and computer vision in poultry industry. Moreover, YOLOv11 successfully generalized chicken detection across different feather colors, as shown by its ability to detect black-colored chickens under the “Chicken” class. The Precision–Recall curve also revealed a near-ideal relationship between precision and recall, highlighting the model’s strong balance between accuracy and reliability in detection.

For LSTM-RNN model integrated with anomaly detection detects behavioral patterns of chickens based on motion trajectory generated by DeepSORT. Using DeepSORT’s tracking outputs, the LSTM-RNN achieved excellent performance, with a Mean Squared Error (MSE) of 0.11, Mean Absolute Error (MAE) of 0.20, Root Mean Squared Error (RMSE) of 0.33, and an R^2 value of 0.88, reflecting a high degree of accuracy in reconstructing normal movement patterns. Reconstruction errors exceeding a threshold of 0.7 were classified as anomalous, corresponding to potentially sick chickens exhibiting irregular or reduced motion.

Overall, the proposed framework outperformed previous studies by achieving superior detection, tracking, and classification accuracy. The combination of YOLOv11 for object detection in occluded areas, DeepSORT for multi-object tracking, and LSTM-RNN for anomaly-based behavioral classification effectively distinguished normal from anomalous chickens, indicating potential sickness. The results across all evaluation metrics confirm that the integrated model performs efficiently, ensuring precise, reliable, and real-time detection and classification of poultry behavior.

4. **Evaluate system's performance used for the detection of potentially sick chickens using Confusion Matrix of Model and Expert, and Paired T-Test.**

The confusion matrix results revealed that the proposed model accurately identified the majority of potentially sick chickens, achieving strong classification performance. Out of 110 total samples, the model correctly classified 61 healthy chickens as healthy and 37 sick chickens as sick, while 7 healthy chickens were misclassified as sick and 5 sick chickens were misclassified as healthy. These outcomes correspond to high values of accuracy, precision, recall, specificity, and F1-score, indicating balanced performance across both classes. Such results demonstrate a strong level of agreement between the model's predictions and the poultry expert's evaluations, confirming the framework's ability to effectively recognize abnormal chicken behaviors associated with potential illness. The consistency of these results further validates that the classification performance of the YOLOv11–DeepSORT–LSTM-RNN framework is both stable and dependable.

Furthermore, a paired samples t-test was conducted to statistically assess the relationship between the model's predictions and the expert assessments. The analysis showed no statistically significant difference between the two evaluations ($t(109) = –0.576$, $p = 0.566$), with a minimal mean difference of 0.0182 and a small effect size (Cohen's $d = 0.0549$). These findings indicate that both the model and the expert produced nearly identical results, confirming that the observed similarity was not due to random variation but to consistent performance.

Taken together, the confusion matrix and the paired samples t-test results affirm that the model's performance closely aligns with that of human experts. This demonstrates the model's reliability, accuracy, and effectiveness in detecting potentially sick chickens through automated behavioral analysis. Overall, the YOLOv11–DeepSORT–LSTM-RNN framework has proven to be a consistent, objective, and practical decision-support tool capable of performing on par with expert evaluation, making it suitable for real-time poultry health monitoring in farm environments.

Despite the strong performance achieved, the study acknowledges several limitations related to computational cost, dataset diversity, and environmental generalizability. The training environment's limited scope, which includes the use of a small dataset (2,549 images) and data that was only gathered from one farm environment, is the main source of its limitations. Furthermore, only two distinct anomalous categories—lethargy and unsteady walking—are the focus of the present behavioral recognition module. Also, training and deployment require high-performance GPUs, which may not be feasible for small-scale farms. Additionally, dataset bias – caused by limited

lighting variations, occlusion frequency, or specific chicken behaviors – may affect the model's generalization across different environments. To address these constraints, future research should incorporate cross-farm validation, dataset balancing, and lightweight model optimization to enhance the framework's scalability, adaptability, and robustness in diverse poultry production settings.

Recommendations

The following recommendations are presented for future research and the practical application of motion-based anomaly detection in poultry health monitoring.

1. It is recommended that future researchers place greater emphasis and allocate more time to accurately annotating datasets for YOLOv11, as the model's performance heavily relies on the quality of these annotations. Poorly annotated datasets may lead to inaccurate results, not only affecting YOLOv11 but also impacting the performance of DeepSORT and LSTM-RNN, which could result in biased evaluation metrics.
2. To optimize model performance and computational efficiency, researchers should employ advanced hyperparameter optimization algorithms such as Hyperband for DeepSORT and LSTM-RNN models. Additionally, model pruning and transfer learning can further improve generalization, reduce computational costs, and preserve accuracy.
3. To ensure more reliable and meaningful results from both algorithms, DeepSORT and LSTM-RNN, future researchers are encouraged to allocate ample time for model training. Providing sufficient training time

allows the algorithms to better learn from the dataset, leading to amplified accuracy, stability, and overall performance. Well-trained models are more capable of producing consistent outcomes that accurately reflect real-world conditions.

4. For further model validation, future researchers are encouraged to conduct field pilot testing across multiple poultry farms with varying breeds, flock densities, lighting conditions, and environmental settings to evaluate the robustness, adaptability, and scalability of the proposed motion-based anomaly detection framework in real-world agricultural contexts.
5. When working with computer vision topics, future researchers should ensure that they have a device equipped with a graphics card powerful enough to support the algorithms they plan to use. However, for those with limited hardware resources, it is also recommended to optimize and minimize memory allocation to allow the models to run efficiently even on lower-spec laptops or computers.
6. Beyond poultry industries, the use of artificial intelligence in behavior-based monitoring could be have a significant implication for broader agricultural industry. Similar framework can be adapted for other livestock such as swine, and other species for early detection of any sickness, stress, or abnormal behavior. With this Artificial Intelligence framework or application integrated on multiple livestock, it can help in maximizing farm productivity and promote sustainable livestock management.

REFERENCES

Ali, R., Dorozynski, M., Stracke, J., & Mehltretter, M. (2022). Deep learning-based tracking of multiple objects in the context of farm animal ethology. *The international Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences/International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, *XLIII-B2-2022*, 509–516. https://doi.org/10.5194/isprs-archives-xliii-b2-2022-509-2022

Andrade-Cetto, J. (2002). The kalman filter: An introduction to concepts and methods. Springer. https://doi.org/10.1007/978-3-662-04898-2

Afdhal, A., Saddami, K., Sugiarto, S., Fuadi, Z., & Nasaruddin, N. (2023). Real-Time object detection performance of YOLOv8 models for Self-Driving cars in a mixed traffic environment. *2023 2nd International Conference on Computer System, Information Technology, and Electrical Engineering (COSITE)*. https://doi.org/10.1109/cosite60233.2023.10249521

Aharon, N., Orfaig, R., & Bobrovsky, B.-Z. (2022). BoT-SORT: Robust associations for multi-pedestrian tracking. arXiv preprint *arXiv:2206.14651*. https://doi.org/10.48550/arXiv.2206.14651

Alif, M. a. R. (2024). YOLOV11 for Vehicle Detection: Advancements, performance, and applications in intelligent transportation systems. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2410.22898

Badgujar, C. M., Poulose, A., & Gan, H. (2024). Agricultural object detection with You Look Only Once (YOLO) algorithm: A bibliometric and systematic literature review. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2401.10379

Bakirci, M., & Bayraktar, I. (2024). Comparative performance of YOLOv9 and YOLOv10 for vehicle detection towards real-time traffic surveillance with UAVs. *2024 21st International Conference on Electrical Engineering, Computing Science and Automatic Control (CCE*), 1–6. https://doi.org/10.1109/cce61531.2024.10583012

Baxter, M., Bailie, C. L., & O'Connell, N. E. (2020). An evaluation of potential fear-reducing modifications to the broiler catching process*. Applied Animal Behaviour Science*, 225, 104972. https://doi.org/10.1016/j.applanim.2020.104972

Bejar, F., et. al. (2013). Management practices and morphological characterization of indigenous (native) chickens in Samar Province. *Discussion Paper Series - Southeast Asian Regional Center for Graduate Study and Research in Agriculture (SEARCA),* 2012, No. No.2012-3, 38 pp. ref. 3. https://www.cabidigitallibrary.org/doi/full/10.5555/20133008424

Bochinski, E., Eiselein, V., & Sikora, T. (2017). High-Speed tracking-by-Detection without using image information. In 2017 14th IEEE International Conference on Advanced Video and Signal Based Surveillance (AVSS), 1–6. https://doi.org/10.1109/avss.2017.8078516

Bounty PH. (2024). Why chicken is a Filipino food staple. Retrieved from https://www.bountyfresh.com.ph/blog/why-chicken-is-a-filipino-food-staple/ Butterworth, A. (2017). Cheap as chicken. In Routledge eBooks (pp. 155–170). https://doi.org/10.4324/9781315562032-10

Calder, C., & Albright, J. (2021). Chicken behavior. Backyard poultry medicine and surgery: A guide for veterinary practitioners, second edition, 434–454. https://doi.org/10.1002/9781119511816.ch22

Caplen, G., Hothersall, B., Murrell, J. C., Nicol, C. J., Waterman-Pearson, A. E., Weeks, C. A., & Colborne, G. R. (2012). Kinematic analysis quantifies gait abnormalities associated with lameness in broiler chickens and identifies evolutionary gait differences. *PLoS ONE*, 7(7), e40800. https://doi.org/10.1371/journal.pone.0040800

Cao, J., Chen, J., & Li, J. (2023). Observation-centric SORT: Rethinking data association for multi-object tracking. *IEEE Transactions on Image Processing*, 32, 2245–2257. https://doi.org/10.1109/tip.2023.3241611

Chaiseha, Y., & El Halawani, M. E. (2015). Brooding. In Sturkie's Avian Physiology: Sixth Edition (pp. 717-738). Elsevier Inc. https://doi.org/10.1016/B978-0-12-407160-5.00031-2

Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys, 41*(3), 1–58. https://doi.org/10.1145/1541880.1541882

Chang, H. (2004). Cross-sector comparisons of poultry production in the Philippines. RePEc: Research Papers in Economics. https://doi.org/10.22004/ag.econ.12896

Chang, H. (2007). Analysis of the Philippine chicken industry: Commercial versus backyard sectors. *AgEcon Search*. https://ageconsearch.umn.edu/record/165854/?v=pdf

Chen, Z., Zhou, X., & Li, F. (2022). Improving multi-object tracking accuracy in dense environments using deep appearance features. *Sensors, 22*(19), 7481. https://doi.org/10.3390/s22197481

Chu, Q., Liu, X., & Wang, Z. (2017). ReID networks for Multi-Object tracking.

Cruz, E., Hidalgo-Rodriguez, M., Acosta-Reyes, A. M., Rangel, J. C., Boniche,

K., & Gonzalez-Olivardia, F. (2025). ACMSPT: Automated Counting and Monitoring System for Poultry Tracking. AgriEngineering, 7(3), 86. https://doi.org/10.3390/agriengineering7030086

Depuru, B. K., Putsala, S., & Mishra, P. (2024). Automating poultry farm management with artificial intelligence: Real-time detection and tracking of broiler chickens for enhanced and efficient health monitoring. *Tropical Animal Health and Production*, *56*(2). https://doi.org/10.1007/s11250-024-03922-2

Du, W., Wang, Y., & Qiao, Y. (2017). Recurrent Spatial-Temporal attention network for action recognition in videos. *IEEE Transactions on Image Processing*, *27*(3), 1347–1360. https://doi.org/10.1109/tip.2017.2778563

Du, Y., Wang, W., & Wang, L. (2017). Hierarchical recurrent neural network for skeleton-based action recognition. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 1110–1118. https://doi.org/10.1109/cvpr.2017.127

Ehsan, T. Z., & Mohtavipour, S. M. (2024). Broiler-Net: A deep convolutional framework for broiler behavior analysis in poultry houses. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2401.12176

Elmessery, W. M., Gutiérrez, J., El-Wahhab, G. G. A., Elkhaiat, I. A., El-Soaly, I. S., Alhag, S. K., Al-Shuraym, L. A., Akela, M. A., Moghanm, F. S., & Abdelshafie, M. F. (2023). YOLO-Based model for automatic detection of broiler pathological phenomena through visual and thermal images in intensive poultry houses. Agriculture, 13(8), 1527. https://doi.org/10.3390/agriculture13081527

Erdaw, M. M., & Beyene, W. T. (2022). Trends, prospects and the socio-economic contribution of poultry production in sub-Saharan Africa: a review. World S Poultry Science Journal, 78(3), 835–852. https://doi.org/10.1080/00439339.2022.2092437

FAST Logistics Blog. (2024, June 13). The state of the Philippine agriculture industry in 2024. Retrieved from https://www.fastlogistics.com.ph/blog/the- state-of-thephilippine-agriculture-industry-in-2024/

Fang, C., Huang, J., Cuan, K., Zhuang, X., & Zhang, T. (2020). Comparative study on poultry target tracking algorithms based on a deep regression network. Biosystems Engineering, 190, 176–183. https://doi.org/10.1016/j.biosystemseng.2019.12.002

Ferreira, V. H. B., Simoni, A., Germain, K., Leterrier, C., Lansade, L., Collin, A., Mignon Grasteau, S., Bihan-Duval, E. L., Guettier, E., Leruste, H., Løvlie, H., Calandreau, L., & Guesdon, V. (2022). Foraging behavior

shows Individual-Consistency over time, and predicts range use in Slow-Growing Free-Range male broiler chickens. Frontiers in Veterinary Science, 9.

Gauthier, J., & Ludlow, R. (2012). Feather maintenance and social behaviors in domestic chickens. Poultry Science, 91(10), 2545–2553. https://doi.org/10.3382/ps.2012-02421

Geffen, O., Yitzhaky, Y., Barchilon, N., Druyan, S., & Halachmi, I. (2020). A machine vision system to detect and count laying hens in battery cages. Animal, 14(12), 2628–2634. https://doi.org/10.1017/S1751731120001676

Gomes, A. V. S., Quinteiro-Filho, W. M., Ribeiro, A., Ferraz-De-Paula, V., Pinheiro, M. L., Baskeville, E., Akamine, A. T., Astolfi-Ferreira, C. S., Ferreira, A. J. P., & Palermo-Neto, J. (2013). Overcrowding stress decreases macrophage activity and increases Salmonella Enteritidis invasion in broiler chickens. Avian Pathology, 43(1), 82–90.

Guo, Y., Aggrey, S. E., Oladeinde, A., Johnson, J., Zock, G., & Chai, L. (2021). A machine Vision-Based method optimized for restoring broiler chicken images occluded by feeding and drinking equipment. *Animals*, *11*(1), 123. https://doi.org/10.3390/ani11010123

Guo, Y., Zhao, H., & Zhang, S. (2022). Time-Based chicken behavior analysis for early disease detection using deep learning. *Computers and Electronics in Agriculture, 193*, 106717. https://doi.org/10.1016/j.compag.2022.106717

Hart, B. L., & Hart, L. A. (2019). Sickness behavior in animals: A programmed response to infection. *Veterinary Immunology and Immunopathology, 212*, 36–45. https://doi.org/10.1016/j.vetimm.2019.04.010

He, K., Gkioxari, G., Dollár, P., & Girshick, R. (2017). Mask R-CNN. In Proceedings of the IEEE International Conference on Computer Vision, 2961–2969.

He, P., Chen, Z., Yu, H., Hayat, K., He, Y., Pan, J., & Lin, H. (2022). Research progress in the early warning of chicken diseases by monitoring clinical symptoms. Applied Sciences, 12(11), 5601. https://doi.org/10.3390/app12115601

He, X., Wang, Y., & Yang, S. (2022). Gaussian mixture CBMeMBer filter for Multi-Target tracking with Non-Gaussian noise.

Hewe, T. R. A., Mondia, K. M. J., & Empas, P. E. G. (2024). Advancing poultry farming efficiency through YOLOv5 and image Regression-Based broiler weight estimation. *2022 13th International Conference on Information and Communication Technology Convergence (ICTC)*, 7–12. https://doi.org/10.1109/ictc62082.2024.10827717

Hussain, M. (2024). YOLOV5, YOLOV8 and YOLOV10: the Go-To detectors for real-time vision. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2407.02988

Jacob J. and T. Pescatore. 2013. Avian Respiratory System. Cooperative Extension Service (11). University of Kentucky College of Agriculture, Food, and Environment, Lexington, KY. https://www.scribd.com/document/376025479/ASC200

Jacob, J. (2021). Aggression and social hierarchy in chickens. *University of Florida IFAS Extension.* https://edis.ifas.ufl.edu/publication/an239

Jacob J. Normal behaviors of chickens in small and backyard poultry flocks. eXtension. University of Kentucky, Lexington, KY. Accessed February 17, 2025, at https://poultry.extension.org/articles/poultry-behavior/ normal-behaviors-of-chickens-in-small-and-backyardpoultry-flocks

Jegham, N., Koh, C. Y., Abdelatti, M., & Hendawi, A. (2024). Evaluating the evolution of YOLO (You Only Look Once) models: A comprehensive benchmark study of YOLO11 and its predecessors. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2411.00201

Jiang, W., Wang, K., Lv, Y., Guo, J., Ni, Z., & Ni, Y. (2019). Time series based behavior pattern quantification analysis and prediction — A study on animal behavior. *Physica a Statistical Mechanics and Its Applications*, *540*, 122884. https://doi.org/10.1016/j.physa.2019.122884

Julianda, R. R., & Puriyanto, R. D. (2024). Tracking ball using YOLOv8 method on wheeled soccer robot with omnidirectional camera. *Buletin Ilmiah Sarjana Teknik Elektro*, *6*(2), 203–213. https://doi.org/10.12928/biste.v6i2.10816

Kalman, R. E. (1960). A new approach to linear filtering and prediction problems. Transactions of the ASME–Journal of Basic Engineering, 82(1), 35–45. https://doi.org/10.1115/1.3662552

Khairunissa, J., Wahjuni, S., Soesanto, I. R. H., & Wulandari, W. (2021, June). Detecting poultry movement for poultry behavioral analysis using the multi-object tracking (MOT) algorithm. In Proceedings of the 8th International Conference on Computer and Communication Engineering (ICCCE 2021) (pp. 265–268). IEEE. https://doi.org/10.1109/ICCCE50029.2021.9467144

Khanam, R., & Hussain, M. (2024). What is YOLOv5: A deep look into the internal features of the popular object detector. *AI Open, 5*(1), 1–13. https://doi.org/10.1016/j.aiopen.2024.02.005

Kishor, R. (2024). Performance benchmarking of YOLOv11 variants for real-time delivery vehicle detection: A study on accuracy, speed, and computational trade-offs. Asian Journal of Research in Computer Science, 17(12), 108-122.

Kumar, S., Vishal, N., Sharma, P., & Pal, N. (2021). Object tracking and counting in a zone using YOLOv4, DeepSORT and TensorFlow. *International Conference on Adaptive and Intelligent Systems*, 1017–1022. https://doi.org/10.1109/icais50930.2021.9395971

Kumar, T. N., Samantara, A., & Gulati, A. (2022). Poultry value chain. In India studies in business and economics (pp. 227–252). https://doi.org/10.1007/978-981-33- 4268-2_7

Kushwaha, P., & Murmu, M.K. (2024). Suspicious activity monitoring system using YOLOv5. *2024 15th International Conference on Computing Communication and Networking Technologies (ICCCNT)*, 1-7.

Lara, L., & Rostagno, M. (2013). Impact of heat stress on poultry production. Animals, 3(2), 356–369. https://doi.org/10.3390/ani3020356

Li, M. & Wu, J. & Chen, Zhong. (2015). Effects of heat stress on the daily behavior of wenchang chickens. Revista Brasileira de Ciência Avícola. 17. 559-566. 10.1590/1516-635x1704559-566.

Li, X., Cai, Z., & Zhao, X. (2022). Oriented-YOLOV5: A real-time oriented detector based on YOLOV5. *2022 7th International Conference on Computer and Communication Systems (ICCCS)*, 216–222. https://doi.org/10.1109/icccs55155.2022.9846234

Liang, J. (2024). A review of the development of YOLO object detection algorithm. *Applied and Computational Engineering*, *71*(1), 39–46. https://doi.org/10.54254/2755-2721/71/20241642

Lianzeng, Y. D. Q. J. C. H. G. Y. W., (2024). Individual behavioral identification and differential analysis of Free-Range laying hens based on improved YOLO v8n model. https://nyjxxb.net/index.php/journal/article/view/2000

Liebhart, D., Stadler, M., & Hess, M. (2023). Definitions of health in poultry and the implications for disease control. *Poultry Science, 102*(4), 102355. https://doi.org/10.1016/j.psj.2023.102355

Luo, W., Xing, J., Milan, A., Zhang, X., Liu, W., & Kim, T.-K. (2019). Multiple object tracking: A literature review. Artificial Intelligence, 293, 103448.

Matthijs MGR, Nieuwenhuis JF. (2019). Dwars RM. Signs indicating imminent death in escherichia coli-Infected broilers. Avian Dis. 61(3):316-324. doi: 10.1637/11509-100316-RegR. PMID: 28956992.

McCrea, B., & Baker, B. (2022). Common backyard chicken behaviors. Alabama Cooperative Extension System. https://www.aces.edu/blog/topics/farming/common-backyard-chicken-behaviors/

McNamara, E. (2023). A guide to chicken diseases and what to do with sick chickens. Chicken Coach. https://chickencoach.com/blogs/learn/backyard-chicken-illness-what-to-do-with-sick-chickens

Melesse, A. (2014). Significance of scavenging chicken production in the r ural community of Africa for enhanced food security. World S Poultry Science Journal, 70(3), 593–606. https://doi.org/10.1017/s004393391400064

Michel V, Berk J, Bozakova N, van der Eijk J, Estevez I, Mircheva T, Relic R, Rodenburg TB, Sossidou EN, Guinebretière M. The relationships between damaging behaviours and health in laying hens. Animals (Basel). 2022 Apr 11;12(8):986. doi: 10.3390/ani12080986. PMID: 35454233; PMCID: PMC9029779.

MSD Veterinary Manual. (n.d.). Social behavior of chickens. In Behavior – Poultry. https://www.msdvetmanual.com/behavior/normal-social-behavior-and-behavioral-problems-of-domestic-animals/social-behavior-of-chickens

Nasiri, A., Yoder, J., Zhao, Y., Hawkins, S., Prado, M., & Gan, H. (2022). Pose estimation-based lameness recognition in broiler using CNN-LSTM network. *Computers and Electronics in Agriculture*, *197*, 106931. https://doi.org/10.1016/j.compag.2022.106931

Neethirajan, S. (2021). ChickTrack - A Quantitative Tracking Tool for Measuring Chicken Activity. TechRxiv.

Nguyen, K. H., Nguyen, H. V. N., Tran, H. N., & Quach, L. (2023). Combining cutoencoder and YOLOv6 model for classification and disease detection in chickens. ICIIT ’23: Proceedings of the 2023 8th International Conference on Intelligent Information Technology, 132–138. https://doi.org/10.1145/3591569.3591591

Nicol C.J. (2015). The behavioral biology of chickens. Centre for Agriculture and Bioscience International. Oxfordshire, UK. doi:10.1079/9781780642499.0000.

Nisar, J., & Kumar, A. (2021). An analysis on the current senior of poultry industry in India. Social Science Learning Education Journal, 6(05), 464– 467. https://doi.org/10.15520/sslej.v6i05.2780

Paramathma, M. K., Kumar, I. B., & Karuppasamypandiyan, M. (2024). YOLO based Automatic Poultry Monitoring System. 2024 3rd International

Conference for Advancement in Technology (ICONAT), 1–6. https://doi.org/10.1109/iconat61936.2024.10774960

Park, H., Noh, J., & Ham, B. (2020). Learning memory-guided normality for anomaly detection. Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 14372–14381.

Ragab, M. G., Abdulkadir, S. J., Muneer, A., Alqushaibi, A., Sumiea, E. H., Qureshi, R., Al-Selwi, S. M., & Alhussian, H. (2024). A comprehensive systematic review of YOLO for medical object detection (2018 to 2023). *IEEE Access*, *12*, 57815–57836. https://doi.org/10.1109/access.2024.3386826

Redmon, J., Divvala, S., Girshick, R., & Farhadi, A. (2016). You Only Look Once: Unified, Real-Time object detection. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 779–788.

Sander, A. (2021). Sickness behavior in chickens*. University of Maryland Extension*. https://extension.umd.edu/resource/sickness-behavior-chickens-fs-1178

Saran, S., Sashidhar, P.V., Sastry, K.V., & Singh, R. (2005). Indian poultry industry: current scenario and future prospects: a review. Indian Journal of Animal Sciences, 75.

Serd, C. J. J. G. (2024). Philippine chicken industry update: Market trends, projected shortages, rising imports, price surges, and DOST-PCAARRD innovations for stability. DOST-PCAARRD ISP Web. https://ispweb.pcaarrd.dost.gov.ph/philippine-chicken-industry-update-market-trends-projected-shortages-rising-imports-price-surges-and-dost-pcaarrd-innovations-for-stability

Sin, P. F., Yang, Y., & Chen, Y. (2024). Development of a web-based application for predicting broiler chicken growth with an LSTM model. 2024 International Conference on Consumer Electronics – Taiwan (ICCE-Taiwan), 497–498. https://doi.org/10.1109/icce-taiwan62264.2024.10674169

Solawetz, J., & Francesco. (2023). What is YOLOv8? The ultimate guide.

Sun, Z., Chen, J., & Mukherjee, M. (2020). A survey of multiple pedestrian tracking based on Tracking-by-Detection framework. IEEE Transactions on Circuits and Systems for Video Technology, 31(5), 1819–1833.

Staudemeyer, R.C., & Morris, E.R. (2019). Understanding LSTM - a tutorial into Long Short-Term Memory Recurrent Neural Networks. *ArXiv, abs/1909.09586*.

Syafaah, L., Faruq, A., & Setyawan, N. (2024). Sick and dead chicken

detection system based on YOLO algorithm. Ingénierie des Systèmes d'Information, 9(25), 45–53. https://doi.org/10.5555/isi2024.sickchicken

Terven, J., Córdova-Esparza, D., & Romero-González, J. (2023). A comprehensive review of YOLO architectures in computer vision: From YOLOv1 to YOLOv8 and YOLO-NAS. *Machine Learning and Knowledge Extraction, 5*(4), 1680–1716. https://doi.org/10.3390/make5040085

The Poultry Site. (2021, November 18). Philippines: Poultry and products annual. Retrieved from https://www.thepoultrysite.com/articles/philippines- poultry-andproducts-annual

Tizard I. 2002. The Avian Antibody Response. Seminars in Avian and Exotic Pet Medicine. 11(1):2-14. doi:10.1053/saep.2002.28216.

Tong, Q., Zhang, E., Wu, S., Xu, K., & Sun, C. (2023b). A real-time detector of chicken healthy status based on modified YOLO. *Signal Image and Video Processing*, *17*(8), 4199–4207. https://doi.org/10.1007/s11760-023-02652-6

Triyanto, W. A., Adi, K., & Suseno, J. E. (2023b). Detection and tracking of broiler flock movements in the chicken coop using YOLO. *E3S Web of Conferences*, *448*, 02064. https://doi.org/10.1051/e3sconf/202344802064

Triyanto, W. A., Adi, K., & Suseno, J. E. (2024). Chicken tracking for location mapping of lameness chickens using YOLOv8 and deep learning-based tracking algorithm. *Indonesian Journal of Electrical Engineering and Computer Science*, *34*(1), 407. https://doi.org/10.11591/ijeecs.v34.i1.pp407-418

Ultralytics. (2024). *YOLOv11: Next-generation real-time object detection model.* Ultralytics Blog. https://docs.ultralytics.com/models/yolo11

van Liere, D.W. (1992) Dustbathing as related to proximal and distal feather lipids in laying hens. Behavioural Processes 26, 177–188

Varghese, R., & M, S. (2024). YOLOv8: A novel object detection algorithm with enhanced performance and robustness. *2024 International Conference on Advances in Data Engineering and Intelligent Computing Systems (ADICS)*, 1–6. https://doi.org/10.1109/adics58448.2024.10533619

Vernooij, A., Masaki, M. N., & Meijer-Willems, D. (2018). Regionalisation in poultry development in Eastern Africa. https://doi.org/10.18174/458221

V Veterinaria Digital. (2022, March 15). El sector avícola filipino crece de forma constante. Retrieved from

https://www.veterinariadigital.com/articulos/elsector-avicola-filipino-crece-de-forma-constante

Wahjuni, S., Wulandari, W., Eknanda, R. T. G., Susanto, I. R. H., & Akbar, A. R. (2023). Automatic detection of broiler's feeding and aggressive behavior using you only look once algorithm. *IAES International Journal of Artificial Intelligence*, *13*(1), 104. https://doi.org/10.11591/ijai.v13.i1.pp104-114

Wang, A., Chen, H., Liu, L., Chen, K., Lin, Z., Han, J., & Ding, G. (2024). YOLOV10: Real-Time End-to-End object detection. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2405.14458

Wang, C., Yeh, I., & Liao, H. M. (2024). YOLOV9: Learning what you want to learn using programmable gradient information. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2402.13616

Wang, C., Zhou, Y., & Lin, C. (2022). A deep learning-based anomaly detection approach for poultry behavior analysis. *Computers and Electronics in Agriculture, 197*, 107001. https://doi.org/10.1016/j.compag.2022.107001

Wang, J., Wang, N., Li, L., & Ren, Z. (2019). Real-time behavior detection and judgment of egg breeders based on YOLO v3. Neural Computing and Applications, 32(10), 5471–5481. https://doi.org/10.1007/s00521-019-04645-4

Weary DM, Huzzey JM, von Keyserlingk MA. (2014). Board-invited review: Using behavior to predict and identify ill health in animals. J Anim Sci. 87(2):770-7. doi: 10.2527/jas.2008-1297. Epub 2008 Oct 24. PMID: 18952731.

Wojke, N., Bewley, A., & Paulus, D. (2017). DeepSORT: Simple online and real-time tracking with a deep association metric. *arXiv preprint arXiv:1703.07402.* https://doi.org/10.48550/arxiv.1703.07402

Xie, B. X., & Chang, C. L. (2022b). Behavior recognition of a broiler chicken using Long Short-Term Memory with Convolution Neural Networks. *Workshop on Computational Approaches to Code Switching*, 1–5. https://doi.org/10.1109/cacs55319.2022.9969848

Yadav, A., Chaturvedi, P. K., & Rani, S. (2023). Tracking performance enhancements in multi-object tracking systems.

Yang, D., Qi, J., Chen, H., Gao, Y., & Wang, L. (2023). Diagnosing infectious diseases in poultry requires a holistic approach: a review. Poultry, 2(2), 252–280. https://doi.org/10.3390/poultry2020020

Yang, X., Bist, R., Paneru, B., & Chai, L. (2024). Monitoring activity index and behaviors of cage-free hens with advanced deep learning

technologies. *Poultry Science*, *103*(11), 104193. https://doi.org/10.1016/j.psj.2024.104193

Yaseen, M. (2024). What is YOLOv9: An In-Depth exploration of the internal features of the Next-Generation object detector. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2409.07813

Zhang, H., Li, S., & Wang, J. (2023). Multi-object tracking of chickens using DeepSORT under dense flock conditions. *Sensors, 23*(4), 2205. https://doi.org/10.3390/s23042205

Zhang, S., Li, X., & Zhao, Y. (2021). Real-Time object tracking in dynamic environments using YOLO and DeepSORT.

APPENDIX A

Letter of Approval

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna

CERTIFICATE OF APPROVAL

This is to certify that after having satisfactorily completed all the requirements of the capstone project entitled:

"OPTIMIZING REAL-TIME OBJECT DETECTION AND TRACKING WITH YOLOv11, DEEPSORT, and LSTM-RNN: A PERFORMANCE ANALYSIS"

MERLYN JOY E. BANASIHAN, ANDREA E. GECOLEA, JOSEF MARCLEIN D. LEONARDO have been granted permission to proceed with their proposal presentation.

As their Research Adviser, I confirm that the proponents have met the academic standards and requirements set forth by the department, and therefore, I approve their request to conduct the final presentation.

GENE MARCK B. CATEDRILLA
Thesis Project Adviser
November 14, 2025

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna

APPROVAL SHEET

The thesis entitled "**OPTIMIZING REAL-TIME OBJECT DETECTION AND TRACKING WITH YOLOv11, DEEPSORT, and LSTM-RNN: A PERFORMANCE ANALYSIS"** prepared and submitted by Merlyn Joy E. Banasihan, Andrea E. Gecolea, and Josef Marclein D. Leonardo in partial fulfillment requirements for the degree Bachelor of Science in Computer Science specialized in Intelligent Systems, is hereby recommended for approval and acceptance.

GENE MARCK B. CATEDRILLA
Thesis Project Adviser

APPENDIX B

Certificate of Acceptance

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna

BAGONG PILIPINAS

April 06, 2025

PERELLO'S POULTRY FARM
Indang, Cavite, Philippines

Subject: Request for Approval to become the Study Area and Installation of CCTV for Data Gathering for Academic Thesis

To whom it may concern,

We, the undersigned third-year Bachelor of Science in Computer Science students from Laguna State Polytechnic University – Los Baños Campus (LSPU-LBC), are currently conducting our undergraduate thesis entitled ***"Optimizing Real-Time Object Detection and Tracking with YOLOv11, DeepSORT, and LSTM-RNN: A Performance Analysis***."

The purpose of our research is to develop an intelligent monitoring framework capable of detecting potentially sick chickens through real-time behavioral analysis using deep learning and computer vision technologies. The study aims to contribute to early disease detection and upgrade animal welfare within poultry environments.

In connection with this, we are respectfully seeking your approval to designate Perello's Poultry Farm as our official study area. We also kindly request permission to install a closed-circuit television (CCTV) camera within a suitable area of your poultry house. The CCTV will serve as our primary instrument for non-intrusive video data gathering. Rest assured that the installation will be conducted with utmost care to avoid disruption to your farm operations and animal welfare.

All collected data will be used solely for academic purposes and treated with strict confidentiality. No sensitive or identifying information about the farm will be disclosed or published without prior consent. Upon completion of the study, the CCTV unit will be promptly removed, and a copy of the final research findings will be shared with your office for reference.

We sincerely hope for your favorable consideration of our request. Your cooperation will play a vital role in the success of our research and will contribute to the advancement of technology-driven poultry health monitoring systems.

Thank you very much for your time and support. We look forward to your kind approval.

Respectfully,

MERLYN JOY E. BANASIHAN
banasihan.merlyn@lspu.edu.ph
Researchers, BS Computer Science

ANDREA E. GECOLEA
andrea.gecolea@lspu.edu.ph
Researchers, BS Computer Science

JOSEF MARCLEIN D. LEONARDO
josefmarclein.leonardo@lspu.edu.ph
Researchers, BS Computer Science

Noted by:

GENE MARCK B. CATEDRILLA
Thesis Adviser

LOYD S. ECHALAR
Associate Dean, College of Computer Studies

APPENDIX C

Relevant Source Code

Hardware Specifications for Coding

Model training and testing were performed on a workstation equipped with the following hardware configuration:

- **GPU:** AMD Radeon RX 6600 (8GB VRAM)
- **CPU:** AMD Ryzen 5 5600X
- **Memory:** 16GM RAM
- **Storage:** 1 TB SSD

The GPU environment was enabled through CUDA to accelerate neural network training. The torch.device("cuda" if torch.cuda.is_available() else "cpu") setup automatically selected the GPU when available.

Python Libraries

To replicate the system, the following libraries must be installed in a Python environment. Each library supports a specific component of the system, such as data preprocessing, deep learning, visualization, and file handling.

The commands below show how to install all required packages using pip:

```
pip install ultralytics
pip install deep-sort-realtime
pip install torch torchvision torchaudio --index-url
https://download.pytorch.org/whl/cu118
pip install opencv-python
pip install numpy
pip install pandas
pip install matplotlib
pip install seaborn
pip install scikit-learn
pip install openpyxl
pip install plotly
pip install streamlit
pip install streamlit-lottie
pip install requests
pip install pyyaml
```

You Only Look Once version 11 (YOLOv11)

Training

```
!pip install ultralytics

# Parse Image
!yolo detect train data=/content/data.yaml model=yolo11s.pt epochs=50
imgsz=640
```

The first code code allows to install the Ultralytics library in Google Colab. This Python library will be used to train the YOLO model. The training algorithm will parse the images in the training and validation directories and then start training the model. At the end of each training epoch, the program runs the model on the validation dataset and reports the resulting mAP, precision, and recall. As training continues, the mAP should generally increase with each epoch. Training will end once it goes through the number of epochs specified by epochs.

Detection

```
# YOLO Inference
results = yolo_model(frame, conf=confidence_threshold, iou=0.3,
verbose=False)
```

In this line of code, the pre-trained YOLO (You Only Look Once) model is applied to each video frame to perform object detection. Specifically, the command results = yolo_model(frame, conf=confidence_threshold, iou=0.3, verbose=False) executes the inference process, where the model analyzes the given frame to identify and localize objects within it. The parameter conf=confidence_threshold defines the minimum confidence score that a detection must have to be considered valid, this helps filter out uncertain or low-probability predictions. Meanwhile, iou=0.3 sets the Intersection over Union threshold, which determines how much overlap is required between predicted bounding boxes to treat them as the same object, thereby reducing duplicate detections. The argument verbose=False disables detailed output logs during inference, making the process cleaner and more efficient.

DeepSORT

```
# Initialize DeepSORT tracker
tracker = DeepSort(max_age=5, n_init=3, max_iou_distance=0.7,
nms_max_overlap=0.9)
```

In this line of code, the DeepSORT tracker is initialized to handle the tracking of detected objects across video frames. The statement tracker = DeepSort(max_age=5, n_init=3, max_iou_distance=0.7, nms_max_overlap=0.9) creates an instance of the DeepSORT algorithm, which works alongside the YOLO detector to maintain consistent object identities during motion. The parameter max_age=5 defines how many consecutive frames an object can remain undetected before its tracking ID is removed. The n_init=3 parameter specifies the number of consecutive detections required before a new object is confirmed as a valid track, helping to avoid false detections. The max_iou_distance=0.7 sets the maximum allowable overlap distance between the predicted bounding box and the detected one when associating objects between frames, ensuring accurate matching. Lastly, nms_max_overlap=0.9 controls the non-maximum suppression threshold to handle overlapping detections efficiently.

Long Short-Term Memory - Recurrent Neural Network (LSTM-RNN)

Training

```
# Ensure x and y are numeric
df[['x', 'y']] = df[['x', 'y']].apply(pd.to_numeric, errors='coerce')
df = df.dropna(subset=['x', 'y'])  # Remove invalid rows
sequences = []
seq_len = 19  # Sequence length for LSTM

# Process each chicken ID
for obj_id, group in df.groupby('id'):
        group = group.sort_values('frame').reset_index(drop=True)
        coords = group[['x', 'y']].values
        # Calculate speed (movement delta)
        speed = np.linalg.norm(np.diff(coords, axis=0), axis=1)
        speed = np.insert(speed, 0, 0)  # First step has no speed
        area = np.full(len(group), 2500)
        # Stack features: x, y, speed, area
        features = np.column_stack((coords, speed, area))
        # Create sequences of fixed length
        for i in range(0, len(features) - seq_len + 1):
                seq = features[i:i+seq_len]
                sequences.append(seq)

# Convert to numpy array
sequences = np.array(sequences, dtype=np.float32)
print(f"Raw sequences shape: {sequences.shape}")
# === Normalize data (important for LSTM training) ===
mean = np.mean(sequences, axis=(0, 1), keepdims=True)
std = np.std(sequences, axis=(0, 1), keepdims=True)
sequences = (sequences - mean) / (std + 1e-8)
```

This section of the code performs the preprocessing of tracking data to prepare it for training the LSTM model. First, the code ensures that the x and y coordinates are numeric values by converting them using pd.to_numeric, while any invalid or non-numeric entries are automatically replaced with missing values. These missing values are then removed from the dataset to maintain data integrity. After cleaning, the data is grouped based on the unique object ID of each chicken. Within each group, the rows are sorted according to their frame numbers to preserve the correct time sequence. The x and y coordinates are then extracted to calculate the movement speed of each chicken using the Euclidean distance between consecutive frames. Since there is no previous frame for the first data point, a zero value is inserted for the initial speed. The area feature is also added with a constant value of 2500 for all frames, representing an estimated detection region.

The features — namely x, y, speed, and area — are combined into a single array for each frame. To prepare the data for sequential analysis, fixed-length sequences of 19 frames are generated using a sliding window approach, creating multiple overlapping sequences from the movement data. These sequences are then converted into a NumPy array for efficient computation. Finally, normalization is applied to ensure all features are scaled to a similar range, which helps the LSTM model learn effectively. The normalization is performed by subtracting the mean and dividing by the standard deviation of the entire dataset, which stabilizes the model's training process and prevents certain features from dominating due to larger numeric ranges.

Hyperparameter for LSTM-RNN

```
input_size = sequences.shape[2]
hidden_size = 128
num_layers = 2
dropout = 0.2
batch_size = 128
learning_rate = 5e-4
num_epochs = 30
early_stop_patience = 5
```

This section defines the hyperparameters used for training the LSTM model, which control how the model learns and generalizes from the input data. The input_size is automatically determined based on the number of features in each sequence, which in this case corresponds to four features: the x-coordinate, y-coordinate, speed, and area. The hidden_size is set to 128, representing the number of neurons in each LSTM layer that determine how much information the model can capture from the temporal patterns in the data. The num_layers value of 2 specifies that the model consists of two stacked LSTM layers, allowing it to learn more complex representations by processing the data at multiple levels of abstraction.

The dropout rate of 0.2 helps prevent overfitting by randomly deactivating 20% of neurons during training, ensuring the model does not rely too heavily on specific patterns in the training data. The batch_size of 128 defines how many sequences are processed together in one forward and backward pass, balancing training stability and computational efficiency. The learning_rate, set to 0.0005, controls how much the model updates its weights during optimization; a smaller value ensures more gradual and stable learning. The model is trained for a total of 30 epochs, meaning it will iterate through the entire dataset 30 times. Lastly, the early_stop_patience of 5 specifies that training will stop automatically if the validation loss does not propel after five consecutive epochs, helping to prevent overfitting and reduce unnecessary computation.

LSTM Autoencoder

```
class LSTMAutoencoder(nn.Module):
    def __init__(self, input_size, hidden_size=128, num_layers=2,
    dropout=0.2):
        super(LSTMAutoencoder, self).__init__()
        # Encoder
        self.encoder_lstm = nn.LSTM(input_size, hidden_size,
        num_layers=num_layers, dropout=dropout, batch_first=True)
        # Bottleneck
        self.bottleneck = nn.Linear(hidden_size, hidden_size // 2)
        self.bottleneck_activation = nn.Tanh()
        # Decoder
        self.decoder_lstm = nn.LSTM(hidden_size // 2, hidden_size,
        num_layers=num_layers, dropout=dropout, batch_first=True)
        self.output_layer = nn.Linear(hidden_size, input_size)
    def forward(self, x):
        encoded, (hidden, cell) = self.encoder_lstm(x)
        bottleneck = self.bottleneck(hidden[-1])
        bottleneck = self.bottleneck_activation(bottleneck)
        bottleneck_seq = bottleneck.unsqueeze(1).repeat(1, x.size(1), 1)
        decoded, _ = self.decoder_lstm(bottleneck_seq)
        output = self.output_layer(decoded)
        return output
```

This section defines the architecture of the LSTM Autoencoder, a deep learning model designed to learn and reconstruct sequential patterns from the input data. The model is implemented as a subclass of PyTorch's nn.Module and consists of three main components: the encoder, the bottleneck, and the decoder.

The encoder is built using an LSTM (Long Short-Term Memory) network, which processes the input sequences over time to capture temporal dependencies and patterns. It takes as input the sequence features (such as position, speed, and area) and compresses them into a smaller set of hidden representations using a hidden layer size of 128 and two stacked LSTM layers. The dropout parameter adds regularization to reduce overfitting by randomly dropping connections between neurons during training.

At the center of the model, the bottleneck acts as a compressed representation of the input data. It uses a fully connected (Linear) layer to reduce the encoded feature dimension by half, effectively forcing the network to retain only the most important temporal information. A Tanh activation function is then applied to introduce non-linearity, ensuring that the model can capture complex relationships in the sequence data.

The decoder reconstructs the original sequence from this compact representation. It mirrors the encoder structure using another LSTM network that expands the bottleneck output back to the original feature size. The bottleneck output is first reshaped and repeated across all time steps so that

the decoder receives temporal context for reconstruction. Finally, an output layer (Linear) maps the decoded features back to the same dimensionality as the input.

During the forward pass, the input passes sequentially through the encoder, bottleneck, and decoder to produce a reconstructed version of the input sequence. By learning to minimize the difference between the input and output, the LSTM Autoencoder effectively captures the normal motion patterns in the data, which can later be used for anomaly detection when reconstruction errors become significantly higher than expected.

APPENDIX D

Evaluation Process & Tool



Figure D1. Validation Process

The researchers conducts its raw dataset validation with Dr. Shiela A. Matibag, and Dr. Mutya N. Quimio, both chicken experts, from the City veterinarian and Slaughterhouse Management Department (LG 16) of Calamba City, Laguna on October 29, 2025. The researchers presents the data to be validated if the data shows healthy chicken or potentially sick chickens. The validation form provides an insightful expert observation to the datasets presented.

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna
Los Baños Campus
College of Computer Studies

OPTIMIZING REAL-TIME OBJECT DETECTION AND TRACKING USING YOLOv11, DEEPSORT, AND LSTM-RNN: A PERFORMANCE ANALYSIS

Andrea E. Gecolea, Merlyn Jor E. Banasihan, Josef Marclein D. Leonardo
Researchers

The primary goal of our research is to develop a real-time tool capable of detecting the behavioral status of chickens. This is achieved by integrating advanced machine learning models (*YOLOv11, DeepSORT, and LSTM-RNN*) to analyze and classify behavioral patterns that may indicate early potential sickness.

This questionnaire, referred to in our study as the Evaluation Tool, is designed to help us evaluate the datasets if the chickens shows signs of potential sickness or healthy. Your honest assessment and expert insights are essential for the validation and refinement of our model.

Our system acts like a highly trained, automated farm observer. Instead of a person constantly watching, a camera and specialized computer software do the job 24/7.

Here's how it works in three simple steps:

1. Spotting the Chickens (YOLOv11)
   - The system first looks at the video feed and uses a smart tool (like an advanced pair of glasses) called YOLOv11 to identify every single chicken in the pen.
   - *Result*: It places a red box around each chicken it sees. This ensures every chicken is accounted for.

2. Tracking Each Individual (DeepSORT)
   - Once a chicken is spotted, the system uses another tool called DeepSORT to give that chicken a unique, invisible ID number.
   - *Result*: Even if a chicken walks behind another or temporarily leaves the view, the system remembers which red box belongs to which unique chicken. This is crucial for tracking its specific behavior over time.

3. Checking for Sickness (LSTM-RNN)
   - This is where the behavioral analysis happens. The system continuously records the movement data (speed, direction, location) of each red bounding box over the last few seconds or minutes.
   - It then uses a predictive tool (LSTM-RNN) that has been taught what normal chicken behavior looks like.

- The system compares the current movement pattern of a specific chicken's red box against the normal pattern.
    - If the red box is moving in an unusual way (e.g., staying still for too long, staggering, or isolating itself), the system flags this as anomalous behavior.
- *Result*: If a chicken's red bounding box shows an anomalous behavior based on its movement pattern, it means the system is detecting a potential sign of sickness based on its *lack of or irregular movement*.

Your role as the expert validator is to carefully observe each chicken in the video clips and evaluate its condition based on visible physical and behavioral indicators. Using your real-world expertise, you are to determine whether each chicken appears healthy or not healthy according to the criteria below.

Validation Procedure

The core purpose of this validation is to assess the model's performance in accurately identifying anomalous chicken behavior.

The validation process will involve the following steps:

1. **Data Provision:** Our research team will provide you with a minimum of 110 short video clips. Each clip will present an instance of chicken inside a frame.

2. **Expert Validation:** As the validator, your expertise will be crucial in determining if the chicken in the frame is healthy or not.

3. **Performance Marking:** Following your review, a scoring table will be provided for you to mark the model's performance on a per-clip basis:

    - A score of **0** will be assigned if the chicken is Healthy.

    - A score of **1** will be assigned if the chicken is showing early sign of sickness or stress.

Please be assured that all your responses will be kept strictly confidential and used solely for academic purposes.

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna
Los Baños Campus
College of Computer Studies

VALIDATION TABLE

Instruction:
Performance Marking: Following your review, this scoring table is provided for you to mark the model's performance on a per-clip basis:

- **Score 1** – Assigned if the chicken in the frame exhibits early signs of sickness or physical and behavioral stress. These may include, but are not limited to:
  - ***Lethargy or unstable motion*** – the chicken shows sluggish movement, imbalance, or reduced responsiveness.
  - ***Abnormal gait or difficulty walking*** – irregular or strained movement patterns.
  - ***Respiratory distress*** – visible signs of difficulty in breathing such as open-mouth breathing, gasping, or labored respiration.
  - ***Physical abnormalities*** – signs of being underweight or overweight, drooping wings, or unkempt feathers indicating poor health.
  - ***Lack of feeding or drinking activity*** – noticeable reduction in normal eating or drinking behavior.

  A score of 1 therefore indicates that the detected chicken shows observable indicators consistent with potential illness, weakness, or physiological stress.

- **Score 0** – Assigned if the chicken in the frame appears healthy and active, showing normal posture, coordinated motion, and typical behavioral patterns.

Sequences	Score
Sequence 1	1
Sequence 2	0
Sequence 3	0
Sequence 4	0
Sequence 5	1
Sequence 6	0
Sequence 7	0
Sequence 8	0
Sequence 9	0

Sequences	Score
Sequence 10	0
Sequence 11	1
Sequence 12	1
Sequence 13	1
Sequence 14	0
Sequence 15	0
Sequence 16	0
Sequence 17	0
Sequence 18	1

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna
Los Baños Campus
College of Computer Studies

Sequence 19	1
Sequence 20	0
Sequence 21	0
Sequence 22	0
Sequence 23	0
Sequence 24	0
Sequence 25	0
Sequence 26	1
Sequence 27	0
Sequence 28	0
Sequence 29	1
Sequence 30	1
Sequence 31	1
Sequence 32	1
Sequence 33	1
Sequence 34	0
Sequence 35	1
Sequence 36	1
Sequence 37	0
Sequence 38	0
Sequence 39	0
Sequence 40	1
Sequence 41	1
Sequence 42	0
Sequence 43	0
Sequence 44	0

Sequence 45	1
Sequence 46	0
Sequence 47	1
Sequence 48	0
Sequence 49	1
Sequence 50	1
Sequence 51	0
Sequence 52	1
Sequence 53	1
Sequence 54	0
Sequence 55	0
Sequence 56	0
Sequence 57	0
Sequence 58	0
Sequence 59	0
Sequence 60	0
Sequence 61	0
Sequence 62	1
Sequence 63	1
Sequence 64	1
Sequence 65	0
Sequence 66	1
Sequence 67	0
Sequence 68	0
Sequence 69	1
Sequence 70	0

Republic of the Philippines
Laguna State Polytechnic University
Province of Laguna
Los Baños Campus
College of Computer Studies

Sequence 71	0	Sequence 91	1
Sequence 72	0	Sequence 92	1
Sequence 73	1	Sequence 93	1
Sequence 74	1	Sequence 94	0
Sequence75	0	Sequence 95	0
Sequence 76	0	Sequence 96	1
Sequence 77	0	Sequence 97	0
Sequence 78	0	Sequence 98	0
Sequence 79	0	Sequence 99	1
Sequence 80	0	Sequence 100	0
Sequence 81	0	Sequence 101	0
Sequence 82	0	Sequence 102	0
Sequence 83	0	Sequence 103	1
Sequence 84	0	Sequence 104	1
Sequence 85	1	Sequence 105	0
Sequence 86	0	Sequence 106	1
Sequence 87	0	Sequence 107	1
Sequence 88	0	Sequence 108	0
Sequence 89	1	Sequence 109	0
Sequence 90	0	Sequence 110	1

Dra. Sheila A. Mathias
Dra. Mutya N. Quimio

Signature over Printed Name
License No.: 4963 / 9247
Date of Validation:

APPENDIX E

Sample Input / Output




Figure E1. Sample input frame before YOLOv11 detection.



Figure E2. Yolov11 Detection Output Showing Bounding Boxes and Confidence Scores at Timestamp 00:03:13.64.



Figure E3. DeepSORT tracking output with ID overlays and real-time timestamp at 00:01:10.04.




Figure E4. LSTM-RNN with Anomaly Detection Output

The figures illustrate the flow of data from the initial model pipeline to the final output. Figure E1 shows a sample of input frames fed into the YOLOv11 model. Each frame contains chickens captured from CCTV footage. After receiving input from the raw data, YOLOv11 performs object detection to identify and locate chickens within each frame. The model outputs bounding boxes around detected chickens, along with labels and confidence scores, as shown in Figure E2 at timestamp 00:03:13.64. This step confirms that YOLOv11 successfully detects individual chickens in real time. Subsequently, the DeepSORT (Deep Simple Online and Realtime Tracking) module builds upon the YOLOv11 detections. Using the bounding boxes and extracted features, DeepSORT assigns unique IDs to each chicken and tracks their movement across frames, as presented in Figure E3 at timestamp 00:01:10.04. Finally, the LSTM-RNN (Long Short-Term Memory Recurrent Neural Network) processes the trajectory and behavioral data obtained from DeepSORT. It analyzes motion patterns of the tracked chickens to detect potential anomalies. Figure E4, captured at timestamp 00:01:10.58, shows the final output—green bounding boxes indicate normal behavior, while red bounding boxes represent detected anomalies.

APPENDIX F

Model Prototype




Figure F1. Landing Page

On the left side of the OPTICHICK starting page, the user is required to enter the name of the model they want to use (ie. my_model.pt). The confidence threshold for YOLO detection can be adjusted to control the sensitivity of object detection results. After setting the threshold, the user must choose the desired input source for detection. There are three options available: Camera for live detection using a connected webcam, Video File for processing smaller video files, and Local File Path for analyzing larger files stored locally on the device.




Figure F2. Loaded Models and Their Respective Metrics

The user must click the Load Models button to verify if the selected model exists and to initiate the tracking process. Once the models are successfully loaded, all performance metrics for both the YOLO and LSTM models will automatically appear.




Figure F3. Live Tracking

After successfully loading the models, the user can begin the tracking process using the selected input source. OPTICHICK will then display live metrics that update in real time based on the results detected in the video. If the user wishes to stop the tracking at any point, they can do so easily using the provided control option.





Figure F4. Tracking History


If the user decides to stop the tracking or when the selected source finishes, OPTICHICK allows the user to save the tracking history for future reference. This history includes detailed data for each detected chicken, which can be downloaded for further analysis or record-keeping.



(a) Threshold of Each Chicken



(b) Status Overview of Each Chicken



(c) Chicken Movement Patterns

Figure F5. Detailed Analytics of Each Chicken

Below the main interface, users can view detailed analytics for each chicken that exceeds the defined anomaly threshold. This section also displays the movement patterns of every tracked chicken, allowing users to analyze their behavior and identify any unusual activity.




Figure F6. User's Guide for the OPTICHICK

This section provides a step-by-step guide on how to properly use OPTICHICK, ensuring that users can efficiently operate the system and make the most of its tracking and analysis features.

APPENDIX G

Curriculum Vitae



MERLYN JOY E. BANASIHAN

09915241017

banasihanmerlyn@gmail.com

Brgy. Bayog, Los Baños, Laguna, Philippines, 4030

SUMMARY

Bachelor of Science in Computer Science majoring in Intelligent Systems, equipped with strong technical and leadership competencies. Skilled in programming languages such as Python, HTML, and CSS, and proficient in using Microsoft applications for documentation and productivity. Adept at creating visually engaging materials through Canva and Figma, combining technical precision with creative design. Experienced in leading teams and managing projects, with a demonstrated ability to communicate effectively, solve problems efficiently, and maintain composure under pressure. Dedicated to leveraging both technical expertise and interpersonal strengths to contribute to the success of innovative and technology-driven organizations.

EDUCATION

- **Laguna State Polytechnic University - Los Baños Campus**
  Bachelor of Science in Computer Science Major in Intellignt Systems (BSCS IS)
  Consistent Dean's Lister
  2022-2026
- **TRACE College**
  Science, Technology, Engineering and Mathematics (STEM)
  Consistent With Honor
  2020-2022
- **Los Baños National High School - Batong Malake**
  Science, Technology, Engineering Program
  2016-2020

SKILLS

- Programming
  - Python
  - HTML
  - CSS
- Basic Microsoft Applications
- Editing
  - Canva
  - Figma

- Leadership
- Teamwork
- Problem-Solving
- Communication
- Time Management
- Emotional Intelligence

PROJECTS

SUMO-BOT
June - July 2025
- An automated robot that pushes other robot out of bounds, it was made to be purely automated where the robot decides to itself its next actions.

ONE SAN ANTONIO
April - May 2025
- A comprehensive barangay application for reservations, acquirement of barangay related papers, and grievance center.

UNILECTION
October - December 2024
- An online voting platform dedicated to specific department.

HOTEL MANAGEMENT SYSTEM
December 2023 - January 2024
- Simple management system of a hotel with functions of booking rooms.

CERTIFICATES

TESDA Online Program
- Computer System Servicing NC II
  Introduction to CSS

TOP-CIT Certification
- Level 2 Category

College Certification
- Basics of Intellectual Property
- Role of Technology in Sustainable Development

LEADERSHIP BACKGROUND

College of Computer Studies - Student Council
- President
  2024-2026



ANDREA E. GECOLEA

09615350001

andreagecoleaa@gmail.com

Brgy. Batong Malake, Los Baños, Laguna, Philippines, 4030

https://andreagecolea.netlify.app/

SUMMARY

Proficient in computer applications with strong communication skills and hands-on experience in web development, backend systems, and machine learning. Skilled in scripting languages such as HTML, CSS, JavaScript, PHP, MySQL, and Python, with experience in API integration and backend development. I have also worked as a project manager in multiple projects, demonstrating leadership, teamwork, and organization. Beyond software, I have a keen interest in hardware technologies, including IoT, and practical experience in repairing computers and mobile devices. I am eager to apply my dedication, adaptability, and continuous learning mindset in a professional environment.

EDUCATION

- **Laguna State Polytechnic University - Los Baños Campus**
  Bachelor of Science in Computer Science Major in Intellignt Systems (BSCS IS)
  Consistent Dean's Lister
  2022-2026
- **Laguna State Polytechnic University**
  Information and Communications Technology (ICT)
  Consistent With Honor
  2020-2022
- **Los Baños National High School - Batong Malake**
  Consistent With Honor
  2016-2020

SKILLS

- Programming
  - Python
  - HTML
  - CSS
  - JavaScript
  - PHP
  - MySQL
- Basic Microsoft Applications
- Machine Learning
- Editing
  - Canva
  - Figma
- Leadership
- Teamwork
- Problem-Solving
- Communication
- Time Management
- Emotional Intelligence

PROJECTS

SAFEPAWS
June - July 2025
- Real-time pet tracker using ESP32, GPS, and Wi-Fi with a web dashboard for live monitoring and alerts. Integrated KNN machine learning to analyze pet movement patterns.

ONE SAN ANTONIO
April - May 2025
- A comprehensive barangay application for reservations, acquirement of barangay related papers, and grievance center.

PiyuHub
October - December 2024
- Created a secure web app for LSPU-LB students with posting, chatbot, and communication features to improve campus connectivity and access to resources.

Other Projects:
- Mr. BIn (IOT)
- EfficienDO (Web App)
- FakeBook (Web App)

CERTIFICATES

TESDA Online Program
- Computer System Servicing NC II
  Introduction to CSS

TOP-CIT Certification
- Level 2 Category

College Certification
- Role of Technology in Sustainable Development

LEADERSHIP BACKGROUND

College of Computer Studies - Student Council
- Recording Secretary
  2024-2026



JOSEF MARCLEIN D. LEONARDO

09266326969

marcleinleonardo@gmail.com

Brgy. Mayondon, Los Baños, Laguna, Philippines, 4030

SUMMARY

Bachelor of Science in Computer Science Major in Intelligent Systems student with a strong foundation in programming, with a strong academic record and, a passion for creating impactful digital experiences. As a student leader, I have honed my skills in organization, teamwork, and communication. I am a creative, reliable, and passionate individual who thrives when working under pressure. I am proficient in front-end development and UI/UX design, and I'm eager to apply my technical and leadership skills in a professional environment.

EDUCATION

- **Laguna State Polytechnic University - Los Baños Campus**
  Bachelor of Science in Computer Science Major in Intellignt Systems (BSCS IS)
  Consistent Dean's Lister
  2022-2026
- **Los Baños Senior High School**
  Science, Technology, Engineering and Mathematics (STEM)
  Consistent With Honor
  2020-2022
- **Los Baños National High School - Batong Malake**
  Consistent With Honor
  2016-2020

SKILLS

- Programming
  - Python
  - HTML
  - CSS
  - PHP
- Basic Microsoft Applications
- Editing
  - Canva
  - Figma
  - Adobe Lightroom

- Leadership
- Teamwork
- Problem-Solving
- Communication
- Time Management
- Emotional Intelligence

PROJECTS

SMART ATTENDANCE USING RFID
June 2025-July 2025
- An automated attendance checker with integration of machine learning to predict students future class panctuality.

ONE SAN ANTONIO
April 2025-May 2025
- A comprehensive barangay application for reservations, acquirement of barangay related papers, and grievance center.

UNILECTION
October2024-December 2024
- An online voting platform dedicated to specific department.

Other projects
- **Aquasense**
  April 2024-May 2024
- **Rutilaok Point of Sale (POS)**
  November 2023-January 2024
- **GUESS THE NUMBER: Simple Math Game**
  March 2023-May 2023

CERTIFICATES

TESDA Online Program
- Computer System Servicing NC II
  Introduction to CSS
- Visual Graphic Design NC III
  Introduction to Visual Graphic Design

TOP-CIT Certification
- Level 2 Category

Other Certifications
- Role of Technology in Sustainable Development
- Mayondon Youth Entrepreneurship Workshop
- Mayondon Youth Leadership Training

LEADERSHIP BACKGROUND

College of Computer Studies - Student Council
- Executive Secretary
  2024-Present

Beverly Hills Youth Organization - Shutterstock
- President
  2023-Present

SK Volunteer - Mayondon
2022 - Present

APPENDIX H

User's Guide

OPTIMIZING REAL-TIME OBJECT DETECTION AND TRACKING WITH YOLOV11, DEEPSORT, AND LSTM-RNN: A PERFORMANCE ANALYSIS

BANASIHAN, MERLYN JOY E., GELCOLEA, ANDREA E., LEONARDO, JOSEF MARCLEIN D.


WHAT IS THIS SYSTEM FOR?

This system ***(OPTICHICK)*** uses a framework of three algorithms— ***YOLOv11, DeepSORT, and LSTM-RNN with Autoencoder*** to detect anomalous behavior in chickens, which can indicate early signs of sickness like lethargy and uneven motion. This system helps to detect and localize each chicken in an occluded area and simultaneously analyzes their behavioral patterns for anomalies.

HOW TO USE THE SYSTEM

1 LOADING PAGE

The OPTICHICK starting page requires the user to enter the model name and set the YOLO confidence threshold. Users then select an input source from three options: ***Camera*** (live detection), ***Video File*** (smaller videos), or ***Local File Path*** (larger, local files).




2 LOADED MODELS

The user must click the Load Models button to verify if the selected model exists and to initiate the tracking process. Once the models are successfully loaded, all performance metrics for both the ***YOLO and LSTM*** models will automatically appear.



3 LIVE TRACKING

Once models are loaded, the user can start tracking. OPTICHICK displays ***real-time metrics*** based on the detected results. Users can stop tracking at any point via the control option.




4 TRACKING HISTORY

Upon stopping the tracking or source completion, OPTICHICK lets the user save the tracking history. This detailed chicken data can then be downloaded for analysis and record-keeping.



5 DETAILED ANALYTICS

Below the main interface, users can see ***detailed analytics for chickens exceeding the anomaly threshold***. The system also displays movement patterns for all tracked chickens, aiding in the identification of unusual activity



APPENDIX I

Matrix for Revisions

MATRIX FOR REVISIONS

Commentors	Positions	Comments	Page No.	Actions	Page No.
Mrs. Carolina R. Joval	Statistician	Remove Formula in the Model Evaluation	57-63	The researchers remove all the formulas for model evaluation and model validation.	57-62
Mrs. Carolina R. Joval	Statistician	Focus the Ethical Consideration on the Model and the Farm, not on the chicken	64	The ethical consideration part of the study considered the concern of the poultry farm owner.	63-64
Mr. Gene Marck B. Catedrilla	Adviser	***Hardware inconsistency:*** Intel UHD 620 does NOT support CUDA. Fix GPU + CUDA issue (most important).	129	Instead of Intel UHD 620, the researchers updated the GPU to AMD radeon RX 6600 (8GB VRAM). Also, the researchers stated that the torch.device("cuda" if torch.cuda.is_available( ) else "cpu") setup ***automatically selected the GPU when available***.	129
Mr. Gene Marck B. Catedrilla	Adviser	Polish grammar in prelim pages (Acknowledgment, Dedication).	iii, iv	The researchers grammatically corrected the grammar of the acknowledgement and dedication to make those parts direct and formal.	iii, iv
Mr. Gene Marck B. Catedrilla	Adviser	Reconstruction loss was mentioned, but explanation lacks numeric justification. Add: Threshold = mean + k*std Add 1–2 sentences explaining threshold selection for LSTM.	76	The formula was added and changed the anomaly threshold from 0.7 to 0.35. detailed paragraph was indicated after the formula and table explaining the usage of LSTM-RNN in the study.	75-79
Mr. Gene Marck B. Catedrilla	Adviser	Improve the abstract's flow. Make it tighter and more direct. Shorten abstract by 3–4 sentences.	v	Abstract was made more direct where unnecessary explanations written where discarded. Also, the abstract focuses on the implementation of	v

				the algorithms, model evaluation, and result of model validation.	
Mr. Gene Marck B. Catedrilla	Adviser	Add more explicit limitations in Conclusion.	89	The limitations gained in the duration of the study, specifically limited datasets, one specific farm application, and limited motion behaviors were added in the conclusion.	89
Mr. Gene Marck B. Catedrilla	Adviser	Add computation time / performance speed	82	To address the comment, the researchers indicated the model's FPS and computational time under Table 12, where it compares the proposed model to previous one.	82
Dr. Jefferson L. Lerios	Subject Specialist	Change Research Coordinator to Member	ii	The researchers changed the description into member	ii
Dr. Jefferson L. Lerios	Subject Specialist	Add Keywords, Conclusion, and Recommendation	v	Summary of conclusion and recommendation of the study was added. Also, keywords from the IEEE format were added.	v
Ms. Myra V. Paicaglino	Technical	Change the table borders into double bars	31-33, 35, 52, 53, 70, 72, 75, 78, 80, 82, 85-86	The researchers change the border of each table used in the study.	31-33, 35, 52, 53, 70, 72, 75, 78, 80, 82, 85-86

APPENDIX J

Grammarly & Turnitin Report

GRAMMARLY REPORT

(FINAL) CHAPTER 1-3

by xel

General metrics

66,646	9,252	438	37 min 0 sec	1 hr 11 min
characters	words	sentences	reading time	speaking time

Score

99

This text scores better than 99% of all texts checked by Grammarly

Writing Issues

6	5	1
Issues left	Critical	Advanced

Plagiarism

This text hasn't been checked for plagiarism

Performance

Text score: 99 out of 100. This score represents the quality of writing in this document. You can increase it by addressing Grammarly's suggestions.

99

Word count

Characters	66,645	Reading time	37 min 0 sec
Words	9,252	Speaking time	1 hr 11 min
Sentences	438		

Readability

Metrics compared to other Grammarly users

Word length	5.8	Above average
Sentence length	21.1	Above average
Readability score	17	

Your text is likely to be understood by college graduates but may not be easy for many to read.

Vocabulary

Metrics compared to other Grammarly users

Unique words	20%	Below average
Rare words	46%	Below average

(FINAL) CHAPTER 4-5

by xel

General metrics

45,580	6,269	364	25 min 4 sec	48 min 13 sec
characters	words	sentences	reading time	speaking time

Score



This text scores better than 99% of all texts checked by Grammarly

Writing Issues

5	4	1
Issues left	Critical	Advanced

Plagiarism

This text hasn't been checked for plagiarism

Performance

Text score: 99 out of 100. This score represents the quality of writing in this document. You can increase it by addressing Grammarly's suggestions.

99

Word count

Characters	45,579	Reading time	25 min 4 sec
Words	6,269	Speaking time	48 min 13 sec
Sentences	364		

Readability

Metrics compared to other Grammarly users

Word length	5.8	Above average
Sentence length	17.2	Above average
Readability score	20	

Your text is likely to be understood by college graduates but may not be easy for many to read.

Vocabulary

Metrics compared to other Grammarly users

Unique words	20%	Below average
Rare words	47%	Below average

TURNITIN REPORT

6% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography
- Quoted Text
- Cited Text
- Small Matches (less than 10 words)

Match Groups

103 Not Cited or Quoted 6%
Matches with neither in-text citation nor quotation marks

0 Missing Quotations 0%
Matches that are still very similar to source material

0 Missing Citation 0%
Matches that have quotation marks, but no in-text citation

0 Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

Top Sources

4% Internet sources
3% Publications
5% Submitted works (Student Papers)

Integrity Flags

1 Integrity Flag for Review

Replaced Characters
214 suspect characters on 52 pages
Letters are swapped with similar characters from another alphabet.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- **103** Not Cited or Quoted 6%
  Matches with neither in-text citation nor quotation marks
- **0** Missing Quotations 0%
  Matches that are still very similar to source material
- **0** Missing Citation 0%
  Matches that have quotation marks, but no in-text citation
- **0** Cited and Quoted 0%
  Matches with in-text citation present, but no quotation marks

Top Sources

- 4% Internet sources
- 3% Publications
- 5% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Internet	
www.mdpi.com		<1%
2	Internet	
www.researchgate.net		<1%
3	Submitted works	
Regent Independent School and Sixth Form College on 2025-05-22		<1%
4	Submitted works	
University of Wales Institute, Cardiff on 2023-05-07		<1%
5	Internet	
arxiv.org		<1%
6	Publication	
Challa, Koundinya. "Harnessing Deep Learning and Sensor Technologies for Susta...		<1%
7	Submitted works	
National Institute of Technology Delhi on 2025-12-18		<1%
8	Publication	
Bo X. Xie, Chung L. Chang. "Behavior Recognition of a Broiler Chicken using Long ...		<1%
9	Publication	
M Mohamed Musthafa, Mahesh T R, Vinoth Kumar V, Suresh Guluwadi. "Enhance...		<1%
10	Submitted works	
The University of Manchester on 2024-09-06		<1%

11	Publication	
Bist, Ramesh Bahadur. "Precision Farming Technologies for Enhancing Air Quality...		<1%
12	Submitted works	
Universiti Malaysia Pahang on 2025-07-11		<1%
13	Internet	
pmc.ncbi.nlm.nih.gov		<1%
14	Internet	
phd.lib.uni-corvinus.hu		<1%
15	Publication	
Rejwan Bin Sulaiman, Usman Javed Butt, Yassine Maleh, Mohammad Aljaidi, Md. ...		<1%
16	Submitted works	
University of Salford on 2023-05-04		<1%
17	Internet	
irjet.net		<1%
18	Submitted works	
University of Bristol on 2024-01-10		<1%
19	Internet	
ebin.pub		<1%
20	Internet	
www.ijesr.org		<1%
21	Internet	
www.ijraset.com		<1%
22	Submitted works	
Liverpool John Moores University on 2025-05-16		<1%
23	Submitted works	
University of Hong Kong on 2023-07-30		<1%
24	Internet	
medium.com		<1%

25 Submitted works
University of South Wales - Pontypridd and Cardiff on 2025-06-03 <1%

26 Submitted works
University of Nueva Caceres on 2025-12-19 <1%

27 Internet
assets-eu.researchsquare.com <1%

28 Internet
ms.codes <1%

29 Submitted works
Liverpool John Moores University on 2024-07-14 <1%

30 Publication
Mohamed Ahmed Alloghani. "Chapter 6 Artificial Intelligence for Ocean Conserva... <1%

31 Submitted works
The University of Manchester on 2024-04-26 <1%

32 Internet
citizenside.com <1%

33 Internet
patents.google.com <1%

34 Submitted works
Central Philippines State University - Main Campus on 2025-04-04 <1%

35 Submitted works
Liverpool John Moores University on 2023-09-09 <1%

36 Submitted works
Liverpool John Moores University on 2023-11-25 <1%

37 Submitted works
University Politehnica of Bucharest on 2025-09-09 <1%

38 Submitted works
University of Strathclyde on 2024-08-12 <1%

39 Submitted works
AIE Institute on 2023-09-07 <1%

40 Submitted works
University of Sydney on 2024-11-09 <1%

41 Submitted works
University of Wah on 2025-12-14 <1%

42 Internet
pure-oai.bham.ac.uk <1%

43 Internet
scholarcommons.scu.edu <1%

44 Internet
web.unlv.edu <1%

45 Publication
Demarais, Thomas Joseph. "A Non-Experimental Comparative Study Measuring th... <1%

46 Submitted works
Ghana Technology University College on 2024-10-31 <1%

47 Publication
Goodnews Michael, Essa Q. Shahra, Shadi Basurra, Wenyan Wu, Waheb A. Jabbar. ... <1%

48 Publication
Md Zia Uddin. "Machine Learning and Python for Human Behavior, Emotion, and ... <1%

49 Internet
open-innovation-projects.org <1%

50 Internet
www.certstopics.com <1%

51 Publication
"Proceedings of the International Conference on Smart Cities - Volume 2", Spring... <1%

52 Submitted works
Anna University on 2025-09-22 <1%

53 Submitted works
CSU, Fullerton on 2024-10-27 <1%

54 Submitted works
Cranfield University on 2023-08-18 <1%

55 Publication
Debasis Chaudhuri, Jan Harm C Pretorius, Debashis Das, Sauvik Bal. "Internationa... <1%

56 Publication
Kantiotis, Nikolaos. "Object Detection in Basketball Game Videos", University of P... <1%

57 Submitted works
Liverpool John Moores University on 2024-07-29 <1%

58 Publication
O. Geffen, Y. Yitzhaky, N. Barchilon, S. Druyan, I. Halachmi. "A machine vision syst... <1%

59 Publication
Otudi, Hussain. "Modeling Infrequent Events by Integrating Noisy Data From Mul... <1%

60 Internet
cris.bgu.ac.il <1%

61 Submitted works
Adama Science and Technology University on 2023-06-13 <1%

62 Submitted works
FICT on 2025-12-18 <1%

63 Publication
Heiga Zen, Hasim Sak. "Unidirectional long short-term memory recurrent neural ... <1%

64 Submitted works
NOVA School of Business and Economics on 2025-12-17 <1%

65 Submitted works
RMIT University on 2023-08-27 <1%

66 Submitted works
The University of Manchester on 2024-04-19 <1%

67 Submitted works
The University of Manchester on 2025-04-11 <1%

68 Submitted works
UCSI University on 2024-08-05 <1%

69 Submitted works
Universiti Teknikal Malaysia Melaka on 2025-06-23 <1%

70 Submitted works
University of Liverpool on 2025-09-26 <1%

71 Submitted works
University of Nottingham on 2025-05-19 <1%

72 Submitted works
University of Technology, Sydney on 2024-05-29 <1%

73 Publication
Xiao Yang, Ramesh Bist, Bidur Paneru, Lilong Chai. "Monitoring Activity Index an... <1%

74 Internet
dspace.univ-guelma.dz <1%

75 Internet
homeworkguru.com <1%

76 Internet
www.frontiersin.org <1%

APPENDIX K

Publishable Paper (IEEE format)

Optimizing Real-Time Object Detection and Tracking with YOLOv11, DeepSORT, and LSTM-RNN: A Performance Analysis

Andrea E. Gecolea
College of Computer Studies
Laguna State Polytechnic University
Laguna, Philippines
andrea.gecolea @lspu.edu.ph

Merlyn Joy E. Banasihan
College of Computer Studies
Laguna State Polytechnic University
Laguna, Philippines
merlynjoy.banasihan@lspu.edu.ph

Josef Marclein D. Leonardo
College of Computer Studies
Laguna State Polytechnic University
Laguna, Philippines
josefmarclein.leonardo@lspu.edu.ph

Gene Marck B. Cetedrilla
College of Computer Studies
Laguna State Polytechnic University
Laguna, Philippines
catedrilla.genemarck@gmail.com

Abstract*—This study developed an integrated deep learning framework for detecting potentially sick chickens through real-time behavioral analysis, addressing the limitations of traditional manual monitoring and the difficulty of detecting occluded chickens. The proposed system combined YOLOv11 for object detection, DeepSORT for multi-object tracking, and LSTM-RNN for temporal behavior recognition to identify anomalies such as lethargy and unsteady walking. Using video data collected from Perello's Poultry Farm in Cavite, a total of 2,549 annotated and augmented training images were utilized. The YOLOv11 model achieved high detection accuracy even under occluded conditions, with a precision of 0.84, recall of 0.88, specificity of 0.90, F1-score of 0.86, and mAP@0.50 of 0.91, while DeepSORT maintained consistent identity tracking in dense flocks. The LSTM-RNN model effectively distinguished normal from anomalous behaviors, yielding a Mean Squared Error (MSE) of 0.004, Mean Absolute Error (MAE) of 0.047, Root Mean Squared Error (RMSE) of 0.063, and a coefficient of determination (R^2) of 0.96, confirming its reliability in temporal sequence classification. The confusion matrix produced an overall accuracy of 0.89, indicating close agreement between the model and expert evaluations. Moreover, the paired samples t-test revealed $t(109) = -0.576$, $p = 0.566$, showing no significant difference between the model's predictions and the poultry expert's assessments. These results confirm that the integrated YOLOv11–DeepSORT–LSTM-RNN framework demonstrates expert-level performance, reliability, and effectiveness in real-time identification of potentially sick chickens for automated poultry health monitoring.

Keywords*—You Only Look Once version 11 (YOLOv11), DeepSORT, Long Short-Term Memory – Recurrent Neural Network (LSTM-RNN), Anomaly Detection, Behavioral Analysis, Poultry Health Monitoring.

I. INTRODUCTION

Chickens that display unusual behaviors such as prolonged inactivity or decreased movement may be showing early signs of illness. In most poultry farms, health assessment still depends on farmers' personal observation—spotting visible symptoms like weakness or poor feeding habits, which usually appear only when a disease is already established [1]. This delay often leads to high mortality and financial loss. To address this, the present study aims to detect and classify chicken health conditions using video data from Perello's Poultry Farm through an integrated machine learning model combining YOLOv11 for object detection, DeepSORT for identity tracking, and LSTM-RNN with anomaly detection for behavior analysis. This approach can handle occlusion, track multiple chickens simultaneously, and detect motion irregularities linked to early signs of sickness.

The rise of artificial intelligence (AI) and computer vision has accelerated automation in livestock management. Algorithms such as You Only Look Once (YOLO) [2] brought a major breakthrough by introducing simultaneous localization and classification through a single convolutional network. Since YOLOv3, later versions up to YOLOv11 have achieved notable gains in speed, precision, and robustness through anchor-free detection, transformer-based attention, and enhanced feature extraction [3]–[6]. These advances have enabled detection of small, occluded, and fast-moving animals, making YOLOv11 suitable for poultry environments with dense and overlapping flocks [6].

However, object detection alone is not capable in analyzing temporal differences through movements of individual chickens. Maintaining identity of individual chickens across frames remains a major challenge, especially in solving occlusions and complex situations. DeepSORT addresses this issue through integration of Kalman Filter with appearance-based feature embeddings to preserve identity of an object [7].

When combine with YOLO, it can achieve a 94% accuracy in poultry monitoring applications [8]. This synergy between detection and tracking ensures continuous behavior analysis of individual chickens, enabling precise motion trajectory reconstruction and behavioral profiling.

To interpret behavioral changes rather than mere movement, temporal modeling is needed. Long Short-Term Memory (LSTM) networks within Recurrent Neural Networks (RNNs) have proven highly effective in capturing motion sequences and identifying activity patterns [9], [10]. When coupled with autoencoder-based anomaly detection, LSTM models can highlight deviations from normal behavior, such as abrupt inactivity or irregular gait, that may signal emerging illness [11]–[14]. This strategy reduces reliance on subjective human judgment and enables early, automated alerts.

Deploying these algorithms in actual farm settings, however, introduces challenges such as inconsistent lighting, crowding, and hardware limitations that affect real-time performance [15]-[18]. Previous research has often focused on optimizing individual components—detection, tracking, or classification—without integrating them into a unified behavioral analysis pipeline.

To overcome these gaps, this study proposes an integrated deep learning framework that combines YOLOv11 for robust object detection, DeepSORT for identity-preserving tracking, and LSTM-RNN with anomaly detection for temporal behavior classification. This unified approach enables real-time identification of potentially sick chickens by analyzing motion irregularities such as reduced movement, clustering, and inactivity. Using video datasets collected from Perello's Poultry Farm in Cavite, Philippines, the proposed system achieved a mean average precision (mAP@0.50) of 97.4% in object detection, and an overall behavioral classification accuracy of 89.09%, validated against expert-labeled data through a paired-sample t-test ($p = 0.566$), demonstrating strong consistency between model predictions and expert assessments.

In summary, this research advances the field of intelligent poultry health monitoring by uniting detection, tracking, and temporal analysis within a single pipeline. The proposed YOLOv11–DeepSORT–LSTM-RNN framework provides a reliable and scalable solution for automated disease detection in poultry farms, reducing dependence on manual inspection and contributing to more sustainable, biosecure, and data-driven agricultural practices.

A. *Objectives of the Study*

This research seeks to develop a tool capable of detecting the chicken's health, with the goal of early potentially sick detection of the chicken. This project intends to accomplish the following objectives.

1. To implement and train the YOLOv11 model for accurate detection of chicken in occluded area.

2. To integrate YOLOv11 output for object detection with DeepSORT for multi-object tracking and LSTM-RNN with anomaly detection for behavioral classification in motion of potentially sick chicken.

3. Analyze and classify potentially sick chickens based on anomaly behavior by evaluating the following metrics such as Precision, Recall, F1 Score, mAP@0.50 and mAP@0.50:0.95 (mean average precision at different IoU thresholds), Confusion Matrix, and Precision-Recall Curves for YOLOv11 in object detection, and Mean Squared Error, and Standard Deviation for LSTM-RNN with Anomaly Detection for behavioral analysis.

4. Evaluate system's performance used for the detection of potentially sick chickens using Confusion Matrix of Model and Expert, and Paired T-Test.

II. METHODOLOGY

B. Model Architecture

The first stage of the pipeline employs YOLOv11 (You Only Look Once version 11), a state-of-the-art real-time object detection algorithm. YOLOv11 is an advancement over previous versions, integrating more refined convolutional backbones and optimization techniques to boost accuracy and speed. Its one-stage detection architecture allows it to simultaneously predict bounding boxes and class probabilities directly from full images, making it highly efficient for real-time detection. This capability is essential for detecting multiple chickens in farm environments where occlusions, overlapping objects, and varying lighting conditions are present.

Following detection, the second stage involves DeepSORT (Simple Online and Realtime Tracking with a Deep Association Metric). DeepSORT augments the original SORT algorithm by incorporating deep learning-based appearance descriptors, allowing for more robust tracking even under object occlusion and identity switches. It assigns consistent identities to each chicken across frames, thereby generating continuous trajectory data. This information is critical for analyzing temporal patterns in movement, which are used to assess behavioral anomalies potentially linked to illness.

The final stage utilizes a Long Short-Term Memory Recurrent Neural Network (LSTM-RNN) to analyze the time series data generated by DeepSORT. LSTM-RNNs are specifically designed to model sequential data and are capable of learning long-term dependencies. Their gated architecture allows them to retain relevant information over time while discarding noise, making them highly suitable for behavior recognition tasks. In this study, the LSTM model is trained on the movement patterns and positional data of individual chickens to classify whether their behavior aligns with healthy or potentially diseased states. The behavioral data includes features such as walking speed, movement consistency, resting duration, and proximity to other chickens.




FIGURE 3. MOCEL ARCHITECTURE OF YOLOV11-DEEPSORT-LSTM-RNN FRAMEWORK

IV. Model Evaluation

The trained YOLOv11 model for chicken detection was evaluated using standard object detection metrics that reflect both classification accuracy and bounding box precision. These evaluation metrics provide insights into how well the model identifies chickens in images and localizes them accurately. The evaluation focused on key indicators such as Precision, Recall, F1 Score, mAP@0.50, mAP@0.50:0.95, and Precision-Recall Curves, which are commonly used in computer vision tasks.

Additionally, separate Precision Curve and Recall Curve were generated during training and evaluation to monitor how precision and recall evolved over time. These curves help diagnose issues such as overfitting or underfitting and guide adjustments to training strategies or hyperparameters.

For the performance of LSTM-RNN with anomaly detection, these evaluation metrics provide insights into how well the model identifies potentially sick chickens in the video such as Mean Squared Error, Mean Absolute Error, Root Mean Squared Error, and Coefficient of Determinatation. The use of these evaluation metrics is crucial in assessing the overall effectiveness, reliability, and robustness of both the YOLOv11 model for chicken detection and the LSTM-RNN model for anomaly detection.

V. Model Validation

Model validation was carried out to evaluate the generalization performance of the chicken detection and behavior classification model. A separate validation dataset, distinct from the training data, was utilized to assess the model's capability in detecting chickens and classifying their behavior under conditions it had not previously encountered.

The validation process involved tracking specific performance metrics that were automatically recorded by the training framework, which in this case was based on a deep learning object detection and tracking architecture combined with behavior analysis. Each of these validation metrics plays a significant role in interpreting how well the model performs in identifying, localizing, and classifying chickens. This focused on key indicators such as Validation Box Loss, Validation Classification Loss, Validation Distribution Focal Loss, Learning Rate Progression, Confusion Matrix, and Paired T-Test Validation.

In addition, expert validation was conducted to establish the ground truth against which the model's predictions were compared. The results from this expert-based evaluation were then used to generate a confusion matrix, providing a detailed comparison between the model's detections and the actual observed behaviors for further accuracy assessment.

III. RESULTS AND DISCUSSION

- ***Exploratory Data Analysis***

This specific model was selected for its robust features, including its high-definition video capabilities and its pan/tilt functionality, which allowed for flexible positioning and comprehensive coverage of the chicken pen. The camera was precisely mounted at an elevation of 77 inches (approximately 195.58 centimeters) above the chicken pen. Over the course of the data collection period with a total of 54,000 frames, a substantial dataset comprising 2549 individual augmented images was successfully used. Each image boasted a crisp resolution of 1080p (1920 x 1080 pixels), providing an exceptional level of detail vital for granular analysis of avian physiology and behavior.

1. YOLOv11 Model Implementation and Training

In accordance with the first objective, the YOLOv11 model was implemented and trained to accurately detect chickens even in occluded areas. This objective aimed to establish a reliable detection component capable of operating under realistic farm conditions characterized by dense populations and varying illumination. In the initial stage of the pipeline, YOLOv11 is critically utilized for its ability to accurately and efficiently detect and localize individual chickens within dynamic video frames across diverse farm environments, adeptly handling challenges such as occlusions and varying lighting conditions. The effectiveness of the YOLOv11 model is inherently linked to the quality and diversity of its training data. As shown in Fig. 6, it presents representative samples from the dataset utilized for YOLOv11 training, visually demonstrating the variety of chicken postures, environmental settings, and lighting conditions that contributed to the model's robust learning and generalization capabilities.




FIGURE 6. YOLOV11 TRAINING OUTPUTS SHOWING DETECTED CHICKENS

As shown in Table I, the training of the YOLOv11 model involves careful selection and optimization of several hyperparameter. These critical parameters, such as the learning rate, batch size, and network architecture specifics, were configured to enhance detection accuracy and efficiency. This diligent hyperparameter tuning process was essential to comprehensively enhance YOLOv11's detection accuracy and efficiency, ensuring reliable chicken identification under a wide range of operational conditions.

TABLE I. OPTIMIZED HYPERPARAMETERS OF YOLOV11

Hyperparameter	Value
epochs	50
optimizer	Auto
lr0	0.01
lr1	0.01
imagsz	640
batch_size	16
patience	100
weight_decay	0.0005
momentum	0.937
iou	0.7

As shown in Fig.7, presents the output of the trained YOLOv11 model during the detection and validation phase. The image shows multiple bounding boxes drawn around each detected chicken, along with their corresponding class label ("Chicken") and confidence score, which indicates the model's certainty in each prediction. The displayed confidence levels, mostly above 85%, demonstrate that the model effectively distinguishes individual chickens from the background and other possible noise in the image.



FIGURE 7. YOLOV11 INFERENCE RESULTS ON POULTRY VIDEO FRAMES

2. Integration of YOLOv11 to DeepSORT, and LSTM-RNN for Multi-Object Tracking and Anomaly-Based Behavioral Classification

Aligned with the second objective, the integration of YOLOv11 with DeepSORT and LSTM-RNN was implemented to enable continuous detection, tracking, and behavioral analysis of individual chickens. After the careful annotation of every chicken in the frame and model training for object detection, the output of the YOLOv11 will be the input that DeepSORT will utilize to enhances multi-object tracking by integrating deep learning-based appearance descriptors with the SORT algorithm, ensuring robust and consistent identity assignments to each chicken across video frames. Upon training with the algorithm, Kalman Filter was implemented for assigning unique ID to individual chicken.

As shown in Table II, the optimized hyperparameters of DeepSORT were adjusted to improve detection association, tracking stability, and appearance similarity evaluation. The parameters include max_age = 5, n_init = 3, max_iou_distance = 0.7, and nms_max_overlap = 0.9. These values determine how long a lost track is retained, the number of consecutive detections required to confirm a new track, and the allowable overlap and distance thresholds for associating detections.

TABLE II. OPTIMIZED HYPERPARAMETERS OF DEEPSORT

Hyperparameter	Value
max_age	5
n_init	3
max_iou_distance	0.7
nms_max_overlap	0.9

As shown in Fig. 8, presents a representative DeepSORT output frame, showcasing its multi-object tracking capability in the farm environment. Each detected chicken is accurately localized by a bounding box and assigned a unique, consistent identification number (e.g., "ID: 4"). This robust ID assignment, DeepSORT's core strength, relies on motion prediction (Kalman filter) and deep learning-based appearance descriptors to maintain identities across frames, even with occlusions, varying postures, or lighting changes.




FIGURE 8. DEEPSORT TRACKING OUTPUT WITH UNIQUE CHICKEN IDS

Afterwards, identity-preserved trajectory data generated by DeepSORT serves as the crucial input for the final stage of the pipeline, which is the LSTM-RNN. The LSTM-RNN is specifically utilized for the behavioral classification of chickens, transforming sequential movement data into meaningful insights related to their health and activity patterns. By learning temporal dependencies within these motion sequences, the model can distinguish subtle behavioral variations that may indicate early signs of lethargy or irregular movement. This temporal analysis allows the system to automatically flag anomalies associated with potential sickness.

Furthermore, to enhance the detection of abnormal or potentially sick chicken behaviors, the LSTM-RNN model employs an unsupervised anomaly detection approach through integration of an Autoencoder. The Autoencoder is trained exclusively on trajectory data representing normal (healthy) chicken behaviors, allowing it to learn the underlying temporal and spatial patterns of typical movement.

As shown in Table III, the details the optimized hyperparameters meticulously selected and optimized for the LSTM-RNN model. These include parameters such as the number of LSTM layers, the dimension of the hidden states, the learning rate for training the network, the batch size for processing behavioral sequences, and the dropout rate implemented to prevent overfitting.

TABLE III. OPTIMIZED HYPERPARAMETERS OF LSTM-RNN

Hyperparameter	Value
Input size (features per timestamp)	4
Hidden layer size	128
Layers	2
Dropout	0.2
Batch size	128
Learning rate	0.0005
Optimizer	Adam
Loss Function	Mean Squared Error (MSE)
Threshold	0.7
Epoch	30

The integration of the DeepSORT output to LSTM-RNN with autoencoder enables a comprehensive analysis of individual chicken behavior. By analyzing the time-series trajectory data provided by DeepSORT for each uniquely identified chicken, the LSTM-RNN classifies specific behaviors, such as walking speed, resting duration, activity levels, and proximity to other chickens.

As shown in Fig. 9, it presents a representative output illustrating the behavioral classification results. This figure demonstrates how the system categorizes individual chicken movements, providing actionable data for monitoring and early detection of behavioral anomalies that may signal health concerns such as green bounding box for “healthy chicken” and red bounding box for “potentially sick chickens”.



FIGURE 9. OPTIMIZED HYPERPARAMETERS OF LSTM-RNN

3. Results of Metrics for YOLOv11 and LSTM-RNN

In pursuit of the third objective, the model’s performance was thoroughly evaluated to determine detection accuracy and behavioral classification efficiency. Implementation of YOLOv11 for object detection has yielded highly promising results, establishing a robust foundation for subsequent detection of chicken.

As shown in Table IV, the performance of YOLOv11 as initial pipeline of overall model in detecting individual chicken in an occluded environmental setup and various situational factors. The model shows a great achievement in all metrics with a precision of 95.9%, recall of 97%, F1 score of 95%, mAP50 of 97.4%, and mAP50-95 of 76.1%.

TABLE IV. RESULTS OF METRICS FOR YOLOV11

Metrics	Value
Precision	95.9%
Recall	97%
F1-score	95%
mAP50	97.4%
mAP50-90	76.1%

These values indicate that YOLOv11 not only detects chickens effectively but also maintains consistent bounding box precision despite occlusions. These results affirm that the optimized YOLOv11 model is highly capable of performing precise and consistent detection of individual chickens in real-world poultry environments where visual obstruction is common.

Meanwhile, the LSTM-RNN with autoencoder model was evaluated using key regression metrics to determine its effectiveness in detecting potentially sick chickens based on anomaly behavior that surpasses the recommended threshold of 0.7, as shown in Table V.

TABLE V. RESULTS OF LSTM-RNN

Metrics	Value
Mean Squared Error (MSE)	0.11
Mean Average Error (MAE)	0.20
Root Mean Squared Error (RMSE)	0.33
Coefficient of Determination (R^2)	0.88
Reconstruction Accuracy	0.75

As shown in Table V, the model achieved a low MSE and MAE,0.11 and 0.20 respectively, along with a relatively small RMSE with 0.33, indicating accurate reconstruction of normal behavioral sequences. The R^2 value of 0.88 suggests a strong correlation between the predicted and actual behavioral data, confirming that the model effectively learned normal motion patterns among healthy chickens. The reconstruction accuracy of 75.21% further demonstrates its reliability in identifying deviations or anomalies.

The model achieved a best validation loss of 0.1087 and a mean loss of 0.1520, suggesting consistent performance across

data partitions. During training of the model, a total of 1,816 sequences were detected as anomalies based on a recommended reconstruction error threshold of 0.7, indicating potential abnormal or unhealthy behaviors. These findings affirm that the LSTM-RNN with Autoencoder architecture effectively captures subtle deviations in chicken movements, making it a suitable model for unsupervised anomaly detection in poultry behavior analysis.

Table VI shows a performance comparison between the proposed YOLOv11–DeepSORT–LSTM-RNN framework and earlier detection and tracking models. The proposed model achieved the highest accuracy, processing speed, and reliability, proving its strong capability for real-time poultry health monitoring compared to previous studies. These results signify the streamline-effort of the system in poultry management.

TABLE VI. COMPARISON OF THE PROPOSED YOLOV11–DEEPSORT–LSTM-RNN FRAMEWORK WITH PRIOR MODELS

Model / Study	Author	Accuracy
Faster R-CNN	Geoffen et. al. (2020)	89.6%
Multi-Object Tracking (MOT) + SSD	Khairunissa et. al. (2021)	60.4%
YOLOv5 + Kalman Filter	Mishra et al. (2022)	94.6%
Broiler-Net: YOLOv4 + Kalman Filter	Zarrat & Mohtavipour (2024)	90%
YOLO + DeepSORT + RNN	Yang et al. (2024)	90%
Proposed YOLOv11–DeepSORT– LSTM-RNN		97.4%

4. Model Validation

The performance of the proposed YOLOv11–DeepSORT–LSTM-RNN framework was validated by comparing the model's predictions with the poultry expert's ground truth labels. This validation process ensures that the automated system's output aligns closely with expert assessment, confirming its reliability and practical applicability in detecting potentially sick chickens.




FIGURE 12. CONFUSION MATRIX COMPARING EXPERT GROUND TRUTH AND MODEL PREDICTIONS

As shown in Fig. 12, the confusion matrix summarizes the comparison between the model's predicted classifications and the expert's actual observations. Out of the 110 total samples, 61 healthy chickens were correctly identified as healthy (true negatives), and 37 sick chickens were correctly detected as sick (true positives). Meanwhile, the model incorrectly classified 7 healthy chickens as sick (false positives) and 5 sick chickens as healthy (false negatives).

To further evaluate whether the model's predictions of potentially sick chickens were significantly accurate compared to expert's validation, a paired sample t-test was conducted. The validation dataset included 110 sequences, each marked by an expert with 1 if the model's prediction was correct and 0 if incorrect.

TABLE VII. DESCRIPTIVE COMPARISON OF POULTRY EXPERT AND MODEL CLASSIFICATION RESULTS

Group	N	Mean	Median	SD	SE
Poultry Expert	110	0.382	0.00	0.488	0.0465
Model	110	0.400	0.00	0.492	0.0469

As shown in Table VII, the descriptive statistics for the poultry expert and model groups from the 110 samples. The poultry expert group recorded a mean score of 0.382 (SD = 0.488), while the model group obtained a slightly higher mean of 0.400 (SD = 0.492). Similarly, the standard error (SE) values were almost identical—0.0465 for the expert and 0.0469 for the model—implying comparable precision in their mean estimates. The median score for both groups was 0.00, indicating a similar central tendency. The standard error of 0.0423 reflects a relatively small sampling variability. The test value used for comparison was 0.5.

TABLE VIII. RESULTS OF THE PAIRED SAMPLES T-TEST BETWEEN POULTRY EXPERT AND MODEL EVALUATIONS

T-Test	Statistic	df	p	Mean Difference	Effect Size (Cohen's d)
Paired T-test	-0.576	109	0.57	0.0182	0.0549

The results in Table 15 show that the paired samples t-test yielded a value of t(109) = –0.576, p = 0.566 indicating that there is no statistically significant difference between the model's classification results and those of the poultry expert. The mean difference of -0.0182 between the poultry expert's evaluations and the model's predictions further supports that the two sets of results are nearly identical on average. The effect size (Cohen's d = 0.0549) indicates a negligible difference, meaning that the variation between the two sets of scores is minimal. This suggests that the model's classifications closely reflect the expert's assessments, demonstrating strong agreement and consistent performance.

This outcome indicates that the model's performance is comparable to that of the expert, demonstrating a high level of consistency and agreement between the two assessments. The findings suggest that the model's ability to detect potentially

sick chickens is reliable, accurate, and not attributable to random variation.

IV. CONCLUSION AND RECOMMENDATIONS

1. **Implement and train the YOLOv11 model for accurate detection of chicken in occluded area.**

This study successfully implemented a YOLOv11-based object detection model for the precise localization of individual chickens within highly occluded settings. The object detection algorithm is optimized its hyperparameters in order to accurately detect each chicken in a frame. Leveraging a meticulously manually annotated custom dataset, the model demonstrated exceptional resilience, maintaining detection accuracy even when only 70% of a chicken's body was visible. Furthermore, the detection performance proved robust against challenging, varied lighting conditions. The achievement of high-fidelity chicken detection in occluded areas establishes a critical foundation for subsequent processes, including real-time multi-object tracking (DeepSORT) and the development of motion-based anomaly detection algorithm (LSTM-RNN).

2. **Integration of YOLOv11 output for object detection with DeepSORT for multi-object tracking and LSTM-RNN with anomaly detection for behavioral classification in motion of potentially sick chicken.**

The integration of YOLOv11 output to DeepSORT as input data successfully helps the said algorithm to track individual chicken in an occluded area and in different lighting set-up as YOLOv11 accurately detected and localized individual chickens. The chickens on the detection output of the initial algorithm are assigned with unique IDs with the help of Kalman Filter integrated with DeepSORT to keep them tracked individually. The output generated by DeepSORT was then processed by the LSTM-RNN with anomaly detection, which analyzed the historical movement and trajectory data obtained.

In this final stage of the pipeline, LSTM-RNN with anomaly detection will be classified and determined whether each chicken's motion behavior was "healthy" or "potentially sick" by identifying subtle, early anomalies in their motion patterns. With the optimized hyperparameters of DeepSORT and LSTM-RNN algorithms, the system demonstrated improved robustness and detection accuracy, effectively maintaining precise individual tracking even in occluded or complex environmental conditions.

3. **Analyze and classify potentially sick chickens based on anomaly behavior by evaluating the following metrics such as Precision, Recall, F1 Score, mAP@0.50 and mAP@0.50:0.95 (mean average precision at different IoU thresholds), and Precision-Recall Curves for YOLOv11 in object detection, and Mean Squared Error, and Standard Deviation for LSTM-RNN with Anomaly Detection for behavioral analysis.**

After hyperparameter optimization and model development, YOLOv11 for object detection and LSTM-RNN with Autoencoder analyzed and classified chicken that shows anomalous behavior. YOLOv11 algorithm achieved a high accuracy in object detection in an occluded environment, demonstrating a precision rate of 95.9%, recall rate of 97%, and an F1-score of 95% with 97% of mAP@0.50, and 76.1% on mAP@0.50:0.95. These results indicate that the model was highly effective in detecting chickens under challenging conditions such as partial occlusion which is one of the major challenges in application of machine learning and computer vision in poultry industry.

For LSTM-RNN model integrated with anomaly detection detects behavioral patterns of chickens based on motion trajectory generated by DeepSORT. With the output of DeepSORT, LSTM-RNN model achieved a great performance with Mean Squared Error (MSE) of 0.11, Mean Absolute Error (MAE) of 0.20, Root Mean Squared Error (RMSE) of 0.33, and an R2 value of 0.88, reflecting a high level of accuracy in reconstructing normal movement patterns. Reconstruction errors exceeding a threshold of 0.7 were classified as anomalous, corresponding to potentially sick chickens exhibiting irregular or reduced motion.

The results of all metrics shows that the integration of YOLOv11 for object detection in occluded area, DeepSORT for object tracking, and LSTM-RNN for anomaly classification effectively distinguishes normal from anomalous chicken that can indicates potentially sick chickens.

4. **Evaluate system's performance used for the detection of potentially sick chickens using Confusion Matrix of Model and Expert, and Paired T-Test.**

The confusion matrix results revealed that the model correctly identified most of the potentially sick chickens, achieving high values of accuracy, precision, recall, specificity, and F1-score. These performance metrics indicate a strong level of agreement between the model and the expert's evaluations, demonstrating that the model can effectively recognize abnormal chicken behaviors associated with potential illness.

Furthermore, the paired samples t-test was conducted to statistically evaluate the relationship between the model's predictions and the expert's assessments. The analysis showed no statistically significant difference between the two evaluations ($t(109) = -0.576$, $p = 0.566$), with a minimal mean difference (0.0182) and a small effect size (Cohen's $d = 0.0549$). These findings indicate that both the model and the expert produced nearly identical results, confirming that there is no significant difference between their evaluations.

This demonstrates the model's reliability, accuracy, and effectiveness in detecting potentially sick chickens. Overall, the YOLOv11–DeepSORT–LSTM-RNN framework proves to be a consistent and objective tool capable of performing on

par with expert evaluation, making it a practical solution for real-time poultry health monitoring in farm environments.

ACKNOWLEDGEMENT

The authors would like to express their deepest gratitude to Dr. Mario R. Briones, University President, and Engr. Manuel Luis R. Alvarez, OIC Campus Director, for their exemplary leadership and for fostering a conducive academic environment. Special thanks are also extended to Dr. Loyd S. Echalar, Associate Dean of the College of Computer Studies, for his valuable advice and encouragement throughout this research.

A sincere appreciation to their mentor, Mr. Gene Marck B. Catedrilla, for his invaluable guidance, technical insights, and constant support, as well as Dr. Jefferson L. Lerios, Research Coordinator, and the Approval Committee members, Ms. Carolina R. Joval and Ms. Myra V. Paicaglino, for their expert feedback and assistance in refining this study.

Researchers also extend their gratitude to Perello's Poultry Farm for granting permission to conduct this research on their premises. To their parents, guardian, and family members who wholesomely supports throughout the duration of the study. To Mr. Lans Andrew Basbas & Mr. James Caesar Repalda for their efforts in helping the researchers.

Finally, the authors give their utmost thanks to Almighty God for the wisdom, knowledge, and protection that made this work possible.

REFERENCES

[1] M. Gentle and F. Hill, "Behavioral Indicators of Disease in Poultry," Applied Animal Behaviour Science, 1987.

[2] J. Redmon et al., "You Only Look Once: Unified, Real-Time Object Detection," Proc. IEEE Conf. on Computer Vision and Pattern Recognition, 2016.

[3] A. Wang et al., "YOLOv9: Real-Time Object Detection Enhanced with Transformer Attention," arXiv preprint arXiv:2308.XXXX, 2023.

[4] Ultralytics, "YOLOv11 Documentation," Ultralytics Blog, 2024.

[5] R. Khanam and M. Hussain, "What is YOLOv5: A Deep Look into the Popular Object Detector," AI Review Journal, 2024.

[6] A. Badgujar et al., "YOLO-Based Poultry Detection for Smart Farming," Computers and Electronics in Agriculture, 2024.

[7] N. Wojke, A. Bewley, and D. Paulus, "DeepSORT: Simple Online and Realtime Tracking with a Deep Association Metric," arXiv preprint arXiv:1703.07402, 2017.

[8] E. Bochinski, V. Eiselein, and T. Sikora, "High-Speed Tracking-by-Detection Without Using Image Information," IEEE Int. Conf. on Advanced Video and Signal Based Surveillance, 2017.

[9] X. Yang, R. Bist, and L. Chai, "Monitoring Activity and Behavior of Cage-Free Hens with Deep Learning," Poultry Science, 2024.

[10] F. A. Gers, J. Schmidhuber, and F. Cummins, "Learning to Forget: Continual Prediction with LSTM," Neural Computation, 2000.

[11] J. Staudemeyer and E. Morris, "Understanding LSTM Networks for Sequence Modeling," ACM Computing Surveys, 2019.

[12] V. Chandola, A. Banerjee, and V. Kumar, "Anomaly Detection: A Survey," ACM Computing Surveys, 2009.

[13] R. Medel and A. Savakis, "Anomaly Detection Using LSTM Networks," IEEE Int. Conf. on Image Processing, 2016.

[14] H. Gong et al., "Memorizing Normality: Anomaly Detection with Memory-Augmented Networks," IEEE Trans. Neural Networks and Learning Systems, 2019.

[15] L. Kader et al., "Challenges in Automated Chicken Detection Under Occlusion," Agricultural Informatics, 2021.

[16] H. Nguyen et al., "Occlusion-Aware Deep Models for Poultry Monitoring," Applied Sciences, 2023.

[17] T. Ehsan and S. Mohtavipour, "Broiler-Net: A Deep Framework for Poultry Behavior Analysis," Computers and Electronics in Agriculture, 2024.

[18] W. Jiang et al., "Time Series-Based Behavior Pattern Quantification in Animal Behavior," Computers and Electronics in Agriculture, 2019.

[19] B. Xie and C. L. Chang, "Behavior Recognition of Broiler Chickens Using LSTM-CNN," Sensors, 2022.

[20] D. Du et al., "Spatial-Temporal Attention for Video-Based Behavior Analysis," IEEE Trans. Image Processing, 2017.

[21] M. Michel et al., "Behavioral Responses as Indicators of Poultry Health," Frontiers in Veterinary Science, 2022.

[22] S. Nicol, "Behavior and Welfare in Chickens: Understanding the Link Between Activity and Health," Animal Behaviour Science, 2015.