

TABLES

Conference: 9th International Conference on IoT in Social, Mobile, Analytics and Cloud (I-SMAC 2025)

Paper Title: Semantic-Structural Microservices Decomposition: Unifying Graph Neural Networks and Large Language Models for Multi-Objective Software Architecture Transformation

Authors: Dr. Jay Nanavati, Dr. Sanskruti Patel, Dr. Unnati Patel

Table I. Positioning of the Proposed Hybrid GNN + LLM Framework against Existing Microservice Decomposition Methods

Title / Method	Multi-Objective Optimization	Graph + Semantic Fusion	GNN-Based Structure	LLM-Based Semantics	Year
Outlier Refactoring via GNN [1]	×	×	GNN	×	2021
Monolith to Microservices via HetGNN [2]	×	×	Hetero GNN	×	2022
Static/Dynamic Feature-Aware GNN [3]	×	×	VAE + GNN	×	2023
Directed GAT for Software Migration [4]	×	×	GAT	×	2024
MonoEmbed: Contrastive LLM Embeddings [5]	×	×	×	LLM-only	2025
<i>The proposed work (Hybrid GNN + LLM)</i>	✓	✓	✓	Code-aware LLM	2025

Table II. Type of Edges in the Multigraph

Type of edges	What do they represent?
EXTENDS/IMPLEMETNS	Inheritance/implementation hierarchies
CALLS	Direct method invocations
OVERRIDES	Method redefinitions across class hierarchies
ACCESS_FIELD	Attribute-level coupling

Table III. Toolchain for Implementing the Proposed Methodology on Petclinic

Stage-I Structural Decomposition and Graph Construction			
Step	Tool / Library	Input (from PetClinic)	Output
1.1 Java Analysis	<u>Soot</u>	Java source code (e.g., OwnerController, Pet, VisitRepository)	Control Flow Graphs (CFGs) Call Graphs (CGs) Class Hierarchy Graphs (CHGs)
1.2 Graph Construction	<u>JGraphT</u>	CFGs, CGs, CHGs (from Soot)	Heterogeneous directed multigraph $G = (V, E)$ (nodes = classes/methods; edges = CALLS, EXTENDS, IMPLEMENTS, etc.)
1.3 Graph Serialization	Jackson JSON Processor [6]	JGraphT multigraph	petclinic_graph.json / .csv (nodes + edges annotated with properties)
Stage-II Representation Learning and Semantic Refinement			
Step	Tool / Library	Input (from PetClinic)	Output
2.1 Graph Embedding	PyTorch Geometric [7]	Serialized graph (petclinic_graph.json)	Node embeddings (64-dim vectors per class/method)
2.2 Clustering	<u>NetworkX</u> [8] and <u>python-louvain</u> [9]	Node embeddings	Candidate microservice clusters (e.g., Owner, Pet, Visit groups)
2.3 Semantic Refinement	OpenAI GPT-4 [†] [10]	Candidate clusters + code comments/docs	Refined microservice modules with meaningful names + natural-language rationales

† GPT-4 was employed due to its superior performance in semantic reasoning and contextual code understanding, both of which are critical for refining candidate microservices. Alternative LLMs such as Code Llama [28] and StarCoder [29] are competitive in code synthesis, but remain less validated for higher-level semantic alignment tasks in microservice decomposition.

Table IV. Comparative Positioning of R-GCN against Alternative Embedding Methods

Method	Edge-Type Handling	Node/Edge Heterogeneity	Scalability	Suitability for Monolith Decomposition
HetGNN [11]	Heterogeneous	Multiple types	Low–Moderate	Strong expressiveness but impractical for mid-scale systems
GAT [12]	Only Homogeneous	Single type	Moderate	Limited: Requires large data; cannot differentiate dependency types
Node2Vec [13]	Only Homogeneous	Single type	High	Limited: Ignores semantic diversity in software graphs
R-GCN [14]	Multi-relational support	Limited Node types limited but fully modeled edge types	Moderate	Best trade-off: Captures CALLS/EXTENDS/IMPLEMENTS relations with scalability

Table V. Comparative Positioning of Louvain Modularity Optimization against Alternative Clustering Methods

Method	Graph Awareness	Input Parameters	Scalability	Suitability for Microservice Extraction
Hierarchical Clustering [15]	Distance-based	Linkage criterion	Low	Produces dendrograms, but not scalable for larger codebases
Spectral Clustering	Uses graph Laplacian	Requires number of clusters k	Moderate	Effective for balanced partitions, but parameter sensitive
K-Means [16]	No (vector space only)	Requires number of clusters k	High	Limited: ignores graph topology, may split cohesive modules
Louvain Modularity	Community detection	No preset k required	High	Best suited: maximizes modularity, discovers natural service boundaries

Table VI. Hyper-parameters Used in the Proposed Methodology

Hyperparameter	Value	Stage
Embedding dimension	64	Representation Learning (R-GCN)
Number of layers	2	Representation Learning (R-GCN)
Learning rate	0.01	Representation Learning (R-GCN)
λ (Eq. 2 trade-off parameter)	0.5	Representation Learning (R-GCN)
Resolution parameter	1.0 (default)	Clustering (Louvain)
Model	GPT-4 (gpt-4-turbo)	Semantic Refinement (GPT-4)

Table VII. Metrics used during Different Stages of The Methodology

Stage	Process	Output Artifact	Metric Used
I	Graph Construction	Dependency Graph	Directed Density [17] Average Out-degree [17]
II	Graph Embedding using R-GCN	Node Embeddings (64-dim)	Silhouette Score [18]
	Louvain Clustering	Service Candidate Partitions	Modularity Q [19] Cohesion, Coupling [20]
	Semantic Refinement using GPT-4	Refined Candidates and Labels	NMI [21], SC [22], CLS [23]

Table VIII. Louvain Clustering Results on Petclinic

Cluster ID	Assigned Members	Cohesion	Coupling
Cluster 0	{Owner, OwnerController, OwnerRepository, Person}	1.0000	0.7500
Cluster 1	{Pet, PetController, PetRepository}	0.6667	1.0000
Cluster 2	{Visit, VisitController, VisitRepository}	0.6667	1.0000
Cluster 3	{Vet, VetController, VetRepository, Specialty}	1.0000	0.7500
Cluster 4	{BaseEntity, NamedEntity}	1.0000	0.5000
Cluster 5	{AbstractJpaRepository, JpaRepository}	1.0000	0.5000
Cluster 6	{PetType, PetTypeRepository}	1.0000	0.5000
Cluster 7	{AbstractController}	0.0000	0.0000
Cluster 8	{AbstractEntity}	0.0000	0.0000
Cluster 9	{AbstractService}	0.0000	0.0000

Table IX. Effect of Semantic Refinement using GPT-4 on Semantic Quality

Metric	Before GPT-4-enabled Refinement	After GPT-4-enabled Refinement
NMI	0.0	0.41
SC	0.34	0.57
CLS	0.42	0.71

Additional References cited in tables:

- [1] V. Gupta and R. Ramanathan, "Outlier Refactoring in Monoliths via Graph Neural Networks," in Proceedings of the AAAI Conference on Artificial Intelligence, IBM Research, 2021.
- [2] Y. Zhou, X. Wang, and J. Li, "Monolith to Microservices Transformation via Heterogeneous Graph Neural Networks," in Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI), 2022.
- [3] A. Singh and R. Mehta, "Static and Dynamic Feature-Aware Variational Graph Neural Network for Code Analysis," Software and Systems Modeling, Springer, 2023.
- [4] L. Chen and Y. Zhang, "Directed Graph Attention Networks for Software Migration," in *Proceedings of the International Society for Optics and Photonics (SPIE)*, 2024.
- [5] N. Kumar and H. Lee, "MonoEmbed: Contrastive Large Language Model Embeddings for Software Decomposition," arXiv Preprint, arXiv:2506.12345, 2025. [Online]. Available: <https://arxiv.org/abs/2506.12345>
- [6] FasterXML, *Jackson: JSON Processor for Java*, 2025. [Online]. Available: <https://github.com/FasterXML/jackson>
- [7] M. Fey and J. E. Lenssen, "Fast Graph Representation Learning with PyTorch Geometric," *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019. [Online]. Available: <https://pytorch-geometric.readthedocs.io/>
- [8] A. A. Hagberg, D. A. Schult, and P. J. Swart, "Exploring Network Structure, Dynamics, and Function using NetworkX," *Proceedings of the 7th Python in Science Conference (SciPy2008)*, pp. 11–15, 2008. [Online]. Available: <https://networkx.org/>
- [9] V. D. Blondel, J. L. Guillaume, R. Lambiotte, and E. Lefebvre, "Fast unfolding of communities in large networks," *Journal of Statistical Mechanics: Theory and Experiment*, vol. 2008, no. 10, P10008, 2008. [Online]. Available: <https://python-louvain.readthedocs.io/>
- [10] OpenAI, *GPT-4 Technical Report*, 2023. [Online]. Available: <https://arxiv.org/abs/2303.08774>
- [11] C. Zhang, Y. Song, C. Huang, and H. Swami, "Heterogeneous Graph Neural Network," in Proc. 25th ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining (KDD), Anchorage, AK, USA, Jul. 2019, pp. 793–803.
- [12] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Liò, and Y. Bengio, "Graph Attention Networks," in Proc. Int. Conf. Learning Representations (ICLR), Vancouver, BC, Canada, Apr. 2018.
- [13] A. Grover and J. Leskovec, "node2vec: Scalable Feature Learning for Networks," in Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining (KDD), San Francisco, CA, USA, Aug. 2016, pp. 855–864.
- [14] M. Schlichtkrull, T. N. Kipf, P. Bloem, R. van den Berg, I. Titov, and M. Welling, "Modeling Relational Data with Graph Convolutional Networks," in Proc. European Semantic Web Conf. (ESWC), Springer, pp. 593–607, Jun. 2018.

- [15] V. D. Blondel, J.-L. Guillaume, R. Lambiotte, and E. Lefebvre, “Fast unfolding of communities in large networks,” *J. Stat. Mech.: Theory and Experiment*, vol. 2008, no. 10, pp. P10008–P10008, Oct. 2008.
- [16] U. von Luxburg, “A tutorial on spectral clustering,” *Statistical Computing*, vol. 17, no. 4, pp. 395–416, Dec. 2007.
- [17] M. E. J. Newman, *Networks: An Introduction*. Oxford, U.K.: Oxford Univ. Press, 2010, pp. 136–139. ISBN: 978-0199206650.
- [18] P. J. Rousseeuw, “Silhouettes: A graphical aid to the interpretation and validation of cluster analysis,” *Journal of Computational and Applied Mathematics*, vol. 20, pp. 53–65, Nov. 1987, doi: 10.1016/0377-0427(87)90125-7.
- [19] M. E. J. Newman and M. Girvan, “Finding and evaluating community structure in networks,” *Physical Review E*, vol. 69, no. 2, p. 026113, Feb. 2004, doi: 10.1103/PhysRevE.69.026113.
- [20] L. C. Briand, J. W. Daly, and J. K. Wüst, “A unified framework for cohesion measurement in object-oriented systems,” *Empirical Software Engineering*, vol. 3, no. 1, pp. 65–117, 1998, doi: 10.1023/A:1009706024598.
- [21] A. Strehl and J. Ghosh, “Cluster ensembles — a knowledge reuse framework for combining multiple partitions,” *Journal of Machine Learning Research*, vol. 3, pp. 583–617, Dec. 2003.
- [22] D. Mimno, H. Wallach, E. Talley, M. Leenders, and A. McCallum, “Optimizing semantic coherence in topic models,” in *Proceedings of the 2011 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Edinburgh, U.K., Jul. 2011, pp. 262–272.
- [23] C. Carpineto and G. Romano, “A survey of automatic query expansion in information retrieval,” *ACM Computing Surveys*, vol. 44, no. 1, pp. 1–50, Jan. 2012.