



Peerless

AutoLab[®] ESR 20

Automated ESR Analyzer



PROCESS REDEFINED

EASY & CONOMICAL

- Plug & play model
- IR laser beam technology
- 40 tests per hour

SMART & TURDY

- Easy loading of tubes
- Result in 30 minutes
- Abnormal sample flagging in 15 mins

RAPID & RELIABLE

- Random loading
- Auto-compensation of result to 18°C
- Alpha numerical keypad support

Genuine quality speaks for itself

TECHNICAL SPECIFICATIONS

Principle	Infrared LED detection
Tube Positions	20
Reading Time	30 minutes
Throughput	40 samples per hour
Measurement Range	1-140 mm/hr
Results	Westergren method mm/hr auto-compensation of result to 18°C (Manley table)
Result Resolution	± 1 mm
Test Tube	1.28 ml blood (pre-filled with 3.8% sodium citrate glass tube)
Memory	50,000 patient results
Instrument QC	Infrared LED detection
Patient ID	Upto 29 digits Alphanumeric patient ID
Tube Detection	Available instant tube detection
Display	4 X 40 character LCD display
Key pad	Supports numerical & alphabets
Interface	RS 232 port for Barcode scanner input (Optional) USB 2.0 for LIS connectivity
Printer	Internal Thermal printer
Operating Temperature	15°C - 33°C
Power Supply	12VDC\2A
Dimension	H 220 mm X W 235 mm X D 170 mm
Weight	2.8 kg

Manufactured & Marketed by:



Peerless Biotech Pvt. Ltd.

36/37, 'Millennium House'
M. K. Srinivasan Nagar Main Road
Rajiv Gandhi Salai, Perungudi
Chennai - 600 096, Tamil Nadu, India

☎ +91 44 2496 0541
✉ info@peerlessbio.com
🌐 www.peerlessbio.com

Customer Care: +91 60093 90093