

Support faster clinical decision making

MEK-6550J/K provides accurate results in just 60 seconds. All relevant information, including 21 parameters for dog, cat, cow or horse, plus 3 histograms, is displayed in color on one screen. This leads to more accurate diagnosis and faster intervention.





Reduce manual eye counting

Expandable animal setting

Six preset animal types — dog, cat, cow, horse, rat and mouse — plus 3 custom animal types allow you automatic counting for a wide range of animals. Custom animal types let you save the settings for your most frequently measured animal types. When you register a new animal type, the Optimum Threshold Search helps you find the best settings. This reduces the workload of smear preparation and manual eye counting.

Panic value with recounting


When a measurement result exceeds the high or low panic values, the sample can be recounted at a different dilution. The sample is recounted in low dilution mode for low values or higher dilution mode for high values. Panic value recounting provides the best measurement for non-typical samples and the most reliable data.



Always be ready

Fully automatic cleaning and priming ensure that the analyzer is always ready to use. MEK-6550J/K provides you with immediate results to support quick clinical decisions.

- Automatic clog removal after every measurement
- Automatic sample nozzle cleaning after every measurement
- Automatic priming and cleaning at power on
- Automatic fluid path cleaning at power off



Gentle veterinary care

Hematology Analyzer MEK-6550J/K

Features

21 parameters: dog, cat, cow, horse 13 parameters: rat, mouse, other animals	6 dilution modes: Normal, High, Higher, Lower, Pre-dilution	Unlimited memory (with SD card)
Top level accuracy and reproducibility	Automatic self-check	QC programs: • Mean • CV calculation • X-R • L & J • XB • XD•CV
Easy touch screen operation	Automatic sampling	Integrated thermal printer
Fast access buttons	Automatic priming and cleaning	Password protection access
Color LCD screen	Automatic sampling nozzle cleaning	Connection capability
Easy maintenance	Automatic clog removal	• RS232 • USB • Printer • Barcode reader
Durable and robust	Automatic waste fluid treatment	Single/double count mode
Compact	Data management	Recount mode

Specifications

Dimensions and Weight

230 W x 450 D x 428 H (mm) , approx. 20 kg

Power

Power requirements:

MEK-6550J: 110-127 VAC +/- 10%, 50/60 Hz
MEK-6550K: 220-240 VAC +/- 10%, 50/60 Hz
Power consumption: less than 120 VA
Cooling system: Natural cooling

Parameters:

WBC, RBC, PLT, HGB, HCT, MCV, MCH,
MCHC, PDW, PCT, LY%, LY#, MO%, MO#,
GR%, GR#, MPV, RDW CV, RDW SD

Throughput

about 60 samples/hour

Dilution Ratio

- Venous blood sample volume: 30 µL in normal and low dilution modes, about 10 µL in high dilution mode, 5 µL in higher dilution mode
WBC/HGB: 200:1 (in normal dilution mode)
RBC/PLT: 40,000:1 (in normal dilution mode)
- Pre-dilution blood sample volume: 10 µL, 20 µL
WBC/HGB: 1200:1, 600:1
RBC/PLT: 240,000:1, 120,000:1

Measuring Range and Reproducibility

WBC	0-59 x 103/µL , 0-599 x 103/µL	within 2.0% CV (4.0-9.0 x 103/µL) Higher dilute mode
*LY%	0-100%	within 5.0% CV (WBC: 4.0-9.0 x 103/µL, LY%: 20-45%)
*MO%	0-100%	within 12.0% CV (WBC: 4.0-9.0 x 103/µL, MO%: 2-10%)
*EO%	0-100%	—
*GR%	0-100%	within 5.0% CV (WBC: 4.0-9.0 x 103/µL, GR%: 40-70%)
*LY	0-59 x 103/µL , 0-599 x 103/µL	—, Higher dilute mode
*MO	0-59 x 103/µL , 0-599 x 103/µL	—, Higher dilute mode
EO	0-59.9 x 103/µL	—
*GR	0-59 x 103/µL , 0-599 x 103/µL	—, Higher dilute mode
RBC	0-14.9 x 106/µL	within 1.5% CV (5.0 x 106/µL)
HGB	0-29.9 g/dL	within 1.5% CV (16g/dL)
HCT	0-99.9%	—
MCV	20-199 fL	within 1.0% CV (70-120 fL)
MCH	10-50 pg	—
MCHC	10-50 g/dL	—
RDW-CV	0-50%	—
RDW-SD	0-199.0 fL	—
PLT	0-1490 x 103/µL	within 4.0% CV (3.0 x 103/µL)
PCT	0-2.9%	—
MPV	0-20 fL	—
PDW	0-50%	—

*Only available for measuring dog, cat, cow and horse samples.

Methods

RBC/PLT/WBC: Electrical resistance
HGB: Photometry
WBC classification: Impedance and lyse action
HCT: Calculated from RBC histogram
MCV, MCH, MCHC: Calculated from RBC, HGB, HCT
PCT: Calculated from PLT histogram
MPV: Calculated from PLT, PCT
RDW-CV, RDW-SD: Calculated from RBC histogram
PDW: Calculated from PLT histogram

Electromagnetic Compatibility

IEC 61326-1:2005
EN 61326-1:2005
IEC 61326-2-6:2005
EN 61326-2-6:2006
CISPR11:2003, Group 1, Class B

Environmental Conditions

Storage temperature: -20-60°C (-4-140°F)
Storage humidity: 10-95% (noncondensing)
Storage atmospheric pressure: 700-1060 hPa
Operating temperature: 15-30°C (59-86°F)
Operating humidity: 30-85%
Operating atmospheric pressure: 700-1060 hPa

SD is a trademark of SD-3C, LLC.

This brochure may be revised or replaced by Nihon Kohden at any time without notice.

Fighting Disease with Electronics



Marketed by:

NIHON KOHDEN INDIA PVT. LTD.

308, Tower-A Spazedge, Sector-47,
Sohna Road, Gurgaon 122002 Haryana, India
Phone: +91 124 493000 (28 Lines)
Fax: +91 124 4931029
Email: info_nki@nkc.co.jp

Manufactured by:

NIHON KOHDEN CORPORATION

1-31-4 Nishiiochiai, Shinjuku-ku,
Tokyo 161-8560, Japan
Phone: +81 (3) 5996-8036
Fax: +81 (3) 59968100
www.nihonkohden.com

Celltac α

Hematology Analyzer MEK-6550K



Gentle veterinary care



Fighting Disease with Electronics

