

# Towards a new approach to reveal dynamical organization of the brain using topological data analysis

Jay Patel

The Ohio State University

*patel.3316@osu.edu*

April 4, 2022

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times[3]

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times[3]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times[3]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization
- This paper takes the existing data and analyze it at the “single participant level”

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times[3]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization
- This paper takes the existing data and analyze it at the “single participant level”
- The approach of this paper is able to probe within and between task transitions of about ( $\sim 4-9$  seconds)

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times[3]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization
- This paper takes the existing data and analyze it at the “single participant level”
- The approach of this paper is able to probe within and between task transitions of about ( $\sim 4-9$  seconds)
- They observe that the revealed individual differences in the dynamical organization of the subject were predictors of the task performance

- They used multiple fMRI datasets which are scans of individuals over ~25 minutes while doing a variety of tasks




- They used multiple fMRI datasets which are scans of individuals over  $\sim 25$  minutes while doing a variety of tasks
- Previously, this data has typically been used in models after some kind of “averaging” procedure

- They used multiple fMRI datasets which are scans of individuals over  $\sim 25$  minutes while doing a variety of tasks
- Previously, this data has typically been used in models after some kind of “averaging” procedure
- The previous approaches have been unable to reveal the optimal temporal and spatial scales which best probe clinically and behaviorally relevant brain dynamics

- They used multiple fMRI datasets which are scans of individuals over  $\sim 25$  minutes while doing a variety of tasks
- Previously, this data has typically been used in models after some kind of “averaging” procedure
- The previous approaches have been unable to reveal the optimal temporal and spatial scales which best probe clinically and behaviorally relevant brain dynamics
- Additionally, they are unable to determine if the brain dynamics are best thought of as continuous or discrete or able to tell whether a particular brain activity is healthy or not

# Pipeline



**Figure:** The method used to convert the 4-dimensional fMRI data into a simplicial complex. Steps b-e are a part of Mapper (the TDA-based algorithm/tool the authors used).

# How Mapper works

- Step 1 the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data

# How Mapper works

- Step 1 the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data
- Step 2 is just binning the space using the provided parameters: number of bins and the percentage overlap between bins

# How Mapper works


- Step 1 the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data
- Step 2 is just binning the space using the provided parameters: number of bins and the percentage overlap between bins
- Step 3 goes through each bin, and performs single-linkage clustering in order to form clusters of nearby points

# How Mapper works

- Step 1 the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data
- Step 2 is just binning the space using the provided parameters: number of bins and the percentage overlap between bins
- Step 3 goes through each bin, and performs single-linkage clustering in order to form clusters of nearby points
- Step 4 treats each cluster as a vertex of a graph and adds an edge between two vertices if they shared a point[4]




# Filtering in Mapper




**Figure:** Toy example of applying a filter to data[4]. The data is sampled from a noisy circle, and the filter used is  $f(x) = ||x - p||^2$ , where  $p$  is the left most point in the data. We divide the range of the filter into 5 intervals which have length 1 and a 20% overlap. For each interval we compute the clustering of the points lying within the domain of the filter restricted to the interval, and connect the clusters whenever they have non-empty intersection. At the bottom is the simplicial complex which we recover whose vertices are colored by the average filter value.

# Diagram of the Filtering process




**Figure:** Our paper uses a very different filter function than the previous example. They use something called the Neighborhood Lens function to take their 271633-dimensional data into  $\mathbb{R}^2$ . This function is part of a patented software that appears to be standard.

# Clustering



**Figure:** Mapper take two parameters when binning the data: Resolution and Gain. Resolution controls the number of bins and Gain controls the overlap between bins.

# Example



**Figure:** After running Mapper on an individual's fMRI data, we are left with a graph like the above. The fMRI datasets ( $1017 \times 271633$  matrix) were compressed to  $279 \pm 60$  points.

# How do we analyze these graphs?

- The most interesting and practical thing we can do with this graph is try to understand the mesoscale structure of this graph

# How do we analyze these graphs?

- The most interesting and practical thing we can do with this graph is try to understand the mesoscale structure of this graph
- The most commonly analyzed mesoscale structures are community structures and core-periphery structures

# How do we analyze these graphs?

- The most interesting and practical thing we can do with this graph is try to understand the mesoscale structure of this graph
- The most commonly analyzed mesoscale structures are community structures and core-periphery structures
- Note: It is necessary to have weights on the edges to perform analysis of community structure or core-periphery structure
- This paper doesn't describe how they acquire weights on the edges and there is no canonical way to assign weights from mapper

# How do we analyze these graphs?

- The most interesting and practical thing we can do with this graph is try to understand the mesoscale structure of this graph
- The most commonly analyzed mesoscale structures are community structures and core-periphery structures
- Note: It is necessary to have weights on the edges to perform analysis of community structure or core-periphery structure
- This paper doesn't describe how they acquire weights on the edges and there is no canonical way to assign weights from mapper
- Two likely possibilities: the weight between two nodes is the number of timeframes they shared, or the weight is something that depends on the mean distance between the timeframes constituting the nodes



# Analyzing the community structure of a graph

- You can think about the community structure as the measure of if there are many “communities” of densely connected nodes (not necessarily cliques) there are where there are only a few connections between communities

# Analyzing the community structure of a graph

- You can think about the community structure as the measure of if there are many “communities” of densely connected nodes (not necessarily cliques) there are where there are only a few connections between communities
- Suppose that you have a weighted graph  $G$  and for each vertex  $i$ , we have “node strength” weight  $k_i$  on  $i$

# Analyzing the community structure of a graph

- You can think about the community structure as the measure of if there are many “communities” of densely connected nodes (not necessarily cliques) there are where there are only a few connections between communities
- Suppose that you have a weighted graph  $G$  and for each vertex  $i$ , we have “node strength” weight  $k_i$  on  $i$
- $Q_{\text{mod}}$  (called the modularity) is the most commonly used metric to assess the community structure of a graph[1]

# Analyzing the community structure of a graph

- You can think about the community structure as the measure of if there are many “communities” of densely connected nodes (not necessarily cliques) there are where there are only a few connections between communities
- Suppose that you have a weighted graph  $G$  and for each vertex  $i$ , we have “node strength” weight  $k_i$  on  $i$
- $Q_{\text{mod}}$  (called the modularity) is the most commonly used metric to assess the community structure of a graph[1]

$$Q_{\text{mod}} = \sum_{i,j} (A_{ij} - P_{ij}) \delta(g_i, g_j)$$

where  $A$  is the adjacency matrix,  $P_{ij} = \frac{k_i k_j}{\sum_{ij} A_{ij}}$ ,  $k_i$  is degree of  $i$ ,  $g_i$  is the community that  $i$  belongs to, and  $\delta$  is the Kronecker delta.


## Some intuition for $Q_{\text{mod}}$

- It is based on the idea that a random graph is not expected to have a cluster structure, so the possible existence of clusters is revealed by the comparison between the actual density of edges in a subgraph and the density one would expect to have in the subgraph if the vertices of the graph were attached regardless of community structure
- This expected edge density ( $P_{ij} = \frac{k_i k_j}{2m}$  where  $m = \sum_{ij} A_{ij}$ ) depends on the chosen null model, i.e. a copy of the original graph keeping some of its structural properties but without community structure[1]

## Some intuition for $Q_{\text{mod}}$

- It is based on the idea that a random graph is not expected to have a cluster structure, so the possible existence of clusters is revealed by the comparison between the actual density of edges in a subgraph and the density one would expect to have in the subgraph if the vertices of the graph were attached regardless of community structure
- This expected edge density ( $P_{ij} = \frac{k_i k_j}{2m}$  where  $m = \sum_{ij} A_{ij}$ ) depends on the chosen null model, i.e. a copy of the original graph keeping some of its structural properties but without community structure[1]
- In this case, the null model that produces the above expected edge density is called the configuration model. This is a very standard type of model in network science because, as opposed to the Erdős-Renyi model, this model allows us to give the network arbitrary degree distributions. (The Erdős-Renyi model only allows for Poisson distribution for the degree sequence).

# How $Q_{\text{mod}}$ scales



**Figure:** There are two different participants' shape graphs and the relations between modularity and various metrics

# Analyzing the core-periphery structure of the graph

- We assign each node a coreness score (CS) by giving higher scores to nodes which lie deeper in the network
- The Borgatti-Everett algorithm is an algorithm that assigns coreness scores to each vertex of the shape graph. If we call  $C_i$  is the coreness of vertex  $i$ , then we can define the core matrix  $C$  by  $C_{ij} = C_i C_j$ . We can define a quality function

$$R_{(\alpha,\beta)} = \sum_{i,j} A_{ij} C_{ij}$$


where  $(\alpha, \beta)$  are the two parameters which determines the boundary between the core and periphery and size of the core respectively. A large  $\alpha$  indicates a sharp transition.

- $$CS(i) = Z \sum_{(\alpha,\beta)} C_i(\alpha, \beta) \times R(\alpha, \beta)$$

where  $Z$  is a normalization factor to make the maximum CS be 1 and this sum is not actually over all  $\alpha, \beta$  but instead over a uniform




# How coreness score (CS) scales



# Trying to explain the topological features using anatomy




# Connectivity in the shape graph for different times



**Figure:** Shows which times during the scan were similar to other times by looking at the connections between times in the shape graph.

# Brains are typically more connected during strenuous tasks



**Figure:** When there is a transition between tasks, this is captured by a dramatic change in the degree of the corresponding nodes. This phenomenon of nodes taken during strenuous activity having high degree is significant





# References I

- [1] Santo Fortunato. “Community detection in graphs”. In: *Physics Reports* 486.3-5 (2010), pp. 75–174. DOI: [10.1016/j.physrep.2009.11.002](https://doi.org/10.1016/j.physrep.2009.11.002). URL: <https://doi.org/10.1016%2Fj.physrep.2009.11.002>.
- [2] Saggar Manish et al. *Towards a new approach to reveal dynamical organization of the brain using topological data analysis*. 2018. URL: <https://www.nature.com/articles/s41467-018-03664-4#citeas>.
- [3] Maria Giulia Preti, Thomas AW Bolton, and Dimitri Van De Ville. “The dynamic functional connectome: State-of-the-art and perspectives”. In: *NeuroImage* 160 (2017). Functional Architecture of the Brain, pp. 41–54. ISSN: 1053-8119. DOI: <https://doi.org/10.1016/j.neuroimage.2016.12.061>. URL: <https://www.sciencedirect.com/science/article/pii/S1053811916307881>.

- [4] Gurjeet Kaur Chatar Singh, Facundo Mémoli, and Gunnar E. Carlsson. “Topological Methods for the Analysis of High Dimensional Data Sets and 3D Object Recognition”. In: (2007).



# The End