

# Towards a new approach to reveal dynamical organization of the brain using topological data analysis

Jay Patel

The Ohio State University

*patel.3316@osu.edu*

March 29, 2022

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times [2]

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times [2]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times [2]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization
- This paper takes the existing data and analyzes it at the “single participant level”

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times [2]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization
- This paper takes the existing data and analyzes it at the “single participant level”
- The approach of this paper is able to probe within and between task transitions of about ( 4-9 seconds)

# Premise

- Little is known about how the brain adapts in order to efficiently complete one task versus another
- Most previous work focuses on analyzing co-fluctuations of the brain at different times [2]
- Collapsing the data into co-fluctuations will make us lose useful information about the overall dynamical organization
- This paper takes the existing data and analyzes it at the “single participant level”
- The approach of this paper is able to probe within and between task transitions of about ( 4-9 seconds)
- They observe that the revealed individual differences in the dynamical organization of the subject were predictors of the task performance

- They used multiple fMRI datasets which are scans of individuals over 25 minutes while doing a variety of tasks




- They used multiple fMRI datasets which are scans of individuals over 25 minutes while doing a variety of tasks
- Previously, this data has typically been used in models after some kind of “averaging” procedure

- They used multiple fMRI datasets which are scans of individuals over 25 minutes while doing a variety of tasks
- Previously, this data has typically been used in models after some kind of “averaging” procedure
- The previous approaches have been unable to reveal the optimal temporal and spatial scales which best probe clinically and behaviorally relevant brain dynamics

- They used multiple fMRI datasets which are scans of individuals over 25 minutes while doing a variety of tasks
- Previously, this data has typically been used in models after some kind of “averaging” procedure
- The previous approaches have been unable to reveal the optimal temporal and spatial scales which best probe clinically and behaviorally relevant brain dynamics
- Additionally, they are unable to determine if the brain dynamics are best thought of as continuous or discrete or able to tell whether a particular brain activity is healthy or not

# Pipeline



**Figure:** The method used to convert the 4-dimensional fMRI data into a simplicial complex. Steps b-e are a part of Mapper (the TDA-based algorithm/tool the authors used).

# How Mapper works

- Step b the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation.

# How Mapper works

- Step b the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data

# How Mapper works

- Step b the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data
- Step c is just binning the space using the provided parameters: number of bins and the percentage overlap between bins

# How Mapper works


- Step b the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data
- Step c is just binning the space using the provided parameters: number of bins and the percentage overlap between bins
- Step d goes through each bin, and performs single-linkage clustering in order to form clusters of nearby points



# How Mapper works

- Step b the filtering into  $\mathbb{R}^2$  is done using something called Stochastic Neighborhood Estimation. SNE, is used over traditional methods like PCA because SNE allows us to preserve the local structure of the original data
- Step c is just binning the space using the provided parameters: number of bins and the percentage overlap between bins
- Step d goes through each bin, and performs single-linkage clustering in order to form clusters of nearby points
- Step e treats each cluster as a vertex of a graph and adds an edge between two vertices if they shared a point [3]

# Example



**Figure:** After running Mapper on an individual's fMRI data, we are left with a graph like the above.

# References I

- [1] Saggar Manish et al. *Towards a new approach to reveal dynamical organization of the brain using topological data analysis*. 2018. URL: <https://www.nature.com/articles/s41467-018-03664-4#citeas>.
- [2] Maria Giulia Preti, Thomas AW Bolton, and Dimitri Van De Ville. “The dynamic functional connectome: State-of-the-art and perspectives”. In: *NeuroImage* 160 (2017). Functional Architecture of the Brain, pp. 41–54. ISSN: 1053-8119. DOI: <https://doi.org/10.1016/j.neuroimage.2016.12.061>. URL: <https://www.sciencedirect.com/science/article/pii/S1053811916307881>.
- [3] Gurjeet Kaur Chatar Singh, Facundo Mémoli, and Gunnar E. Carlsson. “Topological Methods for the Analysis of High Dimensional Data Sets and 3D Object Recognition”. In: (2007).

# The End