



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Experiment No. 3
Apply Decision Tree Algorithm on Adult Census Income Dataset and analyze the performance of the model
Date of Performance: 14/08/23
Date of Submission: 22/08/23



Vidyavardhini's College of Engineering & Technology


Department of Computer Engineering

Aim: Apply Decision Tree Algorithm on Adult Census Income Dataset and analyze the performance of the model.

Objective: To perform various feature engineering tasks, apply Decision Tree Algorithm on the given dataset and maximize the accuracy, Precision, Recall, F1 score. Improve the performance by performing different data engineering and feature engineering tasks.

Theory:

Decision Tree is the most powerful and popular tool for classification and prediction. A Decision tree is a flowchart-like tree structure, where each internal node denotes a test on an attribute, each branch represents an outcome of the test, and each leaf node (terminal node) holds a class label.



Dataset:

Predict whether income exceeds \$50K/yr based on census data. Also known as "Adult" dataset.

Attribute Information:

Listing of attributes:

>50K, <=50K.

age: continuous.



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

workclass: Private, Self-emp-not-inc, Self-emp-inc, Federal-gov, Local-gov, State-gov, Without-pay, Never-worked.

fnlwgt: continuous.

education: Bachelors, Some-college, 11th, HS-grad, Prof-school, Assoc-acdm, Assoc-voc, 9th, 7th-8th, 12th, Masters, 1st-4th, 10th, Doctorate, 5th-6th, Preschool.

education-num: continuous.

marital-status: Married-civ-spouse, Divorced, Never-married, Separated, Widowed, Married-spouse-absent, Married-AF-spouse.

occupation: Tech-support, Craft-repair, Other-service, Sales, Exec-managerial, Prof-specialty, Handlers-cleaners, Machine-op-inspct, Adm-clerical, Farming-fishing, Transport-moving, Priv-house-serv, Protective-serv, Armed-Forces.

relationship: Wife, Own-child, Husband, Not-in-family, Other-relative, Unmarried.

race: White, Asian-Pac-Islander, Amer-Indian-Eskimo, Other, Black.

sex: Female, Male.

capital-gain: continuous.

capital-loss: continuous.

hours-per-week: continuous.

native-country: United-States, Cambodia, England, Puerto-Rico, Canada, Germany, Outlying-US(Guam-USVI-etc), India, Japan, Greece, South, China, Cuba, Iran, Honduras, Philippines, Italy, Poland, Jamaica, Vietnam, Mexico, Portugal, Ireland, France, Dominican-Republic, Laos, Ecuador, Taiwan, Haiti, Columbia, Hungary, Guatemala, Nicaragua, Scotland, Thailand, Yugoslavia, El-Salvador, Trinidad&Tobago, Peru, Hong, Holand-Netherlands.

```
# Import libraries
import os
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline

# To ignore warning messages
import warnings
warnings.filterwarnings('ignore')

# Adult dataset path
adult_dataset_path = "adult_dataset.csv"

# Function for loading adult dataset
def load_adult_data(adult_path=adult_dataset_path):
    csv_path = os.path.join(adult_path)
    return pd.read_csv(csv_path)

# Calling load adult function and assigning to a new variable df
df = load_adult_data()
# load top 3 rows values from adult dataset
df.head(3)
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	relationship	race	
0	90	?	77053	HS-grad	9	Widowed	?	Not-in-family	White	F
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	Not-in-family	White	F
2	66	?	186061	Some-college	10	Widowed	?	Unmarried	Black	F

```
print ("Rows      : ",df.shape[0])
print ("Columns   : ",df.shape[1])
print ("\nFeatures : \n",df.columns.tolist())
print ("\nMissing values : ", df.isnull().sum().values.sum())
print ("\nUnique values : \n",df.nunique())
```

```
Rows      : 32561
Columns   : 15
```

```
Features :
['age', 'workclass', 'fnlwgt', 'education', 'education.num', 'marital.status', 'occupation', 'relationship', 'race', 'sex', 'capit
```

```
Missing values : 0
```

```
Unique values :
age                73
workclass           9
fnlwgt            21648
education          16
education.num       16
marital.status      7
occupation          15
relationship        6
race                5
sex                 2
capital.gain        119
capital.loss         92
hours.per.week      94
native.country       42
income              2
dtype: int64
```

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 32561 entries, 0 to 32560
Data columns (total 15 columns):
#   Column             Non-Null Count  Dtype
---  ---
0   age                 32561 non-null  int64
1   workclass           32561 non-null  object
2   fnlwgt              32561 non-null  int64
3   education           32561 non-null  object
4   education.num       32561 non-null  int64
5   marital.status      32561 non-null  object
```

occupation 32561 non-null object

```
6  relationship    32561 non-null  object
7  race            32561 non-null  object
8  sex             32561 non-null  object
9  capital.gain    32561 non-null  int64
10 capital.loss    32561 non-null  int64
11 hours.per.week  32561 non-null  int64
12 native.country  32561 non-null  object
13 income          32561 non-null  object
dtypes: int64(6), object(9)
memory usage: 3.7+ MB
```

df.describe()

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	
count	32561.000000	3.256100e+04	32561.000000	32561.000000	32561.000000	32561.000000	
mean	38.581647	1.897784e+05	10.080679	1077.648844	87.303830	40.437456	
std	13.640433	1.055500e+05	2.572720	7385.292085	402.960219	12.347429	
min	17.000000	1.228500e+04	1.000000	0.000000	0.000000	1.000000	
25%	28.000000	1.178270e+05	9.000000	0.000000	0.000000	40.000000	
50%	37.000000	1.783560e+05	10.000000	0.000000	0.000000	40.000000	
75%	48.000000	2.370510e+05	12.000000	0.000000	0.000000	45.000000	
max	90.000000	1.484705e+06	16.000000	99999.000000	4356.000000	99.000000	

df.head()

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	relationship	race	sex	capital.gain	capital.
0	90	?	77053	HS-grad	9	Widowed	?	Not-in-family	White	Female	0	
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	Not-in-family	White	Female	0	
2	66	?	186061	Some-college	10	Widowed	?	Unmarried	Black	Female	0	
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	Unmarried	White	Female	0	
4	41	Private	264663	Some-college	10	Separated	Prof-specialty	Own-child	White	Female	0	

```
# checking "?" total values present in particular 'workclass' feature
df_check_missing_workclass = (df['workclass']=='?').sum()
df_check_missing_workclass
```

1836

```
# checking "?" total values present in particular 'occupation' feature
df_check_missing_occupation = (df['occupation']=='?').sum()
df_check_missing_occupation
```

1843

```
# checking "?" values, how many are there in the whole dataset
df_missing = (df=='?').sum()
df_missing
```

```
age            0
workclass      1836
fnlwgt         0
education      0
education.num  0
marital.status 0
occupation     1843
relationship   0
race           0
sex            0
capital.gain   0
capital.loss   0
hours.per.week 0
native.country 583
income         0
dtype: int64
```

```
percent_missing = (df=='?').sum() * 100/len(df)
percent_missing
```

```

age            0.000000
workclass      5.638647
fnlwgt         0.000000
education      0.000000
education.num  0.000000
marital.status 0.000000
occupation     5.660146
relationship   0.000000
race           0.000000
sex            0.000000
capital.gain   0.000000
capital.loss   0.000000
hours.per.week 0.000000
native.country 1.790486
income         0.000000
dtype: float64

```

```

# find total number of rows which doesn't contain any missing value as '?'
df.apply(lambda x: x != '?',axis=1).sum()

```

```

age            32561
workclass      30725
fnlwgt         32561
education      32561
education.num  32561
marital.status 32561
occupation     30718
relationship   32561
race           32561
sex            32561
capital.gain   32561
capital.loss   32561
hours.per.week 32561
native.country 31978
income         32561
dtype: int64

```

```

# dropping the rows having missing values in workclass
df = df[df['workclass'] != '?']
df.head()

```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	relationship	race	sex	capital.gain	capital.loss
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	Not-in-family	White	Female	0	0
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	Unmarried	White	Female	0	0
4	41	Private	264663	Some-college	10	Separated	Prof-specialty	Own-child	White	Female	0	0
5	34	Private	216864	HS-grad	9	Divorced	Other-service	Unmarried	White	Female	0	0

```

# select all categorical variables
df_categorical = df.select_dtypes(include=['object'])

```

```

# checking whether any other column contains '?' value
df_categorical.apply(lambda x: x == '?',axis=1).sum()

```

```

workclass      0
education      0
marital.status 0
occupation     7
relationship   0
race           0
sex            0
native.country 556
income         0
dtype: int64

```

```

# dropping the "?"s from occupation and native.country
df = df[df['occupation'] != '?']
df = df[df['native.country'] != '?']

```

```
df.info()
```

```

<class 'pandas.core.frame.DataFrame'>
Int64Index: 30162 entries, 1 to 32560
Data columns (total 15 columns):
 #   Column              Non-Null Count  Dtype

```



```

0  age          30162 non-null  int64
1  workclass    30162 non-null  object
2  fnlwgt      30162 non-null  int64
3  education    30162 non-null  object
4  education.num 30162 non-null  int64
5  marital.status 30162 non-null  object
6  occupation   30162 non-null  object
7  relationship 30162 non-null  object
8  race         30162 non-null  object
9  sex          30162 non-null  object
10 capital.gain 30162 non-null  int64
11 capital.loss 30162 non-null  int64
12 hours.per.week 30162 non-null  int64
13 native.country 30162 non-null  object
14 income       30162 non-null  object
dtypes: int64(6), object(9)
memory usage: 3.7+ MB

```

```
from sklearn import preprocessing
```

```
# encode categorical variables using label Encoder
```

```
# select all categorical variables
```

```
df_categorical = df.select_dtypes(include=['object'])
df_categorical.head()
```

	workclass	education	marital.status	occupation	relationship	race	sex	native.country	income
1	Private	HS-grad	Widowed	Exec-managerial	Not-in-family	White	Female	United-States	<=50K
3	Private	7th-8th	Divorced	Machine-op-inspct	Unmarried	White	Female	United-States	<=50K
4	Private	Some-college	Separated	Prof-specialty	Own-child	White	Female	United-States	<=50K
5	Private	HS-grad	Divorced	Other-service	Unmarried	White	Female	United-States	<=50K
6	Private	10th	Separated	Adm-clerical	Unmarried	White	Male	United-States	<=50K

```
# apply label encoder to df_categorical
```

```
le = preprocessing.LabelEncoder()
df_categorical = df_categorical.apply(le.fit_transform)
df_categorical.head()
```

	workclass	education	marital.status	occupation	relationship	race	sex	native.country	income
1	2	11	6	3	1	4	0	38	0
3	2	5	0	6	4	4	0	38	0
4	2	15	5	9	3	4	0	38	0
5	2	11	0	7	4	4	0	38	0
6	2	0	5	0	4	4	1	38	0

```
# Next, Concatenate df_categorical dataframe with original df (dataframe)
```

```
# first, Drop earlier duplicate columns which had categorical values
```

```
df = df.drop(df_categorical.columns,axis=1)
df = pd.concat([df,df_categorical],axis=1)
df.head()
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	workclass	education	marital.status	occupation	relatio
1	82	132870	9	0	4356	18	2	11	6	3	
3	54	140359	4	0	3900	40	2	5	0	6	
4	41	264663	10	0	3900	40	2	15	5	9	
5	34	216864	9	0	3770	45	2	11	0	7	
6	38	150601	6	0	3770	40	2	0	5	0	

```
# look at column type
df.info()
```

```

<class 'pandas.core.frame.DataFrame'>
Int64Index: 30162 entries, 1 to 32560
Data columns (total 15 columns):
#   Column                Non-Null Count  Dtype
---  -
0   age                   30162 non-null  int64
1   fnlwgt                30162 non-null  int64
2   education.num         30162 non-null  int64

```

```

3   capital.gain    30162 non-null   int64
4   capital.loss   30162 non-null   int64
5   hours.per.week 30162 non-null   int64
6   workclass      30162 non-null   int64
7   education       30162 non-null   int64
8   marital.status  30162 non-null   int64
9   occupation      30162 non-null   int64
10  relationship    30162 non-null   int64
11  race            30162 non-null   int64
12  sex             30162 non-null   int64
13  native.country  30162 non-null   int64
14  income          30162 non-null   int64

```

```

dtypes: int64(15)
memory usage: 3.7 MB

```

```

# convert target variable income to categorical
df['income'] = df['income'].astype('category')

```

```

# check df info again whether everything is in right format or not
df.info()

```

```

<class 'pandas.core.frame.DataFrame'>
Int64Index: 30162 entries, 1 to 32560
Data columns (total 15 columns):
#   Column                Non-Null Count  Dtype
---  -
0   age                   30162 non-null   int64
1   fnlwgt                30162 non-null   int64
2   education.num         30162 non-null   int64
3   capital.gain          30162 non-null   int64
4   capital.loss          30162 non-null   int64
5   hours.per.week        30162 non-null   int64
6   workclass             30162 non-null   int64
7   education             30162 non-null   int64
8   marital.status        30162 non-null   int64
9   occupation            30162 non-null   int64
10  relationship          30162 non-null   int64
11  race                  30162 non-null   int64
12  sex                   30162 non-null   int64
13  native.country        30162 non-null   int64
14  income                30162 non-null   category
dtypes: category(1), int64(14)
memory usage: 3.5 MB

```

```

# Importing train_test_split
from sklearn.model_selection import train_test_split

```

```

# Putting independent variables/features to X
X = df.drop('income',axis=1)

```

```

# Putting response/dependent variable/feature to y
y = df['income']

```

```
X.head(3)
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	workclass	education	marital.status	occupation	relatio
1	82	132870	9	0	4356	18	2	11	6	3	
3	54	140359	4	0	3900	40	2	5	0	6	
4	41	264663	10	0	3900	40	2	15	5	9	

```
y.head(3)
```

```

1    0
3    0
4    0
Name: income, dtype: category
Categories (2, int64): [0, 1]

```

```

# Splitting the data into train and test
X_train,X_test,y_train,y_test = train_test_split(X,y,test_size=0.30,random_state=99)

```

```
X_train.head()
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	workclass	education	marital.status	occupation	rel
24351	42	289636	9	0	0	46	2	11	2	13	
15626	37	52465	9	0	0	40	1	11	4	7	

```
# Importing decision tree classifier from sklearn library
from sklearn.tree import DecisionTreeClassifier
```

```
# Fitting the decision tree with default hyperparameters, apart from
# max_depth which is 5 so that we can plot and read the tree.
dt_default = DecisionTreeClassifier(max_depth=5)
dt_default.fit(X_train,y_train)
```

```
DecisionTreeClassifier
DecisionTreeClassifier(max_depth=5)
```

```
# check the evaluation metrics of our default model
```

```
# Importing classification report and confusion matrix from sklearn metrics
from sklearn.metrics import classification_report,confusion_matrix,accuracy_score
```

```
# making predictions
y_pred_default = dt_default.predict(X_test)
```

```
# Printing classifier report after prediction
print(classification_report(y_test,y_pred_default))
```

```

              precision    recall  f1-score   support

     0       0.86      0.95      0.91      6867
     1       0.78      0.52      0.63      2182

 accuracy          0.85      9049
 macro avg          0.82      0.74      0.77      9049
 weighted avg       0.84      0.85      0.84      9049
```

```
# Printing confusion matrix and accuracy
print(confusion_matrix(y_test,y_pred_default))
print(accuracy_score(y_test,y_pred_default))
```

```
[[6553  314]
 [1039 1143]]
0.8504807161012267
```

```
!pip install my-package
```

```
Collecting my-package
  Downloading my_package-0.0.0-py3-none-any.whl (2.0 kB)
Installing collected packages: my-package
Successfully installed my-package-0.0.0
```

```
!pip install pydotplus
```

```
Requirement already satisfied: pydotplus in /usr/local/lib/python3.10/dist-packages (2.0.2)
Requirement already satisfied: pyparsing>=2.0.1 in /usr/local/lib/python3.10/dist-packages (from pydotplus) (3.1.1)
```

```
# Importing required packages for visualization
from IPython.display import Image
from six import StringIO
from sklearn.tree import export_graphviz
import pydotplus,graphviz
```

```
# Putting features
features = list(df.columns[1:])
features
```

```
['fnlwgt',
 'education.num',
 'capital.gain',
 'capital.loss',
 'hours.per.week',
 'workclass',
 'education',
 'marital.status',
 'occupation',
 'relationship',
 'race',
 'sex',
```


```
'native.country',
'income']
```

```
!pip install graphviz
```

Requirement already satisfied: graphviz in /usr/local/lib/python3.10/dist-packages (0.20.1)

```
# plotting tree with max_depth=3
dot_data = StringIO()
export_graphviz(dt_default, out_file=dot_data,
                feature_names=features, filled=True, rounded=True)
```

```
graph = pydotplus.graph_from_dot_data(dot_data.getvalue())
Image(graph.create_png())
```




```
# GridSearchCV to find optimal max_depth
from sklearn.model_selection import KFold
from sklearn.model_selection import GridSearchCV
```

```
# specify number of folds for k-fold CV
n_folds = 5
```

```
# parameters to build the model on
parameters = {'max_depth': range(1, 40)}
```

```
# instantiate the model
dtree = DecisionTreeClassifier(criterion = "gini",
                              random_state = 100)
```

```
# fit tree on training data
tree = GridSearchCV(dtree, parameters,
                    cv=n_folds,
                    scoring="accuracy")
tree.fit(X_train, y_train)
```



```
# scores of GridSearch CV
scores = tree.cv_results_
pd.DataFrame(scores).head()
```

	mean_fit_time	std_fit_time	mean_score_time	std_score_time	param_max_depth	prams	split0_test_score	split1_test_score
0	0.017606	0.003309	0.004545	0.000778	1	{'max_depth': 1}	0.747810	0.747810
1	0.019553	0.002510	0.003388	0.000431	2	{'max_depth': 2}	0.812219	0.818612
2	0.024394	0.001255	0.003224	0.000196	3	{'max_depth': 3}	0.828558	0.834241
3	0.031005	0.003047	0.003377	0.000224	4	{'max_depth': 4}	0.832583	0.840871
4	0.038414	0.004430	0.003606	0.000638	5	{'max_depth': 5}	0.834241	0.844897

```

"""
# plotting accuracies with max_depth
plt.figure()
plt.plot(scores["param_max_depth"],
         scores["mean_train_score"],
         label="training accuracy")
plt.plot(scores["param_max_depth"],
         scores["mean_test_score"],
         label="test accuracy")
plt.xlabel("max_depth")
plt.ylabel("Accuracy")
plt.legend()
plt.show()
"""

'\n# plotting accuracies with max_depth\nplt.figure()\nplt.plot(scores["param_max_depth"], \n         scores["mean_train_score"],\n\n         label="training accuracy")\nplt.plot(scores["param_max_depth"], \n         scores["mean_test_score"], \n         label\n         ="test accuracy")\nplt.xlabel("max depth")\nplt.ylabel("Accuracy")\nplt.legend()\nplt.show()\n'

# GridSearchCV to find optimal max_depth
from sklearn.model_selection import KFold
from sklearn.model_selection import GridSearchCV


# specify number of folds for k-fold CV
n_folds = 5

# parameters to build the model on
parameters = {'min_samples_leaf': range(5, 200, 20)}

# instantiate the model
dtree = DecisionTreeClassifier(criterion = "gini",
                              random_state = 100)

# fit tree on training data
tree = GridSearchCV(dtree, parameters,
                    cv=n_folds,
                    scoring="accuracy")
tree.fit(X_train, y_train)

```



```

# scores of GridSearch CV
scores = tree.cv_results_
pd.DataFrame(scores).head()

```

	mean_fit_time	std_fit_time	mean_score_time	std_score_time	param_min_samples_leaf	params	split0_test_score	split
0	0.206307	0.049675	0.006364	0.001320	5	{'min_samples_leaf': 5}	0.825716	
1	0.130202	0.019363	0.006910	0.002911	25	{'min_samples_leaf': 25}	0.841819	
2	0.109869	0.021408	0.005161	0.000183	45	{'min_samples_leaf': 45}	0.843003	
3	0.106612	0.017281	0.008429	0.006759	65	{'min_samples_leaf': 65}	0.841108	
4	0.116716	0.018254	0.009106	0.005065	85	{'min_samples_leaf': 85}	0.838030	

```

"""
# plotting accuracies with min_samples_leaf
plt.figure()
plt.plot(scores["param_min_samples_leaf"],
         scores["mean_train_score"],
         label="training accuracy")
plt.plot(scores["param_min_samples_leaf"],
         scores["mean_test_score"],
         label="test accuracy")
plt.xlabel("min_samples_leaf")
plt.ylabel("Accuracy")
plt.legend()
plt.show()
"""

```

```
\n# plotting accuracies with min_samples_leaf\nplt.figure()\nplt.plot(scores["param_min_samples_leaf"], \nscores["mean_train_score"], \nlabel="training accuracy")\nplt.plot(scores["param_min_samples_leaf"], \nscores["mean_test_score"], \nlabel="test accuracy")\nplt.xlabel("min_samples_leaf")\nplt.ylabel("Accuracy")\nplt.legend()\nplt.show()\n'
```


```
# GridSearchCV to find optimal min_samples_split
from sklearn.model_selection import KFold
from sklearn.model_selection import GridSearchCV
```

```
# specify number of folds for k-fold CV
n_folds = 5
```

```
# parameters to build the model on
parameters = {'min_samples_split': range(5, 200, 20)}
```

```
# instantiate the model
dtree = DecisionTreeClassifier(criterion = "gini",
                              random_state = 100)
```

```
# fit tree on training data
tree = GridSearchCV(dtree, parameters,
                    cv=n_folds,
                    scoring="accuracy")
tree.fit(X_train, y_train)
```



```
# scores of GridSearch CV
scores = tree.cv_results_
pd.DataFrame(scores).head()
```

	mean_fit_time	std_fit_time	mean_score_time	std_score_time	param_min_samples_split	params	split0_test_score	spli
0	0.135789	0.007802	0.005833	0.000620	5	{'min_samples_split': 5}	0.811982	
1	0.129377	0.003017	0.005809	0.000127	25	{'min_samples_split': 25}	0.825006	
2	0.127084	0.003051	0.005815	0.000104	45	{'min_samples_split': 45}	0.835188	
3	0.124147	0.005110	0.006897	0.001300	65	{'min_samples_split': 65}	0.839451	
4	0.090817	0.015012	0.004403	0.000369	85	{'min_samples_split': 85}	0.846081	

```
"""
# plotting accuracies with min_samples_leaf
plt.figure()
plt.plot(scores["param_min_samples_split"],
         scores["mean_train_score"],
         label="training accuracy")
plt.plot(scores["param_min_samples_split"],
         scores["mean_test_score"],
         label="test accuracy")
plt.xlabel("min_samples_split")
plt.ylabel("Accuracy")
plt.legend()
plt.show()
"""
```

```
\n# plotting accuracies with min_samples_leaf\nplt.figure()\nplt.plot(scores["param_min_samples_split"], \nscores["mean_train_score"], \nlabel="training accuracy")\nplt.plot(scores["param_min_samples_split"], \nscores["mean_test_score"], \nlabel="test accuracy")\nplt.xlabel("min_samples_split")\nplt.ylabel("Accuracy")\nplt.legend()\nplt.show()\n'
```

```
# Create the parameter grid
param_grid = {
    'max_depth': range(5, 15, 5),
    'min_samples_leaf': range(50, 150, 50),
    'min_samples_split': range(50, 150, 50),
    'criterion': ["entropy", "gini"]
}
```

```
n_folds = 5
```

```
# Instantiate the grid search model
dtree = DecisionTreeClassifier()
grid_search = GridSearchCV(estimator = dtree, param_grid = param_grid,
                           cv = n_folds, verbose = 1)
```

```
# Fit the grid search to the data
grid_search.fit(X_train,y_train)
```

Fitting 5 folds for each of 16 candidates, totalling 80 fits

```
GridSearchCV
  estimator: DecisionTreeClassifier
    DecisionTreeClassifier
```

```
# cv results
cv_results = pd.DataFrame(grid_search.cv_results_)
cv_results
```

	mean_fit_time	std_fit_time	mean_score_time	std_score_time	param_criterion	param_max_depth	param_min_samples_leaf	param_m
0	0.040022	0.005139	0.003463	0.000684	entropy	5	50	
1	0.038898	0.002205	0.003150	0.000035	entropy	5	50	
2	0.039383	0.001463	0.003649	0.000590	entropy	5	100	
3	0.038811	0.001748	0.003635	0.000666	entropy	5	100	

```
# printing the optimal accuracy score and hyperparameters
print("best accuracy", grid_search.best_score_)
print(grid_search.best_estimator_)
```

```
best accuracy 0.8510400232064759
DecisionTreeClassifier(max_depth=10, min_samples_leaf=50, min_samples_split=50)
```

```
# model with optimal hyperparameters
```

```
clf_gini = DecisionTreeClassifier(criterion = "gini",
                                random_state = 100,
                                max_depth=10,
                                min_samples_leaf=50,
                                min_samples_split=50)

clf_gini.fit(X_train, y_train)
```

```
DecisionTreeClassifier
DecisionTreeClassifier(max_depth=10, min_samples_leaf=50, min_samples_split=50,
                      random_state=100)
```

```
# accuracy score
```

```
clf_gini.score(X_test,y_test)
```

```
0.850922753895458
```


```
#plotting the tree
```

```
dot_data = StringIO()
```

```
export_graphviz(clf_gini, out_file=dot_data,feature_names=features,filled=True,rounded=True)
```

```
graph = pydotplus.graph_from_dot_data(dot_data.getvalue())
```

```
Image(graph.create_png())
```



```
# tree with max_depth = 3
```

```
clf_gini = DecisionTreeClassifier(criterion = "gini",
                                random_state = 100,
                                max_depth=3,
                                min_samples_leaf=50,
                                min_samples_split=50)
```

```
clf_gini.fit(X_train, y_train)
```

```
# score
```

```
print(clf_gini.score(X_test,y_test))
```

```
0.8393192617968837
```

```
15      0.056551      0.001851      0.004291      0.000614      gini      10      100
```


```
# plotting tree with max_depth=3
```

```
dot_data = StringIO()
```

```
export_graphviz(clf_gini, out_file=dot_data,feature_names=features,filled=True,rounded=True)
```



```
graph =  
Image(graph.create_png())
```



```
# classification metrics  
from sklearn.metrics import classification_report, confusion_matrix  
y_pred = clf_gini.predict(X_test)  
print(classification_report(y_test, y_pred))
```

	precision	recall	f1-score	support
0	0.85	0.96	0.90	6867
1	0.77	0.47	0.59	2182
accuracy			0.84	9049
macro avg	0.81	0.71	0.74	9049
weighted avg	0.83	0.84	0.82	9049

```
# confusion matrix  
print(confusion_matrix(y_test,y_pred))  
  
[[6564 303]  
 [1151 1031]]
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Conclusion:

1. Utilizing the Label Encoder technique, categorical attributes have been converted into numerical representations, enabling their utilization in machine learning algorithms that require numerical input by assigning unique integers to distinct categorical values.
2. Hyper-parameter tuning was conducted based on the decision tree model, optimizing key parameters such as Max Depth, Min Samples Split, Min Samples Leaf, and Criterion to enhance model effectiveness:
 - Max Depth: This parameter controls the tree's depth, preventing it from becoming overly complex and overfitting.
 - Min Samples Split: Setting the minimum number of samples required in a node before further splitting helps maintain decision tree balance.
 - Min Samples Leaf: This parameter establishes the minimum number of samples in a leaf node, preventing overly specific decisions.
 - Criterion: This parameter specifies the function used to evaluate split quality, commonly "Gini impurity" or "entropy."
3. The model's accuracy stands at around 84%, implying that it correctly predicted class labels for 84% of the test dataset instances.
4. Breaking down the confusion matrix, we observe:
 - True Positives (TP): 1031
 - True Negatives (TN): 6564
 - False Positives (FP): 303
 - False Negatives (FN): 1151

The model excels in predicting class 0 (high TP and TN), but struggles with class 1 predictions (high FN).

5. Precision for class 1 is relatively strong, at approximately 0.77, indicating that when the model predicts class 1, it is correct about 77% of the time.
6. However, the recall for class 1 is lower, approximately 0.47, signifying that the model misses a substantial portion of actual class 1 instances. In other words, it correctly identifies only around 47% of all class 1 instances.
7. The F1 score for class 1 serves as a balanced metric, considering both precision and recall, offering a comprehensive view of the model's performance.

In summary, while the model shows overall accuracy, it requires improvement in correctly identifying class 1 instances. It excels in avoiding false positives but falls short in capturing all actual positive cases. Further optimization is necessary to enhance its performance, particularly in classifying instances belonging to class 1.