

CS431

Jay Ravaliya

# Topics

- PHP and MySQL.
- Basic User Authentication.
- Table Relationships and Manipulation.

Web App

<http://njit-cs431-chat.herokuapp.com/>

# User Auth

```
1  <!--Register-->
2  <form action="login.php" method="post" autocomplete="off">
3      <input name="username" type="text" placeholder="Username">
4      <input name="password" type="password" placeholder="Password">
5      <input name="confirm-password" type="password" placeholder="Confirm Password">
6      <button name="register" type="submit">Register</button>
7  </form>
8
9  <!--Login-->
10 <form action="login.php" method="post" autocomplete="off">
11     <input name="username" type="text" placeholder="Username">
12     <input name="password" type="password" placeholder="Password">
13     <button name="login" type="submit">Log In</button>
14 </form>
```

# User Auth

```
1  <?php
2      if(isset($_POST["register"]))
3      {
4          // do something
5      }
6      elseif(isset($_POST["login"]))
7      {
8          // do something else
9      }
10     else
11     {
12         // default action
13     }
14  ?>
```

# User Auth

- MD5 is a cryptographic hash function producing a 16-byte hash value expressed in text as a 32-bit hexadecimal number.

Plain Text	Encrypted Text
"Hello, World!"	6cd3556deb0da54bca060b4c39479839
NJIT	207903645c1045e5eb28b80882d6a2f1
Here is some significantly longer text.	706e5d59596d9c4ffd7f31d2c1b64235

# User Auth

```
1 <?php
2     $username = $_POST["username"];
3     $password = $_POST["password"];
4
5     /*
6     *   After verifying input criteria...
7     */
8
9     $result = query("INSERT INTO users (username, password) VALUES (?, ?)", $username, md5($password));
10    if(count($result) == 0)
11    {
12        $query_id = query("SELECT LAST_INSERT_ID() AS id");
13        $_SESSION["id"] = $query_id[0]["id"];
14        redirect("index.php");
15    }
16    else
17    {
18        render("login.php", ["title" => "Login", "error" => "Username already exists - please try again!"]);
19    }
20 ?>
```

# User Auth

```
mysql> SELECT * FROM users;
```

id	username	password
1	jayrav13	9907428621fbb6c4c475cba882fdc0d8
3	ballct89	8a58f11a0d66844c4724dc03ffdcdaa5
4	anish591	5674c6359867087a0c983a81bf29466e

```
3 rows in set (0.02 sec)
```



# User Auth

```
1  <?php
2      $username = $_POST["username"];
3      $password = $_POST["password"];
4
5      $result = query("SELECT * FROM users WHERE username = ? and password = ?", $username, md5($password));
6      if(count($result) == 0)
7      {
8          render("login.php", ["title" => "Login", "error" => "Credentials not found. Please register!"]);
9      }
10     else
11     {
12         $_SESSION["id"] = $result[0]["id"];
13         redirect("index.php");
14     }
15  ?>
```

# Tables

```
mysql> SHOW COLUMNS IN users;
```

Field	Type	Null	Key	Default	Extra
id	int(11)	NO	PRI	NULL	auto_increment
username	varchar(16)	NO	UNI	NULL	
password	varchar(64)	NO		NULL	

```
3 rows in set (0.00 sec)
```

```
mysql> SHOW COLUMNS IN messages;
```

Field	Type	Null	Key	Default	Extra
id	int(11)	NO	PRI	NULL	auto_increment
user_id	int(11)	NO		NULL	
message	text	NO		NULL	

```
3 rows in set (0.01 sec)
```

# Tables

SELECT

users.username AS username,  
messages.\*

FROM

messages

LEFT JOIN

users

ON

messages.user\_id = users.id

ORDER BY

messages.id ASC;

# Tables

```
mysql> SELECT users.username, messages.* FROM messages LE
```

username	id	user_id	message
jayrav13	1	1	Here's my message!
jayrav13	2	1	Here's another!
jayrav13	4	1	Here's another message.
jayrav13	5	1	Let's try one more time.
jayrav13	6	1	Let's try again?
jayrav13	7	1	Sup
jayrav13	8	1	Yo
ballct89	9	3	What up
anish591	10	4	Sup
jayrav13	11	1	Thanks guys!

```
10 rows in set (0.03 sec)
```

GitHub

<https://github.com/jayrav13/cs431-chat>