

Rough-Length First-Crosscut List

A bench-ready plan for STOCK-A through STOCK-O. M = 3/4 x 8-1/4 x 99 inches finished white oak and carries D-101H; keep A full at 72-3/4 inches. N/O are each confirmed finished white oak at 1-3/4 x 11 x 74 inches and remain full-length short-member reserve. Door remains 23-3/4 x 80-1/2 x 1-3/8 in the 24 x 81 jamb with 3/8-inch bottom gap.

STATUS: CHK-RS-01 REQUIRED; G NOW S4S 15/16 X 4-1/2 X 75; G THICKNESS/WIDTH/LENGTH FIT D-101J; OTHER LS-05 GATES UNCHANGED			
1 CONTROLLED-RESERVE RELEASE Map every full board; moisture, metal, defects, warp and clear envelopes.	2 PROVE B/C Full-length 5/16 x 4-3/8 x 81-1/8 faces.	3 PROVE I/K + M/H Two-lane stile yield; M/H remain at least 5/8 thick.	4 RELEASE M/D/G/H 2-inch reserve is total per board; keep A/N/O.

Every board at a glance

STOCK	RAW T x W x L	FIRST-CROSSCUT STATUS	CUT / KEEP NOW	PROTECTED TAIL OR NEXT GATE
A	1 x 5-11/16 x 72-3/4	NO CUT - KEEP FULL 72-3/4 INCHES AS RESERVE	NO CUT - KEEP FULL 72-3/4 INCHES AS RESERVE	Six inches are already charged to damage removal. STOCK-M now carries D-101H, so do not consume A preemptively.
B	1 x 4-15/16 x 85	NO CROSSCUT - KEEP FULL 85 INCHES	NO CROSSCUT - KEEP FULL 85 INCHES	The hinge-stile show face must remain continuous. Full-length clear yield and thin-stock carrier control must be proved before trimming.
C	1 x 5-3/4 x 83-1/8	NO CROSSCUT - KEEP FULL 83-1/8 INCHES	NO CROSSCUT - KEEP FULL 83-1/8 INCHES	Only 2 inches of raw length exceed the face target. One 1/8-inch end cut leaves 1-7/8 inches for both squared ends, so actual clear length controls.
D	1 x 5 x 73-3/4	CUT ONLY AFTER CHK-RS-01 + CHK-ST-01 + CHK-ST-02 PASS	4 x 12-13/16	20 planning tail after shared 2-in end allowance
E	1 x 5-3/4 x 75-1/2	NO CUT - KEEP FULL 75-1/2 INCHES	NO CUT - KEEP FULL 75-1/2 INCHES	Knot locations are unknown. No cut is released until five combined E/F clear envelopes and all face-strip destinations are signed.
F	1 x 5-5/8 x 70-3/4	NO CUT - KEEP FULL 70-3/4 INCHES	NO CUT - KEEP FULL 70-3/4 INCHES	Knot locations are unknown. No cut is released until five combined E/F clear envelopes and all face-strip destinations are signed.
G	15/16 x 4-1/2 x 75	THICKNESS/WIDTH/LENGTH PASS - CUT ONLY AFTER CHK-P-01 + CHK-ST-01 + CHK-ST-02 PASS	4 x 16-9/16	6-1/4 planning tail after shared 2-in end allowance
H	7/8 x 5-3/4 x 79	CUT ONLY AFTER CHK-RS-01 + CHK-ST-01 + CHK-ST-02 PASS AND H THICKNESS / WARP SURVEY	3 x 11-5/16	42-11/16 planning tail after shared 2-in end allowance
I	1-1/2 x 9-1/4 x 84-3/4	NO CROSSCUT - KEEP FULL 84-3/4 INCHES	NO CROSSCUT - KEEP FULL 84-3/4 INCHES	Both continuous lock-stile layers depend on the same board and on the 8-7/8-inch jointed-width gate. Crosscutting first destroys the approved two-lane strategy.
J	1-5/16 x 7 x 79-1/4	NO CUT UNTIL CHK-SM-01 AND SIGNED CM-05 CORE/OFFCUT MAP	NO CUT UNTIL CHK-SM-01 AND SIGNED CM-05 CORE/OFFCUT MAP	J is now the only no-purchase source for the 6-1/2-inch F core stave displaced from L. The named core pattern, the clear 6-1/2-inch width envelope, and every credited offcut must be drawn, dimensioned, and signed before crosscutting.
K	1-3/8 x 9-1/2 x 82-1/2	NO CROSSCUT - KEEP FULL 82-1/2 INCHES	NO CROSSCUT - KEEP FULL 82-1/2 INCHES	This is the most length-critical board and still must pass the 8-7/8-inch jointed-width gate: the face target and one 1/8-inch end cut leave only 1-1/4 inches total for both squared ends.
L	1-5/16 x 6 x 80	NO CUT UNTIL CHK-SM-01 AND SIGNED CM-05 CORE/OFFCUT MAP	NO CUT UNTIL CHK-SM-01 AND SIGNED CM-05 CORE/OFFCUT MAP	The original 7-inch width is obsolete. The current 6-inch width forces the revised J/L swap; the named core pattern, D/F seam directions, and every credited width offcut must be drawn, dimensioned, and signed before crosscutting.
M	3/4 x 8-1/4 x 99	CUT ONLY AFTER CHK-RS-01 + CHK-ST-01 + CHK-ST-02 PASS AND M FINISHED-STOCK SURVEY	3 x 16-1/16	48-7/16 planning tail after shared 2-in end allowance
N	1-3/4 x 11 x 74	NO CUT - KEEP FULL 74 INCHES AS SHORT-MEMBER RESERVE	NO CUT - KEEP FULL 74 INCHES AS SHORT-MEMBER RESERVE	The finished-white-oak board is only 74 inches long and cannot replace an 81-inch stile layer; preserve its wide, thick envelope for a short-core failure.
O	1-3/4 x 11 x 74	NO CUT - KEEP FULL 74 INCHES AS SHORT-MEMBER RESERVE	NO CUT - KEEP FULL 74 INCHES AS SHORT-MEMBER RESERVE	The finished-white-oak board is only 74 inches long and cannot replace an 81-inch stile layer; preserve its wide, thick envelope for a short-core failure.

Cut-Now Details: STOCK-M and STOCK-D

Complete CHK-RS-01 first. These diagrams show representative clear-zone nesting, not blind cumulative marks from a rough end.

STATUS: CUT ONLY WHEN EVERY NAMED BILLET AND THE PROTECTED TAIL ARE VISIBLE INSIDE THE DEFECT MAP.

STOCK-M RAW 3/4 x 8-1/4 x 99 IN

CUT ONLY AFTER CHK-RS-01 + CHK-ST-01 + CHK-ST-02 PASS AND M FINISHED-STOCK SURVEY



Representative nesting after defect map. Planning tail after one shared 2-in end allowance: 48-7/16 in.

STOCK-M CUT: 3 x 16-1/16 in (M-H1, M-H2, M-H3). After milling and rest, each must still reach 15-9/16 in controlled rough length; finished reference 15-1/16 in. **Later:** Keep the tail intact. Only after D-101H passes and FP-05 proves clear envelopes may up to two 16-1/4-inch M-FACE mother billets be cut and planed from whole thickness to 5/16.

STOCK-D RAW 1 x 5 x 73-3/4 IN

CUT ONLY AFTER CHK-RS-01 + CHK-ST-01 + CHK-ST-02 PASS



Representative nesting after defect map. Planning tail after one shared 2-in end allowance: 20 in.

STOCK-D CUT: 4 x 12-13/16 in (D-K1, D-K2, D-L1, D-L2). After milling and rest, each must still reach 12-5/16 in controlled rough length; finished reference 11-13/16 in. **Later:** Keep the tail intact. Only after both lower panels pass and FP-05 is signed, cut one clear 16-1/4-inch D-FACE mother billet and plane it from whole thickness to 5/16.

Board-specific arithmetic

M	3 x 16-1/16 + 3 x 1/8 kerf + 2 shared end allowance = 50-9/16.	Protected tail 48-7/16. After panel release, up to two 16-1/4 face-stock billets are conditional on clear signed zones; full-pattern paper remainder 15-11/16.
D	4 x 12-13/16 + 4 x 1/8 kerf + 2 shared end allowance = 53-3/4.	Protected tail 20. After both lower panels pass, cut one 16-1/4 face-stock mother billet from a clear zone.

Cut-Now Details: STOCK-G and STOCK-H

G is confirmed S4S at 15/16 x 4-1/2 x 75. H remains rough and thickness-critical; a positive length remainder does not release a failed billet.

STATUS: G THICKNESS/WIDTH/LENGTH PASS; CHK-P-01 STILL CONTROLS. H MUST PROVE THE COMPLETE 5/8-INCH YIELD ENVELOPE.

STOCK-G RAW 15/16 x 4-1/2 x 75 IN

THICKNESS/WIDTH/LENGTH PASS - CUT ONLY AFTER CHK-P-01 + CHK-ST-01 + CHK-ST-02 PASS



Representative nesting after defect map. Planning tail after one shared 2-in end allowance: 6-1/4 in.

STOCK-G CUT: 4 x 16-9/16 in (G-J1, G-J2, G-J3, G-J4). After milling and rest, each must still reach 16-1/16 in controlled rough length; finished reference 15-9/16 in. **Tail:** Retain the complete remainder for panel substitutions, same-stock coupons, setup pieces, or repair stock.

STOCK-H RAW 7/8 x 5-3/4 x 79 IN

CUT ONLY AFTER CHK-RS-01 + CHK-ST-01 + CHK-ST-02 PASS AND H THICKNESS / WARP SURVEY



Representative nesting after defect map. Planning tail after one shared 2-in end allowance: 42-11/16 in.

STOCK-H CUT: 3 x 11-5/16 in (H-N1, H-N2, H-N3). After milling and rest, each must still reach 10-13/16 in controlled rough length; finished reference 10-5/16 in. **Tail:** Keep the tail intact until all three panel billets dress to at least 5/8 inch. After D-101N passes and FP-05 is signed, cut up to two clear 16-1/4-inch H-FACE mother billets and plane them from whole thickness to 5/16.

Board-specific arithmetic and yield gate

G	4 x 16-9/16 + 4 x 1/8 kerf + 2 shared end allowance = 68-3/4.	6-1/4 remains after the shared reserve. The 15/16-inch thickness passes; four jointed staves must retain 16-3/8 aggregate width.
H	3 x 11-5/16 + 3 x 1/8 kerf + 2 shared end allowance = 36-5/16.	42-11/16 remains on paper. Each billet must finish at least 5/8 thick; use minimal passes.

Full-Length Holds and Later Cut Map

Board M carries the upper panel; Boards N/O add uncut short-core reserve. Continuous stile yield still controls before consuming a panel or short-member board. Shortening a held board destroys the flexibility that makes the complete door feasible.

STATUS: CONTROLLED-RESERVE ORDER: SURVEY A-O; PROVE B/C; PROVE I/K; SURVEY M/H; KEEP N/O FULL; ONLY THEN RELEASE PANEL CUTS.				
STOCK	KEEP NOW	WHY IT STAYS LONG	AUTHORIZED LATER PATTERN	PAPER REMAINDER
B	FULL 85 IN	The hinge-stile show face must remain continuous. Full-length clear yield and thin-stock carrier control must be proved before trimming.	After CHK-ST-01, flatten and joint one continuous 4-3/8-inch lane, rest it, then plane the whole-thickness board in staged carrier-supported passes. Trim only after it proves the 5/16 x 4-3/8 x 81-1/8 D-101A show-face envelope.	3-3/4 in
C	FULL 83-1/8 IN	Only 2 inches of raw length exceed the face target. One 1/8-inch end cut leaves 1-7/8 inches for both squared ends, so actual clear length controls.	After CHK-ST-01, establish one continuous 4-3/8-inch D-101B show-face lane and preserve its longitudinal width offcut for FP-05. Plane eligible pieces from whole thickness in staged carrier-supported passes; trim the stile face only after it proves 5/16 x 4-3/8 x 81-1/8.	1-7/8 in
E	FULL 75-1/2 IN	Knot locations are unknown. No cut is released until five combined E/F clear envelopes and all face-strip destinations are signed.	Photograph and map every knot, check, and clear zone. FP-05 provisionally assigns three clear 16-1/4-inch face mother billets here, but may shift billets between E and F while preserving at least five accepted billets combined.	24-3/8 in
F	FULL 70-3/4 IN	Knot locations are unknown. No cut is released until five combined E/F clear envelopes and all face-strip destinations are signed.	Photograph and map every knot, check, and clear zone. FP-05 provisionally assigns two clear 16-1/4-inch face mother billets here, but may shift billets between F and E while preserving at least five accepted billets combined.	36 in
I	FULL 84-3/4 IN	Both continuous lock-stile layers depend on the same board and on the 8-7/8-inch jointed-width gate. Crosscutting first destroys the approved two-lane strategy.	Pass CHK-ST-02 at full length and prove at least 8-7/8 inches of clear jointed width. Make one ordinary full-length width rip for two 4-3/8-inch lanes plus the 1/8-inch kerf. Plane one lane to the D-101B 7/8-inch core and the parallel lane to the D-101B 5/16-inch back face; face clear length is 81-1/8 and governs.	3-1/2 in
J	FULL 79-1/4 IN	J is now the only no-purchase source for the 6-1/2-inch F core stave displaced from L. The named core pattern, the clear 6-1/2-inch width envelope, and every credited offcut must be drawn, dimensioned, and signed before crosscutting.	After revised CM-05 proves one clear 6-1/2-inch jointed width envelope, cut three 16-1/4-inch mother billets for D-101C-CORE, D-101M-CORE, and the 6-1/2-inch D-101F-CORE wide stave, plus one 12-inch D-101G-CORE billet. Plane cores to 7/8 and retain every usable longitudinal width offcut for FP-05.	16 in
K	FULL 82-1/2 IN	This is the most length-critical board and still must pass the 8-7/8-inch jointed-width gate: the face target and one 1/8-inch end cut leave only 1-1/4 inches total for both squared ends.	Pass CHK-ST-02 at full length and prove at least 8-7/8 inches of clear jointed width. Make one ordinary full-length width rip for two 4-3/8-inch lanes plus the 1/8-inch kerf. Plane one lane to the D-101A 7/8-inch core and the parallel lane to the D-101A 5/16-inch back face; face clear length is 81-1/8 and governs.	1-1/4 in
L	FULL 80 IN	The original 7-inch width is obsolete. The current 6-inch width forces the revised J/L swap; the named core pattern, D/F seam directions, and every credited width offcut must be drawn, dimensioned, and signed before crosscutting.	After revised CM-05 is signed, cut four 16-1/4-inch mother billets for D-101E-CORE, the 5-inch and 2-1/4-inch D-101D-CORE staves, and the 5-3/4-inch D-101F-CORE top stave. Plane cores to 7/8 and retain every usable longitudinal width offcut for FP-05. L is not authorized for any 6-1/2-inch billet.	12-1/2 in

Release sequence for the held boards

1 SURVEY A-O	Acclimate, metal scan, and record minimum raw thickness/width, cup, bow, twist, defects, and usable clear length before any saw cut.
2 PROVE B + C	Keep full. Each must yield one continuous 5/16 THICK x 4-3/8 WIDE x 81-1/8 LONG face after flatten, rest, staged planing, and recheck.
3 PROVE I + K	Keep full. Prove at least 8-7/8 inches clear jointed width, then rip two 4-3/8-inch lanes. One finishes 7/8; one finishes 5/16; both stay continuous.
4 PROVE M/H; CUT PANELS	M and H must remain at least 5/8 thick after preparation and rest. Then release only the mapped M/D/G/H panel billets; keep A intact as reserve and stop at controlled rough size.
5 SHORT MEMBERS	Map E/F knots, sign J/L core map and FP-05, then cut named billets only. Retain every tail and offcut until the completed door passes.

STOP RULE: If actual combined end loss exceeds the listed reserve, or any billet cannot yield its controlled thickness, width, and clear length, stop and remap before processing another board. Do not shorten a stile, hide an end splice, narrow the door, or borrow critical stock for moulding. Never measure only after all boards have been milled. Never surface below the machine manufacturer's safe minimum length or thickness; keep a longer mother piece or use a verified carrier/sled and guarded procedure.