

Door Shopping List

Rev. G fitted slab: 23-3/4 x 80-1/2 x 1-3/8 inches from the confirmed 24 x 81 jamb; prefit 23-7/8 x 80-5/8. Equal 4-1/4-inch stiles and 15-1/4-inch rails permit a no-resaw layer plan from A-O.

PROJECT / ROOM	BUYER	DATE	SUPPLIER
----------------	-------	------	----------

Door lumber status - LS-05 (supersedes LS-04)

OK	QTY	BUY	SPECIFICATION / GATE	COST
☐	0 BF	General door lumber - NOT RELEASED	All STOCK-A through STOCK-O are in hand and reserved for the door. The complete recorded inventory totals about 71.52 BF. G is confirmed S4S at 15/16 x 4-1/2 x 75 inches; its thickness/width/length fit D-101J, while CHK-P-01 still controls clear yield. M carries D-101H; A remains intact; STOCK-N/O remain full-length short-member reserve. This remains conditional inventory, not proven physical yield.	\$_____
☐	As gated	Specific replacement stock only	Buy only after a signed RS/ST/SM/FP/P/LAM/SEAM gate identifies the failed layer, member family, face pool, panel source, or seam assembly. Never shorten, narrow, splice, or consume a critical stile layer to solve another shortage.	\$_____

Joinery, panel control, and adhesive

OK	QTY	BUY	SPECIFICATION / GATE	COST
☐	60 pc	10 x 50 mm Domino	Factory beech: 26 final, 26 retained setup/test, and 8 spare. Keep the three groups separated.	\$_____
☐	12 pc	6 x 40 mm Domino	Factory beech: 4 final, 4 retained setup/test, and 4 spare for D-101G-to-D-101E/F.	\$_____
☐	40 rec.	3/4-inch foam spacers	Oil- and silicone-free open-cell foam. Controlled minimum is 30; order 40 for 20 installed, both family tests, and a practical spare/alternate reserve. PB265-750XF-1M is reference-only.	\$_____
☐	32 oz minimum	Type II PVA	Fresh and manufacturer-approved for full-area oak lamination. Planning minimum only: verify actual layup-area coverage, spread rate, open time, pressure, temperature, and cure on same-layup coupons.	\$_____

Hardware, finish, and shop supplies

OK	QTY	BUY	SPECIFICATION / GATE	COST
☐	1 set	Brass mortise lock	Complete privacy set with lock body, strike, knobs/spindle, escutcheons, faceplate, and final screws. Buy same-size steel setup screws for every hole plus spares.	\$_____
☐	3	3-1/2-inch butt hinges	Period-compatible brass leaves with matching final screws. Buy same-size steel setup screws for every hole plus spares; confirm load rating.	\$_____
☐	350 mL	Rubio Oil Plus 2C	Pure. Approve a complete color, sheen, and adhesion sample; follow the current product data sheet.	\$_____
☐	1 pack	P80/P100/P120 abrasives	Discs and hand sheets; use clean abrasives and stop at P120 unless the current finish data sheet differs.	\$_____
☐	As needed	Plywood jig stock	Flat 1/2- and 3/4-inch Baltic-birch offcuts for story sticks, stops, supports, and templates; jigs only.	\$_____
☐	1	Oily-waste container	Lidded metal can or water-filled sealed metal container suitable for finish waste and local disposal rules.	\$_____

SUBTOTAL \$_____	TAX / DELIVERY \$_____	TOTAL \$_____
----------------------------	----------------------------------	-------------------------

LS-05 PURCHASE RULE No general door-lumber purchase is released while every A-O yield and coupon gate passes. A failed gate authorizes only the specifically documented replacement. Moulding uses a separate controlled order; never transfer A-O stock to it before final door release.

Lamination and Release Checklist

LS-05 supersedes LS-04, reserves A-O for the door, and conditionally maps a no-resaw balanced laminated frame. Reported finished, rough-sawn, or unspecified-surface dimensions never prove dressed, staged-planed, coupon, or seam-controlled yield.

PROJECT / ROOM	BUYER	DATE	SUPPLIER

Balanced frame lamination - controlled billets

OK	PART(S)	QTY	CONTROLLED BLANK / BILLET	RECEIVED / BOARD
☐	D-101A/B - continuous stile cores	2	7/8 x 4-3/8 x 81 in	
☐	D-101A/B - continuous stile faces	4	5/16 x 4-3/8 x 81-1/8 in	
☐	D-101C/M/E/G - core + paired faces	4	J/L cores + signed no-resaw face pool	
☐	D-101D/F - staggered sheet seams	2	Per CHK-SM-01 + CHK-SEAM-01	
PREGLUE 5/16 show face + 7/8 core + 5/16 back face = 1-1/2 in			FINISHED Surface equally to 1/4 + 7/8 + 1/4 = 1-3/8 in	

Panel yield held inside A-O

OK	PART(S)	QTY	CONTROLLED BLANK / BILLET	RECEIVED / BOARD
☐	D-101H - upper panel	1	5/8 x 16-3/8 x 15-9/16 in	
☐	D-101J - center panel	1	5/8 x 16-3/8 x 16-1/16 in	
☐	D-101N - lower-center panel	1	5/8 x 16-3/8 x 10-13/16 in	
☐	D-101K/L - lower panels	2	5/8 x 7-3/8 x 12-5/16 in	

Receiving and release gates

- | | |
|--|--|
| ☐ Moisture is 6-9% at receipt and is rechecked after acclimation. | ☐ CHK-RS-01 records minimum thickness, width, bow, cup, twist, checks, and defects; no rough face or edge is a datum. |
| ☐ CHK-ST-01 proves B/C each yield one continuous 5/16-inch stile face with no taper, defect, or end joint. | ☐ CHK-ST-02 proves I/K each yield two continuous 4-3/8-inch lanes: one 7/8-inch core and one 5/16-inch face. |
| ☐ CHK-SM-01 maps every J/L core and every staged-planed face, including at least five clear 16-1/4-inch E/F mother billets. | ☐ CHK-FP-01 signs every short-member face strip, seam position, coupon, and repair reserve. |
| ☐ CHK-P-01 conditionally releases M/G/H/D for H/J/N/K-L, with A kept intact as reserve, vertical grain, and a matched lower pair. | ☐ CHK-LAM-01 destructively proves every same-layup family, 1/4-inch finished faces, core clearance, and wood failure. |
| ☐ CHK-SEAM-01 verifies D/F core/show/back seams and mortise clearance before machining. | ☐ Every A-O remnant remains door-only; no material transfers to the separate moulding order. |
| ☐ Factory tenons remain full length; final, setup/test, and spare stock are separated. | ☐ Selected 3/4-inch-long foam is released separately on full-size H/J/N and K/L samples. |
| ☐ Physical lock, strike, hinges, and screws are present before hardware machining. | ☐ Finish color, sheen, adhesion, and application sample is approved on project offcut. |

Shop-owned tool readiness - buy only if missing or worn

- | | |
|--|--|
| ☐ DF 500 with sharp 10 mm and 6 mm cutters. | ☐ Dado stack for supported through-rail grooves only. |
| ☐ Plunge router, 1/4-inch cutter, guide/jig, and positive stops for stopped or segmented grooves. | ☐ Moisture meter, calipers, accurate rules, winding sticks, and two diagonal tapes. |
| ☐ At least five clamps with more than 24 inches of capacity, plus padded cauls, supports, and non-marring pads. | ☐ Labeled test stock for every groove, mortise, spacer, adhesive, and finish setup. |

LS-05 DOOR-STOCK DISPOSITION

All STOCK-A through STOCK-O is reserved for the door, same-layup coupons, setup pieces, substitutions, and repair stock. STOCK-N/O remain full-length short-core reserve. General door-lumber purchase remains zero only while RS/ST/SM/FP/P/LAM/SEAM gates pass.

FIELD HOLD

The completed jamb, floor, hanging, swing, physical hardware, final perimeter, hinge gains, lock machining, strike, and all room-specific moulding lengths remain field-controlled.

Written dimensions and project/specification.yaml govern. The shopping list does not authorize final slab fitting or hardware machining.