

FINAL DOOR LUMBER LIST

DC-1916-001 | Rev. G / LS-05 | Dimensions are THICKNESS x WIDTH x LENGTH | Door slab: 23-3/4 x 80-1/2 x 1-3/8 inches

DOOR STOCK: Boards A-O only. The seven new 2-1/2 x 11 x 148-inch rough boards are reserved for the table and are not assigned to this door.

BOARD	CURRENT SIZE	SURFACE	FINAL DOOR ASSIGNMENT	STATUS
A	1 x 5-11/16 x 72-3/4	Rough	Keep full as emergency panel, face-stock, coupon, setup, or repair reserve.	RESERVE
B	1 x 4-15/16 x 85	Rough	Continuous D-101A hinge-stile show-face layer.	CRITICAL
C	1 x 5-3/4 x 83-1/8	Rough	Continuous D-101B lock-stile show-face layer; usable width offcuts enter the short-face pool.	CRITICAL
D	1 x 5 x 73-3/4	Rough	Four staves for D-101K/L lower panels; conditional short-face billet from the remainder.	PRIMARY
E	1 x 5-3/4 x 75-1/2	Rough / knots	Three clear short-member face billets, subject to the combined E/F knot and defect map.	MAP FIRST
F	1 x 5-5/8 x 70-3/4	Rough / knots	Two clear short-member face billets, subject to the combined E/F knot and defect map.	MAP FIRST
G	15/16 x 4-1/2 x 75	S4S	Four staves for D-101J center panel; size passes, CHK-P-01 still controls clear yield.	PRIMARY
H	7/8 x 5-3/4 x 79	Rough	Three staves for D-101N lower-center panel; eligible tail stock for short faces.	CRITICAL
I	1-1/2 x 9-1/4 x 84-3/4	Rough	D-101B lock-stile core and continuous back-face layer.	CRITICAL
J	1-5/16 x 7 x 79-1/4	Rough	Cores for D-101C/M, D-101F wide stave, and D-101G center muntin.	CRITICAL
K	1-3/8 x 9-1/2 x 82-1/2	Rough	D-101A hinge-stile core and continuous back-face layer.	CRITICAL
L	1-5/16 x 6 x 80	Edges cleaned	Cores for D-101E, both D-101D staves, and the 5-3/4-inch D-101F stave.	MAP FIRST
M	3/4 x 8-1/4 x 99	Finished	Primary D-101H upper-panel stock; tail may provide up to two short-face billets.	PRIMARY
N	1-3/4 x 11 x 74	Finished	Keep full as short-member core, substitution, and repair reserve.	RESERVE
O	1-3/4 x 11 x 74	Finished	Keep full as short-member core, coupon, setup, and repair reserve.	RESERVE

MOULDING: Casing, backband, stop, cap, and other trim stock remain a separate purchase and are not included above.

SHOP GATE: Verify moisture, straightness, defects, clear yield, and the applicable LS-05 check before crosscutting.

Use this sheet as a visual lumber-assignment reference. The controlled cut sheets, yield gates, and written dimensions govern fabrication.