

Door-Only Labeled Lumber Inventory

LS-05 supersedes LS-04. M = 3/4 x 8-1/4 x 99 inches finished white oak and carries D-101H; keep damaged A intact at 72-3/4 inches. N/O are each confirmed finished white oak at 1-3/4 x 11 x 74 inches and remain full-length short-member reserve. No-resaw slab 23-3/4 x 80-1/2 x 1-3/8; prefit 23-7/8 x 80-5/8 in the 24 x 81 jamb with 3/8 bottom gap.

STATUS: G NOW S4S 15/16 X 4-1/2 X 75; THICKNESS/WIDTH/LENGTH FIT D-101J; CHK-P-01 AND OTHER LS-05 GATES UNCHANGED				
STOCK	CURRENT / HISTORICAL T x W x L	CONDITION	DOOR-ONLY USE	DISPOSITION
A	1 X 5 11/16 X 72 3/4 CURRENT; ORIGINAL 78 3/4	Rough-sawn; 6-inch damaged section removed from the original length; verify the new end is sound and map any continuation of the defect before cutting	Keep intact as a door-only reserve for panel substitution, short-face stock, coupons, setup pieces, or repair stock; do not cut while STOCK-M proves D-101H	RESERVE - KEEP FULL AFTER DAMAGE MAP
B	1 X 4 15/16 X 85	Rough-sawn; no defect reported	One continuous D-101A hinge-stile show-face lamella, planed from the whole-thickness board; preserve full length until the 4-3/8 x 81-1/8 clear envelope passes	CRITICAL - STILE FACE SHEET
C	1 X 5 3/4 X 83 1/8	Rough-sawn; no defect reported	One continuous D-101B lock-stile show-face lamella plus longitudinal width offcut for the signed short-member face pool	CRITICAL - STILE FACE SHEET
D	1 X 5 X 73 3/4	Rough-sawn; no defect reported	Primary four-stave allocation, paired two each, for D-101K and D-101L lower panels	CONDITIONAL - DOOR PANELS
E	1 X 5 3/4 X 75 1/2	Rough-sawn; some knots	Short-member face pool; E and F together must yield at least five clear 5/16 x usable-width x 16-1/4 mother billets after every knot and check is excluded	HOLD - SIGNED KNOT AND FACE-POOL MAP REQUIRED
F	1 X 5 5/8 X 70 3/4	Rough-sawn; some knots	Short-member face pool; E and F together must yield at least five clear 5/16 x usable-width x 16-1/4 mother billets after every knot and check is excluded	HOLD - SIGNED KNOT AND FACE-POOL MAP REQUIRED
G	CURRENT S4S: 15/16 X 4 1/2 X 75; WAS ROUGH 1 X 4 7/8 X 78 1/4	S4S; current 15/16-inch thickness exceeds the 5/8-inch panel minimum; verify flatness, moisture, grain, defects, and glue-edge cleanup	Four-stave D-101J center panel; thickness/width/length pass; release crosscuts only after CHK-P-01	CONDITIONAL - CHK-P-01 PANEL MAP
H	7/8 X 5 3/4 X 79	Rough-sawn; no defect reported	Primary three-stave D-101N lower-center-panel glue-up	CRITICAL THICKNESS - DOOR PANEL
I	1 1/2 X 9 1/4 X 84 3/4	Rough-sawn; flatness, straightness, twist, and dressed yield not recorded	Two parallel full-length 4-3/8-inch lanes: continuous D-101B lock-stile core and continuous D-101B back face	CRITICAL - LOCK-STILE CORE AND BACK FACE
J	1 5/16 X 7 X 79 1/4	Rough-sawn; no defect reported	Three 16-1/4-inch core mother billets for D-101C, D-101M, and the 6-1/2-inch D-101F wide core stave, plus D-101G at 12 inches; longitudinal width offcuts enter the signed face pool	CRITICAL 6-1/2-INCH WIDTH - SIGNED CORE/OFFCUT MAP
K	1 6/16 X 9 1/2 X 82 1/2	Rough-sawn; no defect reported	Two parallel full-length 4-3/8-inch lanes: continuous D-101A hinge-stile core and continuous D-101A back face	CRITICAL - HINGE-STILE CORE AND BACK FACE
L	1 5/16 X 6 X 80 CURRENT AFTER EDGE CLEANUP	Edges cleaned/jointed to 6 inches after edge cleanup; faces, thickness, length, flatness, and final dressed yield not reverified	Four 16-1/4-inch core mother billets: D-101E, both D-101D staves at 5 and 2-1/4 inches, and the 5-3/4-inch D-101F top core stave; no 6-1/2-inch billet is assigned to L	HOLD - REVISED SIGNED CORE/OFFCUT MAP
M	3/4 X 8 1/4 X 99 FINISHED	Reported finished white oak; verify actual S4S dimensions, straightness, moisture, grain orientation, color, and clear defect-free envelopes before cutting	Primary three-stave D-101H upper-panel glue-up; after the panel passes, up to two 16-1/4-inch whole-thickness short-face mother billets may enter signed FP-05	PRIMARY - FINISHED PANEL STOCK; VERIFY
N	1 3/4 X 11 X 74 FINISHED WHITE OAK	Finished white oak; finished dimensions confirmed; moisture, grain orientation, flatness, defects, and clear yield require normal shop inspection	Keep full length as door-only reserve. Prefer as a signed fallback for short-member 7/8-inch cores; do not consume it for 5/16-inch faces or 5/8-inch panels unless a documented remap proves that the large planing loss is necessary.	RESERVE - KEEP FULL; SHORT-CORE FALLBACK
O	1 3/4 X 11 X 74 FINISHED WHITE OAK	Finished white oak; finished dimensions confirmed; moisture, grain orientation, flatness, defects, and clear yield require normal shop inspection	Keep full length as door-only reserve. Prefer as a signed fallback for short-member 7/8-inch cores, coupons, or repair stock; do not consume it for 5/16-inch faces or 5/8-inch panels unless a documented remap proves that the large planing loss is necessary.	RESERVE - KEEP FULL; SHORT-CORE FALLBACK

Balanced Laminated Frame Schedule

The engineered layup keeps the centered groove and DF500 machining inside a continuous 7/8-inch core. Every 5/16-inch face is staged-planed from a whole lane or mother billet; there are no through-thickness saw cuts.

STATUS: NO DOOR LUMBER PURCHASE RELEASED; EVERY LAMINATED MEMBER REMAINS ON PHYSICAL-YIELD AND COUPON HOLD.

BALANCED LONG-GRAIN FRAME SECTION

SHOW FACE 5/16 -> 1/4	CORE 7/8	BACK FACE 5/16 -> 1/4
-----------------------	----------	-----------------------

Preglue 1-1/2 in; cure/rest; remove 1/16 equally from both outer faces; finished 1-3/8 in

PREGLUE 5/16 face + 7/8 core + 5/16 face = 1-1/2 in.		FINISHED 1/4 face + 7/8 core + 1/4 face = 1-3/8 in.	MACHINING Laminate, cure, rest, surface symmetrically, then cut grooves, Domino mortises, hinge gains, and lock work.
PART	CORE STOCK / BLANK	FACE STOCK / BLANKS	SEAM CONTROL
D-101A Hinge stile	K 7/8 x 4-3/8 x 81	SF: B BF: K parallel lane B show face and K parallel-lane back face, each 5/16 x 4-3/8 x 81-1/8	one-piece core and continuous faces; no end or edge seam
D-101B Lock stile	I 7/8 x 4-3/8 x 81	SF: C BF: I parallel lane C show face and I parallel-lane back face, each 5/16 x 4-3/8 x 81-1/8	one-piece core and continuous faces; no end or edge seam
D-101C Top rail	J-C-CORE 7/8 x 4-1/4 x 16-1/4	SF: signed FP-05 BF: signed FP-05 two total, each 5/16 x 4-1/4 x 16-1/4	one-piece core and one-piece-width faces
D-101M Upper intermediate rail	J-M-CORE 7/8 x 4-1/4 x 16-1/4	SF: signed FP-05 BF: signed FP-05 two total, each 5/16 x 4-1/4 x 16-1/4	one-piece core and one-piece-width faces
D-101D Lock rail	L-DW-CORE + L-DN-CORE 7/8 x 7-1/4 x 16-1/4	SF: signed FP-05 BF: signed FP-05 two total, each 5/16 x 7-1/4 x 16-1/4	core 2-1/4 from finished top; show face 4-3/8; back face 4-7/8; all +/-1/32
D-101E Lower intermediate rail	L-E-CORE 7/8 x 4-1/4 x 16-1/4	SF: signed FP-05 BF: signed FP-05 two total, each 5/16 x 4-1/4 x 16-1/4	one-piece core and one-piece-width faces
D-101F Bottom rail	L-F1-CORE + J-F2-CORE 7/8 x 12-1/4 x 16-1/4	SF: signed FP-05 BF: signed FP-05 two total, each 5/16 x 12-1/4 x 16-1/4	core 5-3/4; show face 3, 6-1/2, and 9-1/2; back face 2-1/2, 5, and 9; all from finished top and all +/-1/32
D-101G Center muntin	J-G-CORE 7/8 x 3-1/4 x 12	SF: signed FP-05 BF: signed FP-05 two total, each 5/16 x 3-1/4 x 12	one-piece core and one-piece-width faces

Kerf-Aware Door Operations

Preserve B, C, I, K, J, and L at full length. J must prove a 6-1/2-inch width envelope for the wide F core stave; 6-inch L carries both D core staves, E, and the 5-3/4-inch F stave.

STATUS: PAPER NESTING IS NOT A CUTTING RELEASE. MEASURE DRESSED YIELD BEFORE PROCESSING THE NEXT BOARD.

STOCK / OP	TARGET	SEGMENTS	END	RIP / MILLING PLAN	REQUIRED YIELD	STATUS
M M-01	D-101H upper panel	3 x 15-9/16 3 kerf(s)	2	After verifying the reported finished board, crosscut three shop billets, rip each to a staged width above 5.4584 inches, establish glue edges, and preserve aggregate jointed width for the oversize panel blank. Keep the 49-15/16-inch controlled tail intact before M-02	Three staves collectively at least 5/8 x 16-3/8 x 15-9/16 after jointing; 5.4584 inches minimum average jointed stave width	HOLD - VERIFIED MILLING REQUIRED
M M-02	Signed short-member face pool	2 x 16-1/4 2 kerf(s)	0	After D-101H passes, cut up to two clear mother billets from the retained tail and plane each whole-thickness billet to 5/16 on a verified carrier	Two 5/16-inch short-face mother billets at least 16-1/4 inches long; usable jointed widths recorded on FP-05	HOLD - AFTER PANEL AND SIGNED FACE-POOL MAP
B B-01	D-101A-SF continuous hinge-stile show face	1 x 81-1/8 1 kerf(s)	3-3/4	Preserve full length; flatten and joint a 4-3/8-inch clear lane, then plane the whole board in shallow staged passes to a stable 5/16-inch lamella using a verified carrier below normal planer capacity	One continuous glue-ready lamella at least 5/16 x 4-3/8 x 81-1/8	STOP - CONTINUOUS FACE AND CARRIER-PLANING YIELD
C C-01	D-101B-SF continuous lock-stile show face plus longitudinal short-face strips	1 x 81-1/8 1 kerf(s)	1-7/8	Preserve full length; establish a 4-3/8-inch face lane and retain the parallel longitudinal width offcut. Plane the whole-thickness face lane and eligible offcut strips in staged carrier-supported passes to 5/16.	One continuous glue-ready lamella at least 5/16 x 4-3/8 x 81-1/8 plus traceable 16-1/4-inch strips for FP-05 where jointed width survives	STOP - LENGTH-CRITICAL FACE YIELD
D D-01	D-101K and D-101L lower-panel pair	4 x 12-5/16 4 kerf(s)	2	Crosscut four staves after defect mapping; flatten and joint them, then pair two per panel with mirrored grain and color	Four staves at least 5/8 x 3-11/16 x 12-5/16; two glue-ups each at least 5/8 x 7-3/8 x 12-5/16	HOLD - VERIFIED MILLING REQUIRED
D D-02	Signed short-member face pool	1 x 16-1/4 1 kerf(s)	0	After both lower panels pass, cut one clear mother billet from the retained tail and plane the whole-thickness billet to 5/16 on a verified carrier	One 5/16-inch short-face mother billet at least 16-1/4 inches long; usable jointed width recorded on FP-05	HOLD - AFTER PANELS AND SIGNED FACE-POOL MAP
E E-01	Signed short-member face pool	3 x 16-1/4 3 kerf(s)	2	Map every knot and check first. Subject to FP-05, cut three clear mother billets and plane each whole-thickness billet to 5/16 in staged carrier-supported passes.	Three clear 5/16-inch short-face mother billets at least 16-1/4 inches long with signed usable widths	STOP - KNOT MAP AND FACE-POOL RELEASE
F F-01	Signed short-member face pool	2 x 16-1/4 2 kerf(s)	2	Map every knot and check first. Subject to FP-05, cut two clear mother billets and plane each whole-thickness billet to 5/16 in staged carrier-supported passes.	Two clear 5/16-inch short-face mother billets at least 16-1/4 inches long with signed usable widths	STOP - KNOT MAP AND FACE-POOL RELEASE
G G-01	D-101J center panel	4 x 16-1/16 4 kerf(s)	2	The confirmed 15/16-inch S4S thickness passes the 5/8-inch minimum. After CHK-P-01 maps four clear billets, crosscut and make only the minimum glue-edge cleanup required; assemble in vertical-grain sequence.	Four S4S staves collectively at least 5/8 x 16-3/8 x 16-1/16 after glue-edge preparation; each starts 4-1/2 inches wide and 75 inches total length is available	CONDITIONAL - THICKNESS/WIDTH/LENGTH PASS; VERIFY PANEL MAP
H H-01	D-101N lower-center panel	3 x 10-13/16 3 kerf(s)	2	Crosscut three staves only after the board proves 5/8 thickness over every required segment; flatten minimally and joint glue edges	Three staves collectively at least 5/8 x 16-3/8 x 10-13/16 after jointing; 5.4584 inches minimum average jointed stave width	STOP - THICKNESS-CRITICAL PANEL YIELD
H H-02	Signed short-member face pool	2 x 16-1/4 2 kerf(s)	0	After D-101N passes, cut two clear mother billets from the retained tail and plane each whole-thickness billet to 5/16 on a verified carrier	Two 5/16-inch short-face mother billets at least 16-1/4 inches long; usable jointed widths recorded on FP-05	HOLD - AFTER PANEL AND SIGNED FACE-POOL MAP
I I-01	D-101B-CORE and D-101B-BF parallel continuous lanes	1 x 81-1/8 1 kerf(s)	3-1/2	Preserve full length; flatten and joint to at least 8-7/8 inches clear, then make one ordinary full-length width rip yielding two 4-3/8-inch lanes and one 1/8-inch kerf. Plane one lane to a 7/8-inch core and the other, in staged carrier-supported passes, to a 5/16-inch back face.	One continuous 7/8 x 4-3/8 x 81 core and one continuous 5/16 x 4-3/8 x 81-1/8 back face	STOP - TWO-LANE WIDTH, LENGTH, AND THICKNESS YIELD
J J-01	D-101C/M-CORE + D-101F 6-1/2-inch wide core stave	3 x 16-1/4 3 kerf(s)	2	Under revised CM-05, J must prove one clear 6-1/2-inch width. Cut 3 x 16-1/4 mother billets; plane to 7/8; rip C/M at 4-1/4 and the F wide stave at 6-1/2. Save usable offcuts for FP-05.	One-piece C/M cores plus the continuous 6-1/2-inch F core stave, all 7/8 x 16-1/4; traceable offcuts	HOLD - SIGNED CORE/OFFCUT MAP
J J-02	D-101G-CORE	1 x 12 1 kerf(s)	0	From the signed fourth clear envelope, plane the mother billet to 7/8 and width-rip the muntin core at 3-1/4 inches; retain the longitudinal width offcut for FP-05.	One continuous 7/8 x 3-1/4 x 12 muntin core plus a traceable face-pool width offcut	HOLD - SIGNED CORE/OFFCUT MAP
K K-01	D-101A-CORE and D-101A-BF parallel continuous lanes	1 x 81-1/8 1 kerf(s)	1-1/4	Preserve full length; flatten and joint to at least 8-7/8 inches clear, then make one ordinary full-length width rip yielding two 4-3/8-inch lanes and one 1/8-inch kerf. Plane one lane to a 7/8-inch core and the other, in staged carrier-supported passes, to a 5/16-inch back face.	One continuous 7/8 x 4-3/8 x 81 core and one continuous 5/16 x 4-3/8 x 81-1/8 back face	STOP - LENGTH-CRITICAL TWO-LANE YIELD
L L-01	D-101E-CORE + both D-101D core staves + D-101F 5-3/4-inch stave	4 x 16-1/4 4 kerf(s)	2	Under revised CM-05, cut 4 x 16-1/4; plane to 7/8; rip E at 4-1/4, D staves at 5 and 2-1/4, and F top at 5-3/4. L = 6 inches; no 6-1/2 billet. Save usable offcuts for FP-05.	One-piece E core, both D core staves, the 5-3/4-inch F core stave, and traceable offcuts	HOLD - SIGNED CORE/OFFCUT MAP

Release Gates and Separate Moulding Order

Run the gates in order: RS-01 on all boards, ST-01 on B/C, ST-02 on I/K, then P-01 panel cuts, short-member maps, coupons, and seam verification.

STATUS: CONTROLLED RESERVE: AT ANY FAILED GATE, STOP AND REMAP BEFORE PROCESSING ANOTHER BOARD. NEVER SPLICE A STILE.				
GATE	CHECK	PASS CONDITION	FALLBACK	SIGNOFF
CHK-RS-01 STOP	Acclimate and map A-O at full usable length. For A, confirm the current 72-3/4-inch length and inspect the new end after the 6-inch damage removal. For M, verify the reported finished 3/4 x 8-1/4 x 99-inch envelope. For N/O, record moisture, grain, flatness, defects, and clear squared-end yield while preserving their confirmed finished-white-oak 1-3/4 x 11 x 74-inch envelopes. For every board record actual dimensions, straightness, moisture, grain, bow, cup, twist, checks, knots, pith, runout, and clear squared-end limits.	Every proposed billet has a traceable clear envelope; A has a sound squared end and at least 72-3/4 inches of usable mapped reserve length; M has at least 5/8-inch recoverable thickness throughout three 16-1/16-inch panel billets and sufficient clear width for the signed three-stave map; N/O are positively identified and remain full at 74 inches unless a signed fallback map is released; and every lamination family is the same species at 6-9% moisture with layers within one percentage point.	Reallocate only within A-O under a signed map. If M fails, remap D-101H to clear STOCK-A before purchasing panel stock. Use finished-white-oak N/O only for a documented short-member fallback; do not crosscut a long critical board to solve a short-part shortage.	[] PASS [] HOLD ____/____
CHK-ST-01 STOP	Prove the whole-thickness staged plane/rest/carrier method on representative coupons, then prove STOCK-B and STOCK-C at full length.	B yields the D-101A show face and C yields the D-101B show face, each continuous and glue-ready at 5/16 x 4-3/8 x 81-1/8 with no taper, end joint, defect, or unstable grain.	Stop and obtain replacement continuous face stock. Do not shorten, end-splice, or veneer over a failed stile face.	[] PASS [] HOLD ____/____
CHK-ST-02 STOP	Prove the two full-length stile lanes in STOCK-I and STOCK-K before making the single width rip.	Each board has at least 8-7/8 inches of clear jointed width for two 4-3/8-inch lanes plus the 1/8-inch kerf; each yields one straight 7/8 x 4-3/8 x 81 core and one continuous 5/16 x 4-3/8 x 81-1/8 back face after staged planing and rest. K retains the hinge and screw zones; I retains the lock envelope.	Stop and purchase only a replacement long layer for the failed stile. Reducing the 4-1/4-inch finished stile or joining any long layer end-to-end is not authorized.	[] PASS [] HOLD ____/____
CHK-SM-01 STOP	Create and sign the revised CM-05 before cutting J or L. Because L is now 6 inches wide, J carries C, M, the 6-1/2-inch F stave, and G; L carries E, both D staves, and the 5-3/4-inch F stave.	J yields three 16-1/4-inch core mother billets for C, M, and the 6-1/2-inch F stave plus one 12-inch G billet; J must retain at least one clear 6-1/2-inch jointed width envelope. L yields four 16-1/4-inch billets for E, the 5-inch and 2-1/4-inch D staves, and the 5-3/4-inch F stave from its current 6-inch width. Every core is 7/8 inch, clear, continuous in length, and traceable; usable width offcuts are retained for FP-05, whose source pool also requires at least five clear 16-1/4-inch mother billets combined from E/F.	Rearrange only clear J/L envelopes under a revised signed map. If the core map fails, prefer a clear finished-white-oak STOCK-N or STOCK-O short-core remap; if that also fails, purchase only the failed core stock. Never consume a critical stile layer.	[] PASS [] HOLD ____/____
CHK-FP-01 STOP	Complete and sign FP-05 using up to two clear 16-1/4-inch STOCK-M tail billets after D-101H passes, plus D/H tails, eligible C/J/L longitudinal offcuts, and the required remaining clear mother billets from knot-mapped E/F. Keep STOCK-A intact unless a signed substitution is required.	The map assigns both 5/16-inch faces for C/M/D/E/F/G at full rough width and length, keeps C/M/E/G one piece across width, places D seams at 4-3/8 show and 4-7/8 back, places F show seams at 3, 6-1/2, and 9-1/2 and back seams at 2-1/2, 5, and 9, contains no end joints, and identifies coupons and repair reserve.	Reassign clear pool strips without moving a released seam. Keep N/O out of the face pool unless a signed remap accepts the excessive thickness-planing loss. If the complete A-O pool still fails, purchase only the missing face billet; do not alter a stile layer or core allocation.	[] PASS [] HOLD ____/____
CHK-P-01 STOP	Only after CHK-RS-01, CHK-ST-01, and CHK-ST-02 pass, verify thickness and warp throughout every mapped M/G/H/D clear envelope. M must show three clear 16-1/16-inch shop billets within its reported finished 99-inch length and at least 5/8-inch recoverable thickness throughout. Then rough-crosscut only the RL-02 finished-length-plus-1-inch panel billets and mill-test each shorter billet.	Each RL-02 billet yields its LS-05 controlled rough length after flattening and squaring; every stave remains at least 5/8 thick; M/H three-stave glue-ups and G's four-stave glue-up retain at least 16-3/8 aggregate jointed width, and both D pairs retain 7-3/8; all visible, tongue, and glue zones are clear.	If M fails, remap D-101H to clear STOCK-A. Use clear E/F or uncommitted J/L only after the structural short-member map passes; otherwise purchase replacement panel stock.	[] PASS [] HOLD ____/____
CHK-LAM-01 STOP	Press and destructively inspect same-layup coupons before every structural member family; coupon face stock must use the same whole-thickness staged plane/rest/carrier preparation as its production family.	The 5/16 + 7/8 + 5/16 layup measures 1-1/2 before surfacing, cures without voids or slip, then finishes 1/4 + 7/8 + 1/4 at 1-3/8. Sectioned groove and DF samples retain at least 0.200 actual core wood to each face glue line and fail in wood rather than at the adhesive line.	Correct moisture, surface preparation, adhesive spread, pressure, platen, or cauls and remake the coupon. Production members remain on hold.	[] PASS [] HOLD ____/____
CHK-SEAM-01 STOP	Transfer and verify the D-101D and D-101F three-plane seam maps after final width but before Domino machining.	D core/show/back seams are 2-1/4, 4-3/8, and 4-7/8 from top. F core seam is 5-3/4; show seams are 3, 6-1/2, and 9-1/2; back seams are 2-1/2, 5, and 9. Each is within +/-1/32, every face seam is offset at least 1/2 from the nearest core seam, and calculated clearance to the retained medium-width mortise planforms is at least 0.3041 inch for D and 0.4291 inch for F, exceeding the 1/4-inch requirement.	Rebuild the affected sheet or core. Do not move a Domino center without revising the specification, register, story stick, templates, drawings, and lock gate.	[] PASS [] HOLD ____/____

Door Lumber Disposition and Separate Moulding Order

The kerf-aware paper reconciliation is repeated here and remains editable in the companion workbook. A nonnegative remainder never overrides the signed physical-yield gates.

STATUS: NO GENERAL DOOR-LUMBER PURCHASE IS RELEASED. MOULDING IS A SEPARATE S4S ORDER.

Board-length reconciliation

STOCK	AVAILABLE	CUTS + KERFS	END RESERVE	PAPER REMAINDER	DISPOSITION
STOCK-B	85	81-1/4	3-3/4	0	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-C	83-1/8	81-1/4	1-7/8	0	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-D	73-3/4	66-1/8	2	5-5/8	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-E	75-1/2	49-1/8	2	24-3/8	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-F	70-3/4	32-3/4	2	36	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-G	75	64-3/4	2	8-1/4	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-H	79	65-9/16	2	11-7/16	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-I	84-3/4	81-1/4	3-1/2	0	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-J	79-1/4	61-1/4	2	16	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-K	82-1/2	81-1/4	1-1/4	0	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-L	80	65-1/2	2	12-1/2	PAPER FIT ONLY - PHYSICAL GATE CONTROLS
STOCK-M	99	79-13/16	2	17-3/16	PAPER FIT ONLY - PHYSICAL GATE CONTROLS

Door lumber purchase

NO DOOR LUMBER PURCHASE RELEASED

All owner-labeled A-O stock is reserved for the door. STOCK-M supplies the upper panel and additional conditional face stock, STOCK-A remains intact as panel reserve, and confirmed finished-white-oak STOCK-N/O remain full-length short-member reserve. Zero purchase still means conditional measured yield, not proof that every board will satisfy its physical-yield gate. Do not release panel or short-member production cuts until B/C//K pass. Door lumber purchase remains zero only if CHK-RS-01, CHK-ST-01, CHK-ST-02, CHK-SM-01, CHK-FP-01, CHK-P-01, CHK-LAM-01, and CHK-SEAM-01 pass. If a gate fails, stop and remap before consuming another board; if the remap cannot close, buy only a failed layer and never splice a failed stile.

Separate two-face moulding purchase

ID	QTY	MATERIAL	ACTUAL MINIMUM / PURPOSE
BUY-MOULD-4Q	7 boards	S4S quarter-sawn white oak, 4/4 x nominal 6 inches x 8 feet	3/4 inch thick at thinnest point after final preparation, 5-1/2 inches wide, 96 inches long; 13/16-inch thickness preferred four side casings, both head casings, one full-length casing spare/match board, and one three-piece stop mother blank
BUY-MOULD-6Q	2 boards	S4S quarter-sawn white oak, 6/4 x nominal 6 inches x 8 feet	1-1/4 inches thick, 5-1/2 inches wide, 96 inches long all side/head backband for two faces; also yields two optional caps only when square-head field evidence supports them

RELEASED BY

DATE

KERF in

MOISTURE %

LAYERS WITHIN 1%
[] YES