



# HTOC

HEALTHCARE THREAT OPERATIONS CENTER

ThreatConnect Playbook — SET SOAR Tagger

Version 1.0  
April 2026

**Table of Contents**

# Table of Contents

|                                            |          |
|--------------------------------------------|----------|
| <b>Table of Contents</b>                   | <b>2</b> |
| <b>1. Purpose</b>                          | <b>3</b> |
| <b>2. Scope</b>                            | <b>3</b> |
| <b>3. Trigger Configuration</b>            | <b>3</b> |
| <b>4. Selection Logic (TQL)</b>            | <b>4</b> |
| <b>5. Playbook Flow</b>                    | <b>4</b> |
| 5.1 Primary Processing Path                | 5        |
| 5.2 Decision Conditions                    | 5        |
| <b>6. Error Handling and Notifications</b> | <b>6</b> |
| <b>7. Key Configuration Values</b>         | <b>7</b> |
| <b>8. Run Success Criteria</b>             | <b>7</b> |
| <b>9. Troubleshooting</b>                  | <b>8</b> |
| <b>10. Operator Decision Points</b>        | <b>8</b> |
| <b>11. Related Documents</b>               | <b>9</b> |

## 1. Purpose

This playbook identifies newly added Address indicators in HTOC Org, verifies whether they are SOAR-generated, and applies a persistent marker tag (SOAR Indicator PB) to those indicators. It also records processed indicator data in ThreatConnect Local DataStore and sends operational alert emails when key processing steps fail.

The tag is used as a control to prevent reprocessing. Indicators already tagged SOAR Indicator PB are excluded by TQL on future runs.

-

## 2. Scope

This SOP applies to HTOC analysts and ThreatConnect administrators who monitor, modify, or troubleshoot the **SET SOAR Tagger** playbook.

-

## 3. Trigger Configuration

The playbook has two triggers. The timer trigger is the production trigger.

| Trigger Name                       | Type  | Schedule                                  | Status                     |
|------------------------------------|-------|-------------------------------------------|----------------------------|
| **Set SOAR Tag<br>Timer 12 hours** | Timer | `0 0 6,18 * * ?` (6:00<br>AM and 6:00 PM) | **Active —<br>Production** |

| Trigger Name | Type               | Schedule  | Status                            |
|--------------|--------------------|-----------|-----------------------------------|
| SOAR Trigger | HttpLink (Webhook) | On demand | Inactive<br>(manual/testing only) |

-

## 4. Selection Logic (TQL)

The **ThreatConnect Get Indicators** step uses the following TQL:

```
typeName in ("Address") and dateAdded >= "NOW() - 1 DAY" and NOT hasTag(summary in ("SOAR Indicator PB")) and ownerName in ("HTOC Org")
```

| Filter                               | Purpose                                                |
|--------------------------------------|--------------------------------------------------------|
| `typeName in ("Address")`            | Processes IP address indicators only                   |
| `dateAdded >= NOW() - 1 DAY`         | Restricts scope to newly added indicators              |
| `NOT hasTag(..."SOAR Indicator PB")` | Prevents reprocessing of previously handled indicators |
| `ownerName in ("HTOC Org")`          | Restricts to HTOC-owned indicators                     |
| `max_results = 2000`                 | Batch upper bound per execution                        |

-

## 5. Playbook Flow

## 5.1 Primary Processing Path

| Step | App                                              | Action                                               |
|------|--------------------------------------------------|------------------------------------------------------|
| 1    | ThreatConnect Get Indicators                     | Pull candidate indicators by TQL                     |
| 2    | If / Else                                        | Continue only if indicator count > 0                 |
| 3    | Iterator                                         | Process each indicator entity individually           |
| 4    | ThreatConnect Attributes Data Pull               | Get attributes for current indicator                 |
| 5    | Pull Indicator's LastName Value (JMESPath)       | Extract creator last name from attributes            |
| 6    | If 'SOAR' Tag, Else, Skip Tagging                | Continue only when extracted last name equals 'SOAR' |
| 7    | Indicator's Current Tags                         | Retrieve pre-action tag state                        |
| 8    | Assign new Tag to SOAR Indicators                | Add tag 'SOAR Indicator PB'                          |
| 9    | Tag JMESPath                                     | Extract indicator summary/data from tag response     |
| 10   | DataStore                                        | Write indicator data to Local DataStore              |
| 11   | Indicator's Post Action Tags                     | Retrieve post-action tag state                       |
| 12   | Compare Pre/Post Process Tagging (Logger)        | Log before/after tagging state                       |
| 13   | Successful Process / None SOAR Indicator Summary | Log completion outcome                               |

## 5.2 Decision Conditions

**Count gate:** `tc.indicators.count > 0` (numeric compare)

**SOAR gate:** `extracted lastName == "SOAR"`

true -> tag is applied

false -> no tagging; logs non-SOAR summary

-

## 6. Error Handling and Notifications

Failure paths emit Send Email alerts to `jaytlin.askew@hhs.gov`.

| Failure Point             | Email Step                                   | Subject                                        |
|---------------------------|----------------------------------------------|------------------------------------------------|
| Get Indicators step fails | `SET SOAR Tag Failed: GET Indicators Failed` | `SET SOAR Tagger GET Indicator Process Failed` |
| Iterator failure          | `SET SOAR Tag Failed: Iterator Failed`       | `SET SOAR Tagger Iterator Failed`              |
| Tag assignment failure    | `Failed SOAR Tagging`                        | `SET SOAR Tagger Failed`                       |

Additional logging steps include:

Failed Process (ERROR logger)

Get Indicators Debug Summary

[Compare Pre/Post Process Tagging](#)

Successful Process

None SOAR Indicator Summary

-

## 7. Key Configuration Values

| Parameter       | Value                                 |
|-----------------|---------------------------------------|
| Tag applied     | `SOAR Indicator PB`                   |
| TC owner scope  | `HTOC Org`                            |
| Indicator type  | `Address`                             |
| TQL time window | `NOW() - 1 DAY`                       |
| Max results     | `2000`                                |
| Active schedule | Every 12 hours (`6:00 AM`, `6:00 PM`) |

-

## 8. Run Success Criteria

A healthy run should show:

Trigger execution at the scheduled time.

No failure email sent.

For SOAR-created indicators in scope, tag `SOAR Indicator PB` appears after processing.

Local DataStore receives entries keyed by indicator summary.

Success/compare loggers execute for processed indicators.

-

## 9. Troubleshooting

| Symptom                               | Likely Cause                                        | Resolution                                                                   |
|---------------------------------------|-----------------------------------------------------|------------------------------------------------------------------------------|
| No indicators processed               | No new indicators in last day or all already tagged | Validate TQL in ThreatConnect and check indicator ingest timing              |
| Indicators skipped unexpectedly       | Creator last name is not 'SOAR'                     | Review 'ThreatConnect Attributes Data Pull' output and JMESPath extraction   |
| Tag not applied but no clear UI error | Tag step failure path triggered                     | Check failure email body and 'Failed Process' logger content                 |
| Reprocessing occurs                   | Tag removed/renamed or TQL exclusion mismatch       | Confirm tag name is exactly 'SOAR Indicator PB' in both TQL and add-tag step |
| Schedule not running                  | Trigger inactive or playbook disabled               | Verify timer trigger active and playbook enabled in ThreatConnect            |

-

## 10. Operator Decision Points

If the process sends repeated failure emails, pause trigger and validate app permissions on Tags/[Attributes/DataStore apps.](#)

If expected SOAR indicators are not tagged, check attribute extraction path before adjusting TQL.

If throughput exceeds 2000 per run, increase max\_results or run manually between scheduled intervals.



## 11. Related Documents

SOP\_TC\_Playbook\_GetCDNScanningIndicatorsByASN.md

SOP\_TC\_Playbook\_GetKnownScanningIndicatorsByASN\_NonCDN.md

ThreatConnect Playbook documentation: [ThreatConnect Playbooks](<https://docs.threatconnect.com>)