33934번 - 징검다리의 징검다리 성공

☆

골드 V

시간 제한	메모리 제한	제출	정답	맞힌 사람	정답 비율
1 초	1024 MB	272	116	68	37.158%

문제

N개의 호수가 일렬로 늘어서 있다. 각 호수는 왼쪽에서부터 1번에서 N번까지 번호가 매겨져 있으며, 각 호수에는 돌들이 원형으로 배치되어 있다. i번째 호수에는 징검다리를 이루는 돌이 A_i개 있으며, 각 돌에는 1번부터 A_i번까지 번호가 매겨져 있다.

용모는 S번째 호수의 1번 돌 위에 서 있으며, 다음과 같은 규칙으로 이동한다.

- 현재 j번 돌 위에 있다면 같은 호수의 $j+1$번 돌로 이동한다. 단, 현재 A_i번 돌 위에 있다면 1번 돌로 이동한다.
- 현재 j번 돌 위에 있다면 같은 호수의 $j-1$번 돌로 이동한다. 단, 현재 1번 돌 위에 있다면 A_i번 돌로 이동한다.
- 현재 i번째 호수의 돌 위에 있다면 $i-1$번 또는 $i+1$번 호수의 임의의 돌로 이동한다. 단, $i-1$번 호수 또는 $i+1$번 호수가 존재하지 않는다면 해당 방향으로는 이동할 수 없다.
- 한번 밟은 돌은 다시 밟을 수 없다.

용모가 E번째 호수의 임의의 돌에 도착할 때까지, 시작 돌과 끝 돌을 포함하여 정확히 K개의 돌을 밟을 수 있는지 판단하는 프로그램을 작성하시오.

입력

첫 번째 줄에 호수의 개수를 나타내는 정수 N과 시작 호수와 끝 호수의 번호를 나타내는 정수 S, E가 주어진다.

두 번째 줄에 각 호수의 징검다리를 이루는 돌의 개수 $A_1, A_2, \cdots, A_N$이 공백으로 구분되어 주어진다.

세 번째 줄에 용모가 밟아야 하는 서로 다른 돌의 개수 K가 주어진다.

출력

용모가 정확히 K개의 돌을 밟은 후 E번째 호수의 임의의 돌에 도착할 수 있으면 `1`, 그렇지 않으면 `0`을 출력한다.

제한

- $2 \le N \le 200\,000$
- $1 \le S, E \le N, S \ne E$
- $1 \le A_i \le 1\,000$
- $2 \le K \le 10^9$

예제 입력 1 복사

```
7 6 3
4 1 7 2 2 4 9
5
```

예제 출력 1 복사

```
1
```

예제 입력 2 복사

```
5 2 4
2 3 2 6 4
2
```

예제 출력 2 복사

```
0
```

출처

University (/category/5) > 인하대학교 (/category/336) > 2025 인하대학교 프로그래밍 경진대회 (IUPC) (/category/1114) > Contest (/category/detail/4496) K번

University (/category/5) > 인하대학교 (/category/336) > 2025 인하대학교 프로그래밍 경진대회 (IUPC) (/category/1114) > Open Contest (/category/detail/4502) K번

- 문제를 만든 사람: aym506 (/user/aym506)
- 문제를 검수한 사람: 39dll (/user/39dll), chlwnsgud7 (/user/chlwnsgud7), cmgjol010 (/user/cmgjol010), dongggle (/user/dongggle), gumgood (/user/gumgood), hjkim9911 (/user/hjkim9911), jinhan814 (/user/jinhan814), jkw8357 (/user/jkw8357), jthis (/user/jthis), plan_pt (/user/plan_pt), tlsdydaud1 (/user/tlsdydaud1), wjdclgns12 (/user/wjdclgns12)

알고리즘 분류

- 그리디 알고리즘 (/problem/tag/33)
- 애드 혹 (/problem/tag/109)

메모