

NAME

wordif – compares plain-text-files word-by-word, and stores color-marked results in HTML-format.

SYNOPSIS

```
wordif [options] file1 file2
wordif -d [options] directory1 directory2
```

DESCRIPTION

wordif is a wrapper script around the diff(1) utility, that compares two plain-text-files word-by-word in very much the same way as wdiff(1). The resulting HTML 'difference-file(s)' is/are either:

- stored as a disk file (default), or
- send to stdout (with option -o), or
- converted to PDF-format and stored to disk (with option -p)

A difference-file is a unification of the two input text-files, preserving original text sequence. Text present in both files is black. (Groups of) words locally missing in one of the two files are color-tagged as follows:

- deleted text – i.e.: present in file1, and not present (there) in file2 – is red (default), or of any color desired (per option -c);
- inserted text – i.e.: present in file2 and not present (there) in file1 – is green (default), or of any color desired (per option -C);

With option -d, wordif acts on two directories instead of two text-files, It then compares each text-file in directory2 to its equivalent in directory1. To correctly associate each pair of files shared by both directories, their file names must start with same unique number, followed by an underscore.

The resulting difference-files are collected in a directory named diff/, which is either newly created – on the same level as both given directories – or re-used, if already present there.

The name of the difference-file is structured as: DATE_TIME_ 'diff' _NUMBER ' . ' EXT, with

DATE_TIME

timestamp generated by the system's response to the command: `date +%Y%m%d_%H%M"`

NUMBER

the unique number per related input file pair (in case of option -d) or an empty string (otherwise)

EXT the appropriate file-extension: 'html' or 'pdf'

OPTIONS

wordif takes the following options:

- h** Help, showing usage and options listing
- c RGBHEX**
Specify 'deleted-text' color by 6-digit rgb hex-value (default: ff0000 [red])
- C RGBHEX**
Specify 'inserted-text' color by 6-digit rgb hex-value (default: 00ff00 [green])
- d** Specify two directories as arguments instead of two text-files; Compare each file in directory2 to equally unique-numbered file in directory1
- o** Send HTML-text to stdout rather than to file
- p** Output as PDF- instead of HTML-files

COMPATIBILITY

The program 'wkhtmltopdf(1)' must be installed on the system if output to PDF per option -p is desired.

AUTHOR

Written by Rob Toscani (rob_toscani@yahoo.com)

REPORTING BUGS

Please report any bugs to the author by e-mail or via <https://github.com/jazzfan2/wordif/issues>