

NAME

wordif – compares plain-text-files word-by-word, and stores color-marked results in HTML-format.

SYNOPSIS

```
wordif [options] file1 file2
wordif -d[options] directory1 directory2
```

DESCRIPTION

wordif is a wrapper script around the diff(1) utility, that compares two plain-text-files word-by-word in very much the same way as wdiff(1). The resulting HTML 'difference-file(s)' is/are either:

- stored as a disk file (default), or
- send to stdout (with option **-o**), or
- converted to PDF-format and stored to disk (with option **-p**).

A difference-file is a unification of the two input text-files, preserving original text sequence. Text present in both files is black. (Groups of) words locally missing in one of the two files are color-tagged as follows:

- deleted text – i.e.: present in *file1*, and not present (there) in *file2* – is bolt red (default), or of any desired color (per option **-c**);
- inserted text – i.e.: present in *file2* and not present (there) in *file1* – is bolt green (default), or of any desired color (per option **-C**).

With option **-d**, wordif acts on two directories instead of two text-files, It then compares each plain-text-file in *directory2* to its equivalent in *directory1*. Plain-text-files within subdirectories of *directory1* and *directory2* are ignored. To correctly associate each pair of files shared by both directories, their file names must start with the same unique non-negative integer number, followed by an underscore (_). Numbers with prefixed zero(s) are ignored.

The resulting difference-files are collected in a directory named **diff/**, which is either newly created – on the same level as both given directories – or re-used, if already present there.

The name of the difference-file is structured as: *date_time_diff_number.extension* with:

date_time

timestamp generated by the system's response to the command: `date +%Y%m%d_%H%M%S"`

number the unique number per related input file pair (in case of option **-d**) or an empty string (otherwise)

extension

the appropriate file-extension: **html** or **pdf**

OPTIONS

wordif takes the following options:

- h** Help, showing usage and options listing.
- c RGBHEX**
Specify 'deleted-text' color by 6-digit hexadecimal rgb-value (default: **ff0000** [red]).
- C RGBHEX**
Specify 'inserted-text' color by 6-digit hexadecimal rgb-value (default: **00ff00** [green]).
- d** Specify two directories as arguments instead of two text-files. Compare each file in *directory2* to the equally unique-numbered file in *directory1*.
- f FONT**
Set general character font family as a replacement for 'Courier New'. Allowed values for *FONT* are:
H Helvetica

- | | |
|----------|------------------------|
| h | Helvetica Narrow |
| c | Courier |
| n | New Century Schoolbook |
| p | Palatino |
| T | Times New Roman |
| t | Times |
- o** Send HTML-text to stdout rather than to file.
- p** Output as PDF- instead of HTML-files; this option overrides option **-o**
- r** Reunite words that are broken off at the end of a text line.
- z SIZE** Set general character size as a replacement for 12 pts. Also accepts values with decimal point.

COMPATIBILITY

- wordif has been tested on MacOS and GNU/Linux (Debian, Alpine and Tiny Core with Busybox) and can be run by both Bash, ash and Dash shells.
- The program 'wkhtmltopdf(1)' must be installed on the system if output to PDF per option **-p** is desired.

AUTHOR

Written by Rob Toscani (rob_toscani@yahoo.com)

REPORTING BUGS

Please report any bugs to the author by e-mail or via <https://github.com/jazzfan2/wordif/issues>