

***Designed.
Engineered.
Remarkable
Value.***



Land Management Equipment

Powerful attachments to fit your application.





The widest choice of quality land management attachments.



Rotary Brooms

Designed for use by contractors, municipalities, institutions and farmers. Hydraulically driven models for skid steers, PTO driven models for 3-pt. tractor mounts (Cat.I). 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW). All models available in 5-ft., 6-ft., & 7-ft. widths.

- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways & sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Brooms angle up to 30-degrees right or left. Optional manual or hydraulic angle adjustment kits available.
- Height adjustment chains maintain an even operating position.
- Parking stand included as standard equipment.
- Double gearbox drive for smooth power transmission and easy reversal of brush rotation.
- Optional electric solenoid kit also offered.

Skid Steer Rotary Broom

- Hydraulically driven skid steer models in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Variable flow control valve for optimum broom speed.
- Step-through mount design for easy in/out of skid steer cab.
- 4.36 / 1 chain drive ratio for excellent torque.

3-pt. Rotary Broom

- PTO driven 3-pt. tractor mount in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Top "T-Shaft" gearbox allows easy reversal of brush rotation.
- Designed for Category I tractors with 1,000 lbs. or greater 3-pt. lift capacity.

Skid Steer Rotary Broom Specifications

	SSMB-325P	SSMB-325PW	SSMB-326P	SSMB-326PW	SSMB-327P	SSMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	Skid Steer	Skid Steer	Skid Steer	Skid Steer	Skid Steer	Skid Steer
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
Hydraulic Motor Rating	16 GPM	16 GPM	16 GPM	16 GPM	16 GPM	16 GPM
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Sprinkler System	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	640 / 290	637 / 289	740 / 336	736 / 334	840 / 381	833 / 378
Product No.	610961	610960	610966	610965	610971	610970



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

3-pt. Rotary Broom Specifications

	RMB-325P	RMB-325PW	RMB-326P	RMB-326PW	RMB-327P	RMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
PTO RPM Range	540	540	540	540	540	540
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Sprinkler System	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	720 / 326	714 / 324	780 / 354	774 / 351	840 / 381	833 / 378
Product No.	610705	610700	610755	610750	610805	610800



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

Options

Angle Adjustments Kits (all models require either a manual or hydraulic kit)	
Product No. 610702	Manual Angle Adjustment Kit for either skid steers or 3-pt. tractor.
Product No. 610703	3-pt. Hydraulic Angle Adjustment Kit – includes cylinder & hoses less tips.
Product No. 610704	Skid Steer Hydraulic Angle Adjustment Kit – includes electric hydraulic solenoid control valve. For skid steer brooms used on units with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers. Factory installed.
Electric Solenoid Kit (Optional)	
Product No. 610950	Field installed electric hydraulic solenoid valve kit – fits product no. #610703 hydraulic angle kit above.



SmoothCut™ ***Stump Grinders***

Economical and efficient PTO powered stump grinders make stump removal fast and easy. Operator easily controls the grinder from the comfort of the tractor seat. Surefoot™ stabilizer provides solid footing during operation.

- Tractor models require two pair of remote hydraulic outlets.
- Cutting wheel design provides a smoother cutting action and higher productivity.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- Maneuverable – goes anywhere a tractor can; gets into tight places.
- Easy to operate – hydraulic controls allow easy operation from the seat of the power unit using existing hydraulic controls.
- Heavy duty bushings w/grease zerks are used at major pivot points for increased reliability and extended service life.
- Standard pressure relief valve for precise control of cutting feed rate.
- Pressure relief valve helps reduce hydraulic oil heat buildup keeping tractor hydraulics cooler.
- Rubber deflector helps control chips and debris during grinding.
- Parking stand for easy storage.



Surefoot™ stabilizer

Stump Grinder Specifications

	SG-26A	SG-36A
Hitch	Cat. I	Cat. I / II
Overall Estimated Length (in/cm)	75 / 191	80 / 230
Drive System Protection	Slip Clutch	Slip Clutch
Gearbox Rating / Ratio	60 HP / 1:1.5	100 HP / 1:1.46
Cutting Wheel Construction	Welded 2-piece Laminated Steel	
Cutting Wheel Thickness (in/cm)	3/4 / 1.91	
Cutting Wheel Diameter (in/cm)	26 / 66	36 / 91
Cutting Wheel Speed	810 RPM	788 RPM
@ 540 PTO RPM	5,515 ft. / min.	7,430 ft. / min.
Number of Teeth	33	42
Cutting Teeth Construction	Carbide Steel Bolt-in	
Cut Height Above Ground (in/cm)	18 / 46	
Cut Depth Below Ground (in/cm)	10 / 25	15 / 38
Maximum Horizontal Cut (in/cm)	28 / 71	33 / 84
Swing Arc	45°	
Minimum Power / Flow Required	22-PTO HP	45-PTO HP
Maximum Power / Flow	50-PTO HP	100-PTO HP
Drive System	PTO / Series 5	PTO / Series 6
PTO Speed	540 RPM	540 RPM
Weight (lbs/kg)	660 / 299	880 / 399
Product No.	812200	812210



WARNING: Read and understand the operator's manual before operation. Stump grinder will put a heavy load on the rear of your tractor. Be sure your tractor is properly counterbalanced. Damage to equipment or personal injury could occur. Never allow children or bystanders around tractor or stump grinder while operating.



Tree Clipper

Designed for skid steer or tractor front loaders. Solves the problem of trimming hard to reach tree branches and unwanted trees. Ideal for high reach trimming or ground level cutting.

- Mounts to either side of the main frame for excellent visibility.
- Eliminates the unsafe practice of trimming limbs with a chain saw from a loader bucket or ladder.
- Timesaving way to trim and clear trees and brush, that is faster and easier than using a chainsaw.
- When cutting at ground level, unit leaves minimal ground disturbance.
- Heavy-duty 5" x 8" hydraulic cylinder with 2" rod and 1-1/4" pins for positive cutting action.
- Hardened pivot bushings for long service life.
- Self-centering 3/4" T-1 steel blades provides outstanding performance.
- Unit features power tilt to rotate head assembly for best cutting angle.
- Extended reach allows trimming of limbs 12-16 ft. high (depending on tractor /loader used). When cutting trees at ground level, allows easy access under extending branches.
- Design allows unit to cut overhead or horizontally at ground level.
- Cuts limbs and trees up to 8" in diameter.
- Minimum hydraulic pressure required –2000 psi.
- Optional electric solenoid valve and hose kit to fit most skid steer loaders and tractors when only one set of remotes is available.

Tree Clipper Specifications

	TC8-FL	TC8-SS
Frame Construction	Welded Steel	Welded Steel
Clipper Blade Material	T-1 Steel	T-1 Steel
Clipper Capacity (in/cm)	8 / 20 Diameter	8 / 20 Diameter
Main Pivot Tube (in/cm)	2-7/8 / 8 O.D. - 3/8 / .95 Wall	2-7/8 / 8 O.D. - 3/8 / .95 Wall
Length of Reach from main frame (in/cm)	72 / 183	72 / 183
Head Rotator Cylinder Size	2-1/2" x 10"	2-1/2" x 10"
Cutting Head Cylinder Size	5" x 8"	5" x 8"
Degree of Cutting Head Rotation	113°	113°
Mounting for Tractor Loaders	Mgt. Brackets Required*	Fits Loaders w/SS Quick Attach
Mounting for Skid Steers	N/A	Universal Skid Steer
Minimum Hydraulic Pressure	2,000 psi	2,000 psi
Tractor Size Requirements (min. PTO hp)	45 PTO HP**	45 PTO HP**
Weight (lbs/kg)	710 / 322	723 / 328
Product No.	811300	811305

*Bracket for most front loader quick attach systems are available. "Be sure rear of tractor is properly counterbalanced."

Base tractor unit does not include hydraulic hoses to the remotes.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.





Snow Blades

Designed for skid steers and tractor front loaders, heavy duty snow blades remove snow easily from driveways, parking lots or other large areas. Available in 5, 6, 7½ and 9 foot widths. 7½' and 9' blades feature 5 degree lateral oscillation allowing these wider blades to easily follow the ground contour. SBS models utilize the "Universal" skid steer mounting system. SBFL models offer interfacing brackets for most tractor front loaders. SBC models easily install on compact tractors by clamping onto the bucket for fast snow removal.

- Ideal for residential or commercial snow removal.
- Two trip springs for controlled break over in snow.
- Blade floats to clean uneven surfaces.
- Reinforced 21" or 27" high 10-gauge moldboards provide long service life.
- 3/8" x 6" cutting edge of 1044 steel.
- Two clamp-on models for compact tractors.
- Step-through design allows for easy access to skid steer seat.
- Quick hook up on skid steers or front loaders equipped with "Universal" mounting plate.
- Blade angles right or left.
- Adjustable skid shoes are ½" thick and rotate for long life.



Adjustable skid shoes are standard

Snow Blades Specifications – For skid steers and tractors with a recommended HP of 30-95 HP.

	SBFL-27108A	SBS-27108A	SBG-27108A	SBJD-27108A	SBFL-2709A	SBS-2790A	SBG-2790A	SBJD-2709A
Overall Width (in/cm)	108 / 274	108 / 274	108 / 274	108 / 274	90 / 229	90 / 229	90 / 229	90 / 229
Overall Height (in/cm)	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
5° Lateral Oscillation	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	N/A	N/A	N/A	N/A	5	5	5	5
Width @ Full Angle	96 / 244	96 / 244	96 / 244	96 / 244	80 / 203	80 / 203	80 / 203	80 / 203
Tractor Loader Mount	*Brackets Req.	N/A	Euro / Global	400 / 500 JD	*Brackets Req.	N/A	Euro / Global	400 / 500 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	40-95 HP	40-95 HP	40-95 HP	40-95 HP	30-80 HP	30-80 HP	30-80 HP	30-80 HP
Weight (lbs/kg)	665 / 302	690 / 313	640 / 290	670 / 304	555 / 252	530 / 240	510 / 231	510 / 231
Hydraulic Angle Kit	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Crossover Ref. Valve	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Optional Top Deflector	360230	360230	360230	360230	360277	360277	360277	360277
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Product No.	360075	360070	360078	360275	360040	360000	360090	360270

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Snow Blades Specifications – Models 2160 & 2172 are for skid steers and tractors with a recommended HP of 25-45 HP. SBC clamp-on models are for tractors with a recommended HP up to 35 HP.

	SBFL-2172	SBS-2172	SBC-2172	SBJD-2172	SBFL-2160	SBS-2160	SBC-2160	SBJD-2160
Overall Width (in/cm)	72 / 183	72 / 183	72 / 183	72 / 183	60 / 152	60 / 152	60 / 152	60 / 152
Overall Height (in/cm)	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	5	5	5	5	5	5	5	5
Width @ Full Angle	62 / 157	62 / 157	62 / 157	62 / 157	52 / 132	52 / 132	52 / 132	52 / 132
Tractor Loader Mount	*Brackets Req.	N/A	Clamp-On	200 / 400 JD	*Brackets Req.	N/A	Clamp-On	200 / 400 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	<45 HP	<45 HP	<35 HP	<45 HP	<45 HP	<45 HP	<35 HP	<45 HP
Weight (lbs/kg)	366 / 166	350 / 159	335 / 152	395 / 179	347 / 157	334 / 152	305 / 138	375 / 170
Hydraulic Angle Kit	Optional	Optional	N/A	Optional	Optional	Optional	N/A	Optional
Crossover Ref. Valve	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Optional Top Deflector	360223	360223	360223	360223	360220	360220	360220	360223
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Product No.	360160	360130	360290	360225	360140	360100	360280	360250

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Hydraulic/PTO Cement Mixers



Worksaver's Skid Steer Mixer, model SS-590 has direct hydraulic drive of the gearbox which eliminates chain and sprocket maintenance resulting in more up-time on the jobsite. Large 11-cubic ft. drum allows the operator to mix, transport and place 5-cubic ft. of concrete. It's efficient design offers the contractor a cost savings over chain driven models.

- All welded steel drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Direct hydraulic drive of the gearbox eliminates chain & sprocket maintenance.
- Flow control valve allows easy control of mixer speed.
- All welded frame "universal" skid steer with step-through design for easy access to the operators' seat.

Model 580 3-pt. mixer is ideal for mixing feed, fertilizer, inoculating seed, potting soil and other mixing jobs. Hydraulic top link cylinder provides positive dump control. Number 40-roller chain drives mixing drum. Adjustable Cat.I hitch allows easy hook up to most tractors (7/8" dia. lift pins). Sealed ball bearings provide long service life with reduced maintenance.



Cement Mixer Specifications

	580	SS-590
Capacity	Five (5) cu/ft (1 Bag Mix)	Five (5) cu/ft (1 Bag Mix)
Drum Opening (in/cm)	17.5 / 44	20 / 51
Overall Drum Length (in/cm)	32 / 81	32 / 81
Drum Construction	2-Piece Bolted	Welded Steel
Drive System	Tractor PTO	Hydraulic Direct Thru Gearbox
Hydraulic Requirements	N/A	Minimum 8 GPM
Hitch Requirements	Cat. I (7/8" dia. lift pins)	N/A
Drive Ratio	8.77:1	3.18:1
Flow Control Valve	N/A	Standard
Connect Under Pressure Couplers	N/A	Standard
Parking Stands	Standard	Standard
Shipping Weight (lbs/kg)	253 / 115	395 / 180
Product No.	780620	780950



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.



Box Scrapers

Built for years of dependable use, Worksaver Box Scrapers allow you to shape, level and grade smooth your land management projects. Designed for maximum versatility, scarifiers offer 3-depth adjustments to meet a variety of ground conditions. Double beveled reversible cutting edges provide years of service. Robotically welded frames.

- Formed moldboard for superior strength.
- 3-position scarifiers.
- Reversible cutting edges.
- Ideal for leveling, finishing grading and backfilling at building sites, feedlots and outdoor arenas.

Box Scraper Specifications

	SBX-4	SBX-5	SBX-6	SBX-7	SBX-8
Working Width (in/cm)	48 / 122	60 / 152	72 / 183	84 / 213	96 / 244
Overall Depth (in/cm)	21-1/2 / 55	21-1/2 / 55	21-1/2 / 55	21-1/2 / 55	21-1/2 / 55
End Plate Thickness (in/cm)	1/4 / .635	1/4 / .635	1/4 / .635	1/4 / .635	1/4 / .635
Moldboard Thickness	7 ga.	7 ga.	7 ga.	7 ga.	7 ga.
No. of Scarifiers	3	4	5	6	7
Cutting Edge	Reversible	Reversible	Reversible	Reversible	Reversible
Hitch Category	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
Tractor Horsepower	18 - 25	20 - 25	25 - 40	30 - 40	34 - 45
Weight (lbs/kg)	320 / 145	378 / 172	428 / 194	469 / 213	516 / 234
Product No.	341320	341325	341335	341340	341345

**Designed.
Engineered.
Remarkable
Value.**



Caution — A heavy load can cause your tractor to tip over. When moving heavy loads, keep the load as close to the ground as possible, go slowly around turns, and be sure the front or rear of tractor is properly counterbalanced with weights.

Caution — Operators must read & understand operator's manual, particularly the safety warnings and instructions. **The operator is responsible for safety of themselves and others when operating equipment.**



WORKSAVER, INC. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. WORKSAVER, INC. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



Distributed by:

Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100

Phone: 217-324-5973 • Fax: 217-324-3356

E-mail: sales@worksaver.com

Web: www.worksaver.com