

**Worksaver.**

*Designed.  
Engineered.  
Remarkable  
Value.*



## Self-Contained Hydraulic Post Drivers

**Greater versatility, rugged construction, effective,  
fast operation. Ideal for all Skid Steers.**



# Worksaver

## Model HPD-16 HSS/P, HPD-20 HSS/P and HPD-24 HSS/P

- Designed for rugged, heavy-duty use.
- Features its' own hydraulic pump, motor and reservoir.
- Post Driver hydraulic system is independent of Skid Steer system eliminating risk of oil contamination.
- No special return line or fittings required for quick convenient installation.
- Incorporates spin on filter to protect its' hydraulic system.
- Mounts to any Skid Steer with "universal" attaching system.
- Patented slide blocks, made of ultra high molecular weight polyethylene, offer more contact surface for improved performance.
- Standard level indicator for quick accurate driver alignment.
- Spring dampers reduce "whipping action" helping to extend spring life.
- Chrome-plated high tensile steel hydraulic cylinder rod for long life.

### POST DRIVER SPECIFICATIONS

Model Nos.	HPD-16 HSS/P	HPD-20 HSS/P	HPD-24 HSS/P
Max. Post Size	7" x 9'	8-3/4" x 10'	11" x 10'
Impact at Full Stroke	32,000 lbs	80,000 lbs	110,000 lbs
Impact at Half Stroke	16,000 lbs	40,000 lbs	55,000 lbs
Tilt Adjustment <i>Front/Back</i>	----- 17 degrees each way from vertical-----		
Tilt Adjustment <i>Side/Side</i>	----- 20 degrees each way from vertical-----		
No. of Cylinder/Size	Two 3"x6"	Two 3"x6"	Two 3"x6"
Minimum Hydraulic Reg.	10 gpm	10 gpm	10 gpm
Reservoir Capacity	5 gal	5 gal	5 gal
Pump Type	Gear	Gear	Gear
Pressure relief setting	1500 psi	1500 psi	1500 psi
Filter Type (suction)	Spin-on	Spin-on	Spin-on
Hoses (less Couplers)	Standard	Standard	Standard
Mounting	-----"Universal" Skid Steer Quick-Attach Mount-----		
Storage/Transport Locking Straps	----- Standard all Models -----		
Shipping Weight	1,058 lbs	1,215 lbs	1,451 lbs
Product Computer Number	815020	815025	815030



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

**Worksaver.**



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
 Phone: 217-324-5973 • Fax: 217-324-3356  
 E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
 Web: [www.worksaver.com](http://www.worksaver.com)

Information Provided By:

