CONNECTOR TABLE

REF DES	PART NUMBER	DESCRIPTION
P1	D38999/26FJ35PA	CONNECTOR PLUG - PIN CONTACTS
J2	D38999/26FJ35SA	CONNECTOR PLUG - SOCKET CONTACTS

SCHEMATIC LABELS

P1 END: SHIELD FLOAT

J2 END: SHIELD TO PIN 9

WIRE LIST

WIRE NO.	FROM	PIN	TO	PIN	SIGNAL NAME	GAGE	COLOR	LENGTH
C2-1	P1	7	J2	G	RS422_P	24	WHT/ORG	30 IN
C2-2	P1	8	J2	H	RS422_N	24	WHT/BRN	30 IN

BILL OF MATERIALS

ITEM	QTY	PART NUMBER	DESCRIPTION	REF DES
1	1	D38999/26FJ35PA	CONNECTOR PLUG PIN	P1
2	1	D38999/26FJ35SA	CONNECTOR PLUG SOCKET	J2
3	4	M39029/58-360	CONTACT PIN 22D	P1
4	4	M39029/56-348	CONTACT SOCKET 22D	J2
5	1	M83519/1-2	SOLDER SLEEVE SHIELD TERMINATION	J2

DRAWING NOTES

1. CABLE C2 IS A TWISTED SHIELDED PAIR.

2. AT P1 CUT BACK, INSULATE, AND FLOAT THE C2 SHIELD.

3. AT J2 TERMINATE THE C2 SHIELD TO CONTACT 9 USING A SOLDER SLEEVE.