-NOTES-

*All spacing may be adjusted to accommodate interchange ramps, at-grade intersections and driveways.

*No flaggers or spotters.

*Extend device taper at L/3 across shoulder.

*Devices shall not encroach into the adjacent lane.

*Use transverse devices in closed lane every 1000` (recommended).


*Device spacing for the downstream taper shall be 20`.


*All signs black on orange.

*See special provisions for work hour restrictions.

— Right Lane Closure — (I-82 North - Thorp Rd - Bridge #0011631B)

| CHANNELIZING DEVICE SPACING (FEET) | | | |
|---------------------------------------|-------|---------|--|
| MPH | TAPER | TANGENT | |
| 50/70 | 40 | 80 | |
| 35/45 | 30 | 60 | |
| 25/30 | 20 | 40 | |





LEGEND

48" x 48" Signs w/ Flags

Plastic Drum

28" Cones

Type III Barricade

Sequential Arrow

Truck Mounted Attenuator

Based on WSDOT standard Plan TC3, **Single-Lane Closure for Multi-Lane Roadways**

*Not to scale

D&H Flagging Inc.



Jeff Davis

1621 SE Pardee St Portland, OR 97202

Off: (503) 232-2488 Fax: (503) 234-4572 Cell: (503) 793-6133 jeff@d-hflagging.com

Contractor: Parsons Brinkerhoff Contact Person: Jose (Pepe) Garcia Phone: (813) 624-2282 Email: garciaj1@pbworld.com Job Location: I-82 & Thorp Rd Yakima, WA Type of Work: Bridge Inspection

Time: 8am-4pm Date: 9/7/16-9/9/16

D&H PLAN #5679-1 August 19, 2015

-NOTES-

*All spacing may be adjusted to accommodate interchange ramps, at-grade intersections and driveways.

*No flaggers or spotters.

*Extend device taper at L/3 across shoulder.

*Devices shall not encroach into the adjacent lane.

*Use transverse devices in closed lane every 1000` (recommended).


*Device spacing for the downstream taper shall be 20`.

*All signs black on orange.


*See special provisions for work hour restrictions.

— Left Lane Closure — (I-82 North - Thorp Rd - Bridge #0011631B)

| | CHANNELIZING DEVICE SPACING (FEET) | | | |
|-------|---------------------------------------|---------|--|--|
| MPH | TAPER | TANGENT | | |
| 50/70 | 40 | 80 | | |
| 35/45 | 30 | 60 | | |
| 25/30 | 20 | 40 | | |



PCMS



LEGEND

48" x 48" Signs w/ Flags

Plastic Drum

28" Cones

Type III Barricade

Sequential Arrow



Truck Mounted Attenuator

Based on WSDOT standard Plan TC3, **Single-Lane Closure for Multi-Lane Roadways**

*Not to scale

D&H Flagging Inc.

Jeff Davis

1621 SE Pardee St Portland, OR 97202

Off: (503) 232-2488 Fax: (503) 234-4572 Cell: (503) 793-6133 jeff@d-hflagging.com

Contractor: Parsons Brinkerhoff Contact Person: Jose (Pepe) Garcia Phone: (813) 624-2282 Email: garciaj1@pbworld.com Job Location: I-82 & Thorp Rd Yakima, WA Type of Work: Bridge Inspection

Time: 8am-4pm Date: 9/7/16-9/9/16

August 19, 2015

D&H PLAN #5679-2

-NOTES-

*Flip setup for work in opposite lane.

*All signs black on orange.

*Extending the channelizing device taper across shoulder is


*Night Work requires additional roadway lighting at flagging stations. See the standard specifications for additional details.

*See special provisions for work hour restrictions.

LEGEND

Protective Vehicle

48" x 48" Signs w/ Flags



Jeff Davis

1621 SE Pardee St

Portland, OR 97202

Off: (503) 232-2488

Fax: (503) 234-4572 Cell: (503) 793-6133 jeff@d-hflagging.com

D&H PLAN #5679-3