-NOTES-

*All spacing may be adjusted to accommodate interchange ramps, at-grade intersections and driveways.

*No flaggers or spotters.

*Extend device taper at L/3 across shoulder.

*Devices shall not encroach into the adjacent lane.

*Use transverse devices in closed lane every 1000` (recommended).


*Device spacing for the downstream taper shall be 20`.


*All signs black on orange.

*See special provisions for work hour restrictions.

— Left & Center Lane Closure — (I-90 West - Bandera - Bridge #009217C)

CHANNELIZING DEVICE SPACING (FEET)			
MPH	TAPER	TANGENT	
50/70	40	80	
35/45	30	60	
25/30	20	40	





LEGEND

48" x 48" Signs w/ Flags

Traffic Safety Drum

Type III Barricade

Sequential Arrow


Truck Mounted Attenuator

Based on WSDOT Standard Plan TC3, **Double-Lane Closure for Multi-Lane Roadways WSDOT Standard Plan TC7**

Temporary Off-Ramp for Multi-Lane Roadways

*Not to scale

D&H Flagging Inc.





1621 SE Pardee St Portland, OR 97202

Off: (503) 232-2488 Fax: (503) 234-4572 Cell: (503) 793-6133 jeff@d-hflagging.com

Contractor: Parsons Brinkerhoff Contact Person: Jose (Pepe) Garcia Phone: (813) 624-2282 Email: garciaj1@pbworld.com Job Location: I-90 West & NFS Rd 9030 Bandera, WA

Type of Work: Bridge Inspection Time: 8am-4pm

Date: 9/15/16 — 9/16/16

D&H PLAN #5681-1 August 29, 2015

-NOTES-

*All spacing may be adjusted to accommodate interchange ramps, at-grade intersections and driveways.

*No flaggers or spotters.

*Extend device taper at L/3 across shoulder.

*Devices shall not encroach into the adjacent lane.

*Use transverse devices in closed lane every 1000` (recommended).


*Device spacing for the downstream taper shall be 20`.


*All signs black on orange.


*See special provisions for work hour restrictions.

— Right Lane Closure — (I-90 West - Bandera - Bridge #009217C)

CHANNELIZING DEVICE SPACING (FEET)			
MPH	TAPER	TANGENT	
50/70	40	80	
35/45	30	60	
25/30	20	40	







PCMS

D&H
Flagging Inc.
"Women-owned business."



Jeff Davis

1621 SE Pardee St Portland, OR 97202

Off: (503) 232-2488 Fax: (503) 234-4572 Cell: (503) 793-6133 jeff@d-hflagging.com

Contractor: Parsons Brinkerhoff Contact Person: Jose (Pepe) Garcia Phone: (813) 624-2282 Email: garciaj1@pbworld.com Job Location: I-90 West & NFS Rd 9030 Bandera, WA

Type of Work: Bridge Inspection Time: 8am-4pm Date: 9/15/16 — 9/16/16

LEGEND

¥ 48" 2

48" x 48" Signs w/ Flags

I T

Type III Barricade

Sequential Arrow

Traffic Safety Drum



Truck Mounted Attenuator Based on WSDOT standard Plan TC4, Single-Lane Closure for Multi-Lane Roadways

*Not to scale

August 29, 2015 D&H PLAN #5681-2

-NOTES-

*Flip setup for work in opposite lane.

*All spacing may be adjusted to accommodate interchange ramps, at-grade intersections and driveways.

*No flaggers or spotters.

*Extend device taper at L/3 across shoulder.

*Devices shall not encroach into the adjacent lane.

*Use transverse devices in closed lane every 1000` (recommended).

*Device spacing for the downstream taper shall be 20`.

*All signs black on orange.

*See special provisions for work hour restrictions.

LEGEND



48" x 48" Signs w/ Flags



Type III Barricade




Sequential Arrow

Traffic Safety Drum




Truck Mounted Attenuator

Right & Center Lane Closure —(I-90 West - Bandera - Bridge #009217C)



CHANNELIZING DEVICE SPACING (FEET)			
MPH	TAPER	TANGENT	
50/70	40	80	
35/45	30	60	
25/20	20	40	







Jeff Davis

1621 SE Pardee St Portland, OR 97202

Off: (503) 232-2488 Fax: (503) 234-4572 Cell: (503) 793-6133 jeff@d-hflagging.com

Contractor: Parsons Brinkerhoff Contact Person: Jose (Pepe) Garcia Phone: (813) 624-2282 Email: garciaj1@pbworld.com Job Location: I-90 West & NFS Rd 9030 Bandera, WA

Type of Work: Bridge Inspection Time: 8am-4pm Date: 9/15/16 — 9/16/16

uic. 7/13/10 — 7/10/10

August 21, 2015 D&H PLAN #5681-3