COMP 3350 Project #5

Possible points: 100 Due: December 3, 2021 11:59pm CST

Requirements:

- Read the design section and write a program. Submit source file .asm to Canvas.
- Show your work to get full credit. **ZERO** point without steps for a result.
- Please start early. ZERO point for late submission. After the **11:59pm** on the due day, you can't submit your assignment anymore.
- Check deliverables section below. ZERO point for hand-written or scanned homework.
- See my last announcement if you do not like to use visual studio. I provide an free and lightweight alternative.

Deliverables:

- Save your source of assembly program as a .asm file.
- (5 points) Name document of source code as a "Firstname_Lastname.asm".
- (15 points) A screenshot of the result after you compile and run program, correctly demonstrate the decryption result of the input "JPUESZSBAPANNHTXRTLBVLL". The screenshot file should be named as "Firstname_Lastname.png" or "Firstname_Lastname.jpg" or any other valid picture format suffix.
- Submit your "Firstname_Lastname.asm" and "Firstname_Lastname.png" through the Canvas system. You do not need to submit hard copies.

Rebuttal period:

You will be given a period of 2 business days to read and respond to the comments
and grades of your homework or project assignment. The TA may use this opportunity
to address any concern and question you have. The TA also may ask for additional
information from you regarding your homework or project.

Objective:

This program has two objectives. The first objective is to create a procedure that will take plaintext and an encryption key, use the Vigenère cipher, and encrypt the plaintext. The second objective is to create a procedure that will take cypher-text, an encryption key, use the Vigenère cipher, and decrypt the cypher-text.

Assume that all characters will be uppercase letters, no spaces, symbols, etc.

All "high level" directives are not allowed on this homework. (e.g. .IF .ENDIF .REPEAT, etc)

Design:

Create a BYTE array with the label 'input'. This array may be of any length between 2 and 100. In the case of encryption 'input' will hold the plaintext and in the case of decryption 'input' will hold cypher-text.

Create a BYTE array with the label 'key'. This array will have length between 1 and (LENGHTOF input -1). Meaning the lower bound for 'key' is one character and the upper bound is one less than the number of characters in 'input'.

Create a BYTE variable named "options". This variable will be used to determine which procedures should be executed. If 'options' contain the value 1 it means the program should execute encryption procedure. If 'options' contain the value 0 (or any other value than 1) the program should execute decryption procedure.

Create a BYTE array with the label 'output'. This array will have a dynamic length equal to LENGTHOF input. When executing the program using encryption, the variable 'output' will hold the cypher-text and in the case of decryption, 'output' will hold plaintext.

You may create any other values you deem necessary.

You must have three procedures for this homework. The main procedure, a procedure to handle encryption, and another to handle the decryption. You may create other procedures if you wish.

Example of encryption / decryption:

For more information check the Wiki link: (https://en.wikipedia.org/wiki/Vigenère_cipher)

The example below will use the plaintext word MEMORY and the key BAD.

First you "line up" your plaintext word with your key by writing the key directly beneath the plaintext word. Continue to repeat the key under each plaintext character:

MEMORY

BADBAD

In the above example MEMORY is longer than BAD, therefore, BAD was repeated. Next choose each character in the plaintext word, starting with the first and encrypt it.


To encrypt a character, you first find the column on the chart corresponding to the character in the plaintext, e.g. the character M (circled in blue). Next, find the row starting with the key character, e.g. the character B (circled in red). Finally, find where

the plaintext column and the key row intersect, e.g. the character N (circled in red). Continue this for each character.

MEMORY

BADBAD

Ν



MEMORY

BADBAD

ΝE



MEMORY

BADBAD

NEP



Continue until all characters have been encrypted:

Input = MEMORY (plaintext)

Key = BADBAD (key)

output= NEPPRB (cypher-text)

Decrypting is the opposite of encrypting. To decrypt NEPPRB first write the key under the cypher-text. Then find the row starting with the key character. Next, move across that row until you find the cypher-text character. The cypher-text character's column is the plaintext column.

NEPPRB

BADBAD

Μ



NEPPRB

BADBAD

ME



NEPPRB

BADBAD



Continue until the cypher-text has been decrypted:

Input = NEPPRB

Key = BADBAD

Output = MEMORY

(80 points): Read the comments in the template file "project5_template.asm" and finish (1) - (8)

At the top of your ".asm" file, give a brief description of the program, author name and last modified date in the form of comments.

For the code, explain what each assembly line means in plain English. Your comment should be meaningful and reflect the code correctly.