

No.

Process Name/ Title:
Wire Cutting and Crimping /
Troubleshooting Procedure - Tangled wire, Prefeeder

and Feeding Rollers Malfunction

WORK INSTRUCTION

Document No:

Effective Date:

WI-PRO-CNC-030

July 10, 2017

Product Code/Name: Custome

Customer Code: ALL

Rev. No.:

0

Page No.:


Page 1 of 1

Work Procedure/ Illustration Records/Remarks/
Quality Pointers

Applicable Models: (C555 * C558)

ALL

How to perform troubleshooting on: Tangled Wires Prefeeder Malfunction Feeding Rollers Malfunction



- When machine stops because of tangled wire at ① area, untangle it.
 If untangling isn't feasible, scrap tangled portion of the wire.
 Check wire length of crimped wires in receiving tray.
- 2. When machine stops because of tension of cord at ② area, turn ON the power switch ④ (OFF mode for pause) and check wire length of crimped wires in receiving tray.
- 3. If abnormal noise is heard from feeding roller ③, scrap wires left at feeding roller ③ check wire length of crimped wires in receiving tray.
- 4. If machine has stopped because joint got separated, joint have fully passed through, wires are stuck at nozzle, check wire length of crimped wires in receiving tray.

Note:

As for above 1~4, in case there are no crimped wires left in receiving tray, check all preceding units before the abnormality occurred.

NBC (Philippines)
MASTER COPY

							Prepare	Gheck	Approve
							m 21		0
							MI DI	1112	
				<u> </u>	ļ		J.Garcia /	117	40
-	NBCP-1085	NA	Previously established Work Instruction(for history purpose only)	-	-	-	Z. Mendez	9. MERIN	T. SUGIYAMA
Eff./Rev.Date	Doc/DRCN No.	Rev. No.(if applicable)	Details of change	Revise	Check	Approve	Est. date:	07/10/2	017