	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	1 of 9

PARTS:	1. All parts: Connector 6188-0066 (GR); AVSSf 0.3 wires Y-OR L=384±2mm; Black Corrugated tube ø7 L=214±3mm (no slit); Black Corrugated tube ø7 L=116±3mm (no slit); Connector 6189-0451 (W); MRSW CP TVSSf 0.3 GR-B/W L=822±3mm; Black Corrugated tube ø7 L=517±5mm (no slit); Black tape [1pc.]	JIG:	1. Insertion jig with switch cover 2. Locking jig 3. Terminal cover jig

NO.	PROCESS NAME		WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
1	P1	Table Lay-out	**Table Lay-out**  	**Safety Instruction** Be sure to wear required personal protective equipment during operation (gloves, finger cots, etc.) **Housekeeping** 1. Maintain and always practice 5's. 2. Personal things on the workplace is prohibited. Keep it in your locker. **Alert level** For any trouble, inform the Assembly Assistant Supervisor or Line Leader for immediate corrective action.	*Note: Refer to WI-PRO-CNC-017 for Wire and Strip Length Tolerance* 1. No missing parts/tools 2. No excess parts/tools

Revision History							Prepared by	Reviewed by	Approved by	Noted by
01/06/22	1	Change from Pre-launch to Masspro. Improve work procedure/Illustration and quality pointers; Additional Table Lay-out; checkpoint in checking of wire tolerance (Refer to WI-PRO-CNC-017 for Wire and Strip Length Tolerance.)	M. Catapang	J. Loterte	C. Villanueva	A. Arañes	M. Catapang	J. Loterte	C. Villanueva	A. Arañes
09/20/21	0	Initial issue	M. Catapang	J. Loterte	C. Villanueva	A. Arañes				
Eff. Date	Rev. No	Details of Change	Revised	Reviewed	Approved	Noted	Est. Date:	September 20, 2021		

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	2 of 9

PARTS:	1. Connector 6188-0066 (GR)	JIG	1. Insertion jig with switch cover

NO.	PROCESS NAME		WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
2	P1	Connector setting to insertion jig 6188-0066 (GR)	1    1. Press the lock using left thumb.   2. Get the connector **6188-0066 (GR)** using right hand and insert to insertion jig. Release the lock after insertion. ***Note: Follow the connector orientation.***   3. Push the lower wire guide upward using left thumb. Slot for **Yellow wire** will be opened.	n/a	1 CONNECTOR ORIENTATION ILLUSTRATION  1. Use the provided jig per model 2. No wrong orientation of connector 3. No wrong use of connector 4. No damaged connector

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	3 of 9

PARTS:	1. AVSSf 0.3 wires Y L=364±2mm; OR L=364±2mm	**JIG**	1. Insertion jig with switch cover

NO.	PROCESS NAME		1 WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
3	P1	Wire insertion to connector 6188-0066 (GR)	WIRE FACING  1. Hold the insertion jig using left hand. Get the Yellow wire then insert to terminal slot **1** using right hand.  2. Press the button using right thumb. The slot for Orange wire will be opened.  3. Get the Orange wire then insert to terminal slot **2** using right hand.  4. After insertion, push the lock using left thumb and then hold the wires and gently pull out the connector from jig using right hand.	n/a	*Note: Refer to WI-PRO-CNC-017 for Wire and Strip Length Tolerance* 1 1. No loose insertion 2. No wrong insertion 3. One by one insertion 4. No deformed terminal 5. No wrong wire facing Make sure wires are properly inserted. Conduct **Pull-Push-Pull-Push** after insertion. Do not exert extra force. ***Note: Refer to GL-PRO-ASY-029 for Pull-Push procedure.***

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

NBC	WORK INSTRUCTION			Effectivity Date:	January 06, 2022
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1 Page No.: 4 of 9

PARTS:	1. Black Corrugated tube ø7 L= 214±3mm (no slit) 2. Black Corrugated tube ø7 L= 116±3mm (no slit) 3. Assy parts	**JIG**	1. Insertion jig

NO.	PROCESS NAME		1 WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
4	P1	Wire insertion to COT (no slit) ø7 L= 214±3mm **(1ST)** ø7 L= 116±3mm **(2ND)**	 1. Hold the wires using left hand. Get the Corrugated tube (no slit) ø7 L=214±3mm using right hand then insert the Y-OR wires using left hand. 2. Hold the wires using left hand. Get the Corrugated tube (no slit) ø7 L=116±3mm using right hand then insert the Y-OR wires using left hand.	n/a	1. No wrong use of parts 2. No deformed terminal
5		Connector setting to insertion jig 6189-0451 (W) 1	  INSERTION JIG ORIENTATION CONNECTOR ORIENTATTON	n/a	1. Use the provided jig per model 2. No wrong orientation of connector 3. No wrong use of connector 4. No damaged connector

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	5 of 9

PARTS:	1. Connector 6189-0451 (W)	JIG	1. Insertion jig

NO.	PROCESS NAME		1 WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
5	P1	Connector setting to insertion jig 6189-0451 (W) (Continuation)	1  1. Press the lock using left thumb.   2. Get the connector **6189-0451 (W)** using right hand and insert to insertion jig. Release the lock after insertion. ***Note: Follow the connector orientation.***   3. Push the lower wire guide upward using left thumb. Slot for **Yellow wire** will be opened.	n/a	1 **CONNECTOR ORIENTATION ILLUSTRATION**   1. Use the provided jig per model 2. No wrong orientation of connector 3. No wrong use of connector 4. No damaged connector

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	6 of 9

PARTS:	1. Assy parts	JIG	1. Insertion jig

NO.	PROCESS NAME		1 WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
6	P1	Wire insertion to connector 6189-0451 (W)	  1. Hold the insertion jig using left hand. Get the Yellow wire then insert to terminal slot **1** using right hand.  2. Press the button using right thumb. The slot for Orange wire will be opened.  3. Get the Orange wire then insert to terminal slot **2** using right hand.  4. After insertion, push the lock using left thumb and then hold the wires and gently pull out the connector from jig using right hand.	n/a	1. No loose insertion 2. No wrong insertion 3. One by one insertion 4. No deformed terminal 5. No wrong wire facing Make sure wires are properly inserted. Conduct **Pull-Push-Pull-Push** after insertion. Do not exert extra force. ***Note: Refer to GL-PRO-ASY-029 for Pull-Push procedure.***

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	7 of 9

PARTS:	1. Assy parts 2. MRSW CP TVSSf 0.3 GR-B/W L=822±3mm 3. Black Corrugated tube ϕ7 L=517±5mm (no slit)	JIG	1. Locking jig

NO.	PROCESS NAME		1 WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
7	P1	Connector lock	 1. Put the connector into locking jig using right hand then press **2x.** Touch the connector lock if properly locked.  Before pressing After pressing	LOCKING JIG 	***NOTE:*** ***MANUAL LOCKING MAY CAUSE DAMAGED LOCK.*** 1. Use the provided locking jig per model 2. No unlock/half-locked connector 3. No damaged lock
8		Wire insertion to Black Corrugated tube (no slit) ϕ7 L=517±5mm	 1. Get the terminal cover jig using right hand then insert to both terminals **(GR-B/W wires)** using right hand.  2. Get the corrugated tube **ϕ7 L=517±5mm** using right hand then insert the **GR-B/W wires** using left hand. 3. After insertion, remove the cover jig using right hand.	TERMINAL COVER JIG 	1 *Note: Refer to WI-PRO-CNC-017 for Wire and Strip Length Tolerance* 1. No wrong usage of parts 2. No damaged rubber seal

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION			Effectivity Date:	January 06, 2022		
	Process Name/Title:	TAPING ASSEMBLY PROPCESS		Validity Date:	n/a		
	Model Code/Part Number:	178D / 7N0129-7020	Customer: TRJ	Document No.:	WI-ENG-PDE-339A		
	Purpose:	☐ PROTOTYPE ☐ PRE-LAUNCH ■ MASSPRO		Revision No.:	1	Page No.:	8 of 9

PARTS:	1. Assy parts 2. Black tape	JIG	n/a

NO.	PROCESS NAME		1 WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
9	P1	Taping 1 Black corrugated tube to wire near PCB	1  1. Hold the assy parts using left hand, get **Black tape** then conduct pre-taping using both hands.  2. Confirm measurement of **25±3mm** from end of tape up to end of COT then continue the taping process using both hands.  3. Measure from end of COT up to edge of hotmelted wires **46±3mm** then continue the taping process using both hands.	n/a	1. No flip-out tape 2. No peel-off tape 3. No loose tape 4. No missing tape 5. No wrong dimension 6. No wrong use of tape

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

PARTS:	1. Assy parts 2. Black tape	JIG	n/a

NO.	PROCESS NAME		WORK PROCEDURE/ ILLUSTRATION	TOOLS/PPE	QUALITY POINTERS
10	P1	Taping 1 Black corrugated tube to wire near PCB (Continuation)	 4. Confirm measurement of **23±3mm** from end of tape up to edge of PCB then continue the taping process using both hands.  5. After taping, check the measurement and taping condition.		1. No flip-out tape 2. No peel-off tape 3. No loose tape 4. No missing tape 5. No wrong dimension 6. No wrong use of tape

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp