







	WORK INSTRUCTION				Effectivity Date:	June 24, 2024		
	Process Name/Title: CLAMP ASSEMBLY PROCESS				Validity Date:	n/a		
	Model code/Part number: 895B / 7N0091-7020A		Customer: TRJ	Car Model: TOYOTA COROLLA CROSS	Document No.:	WI-ENG-PDE-673		
	Purpose: <input type="checkbox"/> PROTOTYPE <input type="checkbox"/> PRE-LAUNCH <input checked="" type="checkbox"/> MASSPRO				Revision No.:	2	Page No.:	1 of 7


PARTS:		1. Assy parts; Clamp 82711-34490 (B); Clamp 82711-52090 (W); Clamp 82711-35730 (B); Black tape [3pcs]			JIG:	1. Clamp Assembly jig
NO.	PROCESS NAME	2 WORK PROCEDURE/ ILLUSTRATION			TOOLS/PPE	QUALITY POINTERS
1	Clamp assy	<div> <div>TABLE LAY-OUT</div>  </div>			<div> Safety Instruction Be sure to wear prescribed personal protective equipment during operation (gloves, finger cots, etc.) </div> <div> Housekeeping 1. Maintain and always practice 5's. 2. Personal things on the workplace is prohibited. Keep it in your locker. </div> <div> Alert level For any trouble, inform the Assembly Assistant Supervisor or Line Leader for immediate corrective action. </div>	Documents reference/s: 1. Refer to WI-PRO-CNC-664 for Offline assembly process. 1. No missing parts/tools 2. No excess parts/tools <div> <div>CLAMP ILLUSTRATION</div> <div> <div>GOOD</div>  <div>82711-52090 (W)</div> </div> <div> <div>NG</div>  <div>82711-12A80 (W)</div> </div> </div> <div> <div>BAND CLAMP ILLUSTRATION</div> <div> <div>GOOD</div>  <div>82711-34490 (B)</div> </div> <div> <div>NG</div>  <div>82711-16830 (B)</div> </div> </div>










Revision History								Prepared by	Reviewed by	Approved by	Noted by
06/24/24	2	Improved assembly jig. Update table lay-out, Measurement and Visual inspection/Quality checkpoints. Inclusion of Car model "TOYOTA-COROLLA CROSS" .	D.Castillo	C. Villanueva	A. Arañes	n/a	 M. Ariola	 C. Villanueva	 A. Arañes		
05/29/23	1	Improve Work procedure/Illustration on process no. 1-3; Additional notes for spot taping; Inclusion of spot taping switch guide as countermeasure to customer claim for wrong facing of clamp.	M. Ariola	J. Loterte	C. Villanueva	A. Arañes					
05/03/23	0	Initial Issue. Change Process name/Title from TAPING ASSEMBLY PROCESS to CLAMP ASSEMBLY PROCESS; change Document no. from WI-ENG-PDE-664B to WI-ENG-PDE-673 due to separation of process.	M. Ariola	J. Loterte	C. Villanueva	A. Arañes					
Eff. Date	Rev. No	Details of Change	Revised	Reviewed	Approved	Noted	Est. Date:	May 03, 2023		n/a	

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

	WORK INSTRUCTION				Effectivity Date:	June 24, 2024		
	CLAMP ASSEMBLY PROCESS				Validity Date:	n/a		
	Process Name/Title:		Model code/Part number: 895B / 7N0091-7020A		Customer: TRJ	Car Model: TOYOTA COROLLA CROSS		Document No.: WI-ENG-PDE-673
	Purpose: <input type="checkbox"/> PROTOTYPE <input type="checkbox"/> PRE-LAUNCH <input checked="" type="checkbox"/> MASSPRO		Revision No.: 2		Page No.: 2 of 7			


PARTS:	1. Clamp 82711-34490 (B) 2. Clamp 82711-52090 (W) 3. Black tape			JIG:	1. Clamp assembly jig
NO.	PROCESS NAME	WORK PROCEDURE/ ILLUSTRATION		TOOLS/PPE	QUALITY POINTERS
2	Clamp assy	<div><div> 82711-34490 (B)</div><div> 82711-35730 (B)</div><div> 82711-52090 (W)</div><div><div>1. Get 1 pc. of band clamp 82711-34490 (B) then set to clamp location 1 using both hands.</div><div>2. Get 1 pc. of clamp 82711-35730 (B) then set to clamp location 2 using both hands.</div><div>3. Get 1 pc. of clamp 82711-52090 (W) then set to clamp location 4 using both hands.</div><div>4. Initially attach Black tape on clamp location 2 and 4 using both hands.</div></div></div>		n/a	<div>1. No damaged clamp 2. No wrong use of clamp 3. No wrong use of tape 4. No missing clamp</div> <div>Important reminders/Note/s: <i>1. Please check the Clamp first before start of assembly to avoid wrong use of</i></div> <div>STANDARD TAPING FOR CLAMP One wind for under tape </div> <div>CLAMP ILLUSTRATION <div><div>GOOD  82711-52090(W)</div><div>NG  82711-12A80 (W)</div></div><div>BAND CLAMP ILLUSTRATION <div>GOOD  82711-34490 (B)</div><div>NG  82711-16830 (B)</div></div></div>



CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)

MASTER COPY

DCC Stamp

	WORK INSTRUCTION				Effectivity Date:	June 24, 2024		
	Process Name/Title: CLAMP ASSEMBLY PROCESS				Validity Date:	n/a		
	Model code/Part number: 895B / 7N0091-7020A		Customer: TRJ	Car Model: TOYOTA COROLLA CROSS	Document No.:	WI-ENG-PDE-673		
	Purpose: <input type="checkbox"/> PROTOTYPE		<input type="checkbox"/> PRE-LAUNCH	<input checked="" type="checkbox"/> MASSPRO	Revision No.:	2	Page No.:	4 of 7


PARTS:	1. Assy parts		JIG:	1. Clamp assembly jig	
NO.	PROCESS NAME	<div><div>2</div>WORK PROCEDURE/ ILLUSTRATION</div>	TOOLS/PPE	QUALITY POINTERS	
3	Clamp assy	<div><div>Clamp assembly (Continuity)</div><div><div><div>5. Conduct spot taping on COT in clamp location 3. Make 2 winds only then cut the tape . Press the SW button after taping . <i>Note: No excessive windings of tape</i></div><div><div>6. Press the SW button and get the clamp (82711-35730 (B)) in location 2 then put in location 3.</div></div></div></div></div>		<div><div>1. No damaged clamp</div><div>2. No wrong usage of parts</div><div>3. No missing clamp</div><div>4. No missing tape</div></div> <div></div> <div>Important reminders/Note/s: <div>1. <i>Make sure no gap between stopper jig and terminals.</i></div><div>2. <i>Make 2-3 windings for clamp taping.</i></div></div>	






CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)

MASTER COPY

DCC Stamp

	WORK INSTRUCTION				Effectivity Date:	June 24, 2024		
	CLAMP ASSEMBLY PROCESS				Validity Date:	n/a		
	Model code/Part number: 895B / 7N0091-7020A		Customer: TRJ	Car Model: TOYOTA COROLLA CROSS	Document No.:	WI-ENG-PDE-673		
	Purpose: <input type="checkbox"/> PROTOTYPE <input type="checkbox"/> PRE-LAUNCH <input checked="" type="checkbox"/> MASSPRO				Revision No.:	2	Page No.:	5 of 7

PARTS:	1. Assy parts		JIG:	1. Clamp assembly jig	
NO.	PROCESS NAME	<div><div>2</div>WORK PROCEDURE/ ILLUSTRATION</div>	TOOLS/PPE	QUALITY POINTERS	
3	Clamp assy	<div>Clamp assembly (Continuity)</div> <div><div>7. Tape the clamp on location 3 using both hands. Make 3 winds then cut the tape. Press the SW button after taping. Continue the process if sequence light in location 4 was on. <i>Note: Controller will alarm if detect excessive windings of tape.</i></div><div>8. Tape the clamp on location 4 using both hands. Make 3 winds then cut the tape. Press the SW button after taping. Go sound will be heard .</div><div>9. Conduct POINT CHECKING before removing the harness from jig.</div></div>		<div>1. No wrong use of tape 2. No missing tape 3. No damage clamp 4. No missing clamp 5. No skip process</div> <div></div> <div>Important reminders/Note/s: 1. Make sure no gap between stopper jig and terminals. 2. Make 2-3 windings for clamp taping</div>	

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)

MASTER COPY

DCC Stamp

**WORK INSTRUCTION**

Process Name/Title:

CLAMP ASSEMBLY PROCESS

Effectivity Date:

June 24, 2024

Model code/Part number:

895B / 7N0091-7020A

Customer:

TRJ

Car Model:

**TOYOTA COROLLA
CROSS**

Validity Date:

n/a

Purpose:

☐ PROTOTYPE☐ PRE-LAUNCH☒ MASSPRO

Revision No.:

2

Page No.:

6 of 7

PARTS:

1. Assy parts

JIG:


n/a

NO.**PROCESS NAME****2****WORK PROCEDURE/ ILLUSTRATION****TOOLS/PPE****QUALITY POINTERS**




4

Clamp
assy

Measurement

**NOTE:**

- Ⓐ - Taping (B)
- Ⓑ - Clamp (W)
- Ⓒ - Clamp (B)



Wire Type Table		
	Color	Wire Type
1	B	AVSS0.3f
2	B	AVSS0.3f

**MEASURING
TAPE**

Important reminders and note/s:
1. Please use calibrated/verified measuring tape when getting the measurement.

2. For Hatsumono, Nakamono and Owarimono.

Document reference/s:

1. Refer to **WI-PRO-ASY-056** for Sub-assembly Hatsumono Nakamono Owarimono Inspection

1. No wrong dimension

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp

**WORK INSTRUCTION**

Process Name/Title:

CLAMP ASSEMBLY PROCESS

Effectivity Date:

June 24, 2024

Validity Date:

n/a

Model code/Part number:

895B / 7N0091-7020ACustomer: **TRJ**

Car Model:

**TOYOTA COROLLA
CROSS**

Document No.:

WI-ENG-PDE-673

Purpose:

☐ PROTOTYPE☐ PRE-LAUNCH☒ MASSPRO

Revision No.:

2

Page No.:



7 of 7

PARTS:

1. Assy parts

JIG:

n/a

**VISUAL INSPECTION/ QUALITY CHECKPOINTS****CLAMP ASSY****7N0091-7020A****GOOD****NO GOOD****1****No Wrong Facing of Clamp****2****No Unlock/Halflock connector****3****No Missing Tape (Black Tape)**

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

NBC (Philippines)
MASTER COPY

DCC Stamp