
			W	Effectivity Date:		June 22, 2021							
		Process Name/Title:		Validity Date:	n/a								
		Product Name/Code:	100B / 7M0594	<b>4-7020D</b> Cust	tomer:	TRJ		Document No.:		WI-ENG-PDE-286B			
		Purpose:	PROTOTYPE	PRE-	LAUNCH	MASSPRO		Revision No.:	3	Page No.:	1 of 4		
								1	1				
PARTS:	1. Assy parts 2. Black tape								JIG: 1. Locking jig				
NO.	PROCESS NAME WORK PROCEDURE/ ILLUSTRATION							TOOLS/PPE	C	QUALITY POINTERS			
1		Connector lock	Put the connector into locking jig u then press 2x to lock using both ha connector lock to confirm if proper Note: Please refer to GL-PRO-ASY-verification of connector lock.	Before pressing  After pressing	GOOD Full Lock	NG Half Lock	Safety Instruction  Be sure to wear prescribed personal protective equipment during operation (gloves, finger cots, etc.)  Housekeeping 1. Maintain and always practice 5's. 2. Personal things on the	NOTE: MANUAL LOCKING MAY CAUSE DAMAGED LOCK.  1. Use the provided locking jig per model 2. No unlock/half-locked connector					
2	P2	Taping 1 Black corrugated tube to wire near connector	Start of taping  R  25±3mm  tape width	1. Hold the corrugated tube using left hand, get the balck tape then start taping process using both hands.	25±3mm then conti Note: Refer to WI-P	d of the corrugated tube unue the taping process using RO-ASY-001 for taping process that the measurement and	ng both hands.	workplace is prohibited. Keep it in your locker.  Alert level For any trouble, inform the Assembly Assistant Supervisor or Line Leader for immediate corrective action.  MEASURING TAPE	the n  1. No flip-ou 2. No peel-o 3. No loose 4. No missii 5. No wrong	se use calibrated, suring tape when measurement.  ut tape off tape tape ng tape	-		
06/22/21 3 03/17/20 2 04/10/18 n/a	improve Include	ments and update picture in a locking jig	on (WI-PRO-ASY-122B) to Engineerin		). Apply some	M. Catapang C. Villanueva J. Silang A. Morcozo D. Castilo R. Alcantara	O. Merin	Arañes Arañes	Reviewed by	Approved by  A. Shimamura	Noted by  A. Araffes		
Eff. Date Rev. No		,	Details of Change			Revised Checked			10, 2018		,		

	Effectivity Date: June 22, 2021			2, 2021						
Process Name/Title:	ess Name/Title: TAPING ASSEMBLY PROCESS							n/a		
Product Name/Code:	100B	1	7M0594-7020D	Customer:	TRJ	Document No.:		WI-ENG-P	DE-286B	
Purpose:		PROTOTY	PE	PRE-LAUNCH	MASSPRO	Revision No.:	3	Page No.:	2 of 4	



			Effectivity Date:		June 22, 2021							
		Process Name/Title: TAPING ASSEMBLY PROCESS								n/a		
		Product Name/Code:	100B /	7M0594-7020I	Customer:	TR	₹J	Document No.:			WI-ENG-PD	E-286B
		Purpose:	PROTO	DTYPE	PRE-LAUNCH		MASSPRO	Revision No.:		3	Page No.:	3 of 4
		<u> </u>						1		<u> </u>	<u> </u>	
PARTS: 1. As 2. Bla		parts tape							JIG	n/a		
NO.	PF	ROCESS NAME		WORK PROC	EDURE/ ILLU	STRATION		TOOLS/	QI	UALITY PO	DINTERS	
5	<i>P</i> 2	Taping 3 Black Corrugated tube (w/slit) to wire near PCB and terminal tip		2. Measure from end of the 131±3mm then continue th Note: Refer to WI-PRO-ASY	hand the han	to hotmelted wireing both hands.	ng right hand.	6 7 8 9 (0) 1 2 3 4	G TAPE	1. No flip 2. No pe 3. No loc 4. No mi 5. No wr	e use calibra uring tape w leasurement  p-out tape leal-off tape	n

			WORK INSTRUCTION							June 22, 2021			
		Process Name/Title:		TAPING ASS	SEMBLY P	ROCESS		Validity Date:		n/a			
		Product Name/Code:	100B /	7M0594-7020D	Customer:	-	ΓRJ	Document No.:		WI-EN	G-PDE-28	6B	
		Purpose:	PROTOTYPE	<b>E</b> C	PRE-LAUNCH		MASSPRO	Revision No.:		3 Page N	0.:	4 of 4	
	1							1	ı	<u>'</u>			
	Assy parts     Black tape								JIG	n/a			
NO.	PF	ROCESS NAME		WORK PROCE	DURE/ ILLU	JSTRATION		TOOLS/	TOOLS/PPE		QUALITY POINTERS		
6	P2	Taping 4 Half-wrap taping	1/2 shift	1/3	begin taping	Make 1/2 shiftintil the end of coinds and then co	ng. Repeat the process rrugated tube. Make 3	MEASURING 6 7 8 9 1 2 3 4	5 6 7 8 9 (	Note: USE WHITE VISUALIZATIO BUT ACTUAL STAPE.  1. No flip-out tag 2. No peel-off ta 3. No loose tape 4. No missing ta 5. No wrong dim 6. No wrong use  Note: Please use comeasuring to the measure	n SHIFTING SHOULD BE  De pe ension of tape  allibrated,	G LINES, E BLACK	