






	Process Name/ Title:		Document No:	WI-QAD-QAC-289
	PACKING INSTRUCTION			
	WORK INSTRUCTION		Effective Date:	February 5, 2025
	Product Code/Name: A7445	Customer Code: TRQSS	Rev. No.: 0	Page No.: Page 1 of 1

No.	Work Procedure/ Illustration		Records/Remarks/ Quality Pointers		
①	Put Vinyl Sheet (1250 x 1250) inside carton box.		QTY/BOX	120 pcs.	60pcs x 2bdls
			Material Name	Dimension	Quantity
			DC carton	1131*781	1
			Vinyl sheet	1250*1250	1
			Vinyl bag	420*280	2
②	Put the first bundle of products inside the box (60 pcs. Per bundle)		NOTE: 1. Step no. 5 is applicable to FG inspection only.		
③	Put the second bundle on on top of the first bundle with opposite orientation.	 <div>Switches should be at the bottom of connector</div>			
④	Fold the vinyl sheet and close the flaps.	 			
⑤	Put the inner tag on top of vinyl plastic sheet and the outer Tag at the front-right side of the box.	  <div> NOTE: For 4m tag attachment, put it in the front- left side of the box. </div>			

02/05/2025	0	Initial Issue	D. Dadulla	R. Pascua	O. Merin	Prepare	Check	Approve
Eff./Rev. Date	Rev. No.	Details of change	Revise	Check	Approve	Est. date:	February 5, 2025	