			WORK INSTRUCTION						Effectivity Date:		October 30, 2024		
			Process Name/Title:		Validity Date:		n/a						
			Model code/Part number:	D01L / 7M0653-7020A	NE ASSEMBLY PRO Customer: TRJ	Car Model:	Daihatsu	/Tanto	Document No.:		WI-ENG-PDE-	132	
			Purpose:	PROTOTYPE	PRE-LAUNCH	MASSPI	RO		Revision No.:	5	Page No.:	1 of 6	
PARTS:				AVSSf 0.3 Y wire L=373±2mm; AVSSf 0.3 B wire L=831±3mm					JIG:	2. Locking	Insertion jig with switch cover Locking jig		
N	NO.		ROCESS NAME	WORK PROCEDURE/ ILLUSTRATION					TOOLS/PPE	(QUALITY POINTERS		
1	1	n/a	Table Lay-out	Connector 4G5400-0000 (W)/ Connector tray Insertion jig w/ switch cover Lock	AVSSf 0.3 Y v L=373±2mr AVSSf 0.3 L=831±3	B wire mm			Safety Instruction Be sure to wear prescribed person protective equipmed during operation (gloves, finger cotective) Housekeeping 1. Maintain and alwork practice 5's. 2. Personal things the workplace is prohibited. Keep it your locker. Alert level For any trouble, infort the Assembly Assist Supervisor or Linuble and corrective action.	al al port and al	ent reference/se refer to WI-PRI I Strip length tole ing parts/tools	O-CNC-017 for	
ı	ı			Revision History		1			Prepared by	Reviewed by	Approved by	Noted by	
10/30/24	4	inspection Changed (page 1,3)	n/quality checkpoints. table lay-out; Inclusion of Quality	Car Model " DAIHATSU/TANTO". Improve measury Checkpoints (Page 5); Improve Quality pointers: Re/Illustration(process no. 4); Change Process Name OCESS"	eminders/Notes and reference/s	A.Hernandez M. Ariola		rañes n C. nueva A. Ar	não.				
04/09/21				onnector in accordance with color standardization Plastic Parts). Apply some improvements.	n of plastic parts (Please refer to G	L- M.	C.	A. lamura A. Ar	Ohmonder	Jour form	A. Aranes	n/a	

Revised Reviewed Approved Noted Est. Date:


October 29, 2019

CONFIDENTIAL: Any misuse or misappropriation, including unauthorized copying, reproduction in any form, disclosure or publishing of this document or any information herein is strictly prohibited.

Eff. Date Rev. No




Details of Change



	_		WORK INS	TRUCTION				Effectivity Date:	October 30, 2024		
		Process Name/Title: OFFLINE ASSEMBLY PROCESS						Validity Date:	n/a		
		Model code/Part number:	D01L / 7M0653-7020A	Customer: TRJ		Car Model: Daihatsu/Tanto		Document No.:	WI-ENG-PDE-132		
		Purpose:	PROTOTYPE	PRE-LAUNC	CH	MASSPR	RO	Revision No.:	5	Page No.:	3 of 6
PARTS:	1. AVS	Sf 0.3 Y wire L=373±2mm;	; AVSSf 0.3 B wire L=831±3mm				JIG:	1. Insertion jig with switch cover			
NO.	F	ROCESS NAME	WORK PROCEDURE/ ILLUSTRATION			TOOLS/PPE	QUALITY POINTERS				
3	n/a	Wire insertion to connector 4G5400-0000 (W)	1. Hold the insertion jig using left hand, the Y wire then insert to terminal slot 1 right hand. 2 Blac 3. Get the B wire then insert to terminal using right hand.	get using r	2. After insertion ight thumb. The	ertion, push the	ress the button using ire will be opened. R The lock using left wires and gently pull gusing right hand.		4. No defoi 5. No wron 1. Please during in 2. Wire in right. 3. Make inserted. Conduct insertion Do not e Docume 1. Please 017 for Valorerance 2. Please 2. Please	g insertion one insertion remed terminal g wire facing ant reminders/le hold the wire not insertion. Insertion must be sure wires are posertion. Insertion continues are posertion and terminal general force. Insertion wires are poserties	ear terminal from left to roperly I-Push after G-PRO-CNC- rogth

			Effectivity Date:	October 30, 2024						
		Process Name/Title:	Validity Date:		n/a					
		Model code/Part number:	D01L / 7M0653-7020A	Customer: TRJ	Car Model:	Daihatsu/Tanto	Document No.:		WI-ENG-PDE-	132
		Purpose:	PROTOTYPE	PRE-LAUNCH	MASSPE	RO	Revision No.:	5	Page No.:	4 of 6
PARTS:	1. Assy Parts					JIG:	1. Locking jig			
NO.	F	PROCESS NAME	WORK F	PROCEDURE/ ILLUST	RATION		TOOLS/PPE	QUALITY POINTERS		
4	n/a	Connector Lock	BEFORE PRESSING 1. Put the connector into locking jgig using both hands then press 2x using both hands.		AFTER PRESSING	LOCKING JIG	1. Manudamage	ant reminders/ al locking may c d connector lock vided jig per mode ck/Half-locked	ause C.	



WORK INSTRUCTION Effectivity Date: Process Name/Title: OFFLINE ASSEMBLY PROCESS Validity Date:							October 30, 2024 n/a		
	Process Name/Title: Model code/Part number: D01L		omer: TRJ Car Model:	Daihatsu/Tanto	Validity Date: Document No.:		n/a WI-ENG-PDE-1	132	
	Purpose: PROT				Revision No.:	5	Page No.:	6 of 6	
PARTS: n/a					JIG:	n/a			
		VISUAL IN	SPECTION/QUALITY CHE	CKPOINTS					
OFFL	NE INSERTIO	ON	7	M0653	-7020A				
GOOD			5	4				OD OD	
	1 No Unlock cond 2 No Wrong inse		Terminal Back Deformed Ter		5 Check th	e Alig	nment		