

# Embracing Continuous Delivery with Azure Pipelines

## Overview

In this lab, you will learn about the release management features available in Azure Pipelines that automate the deployment of applications. These features help development and operations teams integrate with Azure DevOps Server to configure and automate complex deployments of their automated builds to target stages more easily. Development teams can also model their release processes and track approvals, sign-offs, and visualize their release status.


## Prerequisites

- An Azure account (free from <https://azure.com/free>).
- Complete task 1 from the prerequisite instructions.



## Exercise 1: Embracing Continuous Delivery with Azure DevOps

### Task 1: Setting up Azure resources


1. Start off by creating the Azure resources needed for this lab. This includes a database and two app services: one for QA and one for production. Log into your account at <https://portal.azure.com>.
2. Click **Create a resource** and search for “sql”.



3. Select **SQL Database**.

NAME	PUBLISHER	CATEGORY
 SQL Database	Microsoft	Databases
 SQL server (logical server)	Microsoft	Databases

4. Click **Create**.



- Under **Resource group**, click **Create new**.

#### Project details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

\* Subscription ⓘ

\* Resource group ⓘ

[Create new](#)

- Enter a **Name** of “**partsunlimited**” and click **OK**.

A resource group is a container that holds related resources for an Azure solution.

\* Name

- Enter a **Database name** of “**partsunlimited**” and click **Create new** to create a new server.

#### database details

Enter required settings for this database, including picking a logical server and configuring the compute and storage resources

\* Database name

\* Server ⓘ

[Create new](#)

- Enter a unique name for **Server name**, such as by including your name. Enter an admin username and password you can remember. Note that “**P2ssw0rd**” meets the password requirements. Click **OK** to confirm these options.

## New server

Microsoft



Server name \*

pul-johndoe ✓

.database.windows.net

Server admin login \*

sysadmin ✓

Password \*

..... ✓

Confirm password \*

..... ✓

Location \*

(US) West US 2 ✓

OK

9. Click **Review + create**.

Review + create


Next : Additional settings >

10. Click **Create**. It'll take some time to complete, but you can move on to the next step while it works in the background.




Create

< Previous

11. Click **Create a resource** and search for "web".



12. Select the **Web App** template.

NAME	PUBLISHER	CATEGORY
 Web App	Microsoft	Web
 Web App Bot	Microsoft	AI + Machine Learning
 Web App for Containers	Microsoft	Web


13. Click **Create**.




14. Under **Project Details**, select the same **Subscription** and **Resource Group** used for the database.

**Project Details**

Select a subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

\* Subscription    ▼

\* Resource Group  partsunlimited ▼

[Create new](#)

15. For **Name**, enter a unique name, such as by using your name as part. Since this will be for our QA deployment, append the name with **"-qa"**. Select the **ASP.NET 4.8 Runtime stack**.

**Instance Details**

Name \* pul-johndoe-qa .azurewebsites.net ✓

Publish \* ☒ Code ☐ Docker Container

Runtime stack \* ASP.NET V4.8 ▼

16. Click **Review and create**.

Review and create Next: Monitoring >

17. Click **Create**.

Create Previous

18. Repeat the process above to create a second app service for the production stage. This time, append the **Name** with “-prod” instead.

#### Instance Details

\* Name


pul-johndoe-prod

.azurewebsites.net


19. While the Azure resources are created, go ahead and configure the SQL server.
20. Click the **Resource groups** tab from the left menu. Locate and click the **partsunlimited** group.
21. Click the SQL server resource created earlier.
22. Select the **Firewalls and virtual networks** tab from the **Security** section.
23. Set “**Allow Azure services and resources to access this server**” to **Yes** to allow the App Services to access this SQL server.
24. Click **Save** on the top of the tab.
25. Continue on to the next task. Leave this browser tab open for later.

### Task 2: Creating a continuous release to the QA stage

1. Navigate to your team project on Azure DevOps in a new browser tab. It should be at <https://dev.azure.com/YOURACCOUNT/Parts%20Unlimited>.
2. Navigate to **Pipelines | Releases**.



3. **Delete** the existing **PartsUnlimitedE2E** release pipeline. We'll start fresh here.



4. Click **New pipeline**.



## No release pipelines found

Automate your release process in a few easy steps with a new pipeline



5. There are many starting templates to choose from, or you can even begin with an empty process template. In this case, select the **Azure App Service Deployment** and click **Apply**.

### Featured

#### Azure App Service Deployment


Deploy your application to Azure App Services. Choose from Web App On Windows, Linux, Containers, Function Apps or WebJobs

Apply

#### Deploy Node.js App to Azure App Service

Deploy your Node.js application to Azure Web App

6. Rename the default stage to **"QA"**. This template will deploy to QA, and then to a production stage. We'll set up this one first.

 **Properties** ^  
Name and owners of the stage


Stage name

7. Rename the release pipeline to **"PUL-CICD"**.

All pipelines >

Pipeline


 Tasks ▾

Variables

Retention

8. The first thing to define is exactly what should be deployed. Click **Add** in the **Artifacts** section to specify the artifact to deploy.

Artifacts |  **Add**

 Add artifact




Schedule  
not set

9. There are many types of artifacts, but this one will be pretty simple: a project built from the **PartsUnlimitedE2E** build pipeline that already exists in this team project. Click **Add**.

## Add artifact

Source type



Git



GitHub



Team Found...

4 more artifact types ▾

Project \* ⓘ

Parts Unlimited ▾

Source (Build definition) \* ⓘ

PartsUnlimitedE2E ▾

Default version \* ⓘ

Latest ▾

Source alias ⓘ


\_PartsUnlimitedE2E

ⓘ The artifacts published by each version will be available for deployment in Release Management. The latest successful build of **PartsUnlimitedE2E** published the following artifacts: **drop**.

Add

- Now that the artifact has been defined, it's time to configure the deployment to QA. Click **1 job, 1 task** in the **QA** stage.

Stages | + Add ▾



- Select the **Azure subscription** you used earlier to create the resources and click **Authorize**. If you need to create a connection to an Azure account associated with a different Microsoft account, click **New** and follow that workflow before continuing.



Environment name

QA

Parameters ⓘ | [Unlink all](#)

Azure subscription \* [Manage](#)

Authorize

ⓘ Click Authorize to configure an Azure service endpoint

12. Follow the workflow to authorize access to your Azure account.
13. Enter the **App service name** used earlier when creating the QA app service.

App service name \* [Link](#)

pul-johndoe-qa

14. Return to the **Pipeline** tab.

All definitions > PUL-CICD

Pipeline

Tasks ▾


Variables

Retention

Options

History

15. Click the **Triggers** button to define what triggers will invoke this deployment.



16. **Enable** the **Continuous deployment trigger**. Add a **Build branch filter** that points at the **The build pipeline's default branch**. This will kick off the deployment when the build completes.

## Continuous deployment trigger

Build: \_PartsUnlimitedE2E



Enabled

Creates a release every time a new build is available.

### Build branch filters ⓘ


No filters added.



Branch filter

The build pipeline's default branch


17. **Save** the release pipeline.



+ Release ▾ ≡ View releases ...

### Task 3: Configuring the Azure app services

1. Return to the browser tab open to the Azure portal.
2. Click the **Resource groups** tab from the left menu. Locate and click the **partsunlimited** group created earlier.








Subscriptions: All 2 selected – Don't see

Filter by name...

20 items



3. Click your SQL database (something like **pul-johndoe/partsunlimited**). Make sure you click the database you created and not the server. Note that it may take a few minutes for the database and server to become available, so click the **Refresh** button every once in a while to check in.

<input type="checkbox"/>	NAME ↑↓
<input type="checkbox"/>	 pul-johndoe
<input type="checkbox"/>	 master (pul-johndoe/master)
<input type="checkbox"/>	 partsunlimited (pul-johndoe/partsunlimited)
<input type="checkbox"/>	 pul-johndoe-prod
<input type="checkbox"/>	 pul-johndoe-qa

- In the new blade, click **Show database connection strings**.

Resource group <a href="#">(change)</a>	Server name
partsunlimited	pul-johndoe.database.windows.net
Status	Elastic database pool
Online	No elastic pool
Location	Connection strings
West US	<a href="#">Show database connection strings</a>
Subscription <a href="#">(change)</a>	Pricing tier

- This will provide you with a list of connection strings based on platform. Copy the **ADO.NET** string to your clipboard so you can configure your new web site to use it. Close this blade.


ADO.NET
JDBC
ODBC
PHP

ADO.NET (SQL authentication)






Server=tcp:pul-johndoe.database.windows.net,1433;Initial  
Catalog=partsunlimited;Persist Security Info=False;User ID={your\_username};Password=  
{your\_password};MultipleActiveResultSets=False;Encrypt=True;TrustServerCertificate=Fal

- Open a new instance of **Notepad** and paste the connection string into it. This will make it easier to edit and retrieve later on in case anything happens to the clipboard copy.
- Use the breadcrumb navigation to return to the **partsunlimited** resource group.


Home > Resource groups > partsunlimited


**partsunlimited (pul-johndoe)**  
SQL database

- Click the **QA** app service created earlier.

<input type="checkbox"/>	NAME <span>↑↓</span>
<input type="checkbox"/>	 pul-johndoe
<input type="checkbox"/>	 master (pul-johndoe/master)
<input type="checkbox"/>	 partsunlimited (pul-johndoe/partsunlimited)
<input type="checkbox"/>	 pul-johndoe-prod
<input type="checkbox"/>	 pul-johndoe-qa


- Select the **Configuration** tab from the **Settings** section.



- On this blade you can configure settings for your app, such as connection strings. Click **New connection string**.

## Connection strings

ⓘ Connection strings are encrypted at rest and transmitted over an encrypted channel.




- Locate the **Connection strings** section and add a new entry with the key "**DefaultConnectionString**" and the value pasted from the clipboard. You'll need to locate the "{your\_username}" and "{your\_password}" sections and replace them (including braces) with the actual SQL credentials entered earlier. Be sure the **Type** is set to **SQLAzure** and click **OK**.

Add/Edit connection string

Name	<input type="text" value="DefaultConnectionString"/>
Value	<input type="text" value="ame);Password={your_password};MultipleActiveResultSets=False;Connection Timeout=30;"/>
Type	<input type="text" value="SQLAzure"/>
<input type="checkbox"/> Deployment slot setting	


12. Click **Save** to commit.




13. Repeat the process above to add the same connection string to the production app service.

#### Task 4: Invoking a continuous delivery release to QA


1. Return to the browser tab open to your Azure DevOps project.
2. Now that the release pipeline is in place, it's time to commit a change in order to invoke a build and release. You'll need to make a few changes like this over the course of this lab, so it's recommended that you use a separate tab for **Code | Files** to keep that part of the process separate.



3. Navigate to **PartsUnlimited-aspnet45/src/PartsUnlimitedWebsite/Views/Shared/\_Layout.cshtml**. This is a file that defines the general layout of the site and is a good place to make a change that will be easily visible after deployment.




4. Click **Edit** to edit the file inline.




5. Locate the **Parts Unlimited Logo** and add the text **"v2.0"** after it. This will be an easy thing to check for after deployment.

```
35 | <div class="pull-left logo">
36 |   <a class="block logo-image" href="@Url.Action("Index", "Home", new { Area = string.Empty })">
37 |      v2.0
38 |   </a>
39 |   <a class="block" href="@Url.Action("Index", "Home", new { Area = string.Empty })">
```


6. **Commit** the changes back to the repo. This will kick off a build based on the preconfigured build pipeline.




7. Navigate to the **Pipelines** hub.




8. Open the most recent build for **PartsUnlimitedE2E**. It may be queued, in progress, or already completed.




9. Follow the build until completion.




10. Click the **Releases** tab to see the new release get going.




11. Click the release. As with the build, it may be queued, in progress, or already completed when you get here.



12. Follow the release until it succeeds.



13. You can now close this tab if you prefer.




14. In a new browser tab, navigate to the QA site. It will be the name of your app service plus “.azurewebsites.net”. It should show the **v2.0** added earlier.




#### Task 5: Creating a gated release to the production stage

1. Return to the Azure DevOps browser tab.
2. As release pipelines get more sophisticated, it becomes important to define gates to ensure quality throughout the release pipeline. Since the next stage we're deploying to is production, we'll need to be sure to include both automated quality gates as well as a manual approver gate. Return to the release pipeline browser tab and click **Clone** in the **QA** stage. Since the production stage is virtually the same, we can reuse almost all of the existing configuration.





3. The new stage is added after the current one, which is what we want. However, before we can consider the QA deployment successful, we'll need to define a post-deployment condition. Click the **Post-deployment conditions** button on the **QA** stage.



4. **Enable** the **Gates** option.

## Post-deployment conditions

QA

Post-deployment approvals

Select the users who can approve or reject deployments to this environment

☐ Disabled

Gates ^

Define gates to evaluate after the deployment. [Learn more](#)

☒ Enabled

5. There are several kinds of gates available that can automatically test virtually anything you need to make sure a deployment is in good shape. These could be the return values of Azure functions or REST APIs, queries to Azure for alerts, or work item queries in Azure DevOps. You can also configure how long the platform should delay before evaluating the gates for the first time. In this case, change that to **0** so it will test them immediately after deployment. Then click **Add | Query Work Items**.

Delay before evaluation ⓘ

Minutes ▾

Deployment gates ⓘ

[+ Add](#)



Invoke Azure Function

Invoke Azure function as a part of your process.



Invoke REST API

Invoke REST API as a part of your process.



Query Azure Monitor Alerts

Observe the configured Azure monitor rules for active alerts.



Query Work Items

Executes a work item query and checks for the number of items returned.

6. Select the **Query** for **Shared Queries | Critical Bugs**. We will make it our policy that the QA deployment cannot be considered a success until all critical bugs have been resolved.

Display name \*

Query Work Items

Query \* ⓘ

Critical Bugs

- Expand **Evaluation options** and update the **Time between re-evaluation of gates** to **5**. If this gate fails, we want it to reevaluate the query every 5 minutes until it clears because engineers will need some time to confirm those critical bugs are fixed in the current version. However, if those bugs aren't cleared and the release isn't manually failed, this configuration will automatically fail the gate after 1 day.

Evaluation options ^

Time between re-evaluation of gates ⓘ

5 Minutes

Timeout after which gates fail ⓘ

1 Days

- For the Query Gate to work, Project Build Service would require Read permission to queries. Go to **Azure Boards > Queries > All > Shared Queries > "..."** > **Security**.

The screenshot shows the Azure Boards interface. On the left, the 'Queries' option in the sidebar is highlighted with a red box. In the main area, the 'Queries' section is active, and the 'All' tab is selected. Under 'Shared Queries', the 'Current Sprint' folder is expanded, showing a list of queries. A context menu is open over the '...' icon next to a query, with the 'Security...' option highlighted with a red box.

- Search for the **"(YOUR PROJECT NAME) Build Service"**, if not included by default (not Project Collection Build Service!) and give it **Read > Allow** permission.

## Permissions for Shared Queries



Azure DevOps Groups

BA

Build Administrators

C

Contributors

PA

Project Administrators

R

Readers

PA

Project Collection Administrators

Users

PS

PartsUnlimited Build Service (sriramdasb:

PS

Project Collection Build Service (sriramda

PartsUnlimited Build Service (sriramdasbalaji)

Contribute

Not set

Delete

Not set


Manage Permissions

Not set


Read

Allow


10. We can now turn our focus to the production stage. Select the **Copy of QA** stage.



11. Rename it to **"Prod"**.



12. Click its **Pre-deployment conditions** button.



13. **Enable** the **Pre-deployment approvals** and add yourself as an **Approver**. The idea here is that you won't be asked to approve the production deployment until after the QA deployment has succeeded. At that point, someone on this list will need to approve the


deployment to production. Also clear the box for **User requesting a release of deployment should not approve** if it's checked. For the purposes of this lab, you can approve releases you have requested.

### Pre-deployment approvals ^

Select the users who can approve or reject deployments to this environment



#### Approvers ⓘ




#### Timeout ⓘ

▾


#### Approval policies

- ☒ User requesting a release or deployment should not approve
- ☐ Skip approval if the same approver approved the previous environment ⓘ


14. Click the **Prod** stage's **1 job, 1 task**.



15. Update the **App service name** to reflect the **"-prod"** (instead of **"-qa"**).

App service name \* 

▾




16. **Save** the release pipeline.




17. Repeat the process for changing the codebase at **"PartsUnlimited-aspnet45/src/PartsUnlimitedWebsite/Views/Shared/\_Layout.cshtml"** followed earlier in a new tab. This time, update the version number from **"2.0"** to **"3.0"**. This will invoke the release pipeline.
18. As before, follow the release until it is deploying to QA. Click to follow the release itself once available.


19. Eventually there will be an issue with the QA deployment. While it deployed out successfully, one of the quality gates failed. This will need to be resolved for that stage to be approved. Click the **View post-deployment gates** button.



20. It looks like the **Query Work Items** gate is failing. This means that there is a critical bug that must be cleared.



21. Open a new tab to **Boards | Queries** to locate the bug.



22. Use the query list on the **All** tab to open the **Shared Queries | Critical Bugs** query.

## Queries

Favorites

All

+ New query

Title

My Queries

Assigned to me

Followed work items

Shared Queries

> Current Sprint

All Items

Critical Bugs

23. Open the one bug by clicking it.

Results Editor Charts



Save query



Column options

Copy query URL

ID

Work Item...

Title

1586

Bug



Decline in orders noticed - Please Investigate immediately

24. Ordinarily you'd check the site to confirm the bug was fixed, but we'll skip ahead here and mark it **Done**. Click **Save** and close the tab.

BUG 1586\*

1586 Decline in orders noticed - Please Investigate immediately



0 comments

Add tag



Save

State

Done

Area

Parts Unlimited

Reason


Work finished

Iteration

Parts Unlimited

Details

25. Return to the release pipeline tab. Depending on timing, it may take up to five minutes for Azure DevOps to check the query again. Once it does, the bugs will be cleared and the release will be approved. You can then click **Approve** to approve deployment to production.




26. Confirm the deployment.

☐ Defer deployment for later

Approve Reject

27. Click the **In progress** link to follow the release workflow.



28. It may take a moment for the release to kick off and complete.

PUL-CICD > Release-10 > Prod **▶ In progress**

← Pipeline Tasks Variables **Logs** Tests | Download all logs Edit release

**Deployment status**  
In progress

- ✓ Pre-deployment approvals  
Approved
- ▶ Run on agent  
In progress

**Run on agent**  
Queue: Hosted VS2017 · Agent: Hosted Agent

- ✓ Initialize Agent · succeeded
- ✓ Initialize Job · succeeded
- ✓ Download artifact - \_PartsUnlimitedE2E · succeeded
- ▶ Deploy Azure App Service


Waiting for console output from an agent...

29. Once the release has completed, open a new tab to the production app service URL. It should be the same as your QA URL, but with “-**prod**” instead of “-**qa**”. Note the **v3.0**.



#### Task 6: Working with deployment slots

1. Return to the browser window open to the Azure portal.
2. Azure App Services offer **deployment slots**, which are parallel targets for application deployment. The most common scenario for using a deployment slot is to have a staging stage for your application to run against production services, but without replacing the current production application. If the staging deployment passes review, it can immediately be “swapped” in as the production slot with the click of a button. As an additional benefit, the swap can be quickly reversed in the event an issue is uncovered with the new build. Locate the resource group created earlier and click the **prod** app service.



3. Select the **Deployment slots** tab. If you see a message indicating that your current pricing tier does not support slots, follow the workflow to upgrade this service to a **Production** tier or higher and then return here. You may need to refresh the browser for the **Add Slot** option to become enabled.

#### Deployment


 Quickstart

 Deployment slots

 Deployment Center




- Click **Add Slot**. Note that the **production** slot is considered a “default” slot and is not shown as a separate slot in the user experience.




- Enter a **Name** of “**staging**” and select the **Configuration Source** that matched your existing deployment (there should be only one). Click **Add** to create the slot.

A screenshot of the 'Add Slot' dialog form. The 'Name' field contains the text 'staging'. The 'Clone settings from:' dropdown menu is open, showing 'pul-johndoe-prod' as the selected option. Below the form are two buttons: 'Add' (circled in red) and 'Close'.


- Return to the Azure DevOps tab with the **Prod** stage pipeline editor.
- Select the **Deploy Azure App Service** task.






- Check **Deploy to Slot...** and set the **Resource group** and **Slot** to those created earlier.


App Service name \* 



pul-johndoe-prod

☒ Deploy to Slot or App Service Environment 


Resource group \* 

partsunlimited  

Slot \* 

staging  

9. **Save** the release pipeline.




10. Follow the workflow from earlier to commit a change to the codebase at “**PartsUnlimited-aspnet45/src/PartsUnlimitedWebsite/Views/Shared/\_Layout.cshtml**” by updating the layout template from “**3.0**” to “**4.0**”.
11. Follow the release pipeline through deployment and approve the release to production when requested.
12. When the production deployment has completed, refresh that browser tab. Note that there shouldn't be any change since the deployment was pushed to a different slot.



13. Open a new tab to the **staging** slot. This will be the same as your production URL, but with “**-staging**” appended to the app service name within the domain. This should reflect the new **v4.0**.



14. Return to the browser window open to the **Azure portal**. Click **Swap** in the deployment slots blade.



15. The default options here are exactly what we want: to swap the production and staging slots. Click **Swap**. Note that if your apps rely on **slot-level configuration settings** (such as connection strings or app settings marked "slot"), then the worker processes will be restarted. If you're working under those circumstances and would like to warm up the app before the swap completes, you can select the **Swap with preview** swap type.

● Source

pul-johndoe-prod-staging

● Target **PRODUCTION**

pul-johndoe-prod

**i** Swap with preview can only be used with sites that have deployment slot settings enabled

☐ Perform swap with preview


### Config Changes

This is a summary of the final set of configuration changes on the source and target deployment slots after the swap has completed.

● Source Changes		● Target Changes	
SETTING	TYPE	OLD VALUE	NEW VALUE
No Changes			


**Swap** **Close**

16. Return to the **prod** browser window (not the staging slot) and refresh. It will now be the 4.0 version.



<https://pul-johndoe-prod.azurewebsites.net/>

Fork me on GitHub



v4.0

Parts Unlimited  
a Fabrikam subsidiary