REPLICATION DATA AND CODE FOR "DESERT AND REDISTRIBUTION: JUSTICE AS A REMEDY FOR, AND CAUSE OF, ECONOMIC INEQUALITY" (POLICY STUDIES JOURNAL, 2022)

Bower-Bir, J. S. (2022). Desert and redistribution: Justice as a remedy for, and cause of, economic inequality. *Policy Studies Journal* 50(4): 757–795. https://doi.org/10.1111/psj.12439

1. ABOUT THIS RECORD

- **Creator.** Jacob S. Bower-Bir, ORCID 0000-0002-4825-9850, jbowerbir@gmail.com.
- **Cite this package as.** Bower-Bir, J. Replication Data and Code for "Desert and Redistribution: Justice as a Remedy for, and Cause of, Economic Inequality" (Policy Studies Journal, 2022) [Data set]. Indiana University - DataCORE. DOI forthcoming.
- **Data coverage.** The survey was fielded between 2013-11-19 and 2014-04-08. The original analysis dates from 2014 and the replication from 2026.
- **Methodology.** Online survey. SocialSci, an online survey panel company, fielded my Economic Justice Survey (version 7) to adult U.S. residents. The 2014 cleaning kept 992 records, which hold 991 respondents. Survey weights were raked to 2012 Census Bureau projections for gender, race, education, and household income and to 2012 Pew Research Center figures for party identification. The article's regressions are weighted least squares with a fixed effect for each state and heteroskedasticity-robust standard errors. For this package I rewrote the analysis in R and in Python. The two produce identical tables and reproduce every table and figure in the article but one appendix figure, which needs columns outside this subset. Re-running the analysis found 22 mistyped cells in the published tables, two 2014 cleaning errors, and two figures drawn on mixed scales, all described below.
- **Funding.** The survey was funded by the Ostrom Workshop in Political Theory and Policy Analysis (Ostrom Research Grant, 2013–2014) and the Indiana University Social Science Research Commons (Research Grant, 2013–2014).

- **License.** CC BY 4.0.

2. SUMMARY

This package reproduces every table and figure in the article from the survey data provided (Figure B1 excepted; see Section 5). The original Stata script is included, and I translated the analysis into R and Python. The two programs produce identical tables, both reproduce the results the Stata code gave in 2014, and each compares its output with the published tables cell by cell. The article's findings hold. The re-run found:

- **Twenty-two published cells that differ from the re-run**, all copying errors I made when typing the tables into the manuscript: digits mistyped or transposed, a decimal point in the wrong place, significance stars off by a level (in one case two), three dropped minus signs, two sample sizes, and one adjusted R^2. Four of those are in Table 1, the most visible on Definition, printed as positive when it is negative, as the article's prose correctly states.
- **Two sentences that misread the coefficient on Age²**, a control, in Section 6.1. It is so small that it prints as 0.000. The article calls it positive when it is negative, so support for government action to reduce the income gap (Y_gov_fix_gap) rises with age up to about age 34 and then falls, rather than accelerating. That turning point comes from Y_gov_fix_gap Model 1 in Table 1, the one Table 1 model where Age² is significant.
- **Figures D1 and D2 drawn on two scales at once.** The 2014 plotting code mixed two scalings of Definition. Drawn on one scale (Section 5), the interaction they illustrate is weaker than printed, and the main finding on faith in economic justice holds for nearly the whole sample.

I also found two errors in my 2014 data cleaning. One respondent's submission appears twice in the file the survey panel vendor delivered, under two different survey ids; my cleaning removed every other duplicate but missed this one. And my weighting script put the 54 respondents earning $25,000 to $29,999 per year in the under-$25,000 income group, one bracket off. The scripts therefore produce every table and figure twice: on the published sample (the 992 records, the 2014 weight, the typos fixed), which I call the typos-fixed tables, and on the 991 distinct respondents with the weight recomputed, which I call the final data. Coefficients move by a few hundredths of a unit, every key independent variable in Table 1 keeps its sign and its significance, and no conclusion changes. Section 6 lists every cell that moves.

The correction sent to the journal, `corrigendum_psj.md` (journal DOI 10.1111/psj.70145), is included. Variable and model names are defined in Section 8. To reproduce everything, run `Rscript script_replication.R` or `python3 script_replication.py` in this folder.

3. FILES

Files are named by what they are, then which version, then which program wrote them: `category_item_variant_program.ext`. Underscores separate those fields and hyphens join words inside one field, so a folder sorted by name groups by kind. The tables are in `tables/` and the figures in `figures/`; everything else is in the top folder. Every file the R program writes carries `_R`, and the Python program writes the same files with `_python`. The table pairs are identical. The figure pairs plot the same values, each in its program's own style. `README.pdf` is this document, typeset for readers who would rather not open a markdown file. On DataCORE, the two folders come as `tables.zip` and `figures.zip`.

3.1 Data

FILE	WHAT IT IS
`data_survey_psj-subset.csv`	The survey data: 992 records (991 respondents) and 27 columns, two identifiers and the 25 variables the tables and figures use. No value was changed. The full survey is a separate deposit (see Section 7).
`data_codebook.md`	The 27 columns: question wording, answer options, coding and rescaling, and the label each has in the article.

3.2 Scripts

FILE	WHAT IT IS
`script_replication.R`	The analysis in R: Tables 1, C1, C2, and D1 (32 regressions), Table A1, and Figures 1, 2, 3, 4, D1, and D2, on the published sample and on the final data. Writes every `_R` file below, then prints every cell where the printed tables differ. Base R only.
`script_replication.py`	The same program in Python. Writes the same files with `_python` in place of `_R`, with tables identical to the R output.

FILE	WHAT IT IS
`script_original_stata-2014.do`	The original Stata code that produced the article's tables and the D1 and D2 plots, commands untouched apart from the directory paths stripped from the log and use lines, with comment lines (`// [2026]`) saying which command makes which table or figure. A record, not a runnable script: it reads a file not included here.

3.3 Tables

FILE	WHAT IT IS
`tables/tables_as-published.md`	The four regression tables as printed in the article, copied cell by cell from the published PDF, stars included.
`tables/tables_typos-fixed_R.md` , `tables_typos-fixed_python.md` , `tables_typos-fixed.pdf`	The four regression tables with the typos corrected, on the published 992 records (duplicate included), plus Table A1 and the marginal effects plotted in Figures D1 and D2. Ends with the 22 corrected cells beside their published values. The PDF is a typeset reader copy of the R file.
`tables/tables_final_R.md` , `tables_final_python.md` , `tables_final.pdf`	The same tables estimated on the 991 distinct respondents, without the duplicated record and with the survey weight corrected, ending with a list of every cell that changes at the printed precision. These are the replacement tables offered to the journal. The PDF is a typeset reader copy of the R file.

3.4 Figures

FILE	WHAT IT IS
`figures/figure_1_R.png` , `figure_1_python.png`	Figure 1 charts three percentages from other surveys, written into the scripts. It is not derived from this survey and is drawn once by each program.

FILE	WHAT IT IS
`figures/figure_2_published-sample_R.png` … `figure_D2_published-sample_R.png`, and `_python`	Figures 2, 3, 4, D1, and D2, redrawn by each program from the published sample (992 records, 2014 weight), not copied from the article.
`figures/figure_2_final-data_R.png` … `figure_D2_final-data_R.png`, and `_python`	The same figures drawn from the final data (991 respondents, corrected weights).

3.5 Corrigendum

FILE	WHAT IT IS
`corrigendum_psj.md`, `corrigendum_psj.pdf`	The correction as sent to the journal: the three types of error, the two data-cleaning errors, and corrected Table 1 (991 respondents, corrected weights). It refers to this package for every other table.

4. RUNNING IT

Keep the layout as delivered, with the scripts and the data in one folder and `tables_as-published.md` in a `tables/` subfolder; from DataCORE, unzip `tables.zip` and `figures.zip` beside the other files. The scripts write to `tables/` and `figures/`, creating them if needed. R needs base R only. Python needs pandas, numpy, scipy, statsmodels, and matplotlib.

- `Rscript script_replication.R` writes `tables/tables_typos-fixed_R.md`, `tables/tables_final_R.md`, and the figures, and prints the comparison with the printed tables.
- `python3 script_replication.py` writes the same files with `_python` in place of `_R`, and prints the same comparison.
- To check the two programs against each other, compare `tables/tables_typos-fixed_R.md` with `tables/tables_typos-fixed_python.md`, and `tables/tables_final_R.md` with `tables/tables_final_python.md`. They are identical.

5. WHAT IS REPRODUCED, AND HOW CLOSELY: THE PUBLISHED SAMPLE (992 RECORDS)

- **Tables 1, C1, C2, D1.** Every coefficient, standard error, N, R^2, and adjusted R^2 matches the printed value to the printed decimals, except the 22 corrected cells (a cell is a coefficient with its standard error, a sample size,

or an R^2). The constant's standard error is an approximation of Stata's and is not compared.

- **Table A1**, the sample's composition by gender, race, education, and so on: every group count and share matches.
- **Figure 1** charts three percentages from other surveys, not from this one. As the article's caption says, two come from the 2010 General Social Survey (n = 1,512) and one from a Gallup poll of 2011-11-28 to 2011-12-01 (n = 1,012). The numbers are in the scripts.
- **Figures 2 and 3** match the printed figures. The printed curves are a little more smoothed, and the 2014 smoothing setting was not recorded.
- **Figure 4** drops the duplicated record, as the published figure did. I found the duplicate while drawing that figure, in 2018, and dropped it there, but the regressions dated from 2014 and I failed to rerun them at the time.
- **Figures D1 and D2** are drawn correctly here, so they differ from the printed panels. The printed panels mix two scalings of Definition. The 2014 code built the interaction terms from a rescaled copy of Definition, (Definition + 1) / 2, while entering Definition itself unscaled in most of the models (Section 9 has the details), and then drew the lines as if the two were the same variable. The scripts draw each panel from the Table D1 model the appendix names, with Definition on one scale throughout and, in D1(c), the other two deserve scores held at their means rather than at zero. Both table files list each line's endpoints. What changes: in Figure D1 the lines are about half as steep as printed, so the interaction between Definition and faith in economic justice is weaker than the printed figure suggests, and the article's verdict that the evidence for it is meager stands. In Figure D2 the printed histogram sat on the wrong scale and showed a sizeable group of respondents for whom faith in economic justice raised support for redistribution; drawn correctly, almost no respondents are in that region, and the article's finding that faith in economic justice lowers support holds for nearly the whole sample.
- **Figure B1**, the heat maps in Appendix B, needs the 30 factor ratings this file leaves out. The companion package for Bower-Bir (2021), *Economia Politica* 38(1): 131–170, reproduces them as its Figure 3 from the same survey (IU DataCORE, DOI forthcoming, and https://github.com/jbowerbir/ACADEMIC_pub/tree/main/earning-our-place-ecopol-2020). Table B1 uses no data.

6. WHAT CHANGES WITH THE TWO DATA FIXES (991 RESPONDENTS, CORRECTED WEIGHTS)

`tables/tables_final_R.md` and `tables/tables_final_python.md` re-estimate Tables 1, C1, C2, and D1 on the 991 distinct respondents, with the survey weights re-raked on those respondents and with every respondent in the right income group. The published 2014 weights were raked with the duplicate present and with 54 respondents in the wrong income group. The scripts repeat the 2014 raking, whose method they first confirm by reproducing the shipped weight on all 992 records, and then correct the income groups. The file ends with a list of every cell whose printed value changes. Across the 422 coefficients (each with its standard error) in those tables:

- Coefficients move by a few hundredths of a unit (every variable save age runs from 0 to 1), two in Table D1 excepted.
  - In Table 1 the largest move among the predictors is on Definition in Y_gov_fix_gap Model 3, from −0.518 to −0.471. Definition's other two Y_gov_fix_gap coefficients shrink by about 0.03 in magnitude.
  - Agency, Justice, Rich deserve, Avg. deserve, and Poor deserve move by 0.016 or less.
  - The largest moves anywhere, up to 0.15, are on the two Poor deserve terms of Table D1, Y_prog_tax Model 3, whose standard errors are 0.8 to 0.9 and which were not significant before and are not now.
- Twenty-eight coefficients whose p-values sit near a significance threshold cross it, so their stars change: twenty-four increasing in statistical significance and four decreasing; three constants, not counted here, do the same. Six of the twenty-eight are on the key independent variables and the rest on controls.
  - Definition, in Table 1, Y_gov_fix_gap Model 1, drops from the 1% significance level to the 5% level (p = 0.0099 to 0.012) and stays at 1% in the other two Y_gov_fix_gap models. In Table D1, Y_gov_fix_gap Model 1, its main effect (as opposed to its interaction effect) gains a star (p = 0.108 to 0.062).
  - Agency, in Table 1, Y_prog_tax Model 1, rises from the 5% significance level to the 1% level (p = 0.0119 to 0.00998).
  - Rich deserve, in Table D1, Y_gov_fix_gap Model 3, rises from the 5% significance level to the 1% level (p = 0.015 to 0.008).
  - Poor deserve on Y_prog_tax, the one effect the article already calls statistically questionable, loses a star in two appendix models. In Table

C1 Model E, it moves from the 10% significance level to none (p = 0.096 to 0.108), and in Table C2 Model E, it moves from 5% to 10% (p = 0.041 to 0.0500, a hair above the 5% line). In Table 1 it keeps its one star.

- R^2 values move by at most 0.009, and adjusted R^2 by at most 0.010.
- Every claim in the main text holds. In Appendix D, Definition's main effect in Table D1's Y_gov_fix_gap Model 1 reaches the 10% level on the final data, where the appendix calls it not significant, and the remarks on Figures D1 and D2 change as described in Section 5.

The figures redrawn from the final data (`figures/figure_*_final-data_R.png` and `_python.png`) change little. The density curves of Figures 2 and 3 move by less than 0.02 on peaks of 1.5 to 3. The marginal-effect lines of Figures D1 and D2 move by at most 0.04, well inside their confidence bands. Figure 4 already excludes the duplicate, and Figure 1 is not from this survey.

7. THE DATA

This file holds all 992 records my 2014 cleaning kept. Of the 233 columns in the full survey's analysis file, it keeps the 27 columns (two identifiers and 25 survey variables) the tables and figures use. The R and Python scripts build the variables the regressions need from them (age squared, the married and unemployed indicators, the four-level tax outcome, and the interaction terms), as the 2014 Stata code did. The full survey, with the cleaning scripts, questionnaire, and codebook, will be deposited separately; its DOI will be added to this record.

The 2014 cleaning built some of the columns in the file from the raw answers: the four attitude measures that combine a direction with a strength (`gov_reducegap_str`, `agency_str`, `justice_str`, `gov_help_str`), the three Deserve scores (`desert_rich_tot`, `desert_americans_tot`, `desert_poor_tot`), and the Definition correlation (`corr_ideal_agency`, computed in a separate step before the Stata code ran). I recomputed each from the raw survey items, and each matches on every record. I also recomputed the survey weight (`post_weight`) using the 2014 script's method and population targets. It matches the published weight for every respondent to four decimal places (the largest difference is 0.000014). That re-derivation is how the weighting error came to light; the under-$25,000 group is the only one affected, and Table A1's income counts, which come from a different script, were correct as published.

Three things to know about the identifiers and the sample, beyond the codebook:

- `row` is the row number in the full survey file and the only column that identifies a record uniquely.
- `id` is the vendor's respondent number, kept for matching to the full survey. Use `row`, not `id`, to refer to a record. Two things make `id` unreliable as a key:
  - 55 id values are each carried by two different respondents. The vendor's numbering collided within one fielding batch, and the pairs are different people.
  - One respondent's record is genuinely in the file twice, under ids 1115 and 1157, identical in every answer, so the 992 records hold 991 respondents. The duplicate is kept because the published tables were estimated on all 992 records; dropping it would change every estimate slightly. The one place the published analysis dropped it was Figure 4 (Section 5). Both scripts also estimate every table a second time on the 991 distinct respondents, with the weight corrected (Section 6).
- `corr_ideal_agency` is missing for 29 respondents, so regressions that include it have N = 963 and regressions without it have N = 992 (or 962 and 991, respectively, in the final data).

8. THE REGRESSIONS

Every regression in the tables is one Stata command, `areg <outcome> <predictors> [pw=post_weight], absorb(state)`: a linear regression weighted by the survey weight, with a separate intercept for each state (state fixed effects) and standard errors that remain valid when the spread of the errors differs across respondents (heteroskedasticity-robust, the formula known as HC1).

- The outcome is Y_gov_fix_gap (`gov_reducegap_str`) or Y_prog_tax (built from `progtaxes_str`).
- The predictors are Definition (`corr_ideal_agency`), one measure of perceived economic justice, and the same controls throughout. The justice measure is Agency (`agency_str`) in Model 1, Justice (`justice_str`) in Model 2, and the three deserve scores (`desert_rich_tot`, `desert_americans_tot`, `desert_poor_tot`) in Model 3.
- Table C1 drops Definition and enters each justice measure individually, and Table C2 adds three controls; the models in those two tables are

lettered A to E. Table D1 adds the product of Definition and each justice measure (an interaction).

- The scripts fit the same regressions as weighted least squares with an indicator for each state. The constant they report is the grand-mean intercept, as Stata reports it.

9. TWO THINGS TO KNOW BEFORE WRITING YOUR OWN VERSION

Testing decimals for equality. The 2014 code recodes variables by exact comparison (`if progtaxes2_str == 4`). That works in Stata. In R or Python the test silently matches no rows, because the rescaled values come out a hair off (4.0000000002, not 4). The tax outcome is then wrong and every coefficient in the tax models moves, with no error. Round to the nearest integer first. Both scripts do.

The interaction terms. Lines 96–109 of `script_original_stata-2014.do` (lines 46–59 before the 2026 annotations were added) build the interaction variables from (Definition + 1) / 2, a second rescaling of a column already on 0 to 1, but store them under the unscaled names. So every interaction term in Table D1 uses this rescaled Definition, and in two of the six D1 regressions (Y_gov_fix_gap Model 1, Y_prog_tax Model 3) the Definition variable itself is also the rescaled one. The fit is identical either way; only the printed coefficients differ. The scripts reproduce what the article printed. Build the interactions from Definition as it stands in the file and you will get different coefficients and conclude, wrongly, that the table is wrong.

Each of these fails silently: you get plausible numbers, not an error.

10. CITATION AND LICENSE

Cite the article, and this package by the DOI on its record. Released under CC BY 4.0.