

JavaScript Fundamentals

Introductions

- I'm Ryan Morris
- What is your experience with JavaScript?
- Why are you taking the class?

Setup

- Pre-reqs: Node & NPM
- Download github.com/rm-training/webdev
 - Slides are at: `/slides/fundamental-js.pdf`
- Download dependencies

```
npm install
```

- Start the server

```
npm start
```

- Visit `localhost:3000` and bask in the glory!

Our topics

- Language Basics
- Debugging & Tooling
- Scope & Hoisting
- Intro to OO in JS
- Exception handling
- Manipulating Web Pages
- Event Handling
- AJAX Requests
- Testing

Going further (not covered here):

- Deeper on Object Construction & Classes
- Function patterns
- Modules & the IIFE pattern
- Controlling context w/ call, apply & bind
- Tooling (bundling)

The important stuff

- Hoisting
- Coercion
- Scope
- Context
- The Prototype
- The Event Loop
- Being Asynchronous

Developer Tools

I'll do a quick run through

Text Editor or IDE

Let's set up our editor and perhaps a linter

Tooling

- Node
- Linting and Formatting
 - ESLint
 - Prettier

The Web

I'll run through a quick intro to the structure of a page

Introduction to JavaScript

Approaching JavaScript

- JavaScript is not Java
- It can be as loose or strict as you want it
 - not strictly object-oriented
- Easy to learn but hard to master

JavaScript Traits

- Single-threaded
- Environment manages the memory for you
- Dynamically typed (with weak typing)
- Interpreted & single threaded
- Prototype-based inheritance (vs class-based)
- No built-in file access; limited I/O; safe sandbox in the web
- Weird but fun

ECMAScript

- ES3 - 1999
- ES5 - 2009
- ES6 (ES2015)
- ES2016 (ES7)
- ES2017 (ES8)
- ES2018 (ES9)
- ES.Next

Not just for the browser

- [Node](#) is a runtime for JavaScript from the command line
- Libraries (like Node) help make JavaScript a more general purpose language
- File I/O, etc
- Future version of JavaScript have proposals for memory management, etc

Why JavaScript

- It's the language of the web
- ... and server
- ... and desktop

Syntax Basics

- "C" family of languages
- Whitespace doesn't matter
- Blocks are wrapped in curly braces { }
- Statements *should* be terminated by a semicolon

```
let x = 10;  
  
if (x < 5) {  
    x = 5 + 10;  
}
```

Debugging in the console

- Browser's console is a line interpreter (REPL)
- All browsers have converted on the same API
- `console` object is an interface to the browser's "console"
- `debugger` triggers a breakpoint
- Can view variable scope and state

```
console.log('hi!');  
console.warn('Something bad happened');  
console.table(arrayOfData);  
  
debugger; // trigger a breakpoint
```

Exercise: Try it out

- Open your browser's developer tools
- Log something to the console

```
console.log('Hello World');  
  
let name = 'Robot Cat';  
  
console.log('Hello from ' + name);
```

Values & Operators

Primitives

```
'Hello World'; // Strings
42;           // Numbers
true && false; // Boolean
null;         // No value
undefined;    // Not yet defined
Symbol.iterator; // Symbols -- relevant more once we get into objects
```

Variables

- Variables will *reference* values
- Values themselves are actually *immutable*

```
let x = 10;  
let someValue = 'Hello';  
  
someValue = 100;
```

Declaring Variables

- You can declare a set of variables in a series
- Default value is `undefined`
- Typically `camelCase` and first character is lowercase

```
let x = 10;  
let a, b, c = 100;  
  
const y = 5;  
  
console.log(a); // undefined
```

Var, Let and Const

- variables without a value default to `undefined`
- `var` & `let` allow re-assignment, `const` does not
- variables are not "typed" - they can reference any value
- `let` and `const` can't be redeclared, `var` can

```
let x = 10;  
x = 5;  
  
const element = 1;  
  
let x = 12; // Error!  
element = 2; // Error!
```

Also... *for later*

- determines the `scope` & `hoisting` behavior of the variable

Objects

- Objects are structured data
- Properties (the keys) map to values
- Value can be anything
- Arrays, Functions, and pretty much everything else is type of Object

```
let user = {  
  id: 5,  
  username: 'morris',  
}  
  
console.log(user.id); // 5
```

Functions

- Runnable blocks of code
- Have properties, such as `name` and `length`

```
// statement
function add(x, y) {
    return x + y;
}

console.log(add.length); // 2
console.log(add.name); // "add"

// expression
const add = function(x, y) {
    return x + y;
}
```

Variable Scope

- What variables can you see/access from your current location
- Lexical (as in, *not Dynamic*)
- JS has Global, Function and Block

Global Scope

- Any variable declared outside of a function

```
var x = 10;
```

```
y = 12; // not explicitly declared
```

Function Scope

- Scope *Original*
- `var` declares a variable in Function Scope :

```
var x = 10;  
  
function hello() {  
    var y = 20;  
  
    return x + y;  
}  
  
x = hello(); // x is now 30
```

Question: What are the scopes of each variable here?

```
var x = 10;
var y = 11;

function hello(someValue) {
  var y = 20;

  if (x < y) {
    var z = 30;
  }

  return function () {
    var result = x + y + z;
    return result;
  }
}

hello(200);
```

Block scope

- ES6 introduced block-scope with `let` and `const`
- Scoped to any `{ }` block
 - Objects are *Not* blocks

```
let x = 10;

if (x < 0) {
  let y = 11;
}

function hello() {
  let z = 12;
}
```

Question: Will this work?

```
let x = 10;  
if (x < 0) {  
    let y = 11;  
}  
  
function hello() {  
    return x + y;  
}  
  
hello();
```


Hoisting

- Not all variables are created equally
- `var` will be *hoisted* to the top of function *blocks*
- `let` and `const` are not hoisted

Question: What will be logged to the console?

```
function init() {  
  x = 10;  
  
  var x;  
  
  console.log(x); // what will I log?  
}
```

Question: And this time?

```
function init() {  
    console.log(x); // what will I log?  
  
    var x = 10;  
}
```

Function Hoisting

- `function` *statements* are hoisted, too

```
statement(); // valid  
expression(); // error
```

```
function statement() {};  
var expression = function() {};
```

Arrays

- Serialized data
- Indexed from 0
- Have methods & properties, like length

```
let data = [55,12,32];
```

```
data[0]; // 55
```

```
data.length; // 3
```

```
data.pop(); // 32
```

Numbers

- `Number` object
- 64 bit floating point
 - You lose precision with decimals & large numbers
 - this is not specific to JS
- Special numbers: `NaN` & `Infinity`

```
console.log(5 + 5.5); // 10.5
console.log(0.1 + 0.3); // 0.30000000000000004

typeof(NaN); // "number"
NaN == NaN; // false
1 / 0; // Infinity
```

Strings

- `"double"`, `'single'` or ``back-ticks`` all work
- The back-tick enables string interpolation
 - "String Template Literal"
- Strings have methods & properties, like most things in JS

```
let firstString = "Hello";  
  
console.log(firstString + " World");  
console.log(`${firstString} World`);  
  
firstString.length; // 5
```

Comments

- Single-line with `//`
- Multi-line with `/* */`

Exercise: Using Primitives

1. Open the following file: `src/www/js/primitives/primitives.js`
2. Complete the exercise.
3. Run the tests by opening the `index.html` file in your browser.

Operators

| -----|: -----:|

| Arithmetic | + 0 * / % ** |

| Shortcut | += 0= *= /= %/ **= |

| Inc/Dec | x++ x-- --x ++x |

| Bitwise | ~ % | ^ >> << >>> |

| Comparison | > >= < <= |

| Equality | == != === !== |

| Logic | ! && || |

| Object | . [] |

| String | + |

Coercion

- JavaScript is loosely typed
- Converts values on the fly based on the operators at play

```
8 * null; // 0
```

```
null > 0; // false
```

```
null === 0; // false
```

```
null >= 0; // true ???
```

```
[] + []; // ""
```

```
[] - []; // 0
```

```
(+"5"); // 5 <-- it converted it for me
```

```
!!val; // coerces to a boolean
```

Equality in JavaScript

- Compare values with or without *coercion*
- Coercion is a common cause of bugs / confusion
 - What type will JS coerce something to...?

```
// loose
"1" == 1;           // true
[3] == "3";         // true
[3] == 3;           // true

// strict
"1" === 1;          // false
[3] === "3";        // false

// most strict
Object.is(1, "1");  // false, introduced in ES6
```

Truthy & Falsy

Values can be coerced to true or false.

Things that are false:

```
false;  
null;  
undefined;  
""; // The empty string  
0;  
NaN;
```

Everything else is true, including:

```
"0"; // String  
"false"; // String  
[]; // Empty array  
{}; // Empty object  
Infinity; // Yep, it's true
```

Logical and / or

```
if (5 && "hello") {  
    console.log("I'm in!");  
}  
  
if (0 || false) {  
    console.log("I'm in");  
}
```

Logical Short Circuits

These actually return values

```
// && returns first falsy otherwise last value  
console.log(5 && "hello");  
console.log(12 && 0);  
console.log(12 && false && 50);  
  
// || returns first truthy value otherwise last value  
console.log("a" || "b" || "c");
```

Control flow

- `if` , `else if`, `else`
- `switch` statements
- `!` for negation

```
if (x) {  
    // do something  
} else if (!y) {  
    // do something  
} else {  
    // do something  
}
```

Switch statements

- *Should* always break and include a default

```
switch (x) {  
  case 10:  
    console.log('Case 10');  
    break;  
  case 3:  
  case 2:  
    console.log('Case 2 or 3');  
    break;  
  default:  
}
```


Ternaries

```
return y < 200  
    ? "Value Low"  
    : "Value High";
```

Incidentally this is often used to check if a variable is initialized

```
let x = typeof x === "undefined" ? 10 : x;  
let y = y ? y : 0;  
  
// this won't always work as expected  
if (x === undefined) {  
    // if x is undeclared this will error  
}
```

Iterating

- `for`
- `for...in` for object properties
- `for...of` for all `Iterables`
- `while`, `do...while`
- `break`, `continue`

```
const data = [1,2,3,4];  
  
// simple for loop  
for (let i=0; i < data.length; i++) {  
    console.log(data[i]);  
}
```

Loops continued

```
// for..of
for (let value of data) {
  console.log(value);
}

const user = {
  id: 1,
  name: 'Ryan',
};

// for..in to iterate over object properties
for (let propName in user) {
  console.log(user[propName]);
}
```

Array s also have built-in ways to iterate, we'll see those later...

Question: What is the scope of `i`

```
for (var i=0; i < data.length; i++) {  
    console.log(i);  
}
```

Exercise - Control Flow

1. Open the following file: `src/www/js/control/control.js`
2. Complete the exercise.
3. Run the tests by opening the `index.html` file in your browser.

Objects

Most things in JavaScript are an object, or can behave like one

```
let x = 55;  
  
x.toString(); // "55"  
  
12..toString(); // "12"
```

Dynamic properties

- Access through `.` or `[]` accessors
- You can add/remove properties at any time*

```
const box = {  
  color: "red",  
  height: 12,  
};  
  
box.width = 100;  
box["color"] = "blue";  
  
delete box.width;
```

Functions as Properties

- Can store any value on an object, including functions
- Functions be aware of the object they operate on through `this`
- Referred to as `context`

```
const human = {  
  name: 'Ryan',  
  sayHello: function () {  
    console.log(this.name);  
  }  
}
```


Abbreviated Property Definition

ES6+ introduced short-cuts to defining properties in an object (and class)

```
const bark = function() {}  
const name = "Fido";  
  
const dog = {  
  id: 10,  
  name,  
  bark,  
  sit() {  
    console.log('I am sitting');  
  }  
};
```

Object references & mutability

- *Objects* are mutable and are passed by reference
- `===` is true only when the object is the same instance

Question: What happens to `box` here?

```
const box = {sides: 4};  
  
function mutator(obj) {  
  obj.mutated = true;  
}  
  
mutator(box);  
  
console.log(box); // ?
```

Question: So is this true or false?

```
const box = {sides: 4};  
  
function mutator(object) {  
    console.log(object === box); // ?  
}  
  
mutator(box);
```

Object Property Descriptors

- `Object.defineProperty` to configure additional property behaviors

```
let obj = {};  
Object.defineProperty(obj, "someName",  
  {  
    configurable: false,  
    enumerable: false,  
    writable: false,  
    // getters & setters!  
    get: function() {}  
  }  
);
```

Object Reflection

- `typeof {}`
- Iterate with `for...in`
 - Warning: unspecified order of properties

```
for (let propName in cat) {  
  console.log(cat[propName]);  
}
```

Object Ownership

- Objects can have "own" properties or *inherited*
- Check property ownership with `obj.hasOwnProperty(propName)`

```
let cat = {  
  legs: 4;  
};  
  
cat.toString(); // "[object Object]"  
  
// so... does it have it?  
cat.hasOwnProperty('toString'); // ?
```

Exercise - Copy objects

1. Open the following file: `src/www/js/copy/copy.js`
2. Complete the exercise.
3. Run the tests by opening the `index.html` file in your browser.

Hints:

- `for (let prop in someobj) { /* ... */ }`
- `someobj.hasOwnProperty(prop)`

Cloning and merging objects

- `Object.assign`
- The spread `...` operator

```
const originalObject = {id: 5};

// clone it!
const copiedObject = Object.assign({}, originalObject);

// or another way...
const anotherCopy = {
  ...originalObject
};
```


Object Methods

- Get information out of your object
- Own, Enumerable, etc...

```
Object.keys(obj);  
Object.values(obj);  
Object.entries(obj);  
  
// an array of properties that the object "owns"  
Object.getOwnPropertyNames(obj);
```

Built-in Objects

- String
- Number
- Math
- Date
- Array
- RegExp

Numbers

Constants:

- `Number.MAX_VALUE`
- `Number.NaN`
- etc...

Generics:

- `Number.isInteger(n);`
- `Number.parseInt(n);`
- etc...

Instance methods:

- `num.toString();`
- `num.toFixed();`
- etc...

Strings

- `str.length`
- `str.charAt(i)`
- `str.concat()`
- `str.indexOf(needle)`
- `str.slice(iStart, iEnd)`
- `str.substr(iStart, length)`
- `str.replace(regex|substr, newSubStr|function)`
- `str.toLowerCase()`
- `str.trim()`

Math object

Constants:

- `Math.E`
- `Math.PI`
- etc...

Generics:

- `Math.abs(n)`
- `Math.pow(n, e)`
- etc..

The Date Object

- Represent a point in time
 - Must be *constructed*
- Months start at `0`, days start at `1`

```
let d = new Date(); // today
d = new Date("Wed, 20 Jan 2020 13:30:00 EST");

d = Date.now();
d = Date.UTC();

d.getTime(); // unix timestamp
d.getMonth();
d.getHours();

d.setYear(1990);
```

Arrays

Sequential data, order is maintained

Instance methods

- `arr.shift`, `unshift`, `push`, `pop`
- `concat`, `slice`, `splice`
- `indexOf`, `find`
- `sort`, `reverse`
- `every`, `some`
- `map`, `filter`, `reduce`

Generics

- `Array.isArray(a)`
- etc...

Functions

Functions in JavaScript

- Statement
- Expression (anonymous)
- Arrow Functions
 - Arrow functions are special! We'll cover that more in regards to context

```
function statement(a, b) {  
    return a + b;  
}  
  
typeof statement; // function  
  
const expression = function(a, b) {  
    return a + b;  
}  
  
const arrow = () => a + b;
```

Function Arguments

- All arguments are available in `arguments` property
- Missing values will be `undefined`
- No function overloading in JS

```
function logAll(a) {  
    console.log(arguments);  
  
    // better option is to use "rest" operator...  
    const args = Array.prototype.slice.call(arguments);  
}  
  
logAll(1, 3, "hi");
```

Function Defaults

- *finally*
- These can reference functions, previous arguments

```
function tryDefaults(a=1, b=10, c=a+b) {  
    return a + b + c;  
}
```

```
tryDefaults(undefined, 12);
```

Higher-order Functions

Functions are a values that we can pass around.

Functions that take other functions, or return new functions, are "higher order" functions.

```
let a = [1, 2, 3];  
a.forEach(function(val, index, array) {  
    // Do something...  
});
```

Array Testing

Test if a function returns true on all elements:

```
let a = [1, 2, 3];  
a.every(function(val) {  
    return val > 0;  
});
```

Test if a function returns true at least once:

```
a.some(function(val) {  
    return val > 2;  
});
```

Filtering an array

```
let numbers = [10, 7, 23, 42, 95];

let even = numbers.filter(function(n) {
  return n % 2 === 0;
});

even; // [10, 42]
even.length; // 2
numbers.length; // 5
```

Mapping over an array

```
let strings = [  
    "Mon, 14 Aug 2006 02:34:56 GMT",  
    "Thu, 05 Jul 2018 22:09:06 GMT"  
];  
  
let dates = strings.map(function(s) {  
    return new Date(s);  
});  
  
dates; // [Date, Date]
```

Reducing an array

```
let a = [1, 2, 3];

// Sum numbers in `a`.
let sum = a.reduce(function(acc, elm) {
    // 1. `acc` is the accumulator
    // 2. `elm` is the current element
    // 3. You must return a new accumulator return acc + elm;
}, 0);

sum; // 6
```


Exercise: Arrays & Functional Programming

1. Open the following file:

```
src/www/js/array/array.js
```

2. Complete the exercise.

3. Run the tests by opening the `index.html` file in your browser.

Hint: Use <https://developer.mozilla.org/> for documentation.

Function Patterns

Anonymous Functions

```
let anon = function() {};
```

- A function expression without a name
- Difficult to test in isolation
- Discourages re-use
- Can still be given a name but it's not available outside the function

```
let recursor = function recursive() {  
    recursive();  
};
```

Functions as Callbacks

- When a function is provided as an argument as something to be invoked inline, or under specific circumstances (like an event)

```
function runCallback(callback) {  
  // does things  
  return callback();  
}
```

This is an example of a *higher-order function*.

Functions as Timers

Built-in functions that can establish delays:

```
let timer = setTimeout(() => {  
  console.log('I was delayed');  
}), 500); // delay in ms  
  
// cancel a timer  
clearTimeout(timer);
```

...and intervals:

```
let interval = setInterval(() => console.log('In an interval')), 1000);  
  
// cancel an interval  
clearInterval(interval);
```

Closures

- Extremely common in JavaScript
- When the *outer scope* of a function *closes over* the *inner scope*

```
let makeCounter = function(startingValue) {  
    let n = startingValue;  
  
    return function() {  
        return n += 1;  
    };  
};
```

```
let counter = makeCounter(0); // <-- closure is created when invoked  
counter(); // 1  
counter(); // 2
```

Closures for Privacy & State

```
const Foo = function() {  
  let privateVar = 42;  
  
  return {  
    getPrivateVar: function() {  
      return privateVar;  
    },  
    setPrivateVar: function(n) {  
      if (n) {  
        privateVar = n;  
      }  
    }  
  };  
};  
  
let x = Foo();  
x.getPrivateVar(); // 42
```

Question: How might you avoid initializing this closure?

```
const Foo = function() {  
    // ...  
};
```

```
let x = Foo(); // <--- can we change this or avoid it?  
x.getPrivateVar();
```


The IIFE

Immediately Invoked Function Expression

```
const x = (function() {  
    // ...  
})();
```

Commonly seen for:

- Initializing an old-world module
- Initializing a stateful singleton
- Protecting / Clean Scope

Exercise: Sharing Scope

1. Open the following file:

```
src/www/js/closure/closure.js
```

2. Complete the exercise.

3. Run the tests by opening the `index.html` file in your browser.

Closure Gotcha

Question: What will this output and in what order?

```
for (var i=0; i<3; i++) {  
    setTimeout(function(){  
        console.log(i);  
    }, 1000 * i);  
}  
  
console.log("Howdy!");
```

Scope & Context

Adding Context to a Scope

- We already discussed **scope**
 - Visibility of variables
 - Lexical (you can read it and determine scope)
- There is also **context**
 - Based on location a function was invoked
 - Dynamic, determined at runtime
 - Accessible via `this`

Calling functions through objects

```
let apple = {  
  name: "Apple",  
  color: "red"  
};  
let orange = {  
  name: "Orange",  
  color: "orange"  
};  
  
let logColor = function() {  
  console.log(this.color); // <!-- _this_ is the context...  
};  
  
apple.logColor = logColor;  
orange.logColor = logColor;  
  
apple.logColor(); // "red"  
orange.logColor(); // "orange"
```

Context and the `this` Keyword

- `this` is a keyword
- References the "object of invocation"
- Allows a method to reference an object instance
- Single methods can service many objects
- Central to prototypical inheritance in JS

Setting the `this` variable

- Bound at runtime when a function is invoked
- Arrow functions use their parent function's context
- Can be set manually with `call`, `apply` and `bind`

OO in JS (Intro only)

Creating Objects

- The object literal
- `Object.create()`
- ~~Constructors~~
- Class Keyword

Prototypal Delegation

`Object.create()` will create a new object with a prototypal link to another object.

```
const animal = {  
  legs: 0,  
  fur: true,  
  walk() {  
    console.log('I am walking');  
  },  
};  
  
const dog = Object.create(animal);  
dog.legs = 4;  
  
const mechaDog = Object.create(dog);  
mechaDog.fur = false;
```

Constructor Functions and the `new` Operator

Constructor functions, which utilize the `new` keyword, can be used to create object instances that are linked to the constructor's `prototype`

```
function Animal(legs = 0, fur = false) {  
  this.legs = legs;  
  this.fur = fur;  
};  
  
Animal.prototype.walk = function() {  
  console.log('I am walking');  
};  
  
const dog = new Animal(4, true);
```

Prototype Chain

- Simulates multiple inheritance
- Can't have have more than one "parent" object

```
function Dog() {  
    Animal.call(this, 4, true);  
}  
  
Dog.prototype = Object.create(Animal.prototype);
```

Exercise: Constructor Functions

1. Open the following file: `src/www/js/constructors/constructors.js`
2. Complete the exercise.
3. Run the tests by opening the `index.html` file in your browser.

The Class Keyword

Introduced in ES6 as more concise abstraction for creating objects that delegate to one another.

```
class Animal {  
  constructor(legs = 0, fur = false) {  
    this.legs = legs;  
    this.fur = fur;  
  }  
  
  walk() {  
    console.log('I am walking');  
  }  
};  
  
const dog = new Animal(4, true);
```

Extending Classes

```
class Dog extends Animal {  
    constructor(color) {  
        this.color = color;  
        super(4, true);  
    }  
};  
  
const instance = new Dog();
```


More on class

- Getters/Setters
- Statics
- Super() calls

Exercise: Class Upgrade

1. Re-open the following file: `src/www/js/constructors/constructors.js`
2. Convert your Constructor Function to use the Class keyword instead
3. All tests should continue to pass

Errors in JS

Exception Basics

- Errors propagate as exceptions
- try, catch, throw and finally
- only catch synchronous, run-time errors

Throwing Exceptions

```
if (somethingGoesWrong) {  
    throw "This went wrong";  
}  
  
if (somethingElseGoesWrong) {  
    throw new Error("Something ent wrong");  
}
```

Catching Errors

```
try {  
    // try something...  
    return;  
} catch (e) {  
    if (e instanceof MyCustomError) {  
        throw e; // you can re-throw  
    }  
} finally {  
    // runs even if the try/catch returns!  
    // clean up  
}
```

Built-in errors

- Error - generic
- ReferenceError - variable use
- SyntaxError - error parsing
- TypeError - variable not expected type
- etc...

Custom Errors

Just extend the error class

```
class MyCustomError extends Error {  
    constructor(message) {  
        super(message);  
        this.name = 'MyCustomError';  
    }  
}
```


Exercise: Exceptions

optional

1. Open the following file: `src/www/js/exceptions/exceptions.js`
2. Complete the exercise.
3. Run the tests by opening the `index.html` file in your browser.

JavaScript and the Browser

- HTML for the content & structure
- CSS for presentation
- JavaScript for behavior & business logic

HTML Refresher

- Hyper Text Markup Language
- Plain text
- Very error tolerant
- Tree of nodes

```
<html>
  <head>
    <title>Hello World!</title>
  </head>
  <body>
    <h1 id="title">Welcome</h1>
    <p>
      Awesome <span class="loud">Site!</span>
    </p>
  </body>
</html>
```

HTML Elements

```
<div key="value" key2="value2">  
  Text content of element  
</div>
```

```
<!-- self-closing -->  
<input name="username">
```

The HTML Tree

Let's look at some pages if needed

CSS

- Cascading Style Sheet
- Rule-based language for describing presentation
- Separate file or inline
- Can handle quite a lot these days:
 - Animation
 - Grids
 - Spatial positioning
 - Variables

What does CSS look like?

```
#container {  
    margin: 5px;  
}  
  
p {  
    background-color: white;  
    color: blue;  
    padding: 5px;  
}  
  
.spoiler {  
    display: none;  
}  
  
p.spoiler {  
    display: block;  
    font-weight: bold;  
}
```

CSS Selectors

- Help to specify elements in our page
- Which is key to page manipulation
- Such as:
 - id
 - class
 - element name
 - parent/child relationship
 - combination of the above

How the browser loads the page

- Top to bottom (HTML, JS)
- Loads resources as it comes across them
- Some resources (ie: scripts) can be blocking

```
<script src="somefilename.js"></script>
```

```
<script>  
let x = "Hey, I'm JavaScript!";  
console.log(x);  
</script>
```

```
<button onclick="console.log(x);" >
```

The DOM

- What most people hate(d) in the browser
- The Browser's API for the document
- Represents elements as a tree of nodes
- Live data structure

```
const thingyEl = document.getElementById('thingy');
```

Element Nodes

The HTML:

```
<p id="thingy" class="hi">  
  My <span>text</span>  
</p>
```

Maps *loose*ly to:

```
let node = {  
  tagName: "P",  
  childNodes: NodeList,  
  className: "hi",  
  innerHTML: "My <span>text</span>",  
  id: "thingy",  
  // ...  
};
```

Typically working with the DOM will involve

- Select an element to gain access
- Traverse as needed
- Create/Modify/Add behavior

There are performance considerations when it comes to modifying the DOM.

Selecting

```
<div id="m-id" class="fancy"></div>  
<div class="boring"></div>
```

```
let el = document.getElementById('my-id');  
  
// first matching element  
el = document.querySelector('#my-id');  
el = document.querySelector('div.fancy');  
  
// all matching elements  
el.querySelectorAll('div');
```

There is also...

- `getElementsByTagName`
- `getElementsByClassName`

Traversing

Moving between nodes via their relationships

```
<div class="the-parent">  
  <div class="the-child">  
    <div>TBD</div>  
  </div>  
</div>
```

```
let el = document.querySelector('.the-child');  
  
el.children[0].innerHTML = '<h1>Hi!</h1>';  
el.parentNode;
```

Traversal Properties

- `parentElement`
- `children`
- `firstElementChild`
- `lastElementChild`
- `previousElementSibling`
- `nextElementSibling`

There are also things like `nextSibling` and `childNodes` ; these are older accessors and may not always give you an `Element` object back.

Node Types

`element.nodeType`

- 1: Element
- 3: Text Node
- 8: Comment Node
- 9: Document Node

Creating & Appending New Elements

- createElement
- createTextNode

```
const newEl = document.createElement('h1');  
const text = document.createTextNode("Hello");
```

Insertion

Then you'll put it into the DOM tree:

- `el.appendChild(newEl)`
- `el.insertBefore(newChild, existingChild)`
- `el.replaceChild(newEl, existingEl)`
- `el.removeChild(existingEl)`

```
const newEl = document.createElement('h1');  
const text = document.createTextNode("Hello");  
  
newEl.appendChild(text);  
  
document.getElementById('some-root').appendChild(newEl);
```

Modifying Elements

You can insert HTML strings, which the browser will parse.

```
el.innerHTML = '<h1>Hello World</h1>';  
  
// can do the same with text nodes  
el.textContent = 'Hello';
```

Attributes

```
<div class="user-info" data-user-id="5"></div>
```

```
el.getAttribute(name);  
el.setAttribute(name, value);  
el.hasAttribute(name);  
el.removeAttribute(name);
```

DataSet API

```
<div class="user-info" data-user-id="5"></div>
```

```
el.dataset.userId;
```

classList API

Vanilla JS + the DOM is converging on common patterns.

```
el.classList.add(name);  
el.classList.remove(name);  
el.classList.toggle(name);  
el.classList.contains(name);
```

Exercise: DOM Manipulation

1. Open the following files in your text editor:

```
src/www/js/flags/flags.js  
src/www/js/flags/index.html (read only!)
```

2. Open the `index.html` file in your web browser.

3. Complete the exercise.

Events

The Event Loop

- Single-threaded, asynchronous event model
- Events fire and trigger registered handler functions
 - click, page ready, focus, submit, scroll, etc...
- Browser implements an event loop to process handlers
 - one function at a time; it is blocking

Demo a Runtime: [/js/runtime/](#)

Handling Events

- Select an element
- Define a handler function
- Register the handler on the element

```
const myFunction = function() {};  
  
const el = document.getElementById('container');  
  
el.addEventListener('click', myFunction);
```

Handler Functions

- Always passed an "event object" by the browser
- Context is the element where the handler is registered
- You can de-register them

```
const myFunction = function(eventObject) {  
  console.log(this); // element where I am registered  
  
  eventObject.target; // same  
  eventObject.currentTarget; // element that is currently handling the event...  
};
```

Event Propagation

- Events move throughout the entire DOM tree (from the source of the event to the top level dom node)
- Trickles (first) then Bubbles (second)
- You can control it!

```
eventObject.stopPropagation();  
eventObject.preventDefault();  
eventObject.stopImmediatePropagation();
```

Returning false from a handler will also stop default behavior.

Event Delegation

Using `event.target` and `event.currentTarget` we can have a handler function that manages all the events of a set of child elements.

Example: </demo/events.html>

Event Warnings

- Don't block the thread
- Break up long running functions
 - `setTimeout(continueFn, 0);`
- Debounce event handlers

Context in Callbacks

- When you pass your function to be called elsewhere
 - You can't rely on the **context**!
- Applies to *all callbacks*, not just event handlers

Question: What is wrong here?

```
const user = {
  id: 1,
  initHandlers() {
    const el = document.querySelector('.user');
    el.addEventListener('click', function() {
      console.log(`User #${this.id} was clicked`);
    });
  }
}

user.initHandlers();
```


Context in Callbacks (3 solutions)

1. use an arrow function
2. Maintain via closure, `const that = this;`
3. Lock in the context, `call()` or `bind()`

```
const user = {  
  id: 1,  
  initHandlers() {  
    const el = document.querySelector('.user');  
  
    el.addEventListener('click', () => {  
      console.log(`User #${this.id} was clicked`);  
    });  
  }  
}  
  
user.initHandlers();
```

A full event handler example

```
node.addEventListener("click", function(event) {  
  // `this` === Node the handler was registered on.  
  console.log(this);  
  
  // `event.target` === Node that triggered the event.  
  console.log(event.target);  
  
  // Add a CSS class:  
  event.target.classList.add("was-clicked");  
  
  // You can stop default browser behavior:  
  event.preventDefault();  
});
```

Exercise: Simple User Interaction

1. Open the following files in your text editor:

```
src/www/js/events/events.js  
src/www/js/events/index.html (read only!)
```

2. Open the index.html file in your web browser.

3. Complete the exercise.

Loading data / AJAX

Ajax Basics

- Asynchronous JavaScript and XML
 - It is non-blocking!
- API for making HTTP requests
- Originally handled via `XmlHttpRequest` object
- Can be in any format, usually `json`, `html` or `xml`
- `same-origin` policy / CORS

JSON

- String representation of a JavaScript Object
- Not exact -- functions are not represented

```
let object = {  
  id: 10,  
  name: "Ryan",  
  awards: [1,2,3], // arrays are OK  
  sayName: function() { // functions will be ignored  
    console.log(this.name);  
  }  
}  
JSON.stringify(object); // '{"id":10,"name":"Ryan","awards":[1,2,3]}'  
JSON.parse(string);
```

XHR Object

- The old way of doing AJAX
- Inconsistent and lots of boilerplate

```
let req = new XMLHttpRequest();

req.addEventListener("load", function(e) {
    if (req.status == 200) {
        console.log(req.responseText);
    }
});

req.open("GET", "/example/foo.json");
req.send(null); // this is where you could send a form body
```

Exercise: Making Ajax Requests

XHR or Fetch (skip ahead to learn more)?

1. Open the following files:

```
src/www/js/artists/artists.js  
src/www/js/artists/index.html (read only!)
```

2. Open <http://localhost:3000/js/artists/>

3. Complete the exercise.

Fetch API

- New in modern browsers
- Uses **Promises**
- Easily handles file uploads
- No IE (but Edge is all good)

```
fetch(url, {
  method: "POST",
  credentials: "same-origin",
  headers: {"Content-Type": "application/json; charset=utf-8"},
  body: JSON.stringify(data),
})
.then(function(response) {
  if (response.ok) {
    return response.json();
  }
  throw `expected ~ 200 but got ${response.status}`;
})
.then(console.log);
```

Promises

- Standardized construct to represent some future data
- Composable
- Three states: Pending, Fulfilled, Rejected
- Flattens asynchronous code that would otherwise be deeply nested

```
// this is a rough sketch of 3 ajax requests, each dependent on the previous
req.open("GET", "/users/1.json");
req.addEventListener('load', () => {
  req2.open("GET", "/users/1/posts.json");
  req2.addEventListener('load', () => {
    req3.open("GET", "/posts/35.json");
    req3.addEventListener('load', () => {
      // got all our data!
    });
  });
});
```

Becomes more like:

```
fetch('/users/1.json')
  .then((d) => {
    return fetch('/users/1/posts.json');
  })
  .then((d) => {
    return fetch('/posts/35.json');
  });
```

Promise Creator

- Constructs the Promise
- Decides when it is considered "Resolved" and "Rejected"
- Returns the data or error respectively

```
const delayed = function() {  
  return new Promise(function(resolve, reject) {  
    setTimeout(function() {  
      if (true) {  
        resolve(100);  
      } else {  
        reject(0);  
      }  
    }, 500);  
  });  
};
```

then there is the promise consumer...

Promise Consumer

- `then()`, `catch()`, `finally()` (soon)
- You can chain these
- You can keep using the promise

```
const resolveHandler = (data) => {};  
const rejectionHandler = (error) => {};  
  
delayed.then(resolveHandler, rejectionHandler);  
delayed.then(resolvedHandler);  
  
someOtherThingThatWorksPromises(delayed);
```

The Fetch Function

Notice how the response provides the json data as another Promise

```
fetch("/api/artists", {credentials: "same-origin"})
  .then(function(response) {
    return response.json(); // <-- take note!
  })
  .then(function(data) {
    updateUI(data);
  })
  .catch(function(error) {
    console.log("Ug, fetch failed", error);
  });
```

Exercise: Using the Fetch API

1. Start your server if it isn't running
2. Open `src/www/js/fetch/fetch.js`
3. Fill in the missing pieces
4. To test and debug, open localhost:3000/js/fetch/

Storage APIs

- Allows you to store key/value pairs
- Two levels of persistence and sharing
- Very simple interface
- Keys and values must be strings

Session Storage

- Lifetime: same as the containing window/tab
- Sharing: Only code in the same window/tab
- 5MB user-changeable limit (10MB in IE)
- Basic API:

```
sessionStorage.setItem("key", "value");  
let item = sessionStorage.getItem("key");  
sessionStorage.removeItem("key");
```

Local Storage

- Lifetime: unlimited
- Sharing: Same domain
- 5MB user-changeable limit (10MB in IE)
- Basic API:

```
localStorage.setItem("key", "value");  
let item = localStorage.getItem("key");  
localStorage.removeItem("key");
```

The Storage Object

Properties and methods:

- `length`: The number of items in the store.
- `key(n)`: Returns the name of the key in slot `n`.
- `clear()`: Remove all items in the storage object.
- `getItem(key)`, `setItem(key, value)`, `removeItem(key)`

Testing JavaScript

- We'll use [Jasmine](#)
- Spec-based testing
- Expectations instead of assertions

Example:

```
describe("ES2015 String Methods", function() {  
  describe("Prototype Methods", function() {  
    it("has a find method", function() {  
      expect("foo".find).toBeDefined();  
    });  
  });  
});
```

Basic Expectation Matchers

- `toBe(x)`: Compares with `x` using `===`.
- `toMatch(/hello/)`: Tests against regular expressions or strings.
- `toBeDefined()`: Confirms expectation is not undefined.
- `toBeUndefined()`: Opposite of `toBeDefined()`.
- `toBeNull()`: Confirms expectation is null.
- `toBeTruthy()`: Should be true true when cast to a Boolean.
- `toBeFalsy()`: Should be false when cast to a Boolean.

Numeric Expectation Matchers

- `toBeLessThan(n)`: Should be less than `n`.
- `toBeGreaterThan(n)`: Should be greater than `n`.
- `toBeCloseTo(e, p)`: Difference within `p` places of precision.

Value Matchers

- `toEqual(x)`: Can test object and array equality.
- `toContain(x)`: Expect an array to contain x as an element.

Exercise: Writing a Test with Jasmine

1. Open `src/www/js/jasmine/adder.spec.js`
2. Read the code then do exercise 1 (we'll do exercise 2 later)
3. To test and debug, open
`src/www/js/jasmine/index.html`

Life Cycle Callbacks

Each of the following functions takes a callback as an argument:

- `beforeEach`: Before each it is executed.
- `beforeAll`: Once before any it is executed.
- `afterEach`: After each it is executed.
- `afterAll`: After all it specs are executed.

- Spying

```
let foo;  
  
beforeEach(function() {  
  foo = {  
    plusOne: function(n) {  
      return n + 1;  
    },  
  };  
});
```

Spying (Call Counting)

```
it("should be called", function() {  
    spyOn(foo, 'plusOne');  
  
    let x = foo.plusOne(42);  
  
    expect(foo.plusOne).toHaveBeenCalled();  
    expect(foo.plusOne).toHaveBeenCalledTimes(1);  
    expect(foo.plusOne).toHaveBeenCalledWith(42);  
  
    expect(x).toBeUndefined();  
});
```

Spying and Calling Through

```
it("should call through and execute", function() {  
    spyOn(foo, 'plusOne').and.callThrough();  
  
    let x = foo.plusOne(42);  
  
    expect(foo.plusOne).toHaveBeenCalled();  
    expect(x).toBe(43);  
});
```

Spying and Calling a Fake

```
it("should call a fake implementation", function() {  
    spyOn(foo, 'plusOne').and.callFake(n => n + 2);  
  
    let x = foo.plusOne(42);  
  
    expect(foo.plusOne).toHaveBeenCalled();  
    expect(x).toBe(44);  
});
```

Exercise: Using Jasmine Spies

1. Open `src/www/js/jasmine/adder.spec.js`
2. Read the code then do exercise 2
3. To test and debug, open
`src/www/js/jasmine/index.html`

Testing Time-Based Logic (Setup)

```
let timedFunction;

beforeEach(function() {
    timedFunction = jasmine.createSpy("timedFunction");
    jasmine.clock().install();
});

afterEach(function() {
    jasmine.clock().uninstall();
});
```


Time-based Logic (setTimeout)

```
it("function that uses setTimeout", function() {  
    inFiveSeconds(timedFunction);  
  
    // The callback shouldn't have been called yet:  
    expect(timedFunction).not.toHaveBeenCalled();  
  
    // Move the clock forward and trigger timeout:  
    jasmine.clock().tick(5001);  
  
    // Now it's been called:  
    expect(timedFunction).toHaveBeenCalled();  
});
```

Time-based Logic (setInterval)

```
it("function that uses setInterval", function() {  
    everyFiveSeconds(timedFunction);  
  
    // The callback shouldn't have been called yet:  
    expect(timedFunction).not.toHaveBeenCalled();  
  
    // Move the clock forward a bunch of times:  
    for (let i=0; i<10; ++i) {  
        jasmine.clock().tick(5001);  
    }  
  
    // It should have been called 10 times:  
    expect(timedFunction.calls.count()).toEqual(10);  
});
```

Testing Asynchronous Functions

```
describe("asynchronous function testing", function() {  
  it("uses an asynchronous function", function(done) {  
    // `setTimeout` returns immediately,  
    // so this test does too!  
    setTimeout(function() {  
      expect(done instanceof Function).toBeTruthy();  
      done(); // tell Jasmine we were called.  
    }, 1000);  
  });  
});
```

Exercise: Asynchronous Testing

1. Open `src/www/js/jasmine/delayed.spec.js`
2. Read the code then do exercise 3
3. To test and debug, open
`src/www/js/jasmine/index.html`

Conclusion

Get more

- [You Don't Know JS](#)