

OS Open Source / JDK 9 master

November 13, 2016, 1:10 PM Version 1.0

Overview Issues Measures Code Activity

14 / 223,231 issues

Filters

Clear All Filters

Display Mode

Issues Effort

Type

Bug 6.7k

Vulnerability 11k

Code Smell 205k

Severity

Blocker 2.1k

Critical 43k

Major 178k

Resolution

Unresolved 223k

Fixed 412

jdk / src/demo/share/applets/ArcTest/ArcTest.java

1 duplicated blocks of code must be removed. \*\*\*

Code Smell Major Open Not assigned 20min effort Comment

2 years ago pitfall

Extract the assignment out of this expression. \*\*\*

Bug Major Open Not assigned 5min effort Comment

2 years ago L63 cwe, misra

Remove this call to "exit" or ensure it is really required. \*\*\*

Code Smell Blocker Open Not assigned 30min effort Comment

2 years ago L85 cwe, suspicious

"font" is the name of a field in "Component". \*\*\*

Code Smell Blocker Open Not assigned 5min effort Comment

2 years ago L117 confusing

Extract the assignment out of this expression. \*\*\*

Bug Major Open Not assigned 5min effort Comment

2 years ago L174 cwe, misra

Extract the assignment out of this expression. \*\*\*

Bug Major Open Not assigned 5min effort Comment

2 years ago L175 cwe, misra

Methods should not be empty

Code Smell Critical suspicious Available Since August 30, 2013 Constant/issue: 5min squid:S1186

There are several reasons for a method not to have a method body:

- It is an unintentional omission, and should be fixed to prevent an unexpected behavior in production.
- It is not yet, or never will be, supported. In this case an `UnsupportedOperationException` should be thrown.
- The method is an intentionally-blank override. In this case a nested comment should explain the reason for the blank override.

Noncompliant Code Example

```
public void doSomething() {  
}  
  
public void doSomethingElse() {  
}
```

Compliant Solution

```
@Override  
public void doSomething() {  
    // Do nothing because of X and Y.  
}  
  
@Override  
public void doSomethingElse() {  
    throw new UnsupportedOperationException();  
}
```

Exceptions

Default (no-argument) constructors are ignored when there are other constructors in the class, as are empty methods in abstract classes.

```
public abstract class Animal {  
    void speak() { // default implementation ignored  
    }  
}
```

1 de 2

20/03/2018 22:03

Filters 

Clear All Filters

Display Mode

Issues

Effort

▼ Type

- Bug 6.7k
- Vulnerability 11k
- Code Smell 205k

▼ Severity

Clear

Blocker	2.1k	Minor	122k
Critical	43k	Info	3.2k
Major	178k		

▼ Resolution

Unresolved	223k	Fixed	412
------------	------	-------	-----

Methods should not be empty

Code Smell

Critical

suspicious

Available Since August 30, 2013

Constant/issue: 5min

squid:S1186

There are several reasons for a method not to have a method body:

- It is an unintentional omission, and should be fixed to prevent an unexpected behavior in production.
- It is not yet, or never will be, supported. In this case an `UnsupportedOperationException` should be thrown.
- The method is an intentionally-blank override. In this case a nested comment should explain the reason for the blank override.

### Noncompliant Code Example

```
public void doSomething() {  
}  
  
public void doSomethingElse() {  
}
```

### Compliant Solution

```
@Override  
public void doSomething() {  
    // Do nothing because of X and Y.  
}  
  
@Override  
public void doSomethingElse() {  
    throw new UnsupportedOperationException();  
}
```

### Exceptions

Default (no-argument) constructors are ignored when there are other constructors in the class, as are empty methods in abstract classes.

```
public abstract class Animal {  
    void speak() { // default implementation ignored  
    }  
}
```