

صالح احمد الجبر

project stm32 - salh jbr.ioc - Pinout & Configuration

GENERATE CODE

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

Pinout view

System view

project stm32 - salh jbr.ioc - Pinout & Configuration

Clock Configuration

P

▼ Software Packs

▼ Pinout



I2C2 Mode and Configuration

Mode

I2C

I2C



project stm32 - salh jbr.ioc - Pinout & Configuration

Clock Configuration

P

▼ Software Packs

▼ Pinout

TIM3 Mode and Configuration

Mode

Slave Mode

Trigger Source

☒ Internal Clock

Channel1

Channel2

Channel3

Channel4

Combined Channels

Configuration

Reset Configuration

✔ NVIC Settings

✔ DMA Settings

✔ Parameter Settings

✔ User Constants

NVIC Interrupt Table	Enabled	Preemption Priority	
TIM3 global interrupt	☒	0	0

✔ User Constants	✔ NVIC Settings	✔ DMA Settings
✔ Parameter Settings		

onfigure the below parameters :





Counter Settings	
Prescaler (PSC - 16 bits value)	7999
Counter Mode	Up
Counter Period (AutoReload Regis..	499
Internal Clock Division (CKD)	No Division
auto-reload preload	Disable