

Reshaping Data

IS381 - Statistics and Probability with R

Jason Bryer, Ph.D.

September 22, 2025

One Minute Paper Results


What was the most important thing you learned during this class?

tidyverse
install
studio
latex

What important question remains unanswered for you?

data

Workflow



Source: Wickham & Grolemund, 2017

Tidy Data

“**TIDY DATA** is a standard way of mapping the meaning of a dataset to its structure.”

—HADLEY WICKHAM

In tidy data:

- each variable forms a column
- each observation forms a row
- each cell is a single measurement

each column a variable

id	name	color
1	floof	gray
2	max	black
3	cat	orange
4	donut	gray
5	merlin	black
6	panda	calico

each row an observation


Wickham, H. (2014). Tidy Data. Journal of Statistical Software 59 (10). DOI: 10.18637/jss.v059.i10

Types of Data

- Numerical (quantitative)
 - Continuous
 - Discrete
- Categorical (qualitative)
 - Regular categorical
 - Ordinal



Data Types in R



Data Types / Descriptives / Visualizations

Data Type	Descriptive Stats	Visualization
Continuous	mean, median, mode, standard deviation, IQR	histogram, density, box plot
Discrete	contingency table, proportional table, median	bar plot
Categorical	contingency table, proportional table	bar plot
Ordinal	contingency table, proportional table, median	bar plot
Two quantitative	correlation	scatter plot
Two qualitative	contingency table, chi-squared	mosaic plot, bar plot
Quantitative & Qualitative	grouped summaries, ANOVA, t-test	box plot

Statistics

When describing a quantitative variable we are often interested in two things:

1. A measure of center
2. A measure of spread

The most common measures we will use in this class is the mean and median.

$$\bar{x} = \frac{\Sigma(x_i)}{n}$$

$$S^2 = \frac{\Sigma(x_i - \bar{x})^2}{N}$$

Note that in the numerator for the variance calculation we square the differences (also known as deviations). Squaring terms is common practice in statistics that serves two purposes:

1. It makes all the values positive.
2. It weighs observations that are further from the center more.

Variance

Population Variance:


$$s^2 = \frac{\sum (x_i - \bar{x})^2}{N}$$

Consider a dataset with five values (black points in the figure). For the largest value, the deviance is represented by the blue line ($x_i - \bar{x}$).

See also:

<https://shiny.rit.albany.edu/stat/visualizess/>

<https://github.com/jbryer/VisualStats/>




Variance (cont.)

Population Variance:

$$S^2 = \frac{\sum (x_i - \bar{x})^2}{N}$$

In the numerator, we square each of these deviances. We can conceptualize this as a square. Here, we add the deviance in the y direction.




Variance (cont.)

Population Variance:

$$S^2 = \frac{\sum (x_i - \bar{x})^2}{N}$$

We end up with a square.




Variance (cont.)

Population Variance:

$$S^2 = \frac{\sum (x_i - \bar{x})^2}{N}$$

We can plot the squared deviance for all the data points. That is, each component in the numerator is the area of each of these squares.




Variance (cont.)

Population Variance:

$$s^2 = \frac{\sum (x_i - \bar{x})^2}{N}$$

The variance is therefore the average of the area of all these squares, here represented by the orange square.



Population versus Sample Variance


Typically we want the sample variance. The difference is we divide by $n - 1$ to calculate the sample variance. This results in a slightly larger area (variance) than if we divide by n .

Population Variance (yellow):

$$S^2 = \frac{\sum (x_i - \bar{x})^2}{N}$$

Sample Variance (green):

$$s^2 = \frac{\sum (x_i - \bar{x})^2}{n - 1}$$



Robust Statistics

Consider the following data randomly selected from the normal distribution:

```
set.seed(41)
x <- rnorm(30, mean = 100, sd = 15)
mean(x); sd(x)
```


```
## [1] 103.1934
```

```
## [1] 16.8945
```


```
median(x); IQR(x)
```

```
## [1] 103.9947
```


```
## [1] 25.68004
```



Robust Statistics




Robust Statistics



Let's add an extreme value:

```
x <- c(x, 1000)
```



Robust Statistics

Median and IQR are more robust to skewness and outliers than mean and SD. Therefore,

- for skewed distributions it is often more helpful to use median and IQR to describe the center and spread
- for symmetric distributions it is often more helpful to use the mean and SD to describe the center and spread

About legosets



To install the brickset package:

```
remotes::install_github('jbryer/brickset')
```

To load the load the legosets dataset.

```
data('legosets', package = 'brickset')
```

The legosets data has 19409 observations of 36 variables.

```
names(legosets)
```


```
## [1] "setID"          "number"          "numberVariant"
## [4] "name"           "year"            "theme"
## [7] "themeGroup"     "subtheme"        "category"
## [10] "released"       "pieces"          "minifigs"
## [13] "bricksetURL"    "rating"           "reviewCount"
## [16] "packagingType"  "availability"     "agerange_min"
## [19] "thumbnailURL"   "imageURL"        "US_retailPrice"
## [22] "US_dateFirstAvailable" "US_dateLastAvailable" "UK_retailPrice"
## [25] "UK_dateFirstAvailable" "UK_dateLastAvailable" "CA_retailPrice"
## [28] "CA_dateFirstAvailable" "CA_dateLastAvailable" "DE_retailPrice"
## [31] "DE_dateFirstAvailable" "DE_dateLastAvailable" "height"
## [34] "width"          "depth"           "weight"
```

Structure (str)



```
str(legosets)
```

```
## 'data.frame':    19409 obs. of  36 variables:
## $ setID          : int  7693 7695 7697 7698 25534 7418 7419 6020 22704 7421 ...
## $ number         : chr  "1" "2" "3" "4" ...
## $ numberVariant   : int  8 8 6 4 6 1 1 1 3 4 ...
## $ name           : chr  "Small house set" "Medium house set" "Large house set" ...
## $ year           : int  1970 1970 1970 1970 1970 1970 1970 1970 1970 ...
## $ theme          : chr  "Minitalia" "Minitalia" "Minitalia" "Minitalia" ...
## $ themeGroup      : chr  "Vintage" "Vintage" "Vintage" "Vintage" ...
## $ subtheme       : chr  NA NA NA NA ...
## $ category       : chr  "Normal" "Normal" "Normal" "Normal" ...
## $ released       : logi  TRUE TRUE TRUE TRUE TRUE TRUE ...
## $ pieces         : int  67 109 158 233 NA 1 1 60 65 NA ...
## $ minifigs       : int  NA NA NA NA NA NA NA NA NA NA ...
## $ bricksetURL     : chr  "https://brickset.com/sets/1-8" "https://brickset.com/sets/2-8" "https://brickset.com/sets/3-6" "https://brickset.com/sets/4-4" ...
## $ rating         : num  0 0 0 0 0 0 0 0 0 ...
## $ reviewCount     : int  0 0 1 0 0 0 0 0 0 ...
## $ packagingType   : chr  "{Not specified}" "{Not specified}" "{Not specified}" "{Not specified}" ...
## $ availability    : chr  "{Not specified}" "{Not specified}" "{Not specified}" "{Not specified}" ...
## $ agerange_min    : int  NA NA NA NA NA NA NA NA NA NA ...
## $ thumbnailURL    : chr  "https://images.brickset.com/sets/small/1-8.jpg" "https://images.brickset.com/sets/small/2-8.jpg" "https://images.brickset.com/sets/small/3-6.jpg" "https://images.brickset.com/sets/small/4-4.jpg" ...
## $ imageURL       : chr  "https://images.brickset.com/sets/images/1-8.jpg" "https://images.brickset.com/sets/images/2-8.jpg" "https://images.brickset.com/sets/images/3-6.jpg" "https://images.brickset.com/sets/images/4-4.jpg" ...
## $ US_retailPrice  : num  NA NA NA NA NA NA NA NA NA NA ...
## $ US_dateFirstAvailable: Date, format: NA NA ...
## $ US_dateLastAvailable : Date, format: NA NA ...
## $ UK_retailPrice  : num  NA NA NA NA NA NA NA NA NA NA ...
## $ UK_dateFirstAvailable: Date, format: NA NA ...
## $ UK_dateLastAvailable : Date, format: NA NA ...
## $ CA_retailPrice  : num  NA NA NA NA NA NA NA NA NA NA ...
## $ CA_dateFirstAvailable: Date, format: NA NA ...
## $ CA_dateLastAvailable : Date, format: NA NA ...
## $ DE_retailPrice  : num  NA NA NA NA NA NA NA NA NA NA ...
## $ DE_dateFirstAvailable: Date, format: NA NA ...
## $ DE_dateLastAvailable : Date, format: NA NA ...
## $ height         : num  NA NA NA NA NA ...
## $ width          : num  NA NA NA NA NA ...
```



RStudio Environment tab can help



Environment	History	Connections	Git	Tutorial
R - Global Environment				
Data				
legosets	16355 obs. of 34 variables			
\$ setID	: int	7693 7695 7697 7698 25534 7418 7419 6020 22704 7421 ...		
\$ name	: chr	"Small house set" "Medium house set" "Medium house set" "L...		
\$ year	: int	1970 1970 1970 1970 1970 1970 1970 1970 1970 1970 ...		
\$ theme	: chr	"Minitalia" "Minitalia" "Minitalia" "Minitalia" ...		
\$ themeGroup	: chr	"Vintage" "Vintage" "Vintage" "Vintage" ...		
\$ subtheme	: chr	NA NA NA NA ...		
\$ category	: chr	"Normal" "Normal" "Normal" "Normal" ...		
\$ released	: logi	TRUE TRUE TRUE TRUE TRUE TRUE ...		
\$ pieces	: int	67 109 158 233 NA 1 1 60 65 NA ...		
\$ minifigs	: int	NA NA NA NA NA NA NA NA ...		
\$ bricksetURL	: chr	"https://brickset.com/sets/1-8" "https://brickset.com/sets...		
\$ rating	: num	0 0 0 0 0 0 0 0 0 ...		
\$ reviewCount	: int	0 0 1 0 0 0 0 1 0 ...		
\$ packagingType	: chr	"{Not specified}" "{Not specified}" "{Not specified}" "{No...		
\$ availability	: chr	"{Not specified}" "{Not specified}" "{Not specified}" "{No...		
\$ ageRange_min	: int	NA NA NA NA NA NA NA NA NA ...		
\$ US_retailPrice	: num	NA NA NA NA NA 1.99 NA NA 4.99 NA ...		
\$ US_dateFirstAvailable	: Date, format:	NA NA NA NA ...		
\$ US_dateLastAvailable	: Date, format:	NA NA NA NA ...		
\$ UK_retailPrice	: num	NA NA NA NA NA NA NA NA NA ...		
\$ UK_dateFirstAvailable	: Date, format:	NA NA NA NA ...		
\$ UK_dateLastAvailable	: Date, format:	NA NA NA NA ...		
\$ CA_retailPrice	: num	NA NA NA NA NA NA NA NA NA ...		
\$ CA_dateFirstAvailable	: Date, format:	NA NA NA NA ...		
\$ CA_dateLastAvailable	: Date, format:	NA NA NA NA ...		
\$ DE_retailPrice	: num	NA NA NA NA NA NA NA NA NA ...		
\$ DE_dateFirstAvailable	: Date, format:	NA NA NA NA ...		
\$ DE_dateLastAvailable	: Date, format:	NA NA NA NA ...		
\$ height	: num	NA NA NA NA NA ...		
\$ width	: num	NA NA NA NA NA ...		
\$ depth	: num	NA NA NA NA NA NA NA 5.08 NA ...		
\$ weight	: num	NA NA NA NA NA NA NA NA NA ...		
\$ thumbnailURL	: chr	"https://images.brickset.com/sets/small/1-8.jpg" "https://...		
\$ imageURL	: chr	"https://images.brickset.com/sets/images/1-8.jpg" "https://...		




Table View

Show

10

 entries

Search:

	setID	name	year	theme	themeGroup	category	US_retailPrice	pieces	minifigs	rating
1	9712	Darth Maul	2012	Gear	Miscellaneous	Gear	4.99			3.7
2	28411	TIE Fighter Attack	2019	Star Wars	Licensed	Normal	19.99	77	2	3.5
3	24252	LEGO Minifigures - Series 14 - Monsters {Random bag}	2015	Collectable Minifigures	Miscellaneous	Random				0
4	1448	Head Stand	1998	Town	Modern day	Normal		96	3	0
5	32020	Mania Magazine March - April 1995	1995	Books	Miscellaneous	Book				0
6	28352	Genius LEGO Inventions with Bricks You Already Have	2018	Books	Miscellaneous	Book				0
7	34334	Friendship Flowers	2023	Friends	Modern day	Normal		84		3.8
8	31865	BRICK KICKS Summer 1991	1991	Books	Miscellaneous	Book				0
9	31061	LEGO Space Projects: 52 Galactic Models	2021	Books	Miscellaneous	Book				0
10	30688	James Potter	2020	Collectable Minifigures	Miscellaneous	Normal		7	1	3.8

Showing 1 to 10 of 100 entries

Previous

1

2345...10Next

Data Wrangling Cheat Sheet



Data Transformation with dplyr : : CHEAT SHEET



dplyr functions work with pipes and expect **tidy data**. In tidy data:



Each **variable** is in its own **column**




Each **observation**, or **case**, is in its own **row**



x %>% f(y) becomes **f(x, y)**

Summarise Cases

These apply **summary functions** to columns to create a new table of summary statistics. Summary functions take vectors as input and return one value (see back).




VARIATIONS

summarise_all() - Apply funs to every column.
summarise_at() - Apply funs to specific columns.
summarise_if() - Apply funs to all cols of one type.

Group Cases


Use **group_by()** to create a "grouped" copy of a table. dplyr functions will manipulate each "group" separately and then combine the results.



Manipulate Cases

EXTRACT CASES

Row functions return a subset of rows as a new table.




Logical and boolean operators to use with filter()


<	<=	is.na()	%in%		xor()
>	>=	!is.na()	!	&	

See **?base:logic** and **?Comparison** for help.

ARRANGE CASES




ADD CASES



Manipulate Variables

EXTRACT VARIABLES

Column functions return a set of columns as a new vector or table.




Use these helpers with **select()**, e.g. `select(iris, starts_with("Sepal"))`


contains(match)	num_range(prefix, range)	z, e.g. mpg:cyl
ends_with(match)	one_of(...)	z, e.g. -Species
matches(match)	starts_with(match)	

MAKE NEW VARIABLES

These apply **vectorized functions** to columns. Vectorized funs take vectors as input and return vectors of the same length as output (see back).



RStudio® is a trademark of RStudio, Inc. • CC BY SA RStudio • info@rstudio.com • 844-448-1212 • rstudio.com • Learn more with `browseVignettes(package = c("dplyr", "tidbtle"))` • dplyr 0.7.0 • tidbtle 1.2.0 • Updated: 2017-03



R Syntax Comparison : : CHEAT SHEET

Dollar sign syntax

`goal(data$x, data$y)`

SUMMARY STATISTICS:

one continuous variable:
`mean(mtcars$mpg)`

one categorical variable:
`table(mtcars$cyl)`

two categorical variables:
`table(mtcars$cyl, mtcars$am)`

one continuous, one categorical:
`mean(mtcars$mpg[mtcars$cyl==4])`
`mean(mtcars$mpg[mtcars$cyl==6])`
`mean(mtcars$mpg[mtcars$cyl==8])`

PLOTTING:

one continuous variable:
`hist(mtcars$disp)`

`boxplot(mtcars$disp)`

one categorical variable:
`barplot(table(mtcars$cyl))`

two continuous variables:
`plot(mtcars$disp, mtcars$mpg)`

two categorical variables:
`mosaicplot(table(mtcars$am, mtcars$cyl))`

one continuous, one categorical:
`histogram(mtcars$disp[mtcars$cyl==4])`
`histogram(mtcars$disp[mtcars$cyl==6])`
`histogram(mtcars$disp[mtcars$cyl==8])`

`boxplot(mtcars$disp[mtcars$cyl==4])`
`boxplot(mtcars$disp[mtcars$cyl==6])`
`boxplot(mtcars$disp[mtcars$cyl==8])`

WRANGLING:

subsetting:
`mtcars[mtcars$mpg>30, ]`

making a new variable:
`mtcars$efficient[mtcars$mpg>30] <- TRUE`
`mtcars$efficient[mtcars$mpg<30] <- FALSE`

Formula syntax

`goal(y~x|z, data=data, group=w)`

SUMMARY STATISTICS:

one continuous variable:
`mosaic::mean(~mpg, data=mtcars)`

one categorical variable:
`mosaic::tally(~cyl, data=mtcars)`

two categorical variables:
`mosaic::tally(cyl~am, data=mtcars)`

one continuous, one categorical:
`mosaic::mean(mpg~cyl, data=mtcars)`

tilde

PLOTTING:

one continuous variable:
`lattice::histogram(~disp, data=mtcars)`

`lattice::bwplot(~disp, data=mtcars)`

one categorical variable:
`mosaic::bargraph(~cyl, data=mtcars)`

two continuous variables:
`lattice::xyplot(mpg~disp, data=mtcars)`

two categorical variables:
`mosaic::bargraph(~am, data=mtcars, group=cyl)`

one continuous, one categorical:
`lattice::histogram(~disp|cyl, data=mtcars)`
`lattice::bwplot(cyl~disp, data=mtcars)`

The variety of R syntaxes give you many ways to “say” the same thing

read across the cheatsheet to see how different syntaxes approach the same problem

Tidyverse syntax

`data %>% goal(x)`

SUMMARY STATISTICS:

one continuous variable:
`mtcars %>% dplyr::summarize(mean(mpg))`

one categorical variable:
`mtcars %>% dplyr::group_by(cyl) %>% dplyr::summarize(n())`

the pipe

two categorical variables:
`mtcars %>% dplyr::group_by(cyl, am) %>% dplyr::summarize(n())`

one continuous, one categorical:
`mtcars %>% dplyr::group_by(cyl) %>% dplyr::summarize(mean(mpg))`

PLOTTING:

one continuous variable:
`ggplot2::qplot(x=mpg, data=mtcars, geom = "histogram")`

`ggplot2::qplot(y=disp, x=1, data=mtcars, geom="boxplot")`

one categorical variable:
`ggplot2::qplot(x=cyl, data=mtcars, geom="bar")`

two continuous variables:
`ggplot2::qplot(x=disp, y=mpg, data=mtcars, geom="point")`

two categorical variables:
`ggplot2::qplot(x=factor(cyl), data=mtcars, geom="bar") + facet_grid(.~am)`

one continuous, one categorical:
`ggplot2::qplot(x=disp, data=mtcars, geom = "histogram") + facet_grid(.~cyl)`

`ggplot2::qplot(y=disp, x=factor(cyl), data=mtcars, geom="boxplot")`

WRANGLING:

subsetting:
`mtcars %>% dplyr::filter(mpg>30)`

making a new variable:
`mtcars <- mtcars %>% dplyr::mutate(efficient = if_else(mpg>30, TRUE, FALSE))`

Pipes %>% and |>



The pipe operator (`%>%`) introduced with the `magrittr` R package allows for the chaining of R operations. As of version 4.1, R now has a native pipe operator (`|>`). They take the output from the left-hand side and passes it as the first parameter to the function on the right-hand side.



You can do this in two steps:

```
tab_out <- table(legosets$category)
prop.table(tab_out)
```

Using the pipe (`|>`) operator we can chain these calls in a what is arguably a more readable format:

Or as nested function calls.

```
table(legosets$category) |> prop.table()
```

```
prop.table(table(legosets$category))
```


```
##
##      Book  Collection  Extended      Gear      Normal      Other
## 0.034468546 0.031377196 0.028749549 0.154515946 0.684682364 0.062599825
##      Random
## 0.003606574
```

dplyr::filter()

KEEP ROWS THAT
satisfy
your CONDITIONS

keep rows from... this data... ONLY IF... type MATCHES "otter" AND site MATCHES "bay"

```
filter(df, type == "otter" & site == "bay")
```



type	food	site
otter	urchin	bay
shark	seal	channel
otter	abalone	bay
otter	crab	wharf



@alison_horst

Logical Operators

- `!a` - TRUE if `a` is FALSE
- `a == b` - TRUE if `a` and `b` are equal
- `a != b` - TRUE if `a` and `b` are not equal
- `a > b` - TRUE if `a` is larger than `b`, but not equal
- `a >= b` - TRUE if `a` is larger or equal to `b`
- `a < b` - TRUE if `a` is smaller than `b`, but not equal
- `a <= b` - TRUE if `a` is smaller or equal to `b`
- `a %in% b` - TRUE if `a` is in `b` where `b` is a vector

```
which( letters %in% c('a','e','i','o','u') )
```

```
## [1] 1 5 9 15 21
```

- `a | b` - TRUE if `a` or `b` are TRUE
- `a & b` - TRUE if `a` and `b` are TRUE
- `isTRUE(a)` - TRUE if `a` is TRUE

dplyr

```
mylego <- legosets %>% filter(themeGroup == 'Educational' & year > 2015)
```

Base R

```
mylego <- legosets[legosets$themeGroup == 'Educational' & legosets$year > 2015,]
```

```
nrow(mylego)
```

```
## [1] 99
```


dplyr

```
mylego <- mylego %>% select(setID, pieces, theme, availability, US_retailPrice, minifigs)
```

Base R

```
mylego <- mylego[,c('setID', 'pieces', 'theme', 'availability', 'US_retailPrice', 'minifigs')]
```

```
head(mylego, n = 4)
```


##	setID	pieces	theme	availability	US_retailPrice	minifigs
## 1	26803	103	Education	{Not specified}	NA	6
## 2	26689	142	Education	{Not specified}	NA	4
## 3	26804	98	Education	{Not specified}	NA	6
## 4	26277	188	Education	Educational	94.95	NA

Relocate



dplyr^{1.0.0}::relocate()
move COLUMNS around!

Default: move to FRONT
or move to
.before or .after
A SPECIFIED COLUMN!



@allison_horst



dplyr

```
mylego %>% relocate(where(is.numeric), .after = where(is.character)) %>% head(n = 3)
```

```
##           theme    availability setID pieces US_retailPrice minifigs
## 1 Education {Not specified} 26803    103           NA           6
## 2 Education {Not specified} 26689    142           NA           4
## 3 Education {Not specified} 26804     98           NA           6
```

Base R

```
mylego2 <- mylego[,c('theme', 'availability', 'setID', 'pieces', 'US_retailPrice', 'minifigs')]
head(mylego2, n = 3)
```

```
##           theme    availability setID pieces US_retailPrice minifigs
## 1 Education {Not specified} 26803    103           NA           6
## 2 Education {Not specified} 26689    142           NA           4
## 3 Education {Not specified} 26804     98           NA           6
```


dplyr::rename()

RENAME COLUMNS*

```
df %>% rename(lair=site)
```

species nemesis	status	site lair
narwhal	unknown	ocean
chicken	active	coop
pika	active	mountain

*See `rename_with()` to rename using a function.



@allison-horst

Rename



dplyr


```
mylego %>% dplyr::rename(USD = US_retailPrice) %>% head(n = 3)
```

```
##   setID pieces   theme   availability USD minifigs
## 1 26803   103 Education {Not specified}  NA         6
## 2 26689   142 Education {Not specified}  NA         4
## 3 26804    98 Education {Not specified}  NA         6
```

Base R

```
names(mylego2)[5] <- 'USD'
head(mylego2, n = 3)
```

```
##           theme   availability setID pieces USD minifigs
## 1 Education {Not specified} 26803   103  NA         6
## 2 Education {Not specified} 26689   142  NA         4
## 3 Education {Not specified} 26804    98  NA         6
```



Mutate



dplyr

```
mylego %>% filter(!is.na(pieces) & !is.na(US_retailPrice)) %>%  
  mutate(Price_per_piece = US_retailPrice / pieces) %>% head(n = 3)
```

```
##   setID pieces   theme availability US_retailPrice minifigs Price_per_piece  
## 1 26277   188 Education Educational      94.95         NA      0.5050532  
## 2 25949   280 Education Educational     224.95         NA      0.8033929  
## 3 25954     1 Education Educational      14.95         NA     14.9500000
```

Base R

```
mylego2 <- mylego[!is.na(mylego$US_retailPrice) & !is.na(mylego$Price_per_piece),]  
mylego2$Price_per_piece <- mylego2$Price_per_piece / mylego2$US_retailPrice  
head(mylego2, n = 3)
```


```
## [1] setID      pieces      theme      availability  
## [5] US_retailPrice minifigs    Price_per_piece  
## <0 rows> (or 0-length row.names)
```

Group By and Summarize



```
legosets %>% group_by(themeGroup) %>% summarize(mean_price = mean(US_retailPrice, na.rm = TRUE),
                                                  sd_price = sd(US_retailPrice, na.rm = TRUE),
                                                  median_price = median(US_retailPrice, na.rm = TRUE),
                                                  n = n(),
                                                  missing = sum(is.na(US_retailPrice)))
```

```
## # A tibble: 17 × 6
##   themeGroup      mean_price sd_price median_price      n missing
##   <chr>          <dbl>    <dbl>         <dbl> <int>   <int>
## 1 Action/Adventure  40.2    38.9         30.0  1474    779
## 2 Art and crafts   34.9    47.7         17.5   97      9
## 3 Basic            21.6    19.2         15.0  873   733
## 4 Constraction     16.4    12.4         13.0  502   284
## 5 Educational     182.    188.        130.   503   465
## 6 Girls            35.8    24.0         23.0  240   227
## 7 Historical       34.2    32.4         20.0  473   400
## 8 Junior           22.0    10.1         20.0  228   165
## 9 Licensed         53.3    71.7         30.0 2775  1066
## 10 Miscellaneous   20.7    29.2         13.0 6253  3961
## 11 Model making     74.3    92.1         40.0  771   384
## 12 Modern day       38.2    35.6         30.0 2469  1535
## 13 Pre-school       30.8    22.7         25.0 1562  1103
## 14 Racing           26.8    26.5         15.0  270   176
```




Describe and Describe By

```
library(psych)
describe(legosets$US_retailPrice)
```

```
##      vars      n mean   sd median trimmed   mad   min     max range skew kurtosis
## X1      1 7483 38.96 56.5  19.99    27.7 17.79 1.49 849.99 848.5 5.32    44.74
##
##      se
## X1 0.65
```

```
describeBy(legosets$US_retailPrice, group = legosets$availability, mat = TRUE, skew = FALSE)
```

```
##      item      group1 vars      n      mean      sd median   min     max range      se
## X11      1      {Not specified}  1 1831  26.84733  39.96747  19.99  1.49 789.99 788.5  0.9340335
## X12      2      Educational      1   12 212.86667 105.88283 222.45 14.95 399.95 385.0 30.5657410
## X13      3      LEGO exclusive  1 1039  57.21203 106.63125  12.99  1.99 849.99 848.0  3.3080857
## X14      4  LEGOLAND exclusive  1    2   4.99000   0.00000   4.99  4.99   4.99   0.0  0.00000000
## X15      5      Not sold      1    1 12.99000      NA  12.99 12.99  12.99   0.0      NA
## X16      6      Promotional      1    5   4.79000   0.83666   4.99  3.99   5.99   2.0  0.3741657
## X17      7 Promotional (Airline)  1    0      NaN      NA      NA  Inf  -Inf  -Inf      NA
## X18      8      Retail      1 4290  37.55889  38.44918  24.99  1.99 699.99 698.0  0.5870275
## X19      9      Retail - limited  1  302  63.54381  70.91908  39.99  2.49 449.99 447.5  4.0809343
## X110     10      Unknown      1    1   3.99000      NA   3.99  3.99   3.99   0.0      NA
```



Additional Resources

For data wrangling:

- dplyr website: <https://dplyr.tidyverse.org>
- R for Data Science book: <https://r4ds.had.co.nz/wrangle-intro.html>
- Wrangling penguins tutorial: <https://allisonhorst.shinyapps.io/dplyr-learnr/#section-welcome>
- Data transformation cheat sheet: <https://github.com/rstudio/cheatsheets/raw/master/data-transformation.pdf>

One Minute Paper

1. What was the most important thing you learned during this class?
2. What important question remains unanswered for you?



<https://forms.gle/N8WjTAysfKbGLptLA>