Energy Calibration with ML

Jason Bryslawskyj

October 22, 2018


Energy Calibration

- Sensors in EmCal calibrated by looking for minimum ionizing particles (MIPs)
- Charge deposited by MIPs follows Landau distributions:

Signal = Landau₀(
$$\mu_0, \sigma_0$$
)+Landau₁(μ_0, σ_0)

- Shown as Red, Green
- Background is composed of a Gaussian pedestal (Black)
- + high Energy particles (exp,blue), which are signal for analysis, but BG for calibration
- Regression complicated by zero-supression, which cuts a square notch in a random location between 0 and 10
- Challenge: Fit 200,000 sensors, all with differently shaped signal and background
- Find Most Probable Value (μ) of MIP Landau (Blue Arrow)

Example of charge disposited in single sensor




Energy Calibration

- Sensors in EmCal calibrated by looking for minimum ionizing particles (MIPs)
- Charge deposited by MIPs follows Landau distributions:

Signal = Landau₀(
$$\mu_0, \sigma_0$$
)+Landau₁(μ_0, σ_0)

- Shown as Red. Green
- Background is composed of a Gaussian pedestal (Black)
- + high Energy particles (exp,blue), which are signal for analysis, but BG for calibration
- Regression complicated by
- zero-supression, which cuts a square notch in a random location between 0 and 10
- Challenge: Fit 200,000 sensors, all with differently shaped signal and background

Example of charge disposited in single sensor



Outlook

- Will make additional comparisons between peaks in HIJING and DATA
- Such as hight diffrence between main peaks and subpeaks