

# Lecture 13 – Intro to Complexity theory

NTIN071 Automata and Grammars

---

Jakub Bulín (KTIML MFF UK)

Spring 2024

*\* Adapted from the Czech-lecture slides by Marta Vomlelová with gratitude.  
The translation, some modifications, and all errors are mine.*

## Recap of Lecture 12

- the Diagonal language  $L_D$  is not recursively enumerable
- the Universal language  $L_U$ , the Universal TM: simulate any  $M$  on any  $w$
- recursive languages are closed under complement
- Post's theorem:  $L$  recursive iff both  $L, \bar{L}$  are RE
- $L_U, \bar{L}_D$  are recursively enumerable but not recursive
- reductions between decision problems
- the Halting problem is undecidable
- (Rice's thm: nontriv. properties of programs are undecidable)
- Undecidable problems about context-free grammars
- Source of undecidability: Post's correspondence problem

# Summary of Lecture 13

- time complexity
-

## CHAPTER 5: INTRO TO COMPLEXITY

---

# Time complexity

---

# Asymptotic notation

**Big-O notation:** Let  $f, g : \mathbb{N} \rightarrow \mathbb{R}^+$ . We say that  $f(n) \in O(g(n))$ , if there exist  $C, n_0 \in \mathbb{N}^+$  such that

$$(\forall n \geq n_0) f(n) \leq C \cdot g(n)$$

e.g.  $\limsup_{n \rightarrow \infty} \frac{f(n)}{g(n)} < \infty$ . In that case we say that  $g(n)$  is an [asymptotic] **upper bound** [up to a constant multiple] for  $f(n)$ .

**Note:** Often the imprecise term ‘upper bound’ is used; sometimes you will encounter  $f(n) = O(g(n))$ .

For example,  $f(5n^3 + 2n^2 + 22n + 6) \in O(n^3)$  with  $n_0 = 10, C = 6$ .

**Little-o notation:**  $f(n) \in o(g(n))$ , if for all  $c > 0$  there exists  $n_0 \in \mathbb{N}^+$  so that  $(\forall n \geq n_0) f(n) < c \cdot g(n)$ , i.e.  $\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0$ . Then we say  $f(n)$  is [asymptotically] **dominated** by  $g(n)$ .

Analogously for  $\geq$  instead of  $\leq$ :  $\Omega, \omega$ .

# Classes of time complexity

## Definition

Let  $M$  be a Turing machine that halts on every input. The **time complexity** of  $M$  is the function  $f : \mathbb{N} \rightarrow \mathbb{N}$ , where  $f(n)$  is the maximum number of computation steps for inputs of length  $n$ .

## Definition

For  $t : \mathbb{N} \rightarrow \mathbb{R}^+$ , **TIME**( $t(n)$ ) is the class of all languages decidable by a TM of time complexity in  $O(t(n))$  (i.e., always halts and for  $|w| = n$  correctly answers in at most  $O(t(n))$  steps).

**NB:** Here we mean the standard, single-tape, deterministic TM.

## Example

**Example ( $L = \{0^i 1^j \mid i \geq 0\}$  is in  $\text{TIME}(n^2)$ )**

1. check if the input is  $0^i 1^j$ , if a 0 follows a 1, reject (time  $O(n)$ )
2. return to the beginning: hidden in the constant  $O(2n) = O(n)$
3. go through the 0s, in time  $O(n^2)$ 
  - 3.1 rewrite the next 0 to  $X$
  - 3.2 find the first 1, rewrite to  $X$
  - 3.3 return to the beginning
4. if no more 0s, check that no more 1s remain and accept (if 1 found, reject) (time  $O(n)$ )

⋮

Can we do it faster?



# Can we do it faster?

**Idea:** “compare the binary representations of  $i$  and  $j$ ”,  $\log n$  bits, for each bit need to traverse through the word

**Example** ( $L = \{0^i 1^j \mid i \geq 0\}$  is also in  $\text{TIME}(n \log n)$ )

1. check if the input is  $0^i 1^j$  and even length (time  $O(n)$ )
2. iterate while there are 0s, in time  $O(n \log n)$ 
  - 2.1 rewrite every other 0 to  $X$ , then every other 1 to  $X$
  - 2.2 check if the number of remaining 0s+1s is even, if not, reject
3. if no more 0s, check that no more 1s and accept (time  $O(n)$ )

⋮

Can we do it even faster?

# Time complexity and regular languages

Can we do it even faster? Not really.

## **Theorem**

*Every language decidable in time  $o(n \log n)$  [on a single-tape, deterministic TM] is regular.*

[We omit the proof.]

# Multi-tape TM

## Example (Multi-tape TM for $L = \{0^i 1^i \mid i \geq 0\}$ )

- copy 0s to Tape 2
- at first 1, switch state; erase 1 from Tape 1 & 0 from Tape 2
- accept if both tapes are erased

## Lemma

*Every multi-tape Turing Machine with time complexity  $t(n)$  is equivalent to a [single-tape] Turing Machine with time complexity  $O(t^2(n))$ .*

**Proof:** Simulation of  $n$  steps of a  $k$ -tape TM can be done in  $O(n^2)$  moves since one step takes  $4n + 2k$  moves (heads at most  $2n$  fields apart, read, write, move head marks). □

# Nondeterministic time complexity

The **time complexity** of a **nondeterministic** Turing machine that always halts is defined analogously:  $f(n)$  is the maximum number of steps in **any branch** of the computation tree.

## Definition

For  $t : \mathbb{N} \rightarrow \mathbb{R}^+$ ,  $\text{NTIME}(t(n))$  is the class of all languages decidable by a nondeterm. TM of time complexity in  $O(t(n))$ .

(An NTM **decides**  $L$  if halts on all inputs and recognizes  $L$ .)

## Theorem

*Any nondeterministic TM of time complexity  $t(n) \geq n$ , has a deterministic equivalent of time complexity in  $2^{O(t(n))}$ .*

## Corollary

*If  $t(n) \geq n$ , then  $\text{NTIME}(t(n)) \subseteq \text{TIME}(2^{O(t(n))})$ .*

Recall the construction: BFS of the computation graph, keep a queue of configurations to process.

- At most  $d$  possible transitions for any  $(q, X) \in (Q \setminus F) \times \Gamma$ .
- So after  $k$  steps at most  $d^k$  configurations.
- Processing one configuration can be 'hidden' in the constant.
- Therefore the simulation is in time:

$$O(t(n)d^{t(n)}) = 2^{O(t(n))}$$

- We need to simulate multiple tapes, but:

$$(2^{O(t(n))})^2 = 2^{O(2t(n))} = 2^{O(t(n))}$$



**P vs. NP**

---

# The class P

## Definition

Let **P** (also **PTIME**) be the class of all languages decidable in **polynomial time** by a [single-tape, deterministic] Turing machine:

$$P = \bigcup_k \text{TIME}(n^k)$$

- Path in a graph
- Primality of an integer (Agrawal, Kayal, Saxena 2002)
- Linear programming
- Horn-SAT

(The last two are P-complete under LOGSPACE reductions.)

## Theorem ( $CFL \subseteq P$ )

*Every context free language belongs to P.*

**Proof:** Take a ChNF grammar for  $L$ . Given input  $\omega$ , run the CYK algorithm (polynomial, in  $O(n^3)$ ). □

# The class NP: verifier-based definition

## Definition

A **verifier** for a language  $L$  is an algorithm  $V$  such that:

$$L = \{w \mid \text{there exists a finite string } c \text{ such that } V \text{ accepts } \langle w, c \rangle\}$$

Such a  $c$  is called a **certificate**. It can be over any alphabet!

Complexity of verifiers is only considered wrt. the length of  $w$ : a **polynomial verifier** must halt in time  $O(|w|^k)$  for some  $k > 0$ .

Then we can assume the certificate has polynomial length (otherwise the verifier cannot even read it).

## Definition

**NP** is the class of all languages that have a polynomial verifier.

That is, there is an algorithm that works in time polynomial in  $|w|$  and when given  $w \in L$  and a certificate  $c$  validates that  $c$  is a valid certificate for  $w \in L$ .



# Hamiltonian path

A **Hamiltonian path** in a directed graph  $G$  is a directed path  $P$  that visits each vertex of  $G$  exactly once.

$$\text{HAMPATH} = \{\langle G \rangle \mid G \text{ contains a Hamiltonian path}\}$$

- complexity for graphs can be measured just wrt.  $|V|$  ( $|E|$  is at most quadratic, thus polynomial)
- the **certificate** is the path (sequence of vertices)
- the algorithm verifies that the sequence is indeed a path containing each vertex exactly once; this can be easily done in polynomial time wrt.  $|V|$
- for  $\overline{\text{HAMPATH}}$  we do not know whether a polynomial verifier exists (we only know the problem is in EXPTIME)

# The class $NP$ : nondeterminism-based definition

## Definition

$NP$  is the class of all languages that have a polynomial verifier.

## Theorem

$$NP = \bigcup_k NTIME(n^k).$$

**Idea:** convert a verifier to a nondeterministic TM, and vice versa

$\Rightarrow$  the NTM guesses the certificate, then simulates the verifier

$\Leftarrow$  the verifier takes as a certificate the accepting path of the NTM (more precisely, the sequence of nondeterministic choices that leads to acceptance), then simulates the NTM

# Proof

$\text{NP} \subseteq \bigcup_k \text{NTIME}(n^k)$ : Let  $L \in \text{NP}$  and take a polynomial verifier  $V$  for  $L$ , say it works in time  $C \cdot |\omega|^k$ . Construct an NTM  $M$ :

Given input  $\omega$ :

- nondeterministically guess a certificate  $c$  (of  $|c| \leq C \cdot |\omega|^k$ )
- simulate  $V$  on input  $\langle \omega, c \rangle$
- if  $V$  accepted,  $M$  accepts

$\bigcup_k \text{NTIME}(n^k) \subseteq \text{NP}$ : Let  $L \in \text{NTIME}(n^k)$ , i.e.,  $L = L(M)$  for an NTM  $M$  working in time  $O(n^k)$ . Construct a polynomial verifier  $V$ :

Given input  $\langle w, c \rangle$ , interpret  $c$  as sequence of choices:  $c_i = j$  means “at step  $i$  use  $j$ th possible transition” (order as in  $\text{code}(M)$ )

- simulate  $M$  on input  $w$
- at each step  $i$  choose the  $c_i$ th possible transition
- accept if this computation path leads to acceptance



## Example: CLIQUE is in NP

$\text{CLIQUE} = \{\langle G, k \rangle \mid G \text{ is a graph which contains } K_k \text{ as a subgraph}\}$

**Polynomial verifier for CLIQUE:** input  $\langle \langle G, k \rangle, c \rangle$

- interpret the certificate  $c$  as a list of vertices
- check that  $c$  contains  $k$  vertices
- check that  $c$  induces a complete subgraph of  $G$

**Nondeterministic TM deciding CLIQUE:** input  $\langle G, k \rangle$

- nondeterministically choose a  $k$ -element subset  $c \subseteq V$
- check that  $c$  induces a complete subgraph of  $G$

# Polynomial-time reductions and NP-completeness

---

# Polynomial-time reducibility

Recall the notion of **reduction** between decision problems. Now we additionally require that the algorithm is polynomial-time:

A [total] function  $f : \Sigma^* \rightarrow \Delta^*$  is **polynomial-time computable**, if there exists a [deterministic] Turing Machine  $M$  and  $C, k > 0$  such that for each  $\omega \in \Sigma^*$ ,  $M$  halts in at most  $C \cdot |\omega|^k$  steps with  $f(\omega) \in \Delta^*$  being the non-blank contents of its tape.

## Definition

A language  $A \subseteq \Sigma^*$  is **polynomial-time reducible** to a language  $B \subseteq \Delta^*$ ,  $A \leq_P B$ , if there exists a polynomial-time computable function  $f : \Sigma^* \rightarrow \Delta^*$  such that for all  $\omega \in \Sigma^*$ :

$$\omega \in A \Leftrightarrow f(\omega) \in B$$

Then we call  $f$  a **polynomial-time reduction** from  $A$  to  $B$ .

## Example: Hamiltonian path from source to target

- $\text{HAMPATH} = \{\langle G \rangle \mid G \text{ contains a Hamiltonian path}\}$
- $\text{st-HAMPATH} = \{\langle G, s, t \rangle \mid G \text{ has a H. path from } s \text{ to } t\}$

### Example

HAMPATH and st-HAMPATH are **polynomial-time interreducible**, i.e. each polynomial-time reduces to the other.

**The reduction**  $\text{HAMPATH} \leq_P \text{st-HAMPATH}$ :

Given  $G$  create  $G'$  by adding new vertices  $s, t$  and all edges from  $s$  to  $V_G$  and from  $V_G$  to  $t$ ; define  $f(\langle G \rangle) = \langle G', s, t \rangle$

$$\langle G \rangle \in \text{HAMPATH} \Leftrightarrow \langle G', s, t \rangle \in \text{st-HAMPATH}$$

**The reduction**  $\text{st-HAMPATH} \leq_P \text{HAMPATH}$ : construct  $G'$  by adding new vertices  $s', t'$ , edges  $s' \rightarrow s, t \rightarrow t'$ ;  $f(\langle G, s, t \rangle) = \langle G' \rangle$

## Example: 3SAT is polynomial-time reducible to CLIQUE

A propositional formula is in **CNF** if it is a conjunction of clauses, and **3-CNF** if each clause contains exactly 3 literals.

- **SAT** =  $\{\langle \phi \rangle \mid \varphi \text{ is a satisfiable CNF formula}\}$
- **3SAT** =  $\{\langle \phi \rangle \mid \varphi \text{ is a satisfiable 3-CNF formula}\}$

### Theorem

*3SAT is polynomial-time reducible to CLIQUE.*

**Proof:** Vertices are occurrences of literals (three vertices per clause). Include all edges except for:

- between vertices from the same clause
- between a variable and its negation ( $x$  and  $\neg x$ )

Set  $k = \# \text{clauses}$ . Note: Exactly one literal per clause selected.  $\square$

**Exercise:** 3SAT is polynomial-time interreducible with SAT.