

# Lecture 8 – Equivalence of PDA and CFG, Deterministic PDA

NTIN071 Automata and Grammars

---

Jakub Bulín (KTIML MFF UK)

Spring 2024

*\* Adapted from the Czech-lecture slides by Marta Vomlelová with gratitude.  
The translation, some modifications, and all errors are mine.*

## Recap of Lecture 7

- Testing membership in a context-free language: the Cocke-Younger-Kasami algorithm
- Testing emptiness and finiteness of a context-free language
- Pushdown automaton: extend an  $\epsilon$ -NFA with a stack memory (potentially infinite), pop the top symbol, decide based on  $(q, a, X)$ , can push a finite string of stack symbols
- Acceptance by final state  $L(P)$  and by empty stack  $N(P)$ , conversion between the two options

## **2.10 Equivalence of PDA and context-free grammars**


---

# Equivalence of PDA and CFG

## Theorem

*The following statements about  $L \subset \Sigma^*$  are equivalent:*

- (i) There exists a context-free grammar such that  $L(G) = L$ .*
- (ii) There exists a PDA such that  $L(P) = L$ .*
- (iii) There exists a PDA such that  $N(P) = L$ .*



We have already shown  $(ii) \Leftrightarrow (iii)$ . To prove equivalence with a context-free grammar, we use acceptance by empty stack.

## Context-free grammar to pushdown automaton

---

## The construction

Given  $G = (V, T, \mathcal{P}, S)$ , construct  $P = (\{q\}, T, V \cup T, \delta, q, S)$ :

- (1) for each  $A \in V$ ,  $\delta(q, \epsilon, A) = \{(q, \beta) \mid A \rightarrow \beta \in \mathcal{P}\}$  [apply rule]
- (2) for each  $a \in T$ ,  $\delta(q, a, a) = \{(q, \epsilon)\}$  [match terminal]

## How it works:

- a **leftmost** derivation is simulated by the PDA
- current sentential form = part of input read + stack contents
- see a variable: apply rule, a terminal: read & pop from stack

# An example

## Example

$$I \rightarrow a \mid b \mid Ia \mid Ib \mid I0 \mid I1,$$
$$E \rightarrow I \mid E * E \mid E + E \mid (E)$$

$\Sigma = \{a, b, 0, 1, (, ), +, *\}$ ,  $\Gamma = \Sigma \cup \{I, E\}$ ,  $\delta$  is defined as follows:

- $\delta(q, \epsilon, I) = \{(q, a), (q, b), (q, Ia), (q, Ib), (q, I0), (q, I1)\}$
- $\delta(q, \epsilon, E) = \{(q, I), (q, E * E), (q, E + E), (q, (E))\}$
- $\delta(q, s, s) = \{(q, \epsilon)\}$  for all  $s \in \Sigma$  (e.g.  $\delta(q, +, +) = \{(q, \epsilon)\}$ )
- $\delta(q, x)$  is empty otherwise

**Leftmost derivation:**  $E \Rightarrow E * E \Rightarrow I * E \Rightarrow a * E \Rightarrow a * I \Rightarrow a * b$

The sequence of configurations:

$$(q, a * b, E) \vdash (q, a * b, E * E) \vdash (q, a * b, I * E) \vdash (q, a * b, a * E) \\ \vdash (q, *b, *E) \vdash (q, b, E) \vdash (q, b, I) \vdash (q, b, b) \vdash (q, \epsilon, \epsilon)$$

## Proof that $N(P) = L(G)$

(i)  $w \in L(G) \Rightarrow w \in N(P)$

Start with a leftmost derivation  $S = \gamma_1 \Rightarrow_{lm} \dots \Rightarrow_{lm} \gamma_n = w$ .

Prove by induction on  $i$  that  $(q, w, S) \vdash_P^* (q, v_i, \alpha_i)$ , where  $\gamma_i = u_i \alpha_i$  is the  $i$ -th sentential form and  $u_i v_i = w$ .

If  $\gamma_i$  contains only terminals, set  $\gamma_i = w = u_i, v_i = \epsilon = \alpha_i$ .

Otherwise, write  $\gamma_i = u_i A \alpha_i$ , where  $u_i \in T^*$  and  $A \in V$  is the leftmost variable.

By induction we have  $(q, w, S) \vdash_P^* (q, v_i, A \alpha_i)$ ,  $w = u_i v_i$ .

For the step  $\gamma_i \Rightarrow_{lm} \gamma_{i+1}$  we used some rule  $A \rightarrow \beta \in P$ . The PDA replaces  $A$  on the stack with  $\beta$ , moves to configuration  $(q, v_i, \beta \alpha_i)$ .

We pop all terminals  $v \in \Sigma^*$  from the beginning of  $\beta \alpha$  (matching them with the input):  $v_i = v v_{i+1}$  and  $\beta \alpha = v \alpha_{i+1}$

We got to  $(q, v_{i+1}, \alpha_{i+1})$ , corresponds to the sentential form  $\gamma_{i+1}$ .



## Proof that $N(P) = L(G)$

(ii)  $w \in N(P) \Rightarrow w \in L(G)$

Prove that if  $(q, u, X) \vdash_P^* (q, \epsilon, \epsilon)$ , then  $X \Rightarrow_G^* u$ . By induction on the number of moves. **Basis**  $n = 1$  move:


- $X = a \in \Sigma$ :  $\delta(q, a, a) \ni (q, \epsilon)$ ,  $u = a$ , 0-step derivation
- $X = A \in \Gamma$ :  $\delta(q, \epsilon, A) \ni (q, \epsilon)$  coming from  $A \rightarrow \epsilon \in \mathcal{P}$ ,  $u = \epsilon$

**Induction step**  $n > 1$  moves: if the first move is [match terminal], don't extend the derivation, if it is [apply rule]:  $A$  on top of stack was replaced by  $\beta = Y_1 Y_2 \dots Y_k$ , for a rule  $A \rightarrow \beta \in \mathcal{P}$ .

Split  $u = u_1 \dots u_k$  s.t. while popping  $Y_i$  we read  $u_i$ , i.e.  $(q, u_i u_{i+1} \dots u_k, Y_i) \vdash^* (q, u_{i+1} \dots u_k, \epsilon)$

Thus also  $(q, u_i, Y_i) \vdash^* (q, \epsilon, \epsilon)$ , by induction assumption we get  $Y_i \Rightarrow^* u_i$ . Together:

$$A \Rightarrow Y_1 Y_2 \dots Y_k \Rightarrow^* u_1 Y_2 \dots Y_k \Rightarrow^* \dots \Rightarrow^* u_1 u_2 \dots u_k$$



## **Pushdown automaton to context-free grammar**

---

## An example


Given  $P = (\{q\}, \{\text{if}, \text{else}\}, \{Z\}, \delta, q, Z)$

$$\delta(q, \text{if}, Z) = \{(q, ZZ)\}$$

$$\delta(q, \text{else}, Z) = \{(q, \epsilon)\}$$

if,  $Z \rightarrow ZZ$

else,  $Z \rightarrow \epsilon$



Construct  $G = (V, \{\text{if}, \text{else}\}, \mathcal{P}, S)$

- variables:  $V = \{S, [qZq]\}$
- production rules:
  - $S \rightarrow [qZq]$
  - $[qZq] \rightarrow \text{else}$
  - $[qZq] \rightarrow \text{if}[qZq][qZq]$

In this example,  $S$  and  $[qZq]$  generate the same words, so we can simplify:  $G = (\{S\}, \{\text{if}, \text{else}\}, \{S \rightarrow \text{if}SS \mid \text{else}\}, S)$

## PDA to CFG: the construction

- key event: pop a symbol  $X$ , while changing from state  $q$  to  $r$
- variables:  $[qXr]$  for  $q, r \in Q$  and  $X \in \Gamma$ , plus a new variable  $S$

$$L([qXr]) = \{w \in \Sigma^* \mid (q, w, X) \vdash_P^* (r, \lambda, \lambda)\}$$

- $S$  to choose (guess) in which state the stack is emptied

### The construction

Given  $P = (Q, \Sigma, \Gamma, \delta, q_0, Z_0)$ , construct  $G = (V, T, \mathcal{P}, S)$  where  $V = \{S\} \cup \{[pXq] \mid p, q \in Q, X \in \Gamma\}$  and the productions are:

- (i) for every state  $p \in Q$  add  $S \rightarrow [q_0 X p]$
- (ii) for every transition  $(p, Y_1 Y_2 \dots Y_k) \in \delta(q, a, X)$  (incl.  $a = \epsilon$ ) and all  $k$ -tuples of states  $p_1, \dots, p_{k-1}, p_k \in Q$  add

$$[qXp_k] \rightarrow a[pY_1p_1][p_1Y_2p_2] \dots [p_{k-1}Y_kp_k]$$


In particular, for  $(p, \epsilon) \in \delta(q, a, X)$  (i.e.,  $k = 0$ ) add  $[qXp] \rightarrow a$ .

## Another example: $\{0^n 1^n \mid n > 0\}$

| $\delta$                            | Productions                      |     |
|-------------------------------------|----------------------------------|-----|
|                                     | $S \rightarrow [pZp] \mid [pZq]$ | (1) |
| $\delta(p, 0, Z) \ni (p, A)$        | $[pZp] \rightarrow 0[pAp]$       | (2) |
|                                     | $[pZq] \rightarrow 0[pAq]$       | (3) |
| $\delta(p, 0, A) \ni (p, AA)$       | $[pAp] \rightarrow 0[pAp][pAp]$  | (4) |
|                                     | $[pAp] \rightarrow 0[pAq][qAp]$  | (5) |
|                                     | $[pAq] \rightarrow 0[pAp][pAq]$  | (6) |
|                                     | $[pAq] \rightarrow 0[pAq][qAq]$  | (7) |
| $\delta(p, 1, A) \ni (q, \epsilon)$ | $[pAq] \rightarrow 1$            | (8) |
| $\delta(q, 1, A) \ni (q, \epsilon)$ | $[qAq] \rightarrow 1$            | (9) |

Derivation of 0011:

$$\begin{aligned}
 S &\Rightarrow^{(1)} [pZq] \Rightarrow^{(3)} 0[pAq] \\
 &\Rightarrow^{(7)} 00[pAq][qAq] \\
 &\Rightarrow^{(8)} 001[qAq] \Rightarrow^{(9)} 0011
 \end{aligned}$$




# Sketch of proof that $L(G) = N(P)$

It suffices to show that:

$$[qXp] \Rightarrow^* w \text{ iff } (q, w, X) \vdash^* (p, \epsilon, \epsilon)$$

In both directions, the proof is done by induction (number of moves/steps).



## 2.11 Deterministic pushdown automata

---

## Definition (Deterministic PDA)

A pushdown automaton  $P = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$  is **deterministic** (a **DPDA**) iff both of the following hold:

- The set of possible transitions  $\delta(q, a, X)$  is at most one-element for all  $q \in Q$ ,  $a \in \Sigma \cup \{\epsilon\}$ , and  $X \in \Gamma$ .
- If  $\delta(q, a, X) \neq \emptyset$  for some  $a \in \Sigma$ , then  $\delta(q, \epsilon, X) = \emptyset$ .





## Summary of Lecture 8

- Pushdown automata accept exactly context-free languages (constructions: CFG to PDA and PDA to CFG)